










CAT 4660

Parflex Thermoplastic & Fluoropolymer Products
Hose, Tubing, & Fittings 2017



Parker

ENGINEERING YOUR SUCCESS.

Extra care is taken in the preparation of this literature but Parker is not responsible for any inadvertent typographical errors or omissions. Information subject to change without notice. The information in this catalog is only accurate as of the date of publication. For a more current information base, please consult the Parflex Division web site at www.parker.com/pfd.



FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS AND/OR SYSTEMS
DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.

This document and other information from Parker Hannifin Corporation, its subsidiaries and authorized distributors provide product and/or system options for further investigation by users having technical expertise. It is important that you analyze all aspects of your application and review the information concerning the product or system in the current product catalog. Due to the variety of operating conditions and applications for these products or systems, the user, through its own analysis and testing, is solely responsible for making the final selection of the products and systems and assuring that all performance, safety and warning requirements of the application are met.


The products described herein, including without limitation, product features, specifications, designs, availability and pricing, are subject to change by Parker Hannifin Corporation and its subsidiaries at any time without notice.

Offer of Sale

The items described in this document are hereby offered for sale by Parker Hannifin Corporation, its subsidiaries or its authorized distributors. This offer and its acceptance are governed by the provisions stated in the "Offer of Sale".

©Copyright 2017 Parker Hannifin Corporation, All Rights Reserved

Welcome to The Parflex Division



Our Charter

To be the global leader in engineered polymer-based products while providing system solutions for the conveyance and control of fluids.

As part of the Parker Fluid Connectors Group, the Parflex Division is responsible for the design and manufacture of hoses and tubing to handle extreme applications. Products include thermoplastic and fluoropolymer hose and tubing, hose bundles, harnesses and accessories.

The Parflex Division includes the Ravenna, OH headquarters and manufacturing facilities in:

- Manitowoc, WI
- Fort Worth, TX
- Mansfield, TX
- Stafford, TX
- Randleman, NC
- Monterrey, Mexico
- Huttenfeld, Lampertheim, Germany - sister division, ***polyflex***

The Parflex Advantage

When compared to wire reinforced rubber hose or even metal tubing, thermoplastic hose offers significant added value. Thermoplastic provides excellent chemical compatibility, noise-level reduction and ultraviolet and corrosion resistance, while fiber reinforcement retains flexibility — even at low temperatures. In addition, Parflex has long-length capabilities resulting in less scrap being generated during assembly....fewer connections, results in fewer potential leak points.

For fluoropolymer hose, Parflex hoses are designed to handle high temperatures in chemical and corrosive environments for the industrial mobile, oil and gas, pharmaceutical and food and beverage markets. Specialty products like PAGE-flex™ SBF™ (a hose with 1/2 the minimum bend radius of a conventional smooth bore hose) and USP Class VI certified EPDM rubber covered hoses are available. We also design a full range of Parflex and PAGE hose fittings.

Tap Into Our Resources in our state-of-the-art Polymer Innovation Center, driven by the single purpose of finding solutions to your most demanding fluid connector requirements. Abrasion, chemical compatibility, purity and permeation are just a few of the challenges our engineers work on everyday. The Polymer Innovation Center is your portal to an array of solution-driven abilities and assets, all conveniently situated within a single organization.

Notes

Table of Contents

Intro 1-20

Thermoplastic Hose Advantages _____ 8
Fluoropolymer Hose Advantages _____ 10

A Hose - Thermoplastic A-1

Parflex Thermoplastic Visual Index _____ A-4

Hose - Fluoropolymer A-62

Parflex Fluoropolymer Visual Index ___ A-6

B Tubing Intro B-4

Polyethylene _____ B-12
Nylon _____ B-22
TPE (thermoplastic elastomer) _____ B-32
Polypropylene _____ B-36
Polyurethane _____ B-38

Fluoropolymer Intro B-48

Clear Vinyl _____ B-46
PTFE _____ B-58
FEP _____ B-86
PFA _____ B-102
PVDF _____ B-106

C Coiled Air Hose & Fittings C-1 : C-22

Fast-Stor® Air Hose _____ C-8
Fast-Stor® Fittings _____ C-10
NoMar® Fast-Stor® Assemblies _____ C-17
NoMar® Fast-Stor® Fittings _____ C-18
Ultra-Lite Superbraid® _____ C-20

D Transportation (Fleet) D-1 : D-16

Air Brake Tubing _____ D-4
Diesel Fuel Tubing _____ D-5
BRAKCOIL® _____ D-8
Duo-Coil® _____ D-9
DollyCoil™ _____ D-10
Slider Coil™ _____ D-11
Fifth Wheel Slider Coil _____ D-12
Custom Harnesses, Bundles & Tubing __ D-13
SCR Hose _____ D-14

E Fittings E-1 : E-66

Hose Fittings _____ E-1

F Tooling F-1 : F-22

Crimpers _____ F-5
Pumps _____ F-13
Sewer Hose Swagers & Accessories ___ F-13
Dies _____ F-15
Conversion Kits _____ F-16
Cutting Tools _____ F-17
Hose Accessories _____ F-18
SplashShield Protective Cover _____ F-22

G General Technical G-1 : G-65

Hose Selection, Installation & Mtn. _____ G-4
Hose Assembly & Crimping _____ G-14
Die Selection & Crimping Chart _____ G-43
Technical Data _____ G-44
Material Compatibility Guide _____ G-46

Safety Guide _____ G-62
Offer of Sale _____ G-67
Part Number Index _____ i
Keyword Index _____ iv

For detailed ordering information, please consult price list or contact Parflex Division.

Catalog **Icons & Symbols**

1 Table of Contents

For quick, easy listing of topics covered by section, reference the Table of Contents on pg. 3.

2 Hose Quick Links

- Selection by Visual Index
- Selection by Construction Specifications
  - Thermoplastic
  - Fluoropolymer
- Selection by PSI
  - Thermoplastic
  - Fluoropolymer
- Nomenclature
  - Thermoplastic
  - Fluoropolymer Hose
    - Parflex
    - PAGE
- Material Compatibility Chart
- Government & Agency Specifications

3 Tubing Quick Links

- Selection by Tubing Index
  - Thermoplastic
  - Fluoropolymer
- Selection by Tubing Overview
  - Thermoplastic
  - Fluoropolymer
- Nomenclature - Fluoropolymer
- Tubing/Fitting Compatibility Chart
- Material Compatibility Chart
- Material Codes
- Government & Agency Specifications

4 Fitting Quick Links

- Fittings - Table of Contents
- Standard Fitting Configurations by Connection and End Code
- Hose Fitting Insertion Values
- Media to Fitting and Seal Compatibility
- Hose Fitting Thread Guide
- Tubing/Fitting Compatibility Chart
- Fitting Material Compatibility
- Nomenclature – Fittings

5 Additional Catalogs (catalogs are linked)

- Metal Hose, Flexible Braided Hose CAT 4690 MH
- Ultra High Pressure Thermoplastic Hose, Fittings and Accessories, CAT 4900
- Multitube Instrument and Heat Trace Products, CAT 4200-M-2
- TexLoc Fluoropolymer Tubing, CAT 4150-55
- PAGE Fluoropolymer Hose & Fittings, CAT 5162

How to Find Products

- Agriculture
- Automotive
- Compressed Gas
- Construction
- Electrical
- Fluid Handling
- Food/Beverage
- Forestry
- Grounds/Bldg. Mtn.
- Industrial
- Industrial Pneumatic
- Machine Tool
- Marine
- Material Handling
- Medical
- Military
- Mining
- Oilfield Service
- Paint
- Paving & Road Maintenance
- Personnel Equipment
- Pharmaceutical
- RV & Bus
- Semiconductor
- Sewer Hose
- Transportation
- Utility Equipment
- Waste Refuse

Symbol	Meaning
#	Part Number
	Hose Inner Diameter (I.D.)
	Hose Outer Diameter (O.D.)
	Working Pressure
	Minimum Bend Radius
	Crimp Die
	Crimp Fitting

Symbol	Meaning
	Minimum Burst Pressure
kg lbs	Weight
	Vacuum Rating
	Thread Size
	Hex Size
	Diameter
	Field Attachable Fitting

For detailed ordering information, please consult price list or contact Parflex Division.


Parflex offers more options.

Options that reduce operating costs without


Hose



Tubing





Fittings



For detailed ordering information, please consult price list or contact Parflex Division.

reducing performance.







The thermoplastic hoses in this catalog are recognized for their cleanliness and their ease of use in confined spaces, their flexibility and light weight, their abrasion resistance and the fact that they deliver the same performance as competitive rubber hoses, but in a more compact design. In addition, they are available in much longer lengths than a rubber hose, reducing possible leak points and the accumulation of scrap from producing hose assemblies.

Parflex thermoplastic hoses are also available as a bonded assembly, preventing hose-to-hose abrasion and ease of routing for applications requiring more than one hose.

For tubing, Parflex offers one of the largest selections available from one manufacturer. High and Low Temperature Tubing, Heat Shrink, Retractable Coils and many other specialty designs are available, including convenient harness and bundle integration. Similar to bonding, harnesses and bundles ensures quick assembly, and eliminate waste and improve throughput.

Thermoplastic Tubing

- Polyethylene
- Nylon
- TPE (thermoplastic elastomer)
- Polypropylene
- Polyurethane
- Clear Vinyl
- Airbrake Tubing
- Coiled Tubing

Fluoropolymer Tubing

- PTFE
- FEP
- PFA
- High Purity PFA
- PVDF
- Heat Shrink
- Convoluted
- Spiral Wrap

Parflex supplies a variety of fitting and hose equipment options including crimpers, cutters and more for creating hose assemblies.

For extreme temperatures (above 500°F) or chemical compatibility, Parflex provides Metal Hoses (refer to Catalog 4690) **and for ultra-high pressures, *polyflex* Ultra High Pressure Hose and Fittings** (view Catalog 4900).

For detailed ordering information, please consult price list or contact Parflex Division.

Thermoplastic Hose **Advantages**

Parker Parflex offers an extensive selection of high-quality thermoplastic and fluoropolymer hose and tubing, fittings and accessory solutions for "extreme" applications. We specialize in designing products to meet specific needs for increased profitability and efficiency.




In some product lines, continuous lengths up to 3,500 meters (11,484 feet) are available.

Long **Lengths**

Smaller **I.D.**

The Parflex manufacturing process does not require a mandrel for support of the core tube so hoses can be made to a smaller inner diameter such as 1.3 mm (.051 inch).



Size	Typical 100R17 Hose (rubber) inch / mm		D6R Hose inch / mm		Space Benefit
-4	0.52	13.2	0.46	11.7	11%
-6	0.67	17.0	0.61	15.5	9%
-8	0.81	20.6	0.76	19.3	7%
-10	0.98	24.8	0.96	24.4	2%
-12	1.15	29.2	1.15	29.2	0%
-16	1.47	37.3	1.44	36.5	2%


Compact designs allow for a tighter bend radius, allowing the hose to be used in smaller enveloped areas and facilitate quicker installs (up to 50%).


Compact **O.D.**

For detailed ordering information, please consult price list or contact Parflex Division.

Light **Weight**

Parflex products are lighter in weight due to their fiber reinforcements. In fact, a Parflex hose can weigh more than 70% less than a comparable rubber hose assembly.





In our new Polymer Innovation Center, Parflex engineers blend resins and create patented designed hoses to reduce permeation and withstand hours of abrasion without damaging the hose.

Abrasion **Resistance**

Multi- **Bonded**

Parflex bonded assemblies help prevent hose-to-hose abrasion at high stress levels. Bonding 2 to 11 varying-sized hoses (maximum 10 inches (254 mm) wide) together, bonded assemblies keep hoses from rubbing against each other or tangling.



When will a **fluoropolymer product** add longevity to your application?


High temperatures and extreme chemicals are a couple of reasons.

See next page for more information or visit www.whyfluoropolymers.com

For detailed ordering information, please consult price list or contact Parflex Division.


Fluoropolymer Hose **Advantages**

Parker Parflex manufactures PTFE hose for most markets that require high temperatures, chemical resistant hoses, or have applications where lubricity plays a critical factor in the success of the operation. Increased lubricity facilitates flow and makes for easy cleaning.



Chemical **Compatibility**

The chemical compatibility of fluoropolymers is far greater than conventional thermoplastics or rubber products.



High/Low **Temperatures**

PTFE products boast an operating temperature range of -100°F (73°C) to 500°F (260°C). For FEP and PFA, view specific materials for actual operating temperatures.

For detailed ordering information, please consult price list or contact Parflex Division.

In cold or heat, Fluoropolymers provide improved performance to flexing, vibration and impulse. Customers who make the switch not only reduce unscheduled maintenance repairs, but often, warranty repairs as well.



Shelf Life

Under optimal storage conditions, fluoropolymer and thermoplastic hose and tubing products should have unlimited storage life prior to initial usage.*


***Per SAE J517 - Hose, in bulk form passing visual inspection and proof test, shall be acceptable for use up to and including 40 quarters (10 years) from the date of manufacture. Shelf life of thermoplastic and polytetrafluoroethylene (PTFE) hose is considered to be unlimited. Hose assemblies that pass inspection and proof test shall not be stored for longer than 2 years.**

When will a **thermoplastic product** be more advantageous?

One reason is when you need a multi-line bonded hose.

See previous page for more information or visit www.whythermoplastics.com

Selecting the Correct **Hose**



Before selecting hoses from Catalog 4660, Before selecting hoses from Catalog 4660, it will be easier if you familiarize yourself with the basics of thermoplastic and fluoropolymer hoses by reviewing the symbols on pg. 4 and "Hose Assembly Part Numbers" on page A-12. Also, the Parflex Hose Selection Charts (located in Section A) will help pinpoint the hose you require. It will help you identify individual hoses by:

- Brief general description
- Specific size with corresponding working pressure
- Industry specification (ie. SAE)
- Core tube material
- Reinforcement/type of construction
- Cover material
- Specific page number where further detailed product information can be found

For fittings, refer to the visual indexes in Section E.



For detailed ordering information, please consult price list or contact Parflex Division.

“STAMPED”

Size
The appropriate inside and outside diameters

Temperature
The ambient and minimum/maximum temperature of the material being conveyed


Application
External conditions including abrasion, climate, heat, flexing, routing and degrees of bending

Media
The composition of the substance being conveyed and chemical compatibility with the hose inner core and, if applicable, the outer cover

Pressure
The maximum vacuum or pressure of the system, including pressure spikes

Ends
The appropriate end connection, material and attachment method for the application

Delivery
Testing, quality, packaging, and delivery requirements



Overview **Parflex Part Numbers**

To make ordering of Parflex products easier, a part number description section has been added for hose, tubing and fitting products. For additional nomenclature information, refer to the following pages:

- Hose - Section A .....pgs. A-18 : A-21
- Tubing - Section B .....See specific product page - Fluoropolymer pgs. B-56 : B-57
- Fittings - Section E .....pgs. E-3

Hose Part Numbers

Parflex offers thermoplastic and fluoropolymer hoses in standard and custom designs such as bonded, formed, extra flexible, specialty braid and jackets and more...

Thermoplastic & Fluoropolymer

Example: 520N – 8

520N – 8 – **Hose type** (General Hydraulic Hose)

520N – **8** – **Hose inside diameter** dash size (1/2")

Parflex PAGE Fluoropolymer

Example: 16-SCW


16-SCW – **Hose inside diameter** dash size (1")

16-**SCW** – **Hose type** (Seamless Convoluted with Stainless Steel Braid)

Hose Assembly Part Numbers

Example: F540N0639080808C-30"

This assembly example reflects a 1/2" I.D., 540N hose with a female JIC 37° swivel straight fitting on the first end and a female JIC 37° - swivel - 90° elbow fitting on the other. The fittings are stainless steel and crimped (permanently attached) onto the hose. The overall length is 30".



1. Prefix

F540N0639080808C-30"

F = Crimp
R = Field Attachable
A = 54 Series Factory

2. Hose type

F**540N**0639080808C-30"

General Hydraulic Hose

3. Fitting 1st End

F540N**06**39080808C-30"

SAE 1/2" female JIC 37° swivel straight fitting

4. Fitting 2nd End

F540N063**9**080808C-30"

SAE 1/2" 90° female JIC 37° swivel elbow fitting

5. Size 1st End

F540N0639**08**0808C-30"

1/2"

6. Size 2nd End

F540N063908**08**08C-30"

1/2"

7. Hose End Dash Size

F540N063908080**8**C-30"

1/2"

8. Fitting Material

F540N0639080808**C**-30"

- Blank = Steel (unless noted)
- C = Stainless
- B = Brass

9. Length

F540N0639080808C-**30"**

30" overall length

A complete nomenclature guide for Parflex PAGE hoses is located in Section A on pg. A-21.

Hose Fittings Part Numbers

Parflex has expanded the Fitting Section to include the 56 Series fittings, designed for global availability and with a smaller, compact construction.

Example: 10356-8-6

This example describes a permanent crimp 1/2" Male JIC 37° Rigid hose end with a 3/8" hose end. This fitting is constructed of steel since the designated material is blank.

10356-8-6 – **Fitting Type** (1 = Permanent/Crimp)
1**03**56-8-6 – **End Configuration Code** (Male JIC 37° Rigid)
103**56**-8-6 – **Fitting Series** (56 Series)
10356-**8**-6 – **End Connection Size** (1/2")
10356-8-**6** – **Hose Size** (3/8")

Fitting Material
- Blank = Steel (unless otherwise noted)
- B = All Brass
- C = Stainless Steel
- S = All Carbon Steel – Used only with PTFE Fittings

Tubing Part Numbers

Parflex has expanded the Tubing Section to include the TexLoc® Fluoropolymer product line. In addition to smooth bore tubing, TexLoc products include beading, convoluted tubing and heat shrinkable tubing. This tubing is supplied in natural and colors are available upon request. For a detailed fluoropolymer nomenclature guide, review Section B, pgs. B-56 : B-57.

Thermoplastic

Example: U-21-BLU-0250

U-21-BLU-0250 – **Polyurethane**
U-**2**1-BLU-0250 – **Tube O.D.**
in sixteenths of an inch (1/8")
U-2**1**-BLU-0250 – **Tube I.D.**
in sixteenths of an inch (1/16")
U-21-**BLU**-0250 – **Color** (Blue)
U-21-BLU-**0250** – **Package Qty.** (250')

Available colors

- BLK = Black
- BLU = Blue
- GRY = Gray
- GRN=Green
- None = Natural
- ORG = Orange
- RED = Red
- YEL = Yellow

(colors may vary by product)

Fluoropolymer


Example: 101-0250062-NT-0100

101-0250062-NT-0100 – **Fractional**
1**01**-0250062-NT-0100 – **PTFE**
101-**0250**062-NT-0100 – **Tube O.D.**
inch displayed in decimals (1/4")
101-0250**062**-NT-0100 – **Wall Thickness**
inch displayed in decimals (.062")
101-0250062-**N**T-0100 – **Color** (Natural)
101-0250062-N**T**-0100 – **Bulk Tubing**
101-0250062-NT-**0100** – **Package Qty.** (100')

Available colors

- N = Natural
- 0 = Black
- 6 = Blue
- 1 = Brown
- 8 = Gray
- 5 = Green
- 3 = Orange
- 2 = Red
- 4 = Yellow
- 9 = White

Overview **Parflex Tubing Applications**



Largest selection of tubing material and styles produced by one manufacturer

Temperatures range from -100°F up to 500°F

-Thermopolymer
-TPE (thermoplastic elastomer)
-Fluoropolymer
-Heat Shrinkable
-Convoluted
-Corrugated
-Air Brake
-Antimicrobial



EZ Pack 100 foot boxes

Contact Customer Service for Retail Packaging Options

Benefits of Thermoplastic Tubing Materials and Applications*

Nylon	Strength Chemical Compatibility
Polyethylene	Food Contact Potable Water Price
Polyurethane	Flexibility
Polypropylene	Food Contact Chlorinated Water
Vinyl	Price Flexibility Food Contact Clarity

*Certain materials perform better in particular applications. Contact Customer Service for details.

Typical Applications

- Instrumentation
- Potable Water
- Pneumatics
- Machine Tools
- Pest Control Lines
- Marine Applications
- Weld Spatter/Spark Environments
- Food & Beverage
- Chemical Transfer
- Robotics
- Lubrication
- Semiconductor



Benefits of Fluoropolymer Tubing Materials and Applications*


All	Self extinguishing Chemical resistant FDA & USP Class VI compliant
PTFE	Operates up to 500°F Lowest coefficient of friction Best flex life
FEP	Operates up to 400°F Long, continuous lengths
PFA	Operates up to 500°F Long, continuous lengths High purity resins available
PVDF	Operates up to 265°F Chemical Transfer

*Certain materials perform better in particular applications. Contact Customer Service for details.

Typical Applications


- Pharmaceutical
- Pulp & Paper
- Chemical Delivery
- Paint Equipment
- Heat Exchanger
- Medical Devices
- Environmental Sampling
- Solar Panels
- Food Processing
- Chromatography
- Instrumentation
- Ink Rollers

Where will you find **Parflex?**



























For detailed ordering information, please consult price list or contact Parflex Division.























For detailed ordering information, please consult price list or contact Parflex Division.

Typical Applications - **Parflex**

Mobile Hydraulics

Markets










- Material Handling Equipment
- Marine
- Agricultural Equipment
- Utility Equipment
- Sewer Cleaning Equipment
- Aerial Lift
- Construction Equipment
- Rough Terrain Equipment
- Refuse Haulers
- Mining

Parflex Mobile Hydraulic products meet the needs of four primary market segments: aerial lift, agriculture, construction and material handling.

Applications

- Aerial Lift Hydraulic Tools
- Cold Storage
- Compressor Discharge
- Conveyor Equipment
- Diagnostics/Gaging
- General Hydraulics
  - Off-Road Construction
  - Earth Moving Equipment
  - Lift Trucks
  - Material Handling
  - Construction Equipment
  - Refuse Haulers
  - Agricultural Equipment
- Implement Hydraulic Power
- Lubrication Systems
- Mower Attachments
- Over-the-Sheave
- Pilot Control Lines
- Power Steering
- PTO's
- Turbo Drain Lines

Fluid Handling

Markets



- Industrial Equipment
- Utilities (CNG)
- Semiconductor
- Chemical
- Commercial Refrigeration
- Water Treatment
- Power Cleaning
- Power Generation
- Car Care
- Pharmaceutical
- Bio-Pharm
- Pulp & Paper
- Oil & Gas

Parflex Fluid Handling products are categorized by their thermoplastic and fluoropolymer (PTFE) makeup. Parflex offers standard and custom designed solutions such as bonded, harnessed and formed products.

Applications

- Agricultural Spraying
- Alternative Fuels
- Breathing Air Systems
- Car Care
- Carpet (Power) Cleaning
- Chemical & Gas Transfer
- Chemical Dispensing
- Coolant Lines
- Dispensing
- Food and Beverage
- Lubrication Systems
  - Machine tool
  - Heavy equipment
- Oil & Gas Transfer (Petrochemical)
- Pharmaceutical
- Potable Water Delivery
- Semiconductor (Pure air or gas transfer)
- Sewer Cleaning
- Steam Transfer

For detailed ordering information, please consult price list or contact Parflex Division.

Parflex offers a diverse product line that includes lightweight, non-marring, flexible hose and thermo-plastic or fluoropolymer tubing.

Industrial Pneumatics

Applications

- Air Tools
- Automotive Maintenance
- Carpentry Framing
- End-of-Arm Tooling
- General Robotics
- Metal Working
- Pneumatic Systems
- Robotic Welding
- Testing Equipment



Markets

- Robotics
- Packaging Machinery
- Machine Tool
- Carpentry
- Automotive Maintenance
- Medical Equipment
- Laboratory Equipment
- Furniture Manufacturing
- Paper Manufacturing

Our products thrive in harsh environments

Parflex develops thermoplastic hose products from fiber, wire and aramid fiber reinforced products to steel, stainless steel, and brass fittings to equipment & accessories for today's fastest growing markets.

Industrial Hydraulics

Applications

- Automotive Maintenance
- Dispensers
- Fermenters
- General Hydraulic Lines
- Hydraulic or Vacuum Connections
- Injection Molding
- Lubrication Systems
- Machine Tool
  - Metal Forming
  - Bending Machines
  - Vertical Machining
  - Metal Cutting
- Molding and Transfer Lines for Plastics
- Press Brakes
- Pumps



Markets

- Machine Tools
- Hydraulic Tools
- Mining
- Patient Handling
- Car Care
- Automotive
- Rescue Tools
- Lubrication Systems
- Recreational Vehicles

For detailed ordering information, please consult price list or contact Parflex Division.

Typical Applications - **Parflex**

Transportation

Markets

- Class 8 Heavy Truck
- Standard Box Truck
- Diesel Truck
- Bus
- Refrigeration Truck
- Refuse Truck
- Fire Truck
- Trailers
- Street Sweepers
- Military Vehicles
- RV's

An extensive line of transportation products includes a selection of air brake tubing for standard distribution and large OEMs, air brake harnesses, coils, fuel tubing and 100% pressure-tested fleet tubing for use with diesel fuel.

Applications

- Air Lines
- Coiled Air Brake
- Compressed Natural Gas
- Compressor Discharge
- Exhaust and AC Lines
- Fuel Lines
- Fuel Transfer
- Hydraulics
- Hydrostatic Pumps
- Lubrication Systems
- Power Steering
- Pump Outlets
- SCR System DEF Conveying
- Service/Emergency Connections



Life Science


Markets

- Medical Device
- Medical Equipment
- Dental
- Pharmaceutical
- Veterinary

Parflex has extended the selection of medical tubing capabilities and specializes in the extrusion of precision tolerances for custom tubing and custom profiles of PTFE, ePTFE, FEP, PFA, and ETFE.

Applications

- Air and Gas Transport
- Blood Analyzer
- Catheter Construction
- Clean Room Equipment
- Dental Equipment
- Endoscopic Instruments
- Forming Devices
- General Robotics
- Introducers
- Lab Instruments
- Packaging
- Sheathing
- Tracheotomy Tubes



For detailed ordering information, please consult price list or contact Parflex Division.

Parflex products for the Food and Beverage market are comprised of FDA and NSF compliant hose and tubing. Specialty hoses and tubing products are also available for increased vacuum or purity.

Food & Beverage

Applications

- Transport of Edible Oils, Syrup, Milk and other Food Products
- Chillers
- Commercial Freezers
- Dishwashers
- Dispensing Equipment
- In-plant Transfer for Processing
- Label/Adhesive Machinery
- Packaging Equipment
- Tank Transfer of Raw Products

Markets

- Food
- Beverage

FDA NSF Certified to NSF/ANSI 61 -C-HOT- NSF COMPONENT -NSF-51- RoHs

Parflex Multitube® offers a variety of thermal control tubing products, such as steam and electric trace tubing, as well as analyzer and probe support bundles. Refer to Catalog 4200-M-2, Instrument and Heat Trace Tubing Products for product details.

Energy

Applications

- Analyzers
- Condensate Return Lines
- Cooling Water Lines
- Environmental Monitoring
- Instrumentation Lines
- Liquid Nitrogen Transfer
- Maintenance Bundles
- Probe Support Umbilicals
- Process Lines
- Refrigeration
- Sample Lines
- Stack Gas Sampling
- Steam Purge / Steam Supply Lines

Markets

- Chemical Processing
- Environmental
- Power Generation
- Process Control
- Refineries
- Utilities



For detailed ordering information, please consult price list or contact Parflex Division.

Notes

Thermoplastic

Fluoropolymer



Table of Contents

Introduction

Visual Index A-4
Understanding Parflex Hose A-7
How to Read the Hose Section A-8
Hose Constructions A-9
Thermoplastic Hose Selection - Construction/Specifications, psi A-10
Thermoplastic Hose Selection - Construction/Specifications, MPa A-14
Fluoropolymer Hose Selection - Construction/Specifications, psi A-12
Fluoropolymer Hose Selection - Construction/Specifications, MPa A-16
Nomenclature - Parflex Thermoplastic Hose Assembly A-18
Nomenclature - Parflex PTFE Hose Assembly A-20
Nomenclature - “True-Bore” & Convoluted Hose Assembly A-21

Parflex Thermoplastic Hose

510A Refrigerant A-34
510C General Hydraulic A-35
518C Non-Conductive Hydraulic A-36
518D Non-Conductive Hydraulic A-37
515H Compact/Light Weight A-38
520N/528N General Hydraulic A-39
526BA Breathing Air Refill, 6000 psi A-40
527BA Breathing Air Refill, 7000 psi A-41
528N General Hydraulic, Non-Conductive A-39
53DM/538DM DuraMax™ Low Temperature/Non-Conductive A-42
540N General Hydraulic A-43
540P Specialty Water A-44
55LT Low Temperature A-45
560TJ TOUGHJACKET™ SAE 100R1AT Hydraulic A-30
563TJ TOUGHJACKET™ SAE 100R17 Hydraulic, 3000 psi A-31
56DH/568DH Diagnostic/Non-Conductive A-46
575X/575XN Fast Response, 5000 psi A-47
580N/H580N High Pressure A-48
588N High Pressure, Non-Conductive A-48
590TJ TOUGHJACKET™ SAE 100R2 Hydraulic A-32
594TJ TOUGHJACKET™ SAE 100R19 Hydraulic, 4,000 psi A-33
5CNG Electrically Conductive Compressed Natural Gas A-52
83FR DuraGard™ General Purpose Polyurethane A-49
1035HT High Temperature Power Cleaning A-50
B9 General Purpose Transfer Hose A-51
CNGRP – Regulated Pressure Natural Gas, Electrically Conductive A-53
D6R/D6RX Hybrid® Hose, Constant Pressure, 3000 psi A-22
DuraFlex™ 548N Hydraulic Hose Coil, Non-Conductive A-62
H6 Hydraulic Hose, Constant Pressure 3,000 psi A-25
HFSR Hybrid®, Fire-Screen® A-23
HFS2R Hybrid®, Fire-Screen II® A-24
HJK Highjack® Jackline Hybrid® A-29
HLB Lubrication Line A-54

Parflex Thermoplastic Hose (cont.)

HTB Eliminator® Hybrid®, Compact A-27
M8 E-Z FLEX™ Hybrid® High Pressure, 4000 psi A-28
MSH Marine Steering A-55
MSXL High Pressure Marine Steering A-56
PTH Marine Power Tilt A-57
R6 – Abrasion King® Hybrid® Hose, 3,000 psi A-26
S5N Predator® Water Jetting, 4000 psi A-58
S6 Predator® Water Jetting, 2500 psi A-59
S9 Predator® Water Jetting, 3000 psi A-60
SLH Sewer Leader A-61

Parflex Specialty Hose Highlights

Metal Hose 9A, 9M, 9H, 9P A-83
Multitube® BOP Bundles, Electro-Hydraulic Umbilicals and Hotlines A-84
polyflex Ultra-High Pressure Hose A-85

Parflex Fluoropolymer Hose


919/919B PTFE Hose, Natural & Static Dissipative Core Tube A-63
919J PTFE Hose, Silicone Cover A-64
919U PTFE Hose, High Abrasion Resistance A-65
929/929B Heavy Wall PTFE Hose, Natural & Static Dissipative Core Tube A-66
929BJ PTFE Hose, Static Dissipative Core Tube, Silicone Cover A-67
939/939B Convoluted PTFE Hose, Natural & Static Dissipative Core Tube A-68
943B High Pressure PTFE Hose, Static Dissipative Core Tube, 3000 psi A-69
944B High Pressure PTFE Hose, Static Dissipative Core Tube, up to 4500 psi A-70
950B High Pressure PTFE Hose, Static Dissipative Core Tube, 4000 psi A-71
955B High Pressure PTFE Hose, Static Dissipative Core Tube, 5500 psi A-72

PAGE Fluoropolymer Hose

STW/STB PTFE Hose, "True-Bore", Natural & Static Dissipative Core Tube A-73
SBFW PTFE Hose, PAGE-flex™ SBF™, Natural Core Tube A-74
SCW/SCB Convoluted PTFE Hose, SS Braid, Natural & Static Dissipative Core Tube A-75
PCW/PCB Convoluted PTFE Hose, PP Braid, Natural & Static Dissipative Core Tube A-76
SCWV/SCBV Heavy Wall Convoluted PTFE Hose, SS Braid, Natural & Static Dissipative Core Tube A-77
PCWV/PCBV Heavy Wall Convoluted PTFE Hose, PP Braid, Natural & Static Dissipative Core Tube A-78
SCWV-FS/SCBV-FS Flare-Seal® PTFE Hose, SS Braid, Natural & Static Dissipative Core Tube A-79
PCWV-FS/PCBV-FS Flare-Seal® PTFE Hose, PP Braid, Natural & Static Dissipative Core Tube A-80
NCW/NCB Nomex® Covered PTFE Hose, Natural & Static Dissipative Core Tube A-81
RCTW EPDM Rubber Covered Hose, Natural & Static Dissipative Core Tube A-82


Nomex® is a registered trademark of
E. I. du Pont de Nemours and Company.

Parflex Hose Visual Index


Parflex Thermoplastic		**510A**	Refrigerant	**510C**	General Hydraulic	**518C**	Non-Conductive Hydraulic
		 A-34		 A-35		 A-36	
518D	Non-Conductive Hydraulic	**515H**	Compact/Lightweight	**520N**	General Hydraulic	**528N**	Non-Conductive Hydraulic
 A-37		 A-38		 A-39		 A-39	
526BA	Breathing Air Refill 6000 psi	**527BA**	Breathing Air Refill 7000 psi	**53DM**	DuraMax™ Low Temperature, 3000 psi	**538DM**	DuraMax™ Low Temperature, Non-Conductive 3000 psi
 A-40		 A-41		 A-42		 A-42	
540N	General Hydraulic	**540P**	Specialty Water	**55LT**	Low Temperature	**560TJ**	**TOUGH**JACKET™ General Hydraulic
 A-43		 A-44		 A-45		 A-30	
563TJ	**TOUGH**JACKET™ Constant Pressure, 3000 psi	**56DH**	Diagnostic Hose	**568DH**	Non-Conductive Diagnostic Hose	**575X 575XN**	Fast Response 5000 psi
 A-31		 A-46		 A-46		 A-47	
580N H580N	High Pressure	**588N**	Non-Conductive High Pressure	**590TJ**	**TOUGH**JACKET™General Hydraulic	**594TJ**	**TOUGH**JACKET™ Constant Pressure, 4000 psi
 A-48		 A-48		 A-32		 A-33	
83FR	General Purpose	**1035HT**	High Temp. Power Cleaning	**B9**	General Purpose	**5CNG**	Compressed Natural Gas, Electrically Conductive
 A-49		 A-50		 A-51		 A-52	
CNGRP	Regulated Pressure CNG, Electrically Conductive	**D6R D6RX**	Constant Pressure, 3000 psi	**Duraflex™**	548N Tool Hose, Non-Conductive	**H6**	Hydraulic Hose, Constant Pressure 3,000 psi
 A-53		 A-22 **HYBRID®**				 A-25	
HFSR	Fire-Screen®	**HFS2R**	Fire-Screen II®	**HJK**	Highjack® Jackline	**HLB**	Lubrication Line
 A-23 **HYBRID®**		 A-24 **HYBRID®**		 A-29 **HYBRID®**		 A-54 **HYBRID®**	

For detailed ordering information, please consult price list or contact Parflex Division.

Parflex Hose Visual Index (cont.)

Parflex Thermoplastic (cont.)	HTB	Eliminator® Compact	M8	High Pressure Hydraulic	MSH	Marine Steering
	 A-27 HYBRID®		 A-28 HYBRID®		 A-55	
MSXL	Marine Steering, High Pressure	**PTH**	Marine Power Tilt	**R6**	Constant Pressure 3,000 psi	**S5N**	Predator® Water Jetting 4000 psi
 A-56		 A-57		 A-26		 A-58	
S6	Predator® Water Jetting 2500 psi	**S9**	Predator® Water Jetting 3000 psi	**SLH**	Predator® Sewer Leader		
 A-59		 A-60		 A-61			

Parflex Specialty Hose Highlights

Metal Hose	Multitube®	polyflex
Standard, Ultra Flexible, High Pressure, and Ultra High Pressure	BOP Bundles, Electro-Hydraulic Umbilicals, and Hotlines	Ultra-High Pressure Thermoplastic Hose, Oil & Gas, Water Blast and Hydraulic Tool Hose
 A-83	 A-84	 A-85

Parflex Hose Visual Index (cont.)

Parflex PTFE							
		919 PTFE Hose		**919B** PTFE Hose with Static-Dissipative Tube		**919J** Silicone Covered PTFE Hose	
	A-63		A-63		A-64		
919U High Abrasion Resistance PTFE Hose		**929** Heavy Wall PTFE Hose		**929B** Heavy Wall PTFE Hose with Static-Dissipative Tube		**929BJ** Silicone Covered PTFE Hose with Static-Dissipative Tube	
A-65		A-66		A-66		A-67	
939 Convoluted PTFE Hose		**939B** Convoluted PTFE Hose with Static-Dissipative Tube		**943B** High Pressure PTFE Hose with Static-Dissipative Tube		**944B** High Pressure PTFE Hose with Static-Dissipative Tube	
A-68		A-68		A-69		A-70	
950B High Pressure PTFE Hose with Static-Dissipative Tube		**955B** High Pressure PTFE Hose with Static-Dissipative Tube					
A-71		A-72					

PAGE Product Line PTFE & Specialty							
		STW "True-Bore" with SS Braid		**STB** Static-Dissipative "True-Bore" with SS Braid		**SBFW** PAGE-flex™ SBF™	
	A-73		A-73		A-74		
SCW Convoluted with SS Braid		**SCB** Static-Dissipative Convoluted with SS Braid		**PCW** Convoluted with PP Braid		**PCB** Static-Dissipative Convoluted with PP Braid	
A-75		A-75		A-76		A-76	
SCWV Heavy Wall Convoluted with SS Braid		**SCBV** Static-Dissipative H.W. Convoluted with SS Braid		**PCWV** Heavy Wall Convoluted with PP Braid		**PCBV** Static-Dissipative Heavy Wall Convoluted PP Braid	
A-77		A-77		A-78		A-78	
SCWV-FS Flare-Seal® with SS Braid		**SCBV-FS** Static-Dissipative Flare-Seal® with SS Braid		**PCWV-FS** Flare-Seal® with PP Braid		**PCBV-FS** Static-Dissipative Flare-Seal® with PP Braid	
A-79		A-79		A-80		A-80	
NCW Convoluted with Nomex Braid		**NCB** Static-Dissipative Convoluted w/Nomex Braid		**RCTW** EPDM Rubber Covered Natural			
A-81		A-81		A-82			

For detailed ordering information, please consult price list or contact Parflex Division.

Understanding Parflex Hoses

Parflex hoses are designed to handle extremes. They are used in some of the harshest applications around, such as over-the-sheave or aerial lift, because they are specifically designed to handle extreme abrasion, temperatures, flexing, impulse and other factors that cause many hoses to fail.

Hydraulic & Pneumatic Hose Selection

Parflex offers several lines of hydraulic and pneumatic hoses; General Hydraulic, Specialty and Hybrid® hoses. Specialty hoses were designed to solve specific application problems. Hybrid® Hoses belong specifically to Parflex, with no exact competitor equivalents. These hoses were developed to cross typical SAE boundaries and meet specific challenges our customers were bringing to us. Some of these have the new, **TOUGH**JACKET™ abrasion resistant cover, offering 100x the abrasion protection of a regular polyurethane cover.

The visual index and hose pages indicate which hoses are Hybrid® and **TOUGH**JACKET™ designs.

Review the STAMPED guide (Size, Temperature, Media, Application, Pressure, End Configuration, and Delivery Preferences) on page 13 to help narrow your search for the desired product.

Fluoropolymer Selection

Parflex offers two lines of Fluoropolymer Hoses; the traditional Parflex PTFE hoses, many that meet 100R14 standards, and the PAGE hose line, comprised of specialty braid and construction options.

Hoses in PAGE product line are manufactured with materials that are compliant to the following standards:

FDA 21 CFR 177.1550
USP Class VI
ISO 10093, Sections 5, 6 10 and 11

The visual index and hose pages indicate which hoses are from the PAGE product line.

Hose Assemblies

To determine hose part numbers for assemblies use the following nomenclature pages:

- Parflex Thermoplastic Hose Assembly Nomenclature pg. A-18
- Parflex PTFE Hose Assembly Nomenclature pg. A-20
- PAGE Product Line - “True-Bore” & Convoluted Hose Assembly Nomenclature pg. A-21

How to Read the Hose Section

1	2		3		4		5		6		7
Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi/73˚F	bar/23˚C	inch	mm	lbs./ft.	kg./mtr.	
D604	1/4	6	.51	13	3,000	20.7	2.00	51	.12	.18	43/HY

Base part number example.

NOTE: The primary dimensions are in black. The metric/inch equivalents appear in blue.

1 Part Number

Hose Series Part Number - When two part numbers are listed, the second number is the static-dissipative or non-conductive design.

2 Inside Diameter

A critical value along with pressure when calculating fluid flow rate and pressure drop.

3 Outside Diameter

A critical measurement when considering hose fittings and applications where envelope size is limited.

4 Working Pressure

Working pressure rating must meet or exceed the maximum operating pressure of the system including pressure spikes.

5 Minimum Bend Radius

Minimum radius that the hose can be bent. Exceeding the bend radius can cause kinking, inner tube washout, or excessive stress on reinforcement resulting in shortened service life.

6 Weight

Provided where weight is a critical parameter in the design of the system.

7 Approved Fitting

Permanent or field attachable fitting series approved for selected hose. Products with no fitting selection are only available in factory built assemblies.

Hose Constructions

Thermoplastic Hose Construction

1. Core

Contains Media

Materials: Nylon, Polyethylene, Polyurethane, Copolyester

2. Reinforcement

Provides Resistance to Internal Pressure

Materials: Fiber (Nylon, Polyester, Aramid), Steel, Stainless Steel

3. Cover

Protects Reinforcement

Advantages: Aesthetics, Color and Marking

Materials: Polyurethane, Nylon, Synthetic Rubber, Copolyester, Polyurethane, Proprietary Blend (PFX)




Introducing, New TOUGHJACKET™ Covers

TOUGHJACKET™

Manufactured from Parflex **TOUGH**JACKET™ Polyurethane and designed to withstand the strains of demanding use. Look for the TJ - Currently found on 560TJ, 563TJ, 590TJ and 594TJ.

Fluoropolymer Hose Construction



1. Core

Contains Media

Materials: PTFE, FEP or PFA

Style: Smoothbore or Convoluted

2. Reinforcement

Provides Resistance to Internal Pressure

Materials: Steel, Stainless Steel, Polypropylene, Nomex®, Proprietary Composite

3. Cover or Protective Sleeve

Protects Reinforcement

Materials: Silicone, Polyolefin, EPDM Rubber

Nomex® is a registered trademark of E. I. du Pont de Nemours and Company.

Thermoplastic Hose Selection psi

Reinforcement Type		PSI Thermoplastic Hose Working Pressures											
		3/32	1/8	3/16	1/4	5/16	3/8	1/2	5/8	3/4	1	1 1/4	1 1/2
	Dash Size	-1.5	-2	-3	-4	-5	-6	-8	-10	-12	-16	-20	-24
	Hose / Description	psi	psi	psi	psi	psi	psi	psi	psi	psi	psi	psi	psi
Wire	CNGRP Regulated Pressure CNG								500				
	D6R/D6RX Hybrid® - Constant Pressure Hydraulic				3000	3000	3000	3000	3000	3000	3000		
	H6 Constant Pressure Hydraulic				3000	3000	3000	3000	3000	3000			
	HFSR Hybrid® - General Hydraulic				3263	3118	2611	2500		1523	1276		
	HFS2R Hybrid® - General Hydraulic				5000		4000	3500	2750	2250	2000		
	R6 Constant Pressure Hydraulic				3000		3000	3000	3000	3000	3000		
	M8 Hybrid® - High Pressure Hydraulic						4000	4000	4000				
	HTB Hybrid® - Compact High Pressure				7000		5500	5000	4000	4000	3500		
	HJK Hybrid® - Jackline				10000								
	560TJ General Hydraulic **TOUGH**JACKET™			3625	3250	3000	2750	2500	2000	1750			
	563TJ Constant Pressure **TOUGH**JACKET™				3045		3045	3045					
	590TJ General Hydraulic **TOUGH**JACKET™				5000		4000	3500		2500	2000		
	594TJ Constant Pressure **TOUGH**JACKET™				4061		4061	4061	4061				
Fiber	510A Industrial Refrigerant		2500	3000	2750	2500	2250	2000		1250	1000		
	510C General Hydraulic		2500	3250	3000	2500	2250	2250		1250	1000		
	518C Non-conductive Hydraulic		2500**	3250**	3000**	2500**	2250**	2250**		1250**	1000**		
	518D Non-conductive Hydraulic		3000**	3250**	3000**	2500**	2250**	2250**		1250**			
	515H Compact/Lightweight Hydraulic			2175	2000	1750	1500	1500					
	520N / 528N General Hydraulic / Non-conductive Hydraulic			5000	5000	4500	4000	3500	2750				
	526BA Breathing Air Refill			6000	6000		6000						
	527BA Breathing Air Refill			7000	7000								
	53DM / 538DM Low Temperature Hydraulic				3000		3000	3000	3000	3000			
	540N General Hydraulic		3000	3000	2750	2500	2250	2000		1250			
	540P Specialty Water				2750		2250	2000		1250			
	55LT Low Temperature Hydraulic		3000	3250	3000	2500	2250	2000					
	56DH / 568DH Diagnostic	6000	6000										
	575X/575XN Fast Response Hydraulic			5000	5000		5000	5000		5000	5000		
	580N / 588N General Hydraulic / Non-conductive Hydraulic							3500	2750	2250	2000		
	H580N General Hydraulic										3000		
	1035HT Power Cleaning				1750		1500						
	83FR General Purpose Air/Water				300		300	300		300			
	B9 General Purpose Transfer			250	250	250	250	250	250				
	5CNG Compressed Natural Gas				5000		5000	5000		5000	5000		
	HLB Lubrication		3000	3000									
	MSH Marine Steering					1000	1000						
	MSXL H.P. Marine Steering					1500							
	PTH Power Tilt			3000									
	S5N Sewer Cleaning - Lateral Cleaning							4000					
	S6 Sewer Cleaning									2500	2500		
	S9 Sewer Cleaning									3000	3000		
	SLH Sewer Cleaning Leader Hose							4000		3000	3000		
	Duraflex - 548N Hydraulic Hose Coil, Non-Conductive						2250						

*View Government & Agency Specifications for exceptions, pg. G-61
**View actual hose chart for ANSI pressure ratings

Legend

F - Fiber
H - Copolyester
EPDM - EPDM Rubber
UTJ - TOUGHJACKET™
N - Nylon
O - Polyethylene
S - Silicone
X - TPV
R - Smooth Synthetic Rubber
PFX - Proprietary Blend (PFX)
U - Polyurethane

For detailed ordering information, please consult price list or contact Parflex Division.

Parker Hannifin Corporation | Parflex Division | Ravenna, Ohio | **parker.com/pfd**

Construction/Specifications

PSI Thermoplastic Construction and Specifications

Core Tube	Reinforcement Material	Cover Material	SAE Specification	Additional Specifications	Page #	Description	Hose	Reinforcement Type
N	Wire	X	-	ANSI CSA NGV 3.1; NFPA 52; CSA 12.3, Class C	A-53	Regulated Pressure CNG	CNGRP	Wire
H	Wire	R	100R17	MSHA/ ISO 11237 Type R17	A-22	Hybrid® - Constant Pressure Hydraulic	D6R/D6RX	
H	Wire	H	100R17		A-25	Constant Pressure Hydraulic	H6	
H	Wire	R	100R1AT		A-23	Hybrid® - General Hydraulic	HFSR	
H	Wire	R	-	MSHA	A-24	Hybrid® - General Hydraulic	HFS2R	
H	Wire	F	100R17		A-26	Constant Pressure Hydraulic	R6	
H	Wire	R	100R19	MSHA	A-28	Hybrid® - High Pressure Hydraulic	M8	
H	Wire	R		MSHA	A-27	Hybrid® - Compact High Pressure	HTB	
H	Wire	R	-	IJ-100 / MSHA	A-29	Hybrid® - Jackline	HJK	
H	Wire	UTJ	100R1AT	MSHA, DNV	A-30	General Hydraulic **TOUGH**JACKET™	560TJ	
H	Wire	UTJ	100R17	MSHA	A-31	Constant Pressure **TOUGH**JACKET™	563TJ	
H	Wire	UTJ	100R2	MSHA, DNV	A-32	General Hydraulic **TOUGH**JACKET™	590TJ	
H	Wire	UTJ	100R19	MSHA	A-33	Constant Pressure **TOUGH**JACKET™	594TJ	
PFX	Fiber	U	100R7	MSHA*	A-34	Industrial Refrigerant	510A	Fiber
H	Fiber	PFX	100R7*	MSHA*, DNV	A-35	General Hydraulic	510C	
H	Fiber	PFX	100R7*	ANSI A92.2, DNV	A-36	Non-conductive Hydraulic	518C	
N	Fiber	PFX	100R7	ANSI A92.2, DNV	A-37	Non-conductive Hydraulic	518D	
H	Fiber	U	-	MSHA	A-38	Compact/Lightweight Hydraulic	515H	
N	Fiber	U	100R8	MSHA*, DNV	A-39	General Hydraulic / Non-conductive Hydraulic	520N/ 528N	
N	Fiber	U	-	CGA / NFPA 1901	A-40	Breathing Air Refill	526BA	
N	Fiber	U	-	CGA / NFPA 1901	A-41	Breathing Air Refill	527BA	
H	Fiber	H	100R18		A-42	Low Temperature Hydraulic	53DM / 538DM	
N	Fiber	U	100R7	MSHA, DNV	A-43	General Hydraulic	540N	
O	Fiber	U	100R7	FDA	A-44	Specialty Water	540P	
H	Fiber	H	100R7		A-45	Low Temperature Hydraulic	55LT	
N	Fiber	U	-	MSHA*	A-46	Diagnostic	56DH / 568DH	
N	Fiber	U	-	MSHA*, DNV	A-47	Fast Response Hydraulic	575X/575XN	
N	Fiber	U	100R8	MSHA, DNV	A-48	General Hydraulic / Non-conductive	580N / 588N	
N	Fiber	U	100R8	DNV	A-48	General Hydraulic	H580N	
N	Fiber	U	-		A-50	Power Cleaning	1035HT	
U	Fiber	U	UL94HB	MSHA	A-49	General Purpose Air/Water	83FR	
U	Fiber	U	-		A-51	General Purpose Transfer	B9	
N	Fiber	U	-	ANSI CSA NGV 4.2; ECE R110*; NFPA 52; CSA 12.52 Class A, Class D	A-52	Compressed Natural Gas	5CNG	
H	Fiber	U	-	MSHA	A-54	Lubrication	HLB	
N	Fiber	U	-		A-55	Marine Steering	MSH	
N	Fiber	U	-		A-56	H.P. Marine Steering	MSXL	
N	Fiber / SS Wire	U	-		A-57	Power Tilt	PTH	
N	Fiber	U	-	Wastec / NSWMN / WEMI	A-58	Sewer Cleaning - Lateral Cleaning	S5N	
H	Fiber	U	-	Wastec / NSWMN / WEMI	A-59	Sewer Cleaning	S6	
H	Fiber	U	-	Wastec / NSWMN / WEMI	A-60	Sewer Cleaning	S9	
H	Wire	R	-	Wastec / NSWMN / WEMII	A-61	Sewer Cleaning Leader Hose	SLH	
N	Fiber	U	100R7		A-62	Hydraulic Hose Coil, Non-Conductive	Duraflex - 548N	

Fluoropolymer Hose Selection psi

Reinforcement Type		PSI Fluoropolymer Hose Working Pressures														
	Fractional Size		Nominal Sizes													
			1/8	3/16 (15/64)	1/4	5/16	13/32 (7/16)	1/2	5/8	7/8 (29/32)	1-1/8	1/8	1/4	3/8	1/2	5/8
	Dash Size		-3	-4	-5	-6	-8	-10	-12	-16	-20	-3	-4	-6	-8	-10
			psi	psi	psi	psi	psi	psi	psi	psi	psi	psi	psi	psi	psi	psi
Wire	919	PTFE Hose	3000	3000	3000	2500	2000	1500	1200	1000	625					
	919B	PTFE Hose with static-dissipative core		3000	3000	2500	2000									
	919J	Silicone Covered PTFE Hose		3000	3000	2500	2000	1500	1200							
	919U	High Abrasion Resistance PTFE Hose		3000		2500	2000		1200	1000						
	929	Heavy Wall PTFE Hose		3000		2500	2000									
	929B	Heavy Wall PTFE Hose with static-dissipative core		3000		2500	2000		1200	1250						
	929BJ	Silicone Covered PTFE Hose with static-dissipative core		3000		2500	2000		1200	1250						
	939	Convoluted PTFE Hose												1500	1350	1000
	939B	Convoluted PTFE Hose with static-dissipative core												1500	1350	1000
	943B	High Pressure PTFE Hose with static-dissipative core				3000	3000	3000	3000	3000						
	944B	High Pressure PTFE Hose with static-dissipative core		4500		4500	4500	4500	4500	4000						
	950B	High Pressure PTFE Hose with static-dissipative core		4000		4000	4000	4000	4000	4000						
	955B	High Pressure PTFE Hose with static-dissipative core		5500		5500	5500	5500	5500	5500						
	STW Z-STW*	PAGE Heavy Wall PTFE Hose *Double Braid										3000	3000	2000	1750	
	STB Z-STB*	PAGE Heavy Wall PTFE Hose with static-dissipative core *Double Braid										3000	3000	2000	1750	
	SCW	PAGE Convoluted PTFE Hose											1500	1500	1500	
	SCB	PAGE Convoluted PTFE Hose with static-dissipative core											1500	1500	1500	
	SCWV	PAGE Heavy Wall Convoluted PTFE Hose													1500	
	SCBV	PAGE Heavy Wall Convoluted PTFE Hose with static-dissipative core													1500	
	SCWV-FS	PAGE Flare-Seal® PTFE Hose													500	
	SCBV-FS	PAGE Flare-Seal® PTFE Hose with static-dissipative core													500	
Fiber	PCW	PAGE Convoluted PTFE Hose, PP Braid											350	350	300	
	PCB	PAGE Convoluted PTFE Hose with static-dissipative core, PP Braid											350	350	300	
	PCWV	PAGE Heavy Wall Convoluted PTFE Hose, PP Braid													300	
	PCBV	PAGE Heavy Wall Convoluted PTFE Hose with static-dissipative core, PP Braid													300	
	PCWV-FS	PAGE Flare-Seal® PTFE Hose, PP Braid													300	
	PCBV-FS	PAGE Flare-Seal® PTFE Hose with static-dissipative core, PP Braid													300	
Other	RCTW	PAGE Rubber Covered EPDM													500	
	NCW	PAGE Nomex Braid Convoluted											725	400	280	
	NCB	PAGE Nomex Braid Convoluted with static-dissipative core											725	400	280	
	SBFW	PAGE Page-Flex™ SBF™												300	300	

*Z indicates double braid.

Legend

PTFE – Polytetrafluoroethylene
PFA – Perfluoroalkoxy
FEP – Fluorinated Ethylene Propylene
PTFE-S – Polytetrafluoroethylene, Static Dissipative
PFA-S – Perfluoroalkoxy, Static Dissipative
NB - Nomex Braid
PP - Polypropylene
S – Silicone
U – Polyurethane

For detailed ordering information, please consult price list or contact Parflex Division.

Construction/Specifications

PSI Fluoropolymer Construction and Specifications

3/4	1	1 1/4	1 1/2	2	2-1/2	3	4	Core Tube	Reinforcement Material	Cover Material	Page #	Fractional Size		Reinforcement Type
-12	-16	-20	-24	-32	-40	-48	-64					Dash Size		
psi	psi	psi	psi	psi	psi	psi	psi							
								PTFE	SS Wire	—	A-63	PTFE Hose	919	Wire Braid
								PTFE-S	SS Wire	—	A-63	PTFE Hose with static-dissipative core	919B	
								PTFE	SS Wire	S	A-64	Silicone Covered PTFE Hose	919J	
								PTFE	SS Wire	U	A-65	High Abrasion Resistance PTFE Hose	919U	
								PTFE	SS Wire	—	A-66	Heavy Wall PTFE Hose	929	
								PTFE-S	SS Wire	—	A-66	Heavy Wall PTFE Hose with static-dissipative core	929B	
								PTFE-S	SS Wire	S	A-67	Silicone Covered PTFE Hose with static-dissipative core	929BJ	
1100	1000	1000	750	250				PTFE	SS Wire	—	A-68	Convoluted PTFE Hose	939	
1100	1000	1000	1000	1000				PTFE-S	SS Wire	—	A-68	Convoluted PTFE Hose with static-dissipative core	939B	
								PTFE-S	SS Wire	—	A-69	High Pressure PTFE Hose with static-dissipative core	943B	
								PTFE-S	SS Wire	—	A-70	High Pressure PTFE Hose with static-dissipative core	944B	
								PTFE-S	SS Wire	—	A-71	High Pressure PTFE Hose with static-dissipative core	950B	
								PTFE-S	SS Wire	—	A-72	High Pressure PTFE Hose with static-dissipative core	955B	
1000	1000 1200*	1000*	900*					PTFE	SS Wire	—	A-73	PAGE Heavy Wall PTFE Hose *Double Braid	STW Z-STW*	
1000	1000 1200*	1000*	900*					PTFE-S	SS Wire	—	A-73	PAGE Heavy Wall PTFE Hose with static-dissipative core *Double Braid	STB Z-STB*	
1200	1000	750	650	450				PTFE	SS Wire	—	A-75	PAGE Convoluted PTFE Hose	SCW	
1200	1000	750	650	450				PTFE-S	SS Wire	—	A-75	PAGE Convoluted PTFE Hose with static-dissipative core	SCB	
1200	1000	750	650	450	200	175	150	PTFE	SS Wire	—	A-77	PAGE Heavy Wall Convoluted PTFE Hose	SCWV	
1200	1000	750	650	450	200	175	150	PTFE-S	SS Wire	—	A-77	PAGE Heavy Wall Convoluted PTFE Hose with static-dissipative core	SCBV	
425	350	325	300	250	200	175	150	PTFE	SS Wire	—	A-79	PAGE Flare-Seal® PTFE Hose	SCWV-FS	
425	350	325	300	250	200	175	150	PTFE-S	SS Wire	—	A-79	PAGE Flare-Seal® PTFE Hose with static-dissipative core	SCBV-FS	
250	250	200	200	200	200	200	200	PTFE	PP	—	A-76	PAGE Convoluted PTFE Hose, PP Braid	PCW	Fiber
250	250	200	200	200	200	200	200	PTFE-S	PP	—	A-76	PAGE Convoluted PTFE Hose with static-dissipative core, PP Braid	PCB	
250	250	200	200	200	150	125	100	PTFE	PP	—	A-78	PAGE Heavy Wall Convoluted PTFE Hose, PP Braid	PCWV	
250	250	200	200	200	150	125	100	PTFE-S	PP	—	A-78	PAGE Heavy Wall Convoluted PTFE Hose with static-dissipative core, PP Braid	PCBV	
250	250	200	200	200	150	125	100	PTFE	PP	—	A-80	PAGE Flare-Seal® PTFE Hose, PP Braid	PCWV-FS	
250	250	200	200	200	150	125	100	PTFE-S	PP	—	A-80	PAGE Flare-Seal® PTFE Hose with static-dissipative core, PP Braid	PCBV-FS	
500	450	375	375	300	200	200	150	FEP	Double Wire Helix	EPDM	A-82	PAGE Rubber Covered EPDM	RCTW	Other
200	200							PTFE	NB	—	A-81	PAGE Nomex® Braid Convoluted	NCW	
200	200							PTFE-S	NB	—	A-81	PAGE Nomex® Braid Convoluted with static-dissipative core	NCB	
250	250		200					PFA	Bonded Wire-Silicone-Fiber	—	A-74	PAGE Page-Flex™ SBF™	SBFW	

Nomex® is a registered trademark of E. I. du Pont de Nemours and Company.

For detailed ordering information, please consult price list or contact Parflex Division.

Thermoplastic Hose Selection MPa

Reinforcement Type		MPaThermoplastic Hose Working Pressures											
		3/32	1/8	3/16	1/4	5/16	3/8	1/2	5/8	3/4	1	1 1/4	1 1/2
	Dash Size	-1.5	-2	-3	-4	-5	-6	-8	-10	-12	-16	-20	-24
	Hose / Description	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa
Wire	CNGRP Regulated Pressure CNG								3.45				
	D6R/D6RX Hybrid® - Constant Pressure Hydraulic				21.0	21.0	21.0	21.0	21.0	21.0	21.0		
	H6 Constant Pressure Hydraulic				20.7	20.7	20.7	20.7	20.7	20.7			
	HFSR Hybrid® - General Hydraulic				22.5	21.5	18.0	17.2		10.5	8.8		
	HFS2R Hybrid® - General Hydraulic				34.5		27.6	24.1	19.0	15.5	13.7		
	R6 Constant Pressure Hydraulic				20.7		20.7	20.7	20.7	20.7	20.7		
	M8 Hybrid® - High Pressure Hydraulic						27.6	27.6	27.6				
	HTB Hybrid® - Compact High Pressure				48.3		37.9	34.5	27.6	27.6	24.1		
	HJK Hybrid® - Jackline				69.0								
	560TJ General Hydraulic **TOUGH**JACKET™			25.0	22.4	20.6	19.0	17.2	13.7	12.0			
	563TJ Constant Pressure **TOUGH**JACKET™				21.0		21.0	21.0					
	590TJ General Hydraulic **TOUGH**JACKET™				34.5		27.6	24.1		17.2	13.8		
	594TJ Constant Pressure **TOUGH**JACKET™				28.0		28.0	28.0	28.0				
Fiber	510A Industrial Refrigerant		17.2	20.7	19.0	17.2	15.5	13.7		8.6	6.9		
	510C General Hydraulic		17.2	22.4	20.7	17.2	15.5	15.5		8.6	6.9		
	518C Non-conductive Hydraulic		17.2**	22.4**	21.0**	17.2**	15.5**	15.5**		8.7**	6.9**		
	518D Non-conductive Hydraulic		21.0**	22.4**	20.7**	17.2**	15.5**	15.5**		8.7**			
	515H Compact/Lightweight Hydraulic			15.0	13.8	12.0	10.3	10.3					
	520N / 528N General Hydraulic / Non-conductive Hydraulic			34.5	34.5	31.0	27.6	24.1	19.0				
	526BA Breathing Air Refill			41.4	41.4		41.4						
	527BA Breathing Air Refill			48.3	48.3								
	53DM / 538DM Low Temperature Hydraulic				20.7		20.7	20.7	20.7	20.7			
	540N General Hydraulic		20.7	20.7	19.0	17.2	15.5	13.8		8.6			
	540P Specialty Water				19.0		15.5	13.8		8.6			
	55LT Low Temperature Hydraulic		20.7	22.4	20.7	17.2	15.5	13.8					
	56DH / 568DH Diagnostic	41.4	41.4										
	575X/575XN Fast Response Hydraulic			34.5	34.5		34.5	34.5		34.5	34.5		
	580N / 588N General Hydraulic / Non-conductive Hydraulic							24.1	19.0	15.5	13.8		
	H580N General Hydraulic										20.7		
	1035HT Power Cleaning				12.1		10.3						
	83FR General Purpose Air/Water				2.1		2.1	2.1		2.1			
	B9 General Purpose Transfer			1.7	1.7	1.7	1.7	1.7	1.7				
	5CNG Compressed Natural Gas				34.5		34.5	34.5		34.5	34.5		
	HLB Lubrication		20.7	20.7									
	MSH Marine Steering					6.9	6.9						
	MSXL H.P. Marine Steering					10.3							
	PTH Power Tilt			20.7									
	S5N Sewer Cleaning - Lateral Cleaning							27.6					
	S6 Sewer Cleaning									17.2	17.2		
	S9 Sewer Cleaning									20.7	20.7		
	SLH Sewer Cleaning Leader Hose							27.6		20.7	20.7		
	Duraflex - 548N Hydraulic Hose Coil, Non-Conductive						15.5						

*View Government & Agency Specifications for exceptions, pg. G-61
**View actual hose chart for ANSI pressure ratings

Legend

F - Fiber
H - Copolyester
EPDM - EPDM Rubber
UTJ - TOUGHJACKET™
N - Nylon
O - Polyethylene
S - Silicone
X - TPV
R - Smooth Synthetic Rubber
PFX - Proprietary Blend (PFX)
U - Polyurethane

For detailed ordering information, please consult price list or contact Parflex Division.

Parker Hannifin Corporation | Parflex Division | Ravenna, Ohio | **parker.com/pfd**

Construction/Specifications

MPA Thermoplastic Construction and Specifications

Core Tube	Reinforcement Material	Cover Material	SAE Specification	Additional Specifications	Page #	Description	Hose	Reinforcement Type
N	Wire	X	-	ANSI CSA NGV 3.1; NFPA 52; CSA 12.3, Class C	A-53	Regulated Pressure CNG	CNGRP	Wire
H	Wire	R	100R17	MSHA/ ISO 11237 Type R17	A-22	Hybrid® - Constant Pressure Hydraulic	D6R/D6RX	
H	Wire	H	100R17		A-25	Constant Pressure Hydraulic	H6	
H	Wire	R	100R1AT		A-23	Hybrid® - General Hydraulic	HFSR	
H	Wire	R	-	MSHA	A-24	Hybrid® - General Hydraulic	HFS2R	
H	Wire	F	100R17		A-26	Constant Pressure Hydraulic	R6	
H	Wire	R	100R19	MSHA	A-28	Hybrid® - High Pressure Hydraulic	M8	
H	Wire	R		MSHA	A-27	Hybrid® - Compact High Pressure	HTB	
H	Wire	R	-	IJ-100 / MSHA	A-29	Hybrid® - Jackline	HJK	
H	Wire	UTJ	100R1AT	MSHA, DNV	A-30	General Hydraulic **TOUGH**JACKET™	560TJ	
H	Wire	UTJ	100R17	MSHA	A-31	Constant Pressure **TOUGH**JACKET™	563TJ	
H	Wire	UTJ	100R2	MSHA, DNV	A-32	General Hydraulic **TOUGH**JACKET™	590TJ	
H	Wire	UTJ	100R19	MSHA	A-33	Constant Pressure **TOUGH**JACKET™	594TJ	
PFX	Fiber	U	100R7	MSHA*	A-34	Industrial Refrigerant	510A	Fiber
H	Fiber	PFX	100R7*	MSHA*, DNV	A-35	General Hydraulic	510C	
H	Fiber	PFX	100R7*	ANSI A92.2, DNV	A-36	Non-conductive Hydraulic	518C	
N	Fiber	PFX	100R7	ANSI A92.2, DNV	A-37	Non-conductive Hydraulic	518D	
H	Fiber	U	-	MSHA	A-38	Compact/Lightweight Hydraulic	515H	
N	Fiber	U	100R8	MSHA*, DNV	A-39	General Hydraulic / Non-conductive Hydraulic	520N/ 528N	
N	Fiber	U	-	CGA / NFPA 1901	A-40	Breathing Air Refill	526BA	
N	Fiber	U	-	CGA / NFPA 1901	A-41	Breathing Air Refill	527BA	
H	Fiber	H	100R18		A-42	Low Temperature Hydraulic	53DM / 538DM	
N	Fiber	U	100R7	MSHA, DNV	A-43	General Hydraulic	540N	
O	Fiber	U	100R7	FDA	A-44	Specialty Water	540P	
H	Fiber	H	100R7		A-45	Low Temperature Hydraulic	55LT	
N	Fiber	U	-	MSHA*	A-46	Diagnostic	56DH / 568DH	
N	Fiber	U	-	MSHA*, DNV	A-47	Fast Response Hydraulic	575X/575XN	
N	Fiber	U	100R8	MSHA, DNV	A-48	General Hydraulic / Non-conductive	580N / 588N	
N	Fiber	U	100R8	DNV	A-48	General Hydraulic	H580N	
N	Fiber	U	-		A-50	Power Cleaning	1035HT	
U	Fiber	U	UL94HB	MSHA	A-49	General Purpose Air/Water	83FR	
U	Fiber	U	-		A-51	General Purpose Transfer	B9	
N	Fiber	U	-	ANSI CSA NGV 4.2; ECE R110*; NFPA 52; CSA 12.52 Class A, Class D	A-52	Compressed Natural Gas	5CNG	
H	Fiber	U	-	MSHA	A-54	Lubrication	HLB	
N	Fiber	U	-		A-55	Marine Steering	MSH	
N	Fiber	U	-		A-56	H.P. Marine Steering	MSXL	
N	Fiber / SS Wire	U	-		A-57	Power Tilt	PTH	
N	Fiber	U	-	Wastec / NSWMN / WEMI	A-58	Sewer Cleaning - Lateral Cleaning	S5N	
H	Fiber	U	-	Wastec / NSWMN / WEMI	A-59	Sewer Cleaning	S6	
H	Fiber	U	-	Wastec / NSWMN / WEMI	A-60	Sewer Cleaning	S9	
H	Wire	R	-	Wastec / NSWMN / WEMII	A-61	Sewer Cleaning Leader Hose	SLH	
N	Fiber	U	100R7		A-62	Hydraulic Hose Coil, Non-Conductive	Duraflex - 548N	

Fluoropolymer Hose Selection MPa

Reinforcement Type			MPa Fluoropolymer Hose Working Pressures														
		Fractional Size	Nominal Sizes														
			1/8	3/16 (15/64)	1/4	5/16	13/32 (7/16)	1/2	5/8	7/8 (29/32)	1-1/8	1/8	1/4	3/8	1/2	5/8	
		Dash Size	-3	-4	-5	-6	-8	-10	-12.1	-16	-20	-3	-4	-6	-8	-10.3	
			MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa	
Wire	919	PTFE Hose	20.7	20.7	20.7	17.2	13.8	10.3	8.3	6.9	4.3						
	919B	PTFE Hose with static-dissipative core		20.7	20.7	17.2	13.8										
	919J	Silicone Covered PTFE Hose		20.7	20.7	17.2	13.8	10.3	8.3								
	919U	High Abrasion Resistance PTFE Hose		20.7		17.2	13.8		8.3	6.9							
	929	Heavy Wall PTFE Hose		20.7		17.2	13.8										
	929B	Heavy Wall PTFE Hose with static-dissipative core		20.7		17.2	13.8		8.3	9							
	929BJ	Silicone Covered PTFE Hose with static-dissipative core		20.7		17.2	13.8		8.3	9							
	939	Convoluted PTFE Hose												10.3	9.3	6.9	
	939B	Convoluted PTFE Hose with static-dissipative core												10.3	9.3	6.9	
	943B	High Pressure PTFE Hose with static-dissipative core				20.7	20.7	20.7	20.7	20.7							
	944B	High Pressure PTFE Hose with static-dissipative core		31.0		31.0	31.0	31.0	31.0	27.5							
	950B	High Pressure PTFE Hose with static-dissipative core		27.5		27.5	27.5	27.5	27.5	27.5							
	955B	High Pressure PTFE Hose with static-dissipative core		37.9		37.9	37.9	37.9	37.9	37.9							
	STW Z-STW*	PAGE Heavy Wall PTFE Hose *Double Braid										20.7	20.7	13.8	12.1		
	STB Z-STB*	PAGE Heavy Wall PTFE Hose with static-dissipative core *Double Braid										20.7	20.7	13.8	12.1		
	SCW	PAGE Convoluted PTFE Hose											10.3	10.3	10.3		
	SCB	PAGE Convoluted PTFE Hose with static-dissipative core											10.3	10.3	10.3		
	SCWV	PAGE Heavy Wall Convoluted PTFE Hose													10.3		
	SCBV	PAGE Heavy Wall Convoluted PTFE Hose with static-dissipative core													10.3		
	SCWV-FS	PAGE Flare-Seal® PTFE Hose													3.5		
	SCBV-FS	PAGE Flare-Seal® PTFE Hose with static-dissipative core													3.5		
Fiber	PCW	PAGE Convoluted PTFE Hose, PP Braid											2.4	2.4	2.1		
	PCB	PAGE Convoluted PTFE Hose with static-dissipative core, PP Braid											2.4	2.4	2.1		
	PCWV	PAGE Heavy Wall Convoluted PTFE Hose, PP Braid													2.1		
	PCBV	PAGE Heavy Wall Convoluted PTFE Hose with static-dissipative core, PP Braid													2.1		
	PCWV-FS	PAGE Flare-Seal® PTFE Hose, PP Braid													2.1		
	PCBV-FS	PAGE Flare-Seal® PTFE Hose with static-dissipative core, PP Braid													2.1		
Other	RCTW	PAGE Rubber Covered EPDM													3.5		
	NCW	PAGE Nomex Braid Convoluted											725	400	280		
	NCB	PAGE Nomex Braid Convoluted with static-dissipative core											725	400	280		
	SBFW	PAGE Page-Flex™ SBF™												2.1	2.1		

*Z indicates double braid.

Legend

PTFE – Polytetrafluoroethylene
PFA – Perfluoroalkoxy
FEP – Fluorinated Ethylene Propylene
PTFE-S – Polytetrafluoroethylene, Static Dissipative
PFA-S – Perfluoroalkoxy, Static Dissipative
NB - Nomex Braid
PP - Polypropylene
S – Silicone
U – Polyurethane

For detailed ordering information, please consult price list or contact Parflex Division.

Construction/Specifications

MPA Fluoropolymer Construction and Specifications

3/4	1	1 1/4	1 1/2	2	2-1/2	3	4	Core Tube	Reinforcement Material	Cover Material	Page #	Fractional Size		Reinforcement Type
-12.	-16	-20	-24	-32	-40	-48	-64					Dash Size		
MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa							
								PTFE	SS Wire	—	A-63	PTFE Hose	919	Wire Braid
								PTFE-S	SS Wire	—	A-63	PTFE Hose with static-dissipative core	919B	
								PTFE	SS Wire	S	A-64	Silicone Covered PTFE Hose	919J	
								PTFE	SS Wire	U	A-65	High Abrasion Resistance PTFE Hose	919U	
								PTFE	SS Wire	—	A-66	Heavy Wall PTFE Hose	929	
								PTFE-S	SS Wire	—	A-66	Heavy Wall PTFE Hose with static-dissipative core	929B	
								PTFE-S	SS Wire	S	A-67	Silicone Covered PTFE Hose with static-dissipative core	929BJ	
7.6	6.9	6.9	5.2	1.7				PTFE	SS Wire	—	A-68	Convoluted PTFE Hose	939	
7.6	6.9	6.9	5.2	1.7				PTFE-S	SS Wire	—	A-68	Convoluted PTFE Hose with static-dissipative core	939B	
								PTFE-S	SS Wire	—	A-69	High Pressure PTFE Hose with static-dissipative core	943B	
								PTFE-S	SS Wire	—	A-70	High Pressure PTFE Hose with static-dissipative core	944B	
								PTFE-S	SS Wire	—	A-71	High Pressure PTFE Hose with static-dissipative core	950B	
								PTFE-S	SS Wire	—	A-72	High Pressure PTFE Hose with static-dissipative core	955B	
6.9	6.9 8.3*	6.9*	6.2*					PTFE	SS Wire	—	A-73	PAGE Heavy Wall PTFE Hose *Double Braid	STW Z-STW*	
6.9	6.9 8.3*	6.9*	6.2*					PTFE-S	SS Wire	—	A-73	PAGE Heavy Wall PTFE Hose with static-dissipative core *Double Braid	STB Z-STB*	
8.3	6.9	5.2	4.5	3.1				PTFE	SS Wire	—	A-75	PAGE Convoluted PTFE Hose	SCW	
8.3	6.9	5.2	4.5	3.1				PTFE-S	SS Wire	—	A-75	PAGE Convoluted PTFE Hose with static-dissipative core	SCB	
8.3	6.9	5.2	4.5	3.1	1.4	1.2	1.0	PTFE	SS Wire	—	A-77	PAGE Heavy Wall Convoluted PTFE Hose	SCWV	
8.3	6.9	5.2	4.5	3.1	1.4	1.2	1.0	PTFE-S	SS Wire	—	A-77	PAGE Heavy Wall Convoluted PTFE Hose with static-dissipative core	SCBV	
2.9	2.4	2.2	2.1	1.7	1.4	1.2	1.0	PTFE	SS Wire	—	A-79	PAGE Flare-Seal® PTFE Hose	SCWV-FS	
2.9	2.4	2.2	2.1	1.7	1.4	1.2	1.0	PTFE-S	SS Wire	—	A-79	PAGE Flare-Seal® PTFE Hose with static-dissipative core	SCBV-FS	
1.7	1.7	1.4	1.4	1.4	1.4	1.4	1.4	PTFE	PP	—	A-76	PAGE Convoluted PTFE Hose, PP Braid	PCW	Fiber
1.7	1.7	1.4	1.4	1.4	1.4	1.4	1.4	PTFE-S	PP	—	A-76	PAGE Convoluted PTFE Hose with static-dissipative core, PP Braid	PCB	
1.7	1.7	1.4	1.4	1.4	1.0	.86	.69	PTFE	PP	—	A-78	PAGE Heavy Wall Convoluted PTFE Hose, PP Braid	PCWV	
1.7	1.7	1.4	1.4	1.4	1.0	.86	.69	PTFE-S	PP	—	A-78	PAGE Heavy Wall Convoluted PTFE Hose with static-dissipative core, PP Braid	PCBV	
1.7	1.7	1.4	1.4	1.4	1.0	.86	.69	PTFE	PP	—	A-80	PAGE Flare-Seal® PTFE Hose, PP Braid	PCWV-FS	
1.7	1.7	1.4	1.4	1.4	1.0	.86	.69	PTFE-S	PP	—	A-80	PAGE Flare-Seal® PTFE Hose with static-dissipative core, PP Braid	PCBV-FS	
3.5	3.1	2.6	2.6	2.1	1.4	1.4	1.0	FEP	Double Wire Helix	EPDM	A-82	PAGE Rubber Covered EPDM	RCTW	Other
200	200							PTFE	NB	—	A-81	PAGE Nomex® Braid Convoluted	NCW	
200	200							PTFE-S	NB	—	A-81	PAGE Nomex® Braid Convoluted with static-dissipative core	NCB	
1.7	1.7		1.4					PFA	Bonded Wire-Silicone-Fiber	—	A-74	PAGE Page-Flex™ SBF™	SBFW	

Nomex® is a registered trademark of E. I. du Pont de Nemours and Company.

For detailed ordering information, please consult price list or contact Parflex Division.

Parflex Thermoplastic Hoses

Parflex Thermoplastic Hose Assembly Nomenclature



F	540N	06	39	12	12	12	-	52

F – Prefix

F – Parkrimp
(i.e. 56 series)

A – Factory Crimp
(i.e. 54 series)

R – Field Attachable
(i.e. 51 series)

540N – Hose

1035HT	563TJ	HFS2R
510A	56DH/568DH	HJK
510C	575X/575XN	HLB
515H	580N	HTB
518C	588N	M8
518D	590TJ	MSH
520N	594TJ	MSXL
526BA	5CNG	PTH
527BA	83FR	R6
528N	B9	S5N
53DM/538DM	CNGRP	S6
540N	D6R/D6RX	S9
540P	H580N	SLH
55LT	H6	
560TJ	HFSR	

06-39 – Fitting Configuration*

01 – Male Pipe Thread (with hex) - NPTF
02 – Female Pipe Thread - NPT
03 – Male SAE (JIC) 37° Flare
05 – Male Straight Thread w/ O-Ring
06 – Female SAE (JIC) 37° Swivel
07 – Female Pipe Swivel
13 – Male Pipe Swivel - NPTF
37 – Female SAE (JIC) 37° Swivel - 45° Elbow
39 – Female SAE (JIC) 37° Swivel - 90° Elbow
41 – Female SAE (JIC) 37° Swivel - 90° Long Elbow
JC – Female Seal-Lok™ (ORFS) Swivel Short
FU – Female JIC/BSP 30° Flare Swivel
MU – Metric Female JIC/BSP 30° Flare Swivel
JO – Male Seal-Lok™ (ORFS) Rigid Strt w/O-Ring
GU – Female JIC/BSP Parallel Pipe Swive (60° Cone)
JS – Female Seal-Lok™ (ORFS) Swivel
J7 – Female Seal-Lok™ (ORFS) Swivel - 45° Elbow
J9 – Female Seal-Lok™ (ORFS) Swivel - 90° Elbow
TU – Universal Tube Stub
AL – A-Lok® Compression

* See pg. E-4 for detailed list of available fitting configurations.



For detailed ordering information, please consult price list or contact Parflex Division.

12 Connection Size 1

-2	=	1/8
-3	=	3/16
-4	=	1/4
-5	=	5/16
-6	=	3/8
-8	=	1/2
-10	=	5/8
-12	=	3/4
-16	=	1
-20	=	1-1/4

12 Connection Size 2

-2	=	1/8
-3	=	3/16
-4	=	1/4
-5	=	5/16
-6	=	3/8
-8	=	1/2
-10	=	5/8
-12	=	3/4
-16	=	1
-20	=	1-1/4

12 Hose Size

-2	=	1/8
-3	=	3/16
-4	=	1/4
-5	=	5/16
-6	=	3/8
-8	=	1/2
-10	=	5/8
-12	=	3/4
-16	=	1

C Fitting Material

** No Material Designation, Steel

C = Stainless Steel

B = Brass


52 Overall Length

Expressed in inches

NOTE: Face Seal type fittings are measured from sealing face.

Displacement Angle

Specified only if two elbow fittings are used to construct hose assembly.*



*Starting with either end as the far end, measure the angle clockwise to describe the displacement of the near end.



Parflex PTFE Hoses

Parflex PTFE Hose Assembly Nomenclature



P	919	06	39	06	06	06	C	-	30

P – Prefix

P – Permanent Crimp
(i.e. 91N series)

R – Field Attachable
(i.e. 90 series)

Factory Crimp
(i.e. 94 series)

919 – Hose

Natural	Static Dissipative
919	919B
919J	929BJ
919U	–
929	929B
939	939B
–	943B
	944B
–	950B
	955B

06-39 – Fitting Configuration*

01 – Male Pipe Thread (with hex) - NPTF
02 – Female Pipe Thread - NPT
03 – Male SAE (JIC) 37° Flare
05 – Male Straight Thread w/ O-Ring
06 – Female SAE (JIC) 37° Swivel
07 – Female Pipe Swivel
37 – Female SAE (JIC) 37° Swivel - 45° Elbow
39 – Female SAE (JIC) 37° Swivel - 90° Elbow
41 – Female SAE (JIC) 37° Swivel - 90° Long Elbow
JC – Female Seal-Lok™ (ORFS) Swivel Short
FU – Female JIC/BSP 30° Flare Swivel
MU – Metric Female JIC/BSP 30° Flare Swivel
GU – Female JIC/BSP Parallel Pipe Swive (60° Cone)
JS – Female Seal-Lok™ (ORFS) Swivel
J7 – Female Seal-Lok™ (ORFS) Swivel - 45° Elbow
J9 – Female Seal-Lok™ (ORFS) Swivel - 90° Elbow
TU – Universal Tube Stub
AL – A-Lok® Compression

* See pg. E-4 for detailed list of available fitting configurations.

06 – Connection Size 1

-4	=	1/4
-5	=	5/16
-6	=	3/8
-8	=	1/2
-10	=	5/8
-12	=	3/4
-16	=	1
-20	=	1-1/4
-24	=	1-1/2
-32	=	2

06 – Connection Size 2

-4	=	1/4
-5	=	5/16
-6	=	3/8
-8	=	1/2
-10	=	5/8
-12	=	3/4
-16	=	1
-20	=	1-1/4
-24	=	1-1/2
-32	=	2

06 – Hose Size

-4	=	1/4
-5	=	5/16
-6	=	3/8
-8	=	1/2
-10	=	5/8
-12	=	3/4
-16	=	1
-20	=	1-1/4
-24	=	1-1/2
-32	=	2

C – Fitting Material

** No Material Designation

C = Stainless Steel

B = Brass (91N)

S = All Steel (91N)

30 – Overall Length


Expressed in Inches

OAL measured from centerline of fitting seat if elbow fittings are used.

NOTE: Face Seal type fittings are measured from sealing face.

– Displacement Angle


Specified only if two elbow fittings are used to construct hose assembly.*



*Starting with either end as the far end, measure the angle clockwise to describe the displacement of the near end.

For detailed ordering information, please consult price list or contact Parflex Division.

"True-Bore" & Convoluted Hose Assembly Nomenclature



32		J	03	C	13	C	0	–	0	1	2	0	–		
Size Code	Z for Double Braid	Hose Code	Fitting End 1	Fitting Material End 1	Fitting End 2	Fitting Material End 2	Flange Material		Length in Inches					Length in 1/8" increments	Accessory Code

Size Code	
1/4"	04
5/16"	05
3/8"	06
1/2"	08
5/8"	10
3/4"	12
7/8"	14
1"	16
1-1/4	20
1-1/2"	24
2"	32
2-1/2"	40
3"	48
4"	64

Hose Code	
STW	STB
SCW	SCB
SCWV	SCBV
SCWV-FS	SCBV-FS
SBFW	-
NCW	NCB
PCW	PCB
PCWV	PCBV
PCWV-FS	PCBV-FS
RCTW	-

Fitting Code	
Industrial Thread	
Male Pipe NPT Hex	03
Female Pipe NPT Hex	06
Male Pipe NPT Step Down	13
Male Pipe NPT Step Up	23
Male Union Step Up	34
Male Union Step Down	35
JIC Female Swivel	30
Male JIC 37°	31
JIC Female Step Up	32
Male Union	33
Female Union	36
Female NPSH	27
Female ORFS Swivel	80
Male ORFS	81
Male O-Ring Boss	86
Flanges	
Flange Retainer	05
Flare-Seal® Flange Retainer	29
Cam Lock	
Female Cam Lock	07
With Locking Handles	17
Male Cam Lock	08
Sanitary	
Sanitary Tri Clamp	40
Sanitary Tri Clamp 45°	4K
Sanitary Tri Clamp 90°	4L
Sanitary 1-Step Up	4A
Sanitary 2-Step Up	4B
Sanitary 3-Step Up	4C
Sanitary Flare Seal™	4F
Sanitary Mini	42
Sanitary Mini Step Up	43
I-Line Male	48
I-Line Female	49
Bevel Seat Female	45
Bevel Seat Male	46
Tube and Vacuum	
PAGElok™ Tube Adapter	38
PAGElok™ Tube Compression Fitting	39
Special Ends	
Standard Cuffed Ends	90
Non Standard Fitting	99

Fitting Material	
304 Stainless (SS 304)	4
316 Stainless (SS 316)	6
316 Stainless (SS 15Ra) Electropolished to 15Ra	E
Carbon Steel	C
PFA Encapsulated	T
Hastelloy	H
Monel	M

Flange Material	
None	0
Carbon Steel Epoxy Coated	D
304SS	4
316SS	6
Kynar	K
Polypropylene	P
Non Standard	X

Accessory Code	
None	
Spring Guard	S
Armour Guard	A
End Bend Restrictors	E
Fire Sleeve	F
Rubber Sleeve	H
FEP Heat Shrink	T
Polyolefin Heat Shrink	P
Silicone Sleeve	M
Vacuum Spring Wire	W
Specials	X

Example: 32J03C13C0-0120-A
Size: 2" **Style:** SCWV
Braid: 316 SS Single Braid
Core: Heavy Wall Open Pitch Convoluted PTFE
End 1: 2" Male Pipe NPT Hex
End 2: 2" Male Pipe NPT Step Down

Length: 120" from end of Male NPT to end of Male Step Down

NOTE: Length calculations for PAGE hose assemblies are typically made sealing surface to sealing surface per the NAHAD Fluoropolymer Hose Assembly Specification Guidelines unless otherwise requested by customer at time of order.

The part numbering system shows the entire product line offered by the Parker PAGE International business unit. This catalog section only displays a few common hoses.

For detailed ordering information, please consult price list or contact Parflex Division.

D6R/D6RX – Hybrid® Hose



Features

- Up to 40% lighter than comparable rubber hoses
- Wide range of fluid compatibility
- Compact hose construction
- Bend radius less than half of conventional SAE 100R1AT & 100R2 hoses
- UV resistant cover
- Low force to flex
- 3,000 psi working pressure

Applications/Markets



- Medium pressure hydraulic applications
- Agricultural Equipment
- Construction Equipment
- Lubricating Oils
- Transportation

Certifications

- Meets/Exceeds ISO 11237 Type R17 Pressure requirements
- Meets/Exceeds SAE 100R17 Performance
- MSHA accepted

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./m.	
D6R04*	1/4	6	.46	12	3,000	21.0	1.50	38	0.10	0.14	56
D6R05	5/16	8	.52	13	3,000	21.0	1.75	44	0.12	0.18	56
D6R06*	3/8	10	.61	16	3,000	21.0	2	51	0.17	0.25	56
D6R08*	1/2	13	.76	19	3,000	21.0	3	76	0.26	0.38	56
D6R10	5/8	16	.97	25	3,000	21.0	3.50	89	0.43	0.64	56
D6R12	3/4	19	1.14	29	3,000	21.0	4.25	108	0.71	1.06	56
D6R16	1	25	1.45	37	3,000	21.0	6	152	0.91	1.36	56

Construction

Tube: Copolyester

Reinforcement: High Tensile Steel Wire

Cover: Smooth Synthetic Rubber

Operating Parameters

Temperature Range:

- Petroleum base hydraulic fluids and lubricating oils within a temperature range -40°F (-40°C) to +250°F (121°C)
- Synthetic, synthetic blend, water, and water/oil emulsion hydraulic fluids limited to +135°F (+57°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +2% to -4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

56 Series – pg. E-10

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Color

● Black

Notes

* X designates a continuous, long length reel (ie D6RX04)

HFSR Hybrid® Hose with Rubber Cover



Features

- Up to 40% lighter than comparable rubber hoses
- Wide range of fluid compatibility
- Compact hose construction
- Bend radius less than half of conventional SAE 100R1AT & 100R2 hoses
- UV resistant cover
- Low force to flex

Certifications

- Meets/Exceeds SAE 100R1AT Performance
- Meets/Exceeds ISO 1436 Type 1SN Pressure requirements

Applications/Markets



- Industrial
- Construction
- Waste & Refuse
- Utility Equipment
- Paving and road maintenance

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi@73°C	MPa@23°F	inch	mm	lbs./ft.	kg./m.	
HFSR04	1/4	6	.46	12	3,263	22.5	1.50	38	0.10	0.14	56
HFSR05	5/16	8	.52	13	3,118	21.5	1.75	45	0.12	0.18	56
HFSR06	3/8	10	.61	16	2,611	18.0	2	51	0.17	0.25	56
HFSR08	1/2	13	.74	19	2,500	17.2	3	76	0.21	0.32	56
HFSR12	3/4	19	1.02	26	1,523	10.5	4.25	108	0.31	0.46	56
HFSR16	1	25	1.31	33	1,276	8.8	7.50	191	0.44	0.66	56

Construction

Tube: Copolyester

Reinforcement: High Tensile Steel Wire

Cover: Smooth Synthetic Rubber

Operating Parameters

Temperature Range:

- Petroleum base hydraulic fluids and lubricating oils within a temperature range -40°F (-40°C) to +250°F (121°C)
- Synthetic, synthetic blend, water, and water/oil emulsion hydraulic fluids limited to +185°F (+85°C)
- Water/glycol hydraulic fluids limited to +135°F (+57°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +2% to -4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

56 Series – pg. E-10

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Color

● Black

HFS2R – Fire-Screen II® Hybrid® Hose



Features

- Up to 40% lighter than comparable rubber hoses
- Wide range of fluid compatibility
- Compact hose construction
- Bend radius less than half of conventional SAE 100R1AT & 100R2 hoses
- UV resistant cover
- Low force to flex

Certifications

- MSHA Accepted

Applications/Markets



- Medium pressure hydraulic applications
- Mobile Equipment
- Machine Tools
- Agricultural Equipment

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
HFS2R04	1/4	6	.49	12	5,000	34.5	2.00	51	.21	.31	56
HFS2R06	3/8	10	.64	16	4,000	27.6	2.50	64	.23	.34	56
HFS2R08	1/2	13	.76	19	3,500	24.1	3.50	89	.29	.43	56
HFS2R10	5/8	16	.93	24	2,750	19.0	4.00	102	.38	.57	56
HFS2R12	3/4	19	1.07	27	2,250	15.5	4.75	121	.45	.67	56
HFS2R16	1	25	1.40	35	2,000	13.8	6.00	152	.80	1.19	56

Construction

Tube: Copolyester

Reinforcement: One or two braids of High Tensile Steel Wire

Cover: Smooth Synthetic Rubber

Operating Parameters

Temperature Range:

- Petroleum base hydraulic fluids and lubricating oils within a temperature range -40°F (-40°C) to +212°F (100°C)
- Synthetic, synthetic blend, water, and water/oil emulsion hydraulic fluids limited to +185°F (+85°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +2% to -4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

56 Series – pg. E-10

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

● Black

For detailed ordering information, please consult price list or contact Parflex Division.

H6 – Hydraulic Hose, Constant Pressure 3,000 psi



Features

- Largest temperature range in a medium pressure hydraulic hose
- Low length change under pressure

Certifications

- Meets/Exceeds SAE 100R17 Performance

Applications/Markets



- Medium pressure hydraulic applications
- Over-the-sheave and boom hose applications

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
H604	1/4	6	.49	12	3,000	20.7	2.00	51	.12	.18	56
H605	5/16	8	.56	14	3,000	20.7	2.25	57	.14	.21	HY
H606	3/8	10	.65	17	3,000	20.7	2.50	64	.19	.28	56
H608	1/2	13	.78	20	3,000	20.7	3.50	89	.29	.43	56
H610*	5/8	16	1.00	25	3,000	20.7	4.00	102	.47	.70	HY
H612*	3/4	19	1.17	30	3,000	20.7	4.75	121	.69	1.03	HY

Construction

Tube: Copolyester

Reinforcement: One or two braids of High Tensile Steel Wire

Cover: Abrasion-resistant Copolyester

Operating Parameters

Temperature Range:

- (H604 thru H608) -70°F (-57°C) to +250°F (121°C)
  (H610 thru H612) -50°F (-45°C) to +250°F (121°C)
- Synthetic, synthetic blend, water, and water/oil emulsion hydraulic fluids limited to +135°F (+57°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +2% to -4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

56 Series – pg. E-10 HY Series

HY Series - Available from Parker Hose Products Division

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

● Black

Notes

- *Two wire braid, Non-perforated cover
- Twin line hose available
- Preformed assemblies
- Non-Perforated Cover

R6 – Abrasion King® Hose, Constant Pressure 3,000 psi



Features

- Light weight
- Excellent flexibility
- Excellent abrasion resistance
- Blue plait provides hose identification

Certifications

- Meets/Exceeds SAE 100R17 Performance

Applications/Markets

- Medium pressure hydraulic applications
- Agricultural Equipment

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
R604	1/4	6	.53	13	3000	20.7	2.00	51	.11	.16	HY
R606	3/8	10	.69	18	3000	20.7	2.50	64	.20	.30	HY
R608	1/2	13	.84	21	3000	20.7	3.50	89	.27	.40	HY
R610*	5/8	16	1.09	28	3000	20.7	4.00	102	.51	.76	HY
R612*	3/4	19	1.24	31	3000	20.7	4.75	121	.71	1.06	HY
R616*	1	25	1.55	39	3000	20.7	6.00	152	1.00	1.49	43

Construction

Tube: Copolyester

Reinforcement: One or two braids of High Tensile Steel Wire

Cover: Abrasion-resistant Nylon Fabric

Operating Parameters

Temperature Range:

- (R604 thru R610) -50°F (-45°C) to +250°F (121°C)
  (R612 thru R616) -50°F (-45°C) to +212°F (100°C)
- Synthetic, synthetic blend, water, and water/oil emulsion hydraulic fluids limited to +135°F (+57°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +2% to -4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

HY Series 43 Series

Fittings available from Parker Hose Products Division

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

● Black

Notes

*Two wire braid

For detailed ordering information, please consult price list or contact Parflex Division.

HTB – Eliminator® Hybrid® Hose



Features

- Four-spiral wire hose performance in a high tensile two-wire braid construction
- Excellent flexibility
- Compact design

Certifications

- MSHA Accepted

Applications/Markets



- High-pressure hydraulic applications typically reserved for spiral wire reinforced hoses

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
HTB04*	1/4	6	.62	16	7,000	48.3	4.00	102	.27	.40	HY
HTB06	3/8	10	.76	19	5,500	37.9	6.00	152	.37	.55	43
HTB08	1/2	13	.90	23	5,000	34.5	7.00	178	.46	.68	43
HTB10	5/8	16	1.03	26	4,000	27.6	8.00	203	.52	.77	43
HTB12	3/4	20	1.20	30	4,000	27.6	9.50	241	.73	1.09	43
HTB16	1	25	1.50	38	3,500	24.1	12.00	305	1.01	1.50	43

Construction

Tube: Copolyester

Reinforcement: Two braids of High Tensile Steel Wire

Cover: Smooth Synthetic Rubber

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +212°F (100°C)
- Synthetic, synthetic blend, water, and water/oil emulsion hydraulic fluids limited to +135°F (+57°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +2% to -4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°)

Fittings

HY Series 43 Series

Fittings available from Parker Hose Products Division

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Color

● Black

Notes

*Factory-made assemblies only 04

M8 – E-Z FLEX™ Hybrid® Hose



Features

- Four-spiral wire hose performance in a high tensile two-wire braid construction
- Excellent flexibility
- Compact design

Certifications

- Meets/Exceeds SAE 100R19 Performance
- MSHA Accepted

Applications/Markets



- Medium pressure hydraulic applications
- Agricultural Equipment
- Construction Equipment
- Construction Equipment
- Lubricating Oils
- Transportation

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
M806	3/8	10	.76	19	4,000	27.6	2.50	64	.37	.55	43
M808	1/2	13	.90	23	4,000	27.6	3.50	89	.46	.68	43
M810	5/8	16	1.07	27	4,000	27.6	4.00	102	.63	.94	43

Construction

Tube: Copolyester

Reinforcement: Two braids of High Tensile Steel Wire

Cover: Smooth Synthetic Rubber

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +250°F (121°C)
- Synthetic, synthetic blend, water, and water/oil emulsion hydraulic fluids limited to +135°F (+57°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +2% to -4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

43 Series - Available from Parker Hose Products Division

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

● Black

For detailed ordering information, please consult price list or contact Parflex Division.

HJK – Highjack® Jackline Hybrid® Hose



Features

- 10,000 psi Jack Hose

Certifications

- MSHA Accepted
- Meets I J-100 Requirements

Applications/Markets

- Used for high pressure jack line applications
- Not for high impulse applications

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight	
#									lbs	kg
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.
HJK04	1/4	6	.62	16	10,000	69	4.0	102	.27	.40

Construction

Tube: Copolyester

Reinforcement: Two braids of High Tensile Steel Wire

Cover: Smooth Synthetic Rubber

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +150°F (65°C)
- Synthetic, synthetic blend, water, and water/oil emulsion hydraulic fluids limited to +135°F (+57°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

HY Series - Available from Parker Hose Products Division

Connection configurations limited to: Male Pipe (01)

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

● Black

Notes

Factory-made assemblies only

560TJ – TOUGHJACKET™ SAE 100R1AT Hydraulic Hose



TOUGHJACKET™

Features

- Twin or multi-line available. Lighter and smaller than 100R1AT with longer lengths
- Fast response hose
- Polyurethane cover for best abrasion resistance

Certifications

- Meets/Exceeds SAE 100R1AT Performance
- MSHA Accepted

Applications/Markets



- Hydraulic circuits and systems wherever 100R1AT hose is specified
- Industrial equipment
- Machine Tools

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
560TJ-3	3/16	5	0.39	10	3,626	25.0	0.75	19	.07	.11	56
560TJ-4	1/4	6	0.47	12	3,263	22.5	1.50	38	.09	.14	56
560TJ-5	5/16	8	0.53	13	3,118	21.5	1.75	44	.11	.16	56
560TJ-6	3/8	10	0.61	16	2,750	19.0	2.00	51	.14	.21	56
560TJ-8	1/2	13	0.75	19	2,500	17.2	3.00	76	.19	.29	56
560TJ-10	5/8	16	0.93	24	2,000	13.8	4.00	102	.31	.47	56
560TJ-12	3/4	19	1.04	26	1,750	12.1	4.25	108	.28	.42	56

Construction

Tube: Copolyester

Reinforcement: High Tensile Steel Wire Braid

Cover: Polyurethane TOUGHJACKET™

Operating Parameters

Temperature Range:

- Petroleum base hydraulic fluids and lubricating oils within a temperature range -40°F (-40°C) to +250°F (121°C)
- Synthetic, synthetic blend, water, and water/oil emulsion hydraulic fluids limited to +185°F (+85°C)
- Water/glycol hydraulic fluids limited to +135°F (+57°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

56 Series – pg. E-10

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

● Black

Notes

Non-perforated cover

563TJ – TOUGHJACKET™ SAE 100R17 Hydraulic Hose
3,000 psi Constant Working Pressure



TOUGHJACKET™

Features

- Low length change under pressure makes it an ideal solution for boom or cable track applications where long lengths are required
- 2%-5% smaller O.D. than comparable 100R17 hoses
- 23%-42% lighter than comparable 100R17 hose
- Excellent flexibility
- Consistent long-lengths

Certifications

- Meets/Exceeds SAE 100R17 Performance
- MSHA Accepted

Applications/Markets



- Medium pressure hydraulic applications
- Agricultural Equipment
- Construction Equipment
- Lubricating Oils
- Transportation

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
563TJ-4	1/4	6.3	0.47	11.9	3,045	21.0	1.50	38	0.09	0.14	56
563TJ-6	3/8	10	0.64	16.3	3,045	21.0	2.00	51	0.19	0.29	56
563TJ-8	1/2	13	076	19.3	3,045	21.0	2.75	70	0.24	0.36	56

Construction

Tube: Copolyester

Reinforcement: High Tensile Steel Wire Braid

Cover: Polyurethane TOUGHJACKET™

Operating Parameters

Temperature Range:

- Petroleum base hydraulic fluids and lubricating oils within a temperature range -40°F (-40°C) to +250°F (121°C)
- Synthetic, synthetic blend, water, and water/oil emulsion hydraulic fluids limited to +185°F (+85°C)
- Water/glycol hydraulic fluids limited to +135°F (+57°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +/-1%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

56 Series – pg. E-10

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

● Black

Notes

Non-perforated cover

590TJ – TOUGHJACKET™ SAE 100R2 Hydraulic Hose



TOUGHJACKET™

Features

- Two wire strength, one wire construction, improved bend radius results
- Twin and multi-line available
- Polyurethane cover for best abrasion resistance

Certifications

- Meets/Exceeds SAE 100R2 Performance
- MSHA Accepted

Applications/Markets



- Construction Equipment
- Machine Tools
- Hydrostatic Transmission
- Refuse Vehicles
- Agriculture Equipment

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
590TJ-4*	1/4	6	.53	13	5,000	34.5	1.75	44	.14	.21	56
590TJ-6*	3/8	10	.65	17	4,000	27.6	2.25	57	.20	.30	56
590TJ-8*	1/2	13	.78	20	3,500	24.1	3.25	82	.26	.38	56
590TJ-12	3/4	19	1.08	28	2,500	17.2	4.72	120	.39	.58	43
590TJ-16	1	25	1.43	36	2,000	13.8	8.00	203	.59	.88	43

Construction

Tube: Copolyester

Reinforcement: Aramid Fiber, High Tensile Steel Wire Braid

Cover: Polyurethane TOUGHJACKET™

Operating Parameters

Temperature Range:

- Petroleum base hydraulic fluids and lubricating oils within a temperature range -40°F (-40°C) to +250°F (121°C)
- * Synthetic, synthetic blend, water, and water/oil emulsion hydraulic fluids limited to +185°F (+85°C)
- Water/glycol hydraulic fluids limited to +135°F (+57°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

56 Series – pg. E-10 43 Series

43 Series – Available from Parker Hose Products Division

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

● Black

Notes5

Non-perforated cover

For detailed ordering information, please consult price list or contact Parflex Division.

594TJ – TOUGHJACKET™ SAE 100R19 Hydraulic Hose
4,000 psi Constant Working Pressure



TOUGHJACKET™

Features

- Four-spiral wire hose performance in a high tensile two-wire braid construction
- Excellent flexibility
- Consistent long-lengths

Certifications

- Meets/Exceeds SAE 100R19 Performance
- MSHA Accepted

Applications/Markets



- Medium pressure hydraulic applications
- Agricultural Equipment
- Construction Equipment
- Lubricating Oils
- Transportation

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
594TJ-4*	1/4	6.3	0.49	12.5	4,061	28.0	1.75	45	0.13	0.20	56
594TJ-6*	3/8	10	0.72	18.2	4,061	28.0	2.50	65	0.31	0.46	56
594TJ-8*	1/2	13	0.85	21.5	4,061	28.0	3.50	90	0.39	0.58	43
594TJ-10	5/8	16	1.04	26.4	4,061	28.0	3.94	100	0.59	0.88	43

Construction

Tube: Copolyester

Reinforcement: Two Braids of High Tensile Steel Wire

Cover: Polyurethane TOUGHJACKET™

Operating Parameters

Temperature Range:

- Petroleum base hydraulic fluids and lubricating oils within a temperature range -40°F (-40°C) to +250°F (121°C)
- * Synthetic, synthetic blend, water, and water/oil emulsion hydraulic fluids limited to +185°F (+85°C)
- Water/glycol hydraulic fluids limited to +135°F (+57°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

56 Series – pg. E-10 43 Series

43 Series – Available from Parker Hose Products Division

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

● Black

Notes

Non-perforated cover

510A – Refrigerant Hose



Features

- Excellent impulse life
- Compatible with most common hydraulic and refrigeration media

Certifications

- Meets/Exceeds SAE 100R7 except -2
- MSHA Accepted except -4, -5, -6

Applications/Markets



- Industrial and mobile refrigeration systems

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series	Field Attachable Series
#									lbs	kg		
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.		
510A-2	1/8	3	.34	9	2,500	17.2	0.50	13	.03	.05	56	–
510A-3	3/16	5	.43	11	3,000	20.7	2.00	51	.05	.07	56	51
510A-4	1/4	6	.47	12	2,750	19.0	2.50	64	.05	.08	56	51
510A-5	5/16	8	.57	14	2,500	17.2	3.00	76	.08	.12	56	51
510A-6	3/8	10	.64	16	2,250	15.5	4.00	102	.08	.13	56	51
510A-8	1/2	13	.81	21	2,000	13.8	5.50	140	.13	.20	56	51
510A-12	3/4	19	1.10	28	1,250	8.6	7.50	191	.19	.29	–	51
510A-16	1	25	1.40	36	1,000	6.9	10.00	254	.28	.41	–	51

Construction

Tube: Proprietary Nylon Blend
Reinforcement: Fiber
Cover: Polyurethane

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +212°F (100°C)

Vacuum Rating: 28 inch Hg
Change in length at Max. Working Pressure: +/-3%
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

56 Series – pg. E-10 51 Series – pg. E-5

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

● Black

Notes

- Perforated cover
- 51 Series field attachable couplings are not intended for use on hose that has previously been in service

510C – General Hydraulic Hose



Features

- Excellent abrasion resistance
- Excellent flexibility
- Medium pressure service for permanent and field attachable fittings

Certifications

- Meets/Exceeds SAE 100R7 except -2
- MSHA Accepted except -4

Applications/Markets



- Industrial hydraulic systems
- Mobile hydraulic systems
- On-highway hydraulics systems (car carriers & trailers)

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series	Field Attachable Series
#									lbs	kg		
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.		
510C-2	1/8	3	.34	9	2,500	17.2	0.50	13	.03	.05	56	–
510C-3	3/16	5	.43	11	3,250	22.4	0.75	19	.05	.07	56	51*
510C-4	1/4	6	.47	12	3,000	20.7	1.50	38	.05	.08	56	51*
510C-5	5/16	8	.57	14	2,500	17.2	1.75	44	.08	.11	56	51
510C-6	3/8	10	.64	16	2,250	15.5	2.00	51	.10	.14	56	51
510C-8	1/2	13	.81	21	2,250	15.5	3.00	76	.15	.22	56	51
510C-12	3/4	19	1.09	28	1,250	8.7	5.00	127	.21	.31	56	51
510C-16	1	25	1.32	34	1,000	6.9	8.00	203	.27	.40	56	51

Construction

Tube: Copolyester

Reinforcement: Fiber

Cover: Proprietary Blend (PFX)

Operating Parameters

Temperature Range:

- 40°F (-40°C) to +212°F (100°C)
- Synthetic, synthetic blend, water, and water/oil emulsion hydraulic fluids limited to +135°F (+57°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

56 Series – pg. E-10 51 Series – pg. E-5

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

● Black

Notes

- Perforated cover
- *3/16" and 1/4" working pressure reduced to 3,000 and 2,750 psi respectively when using field attachable couplings
- 51 Series field attachable couplings are not intended for use on hose that has previously been in service

518C – Non-Conductive Hose



Features

- Twin or multi-line constructions available
- High density braid for maximum impulse life without loss of flexibility

Certifications

- Meets SAE J517 for less than 50 micro-amps leakage under 75,000 volts per ft.
- Meets/Exceeds SAE 100R7 specifications and Electrical Standards except 518C-2 with respect to maximum working pressure
- ANSI A92.2

Applications/Markets



- Medium pressure hydraulic service where hydraulic circuit exposure and contact with high voltage may be encountered
- Aerial lift equipment
- Hydraulic tools where exposure to high voltage may be encountered

Part Number	Nominal I.D.		Maximum O.D.		ANSI A92.2 Max. Working Pressure		SAE 100R7 Max. Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series	Field Attachable Series
#											lbs	kg		
	inch	mm	inch	mm	psi	MPa	psi	MPa	inch	mm	lbs./ft.	kg./mtr.		
518C-2	1/8	3	.34	9	3,150	21.7	2,500	17.2	0.50	13	.03	.05	56	–
518C-3	3/16	5	.43	11	3,250	22.4	3,250	22.4	0.75	19	.05	.07	56	51*
518C-4	1/4	6	.47	12	3,150	21.7	3,000	21.0	1.50	38	.05	.08	56	51*
518C-5	5/16	8	.57	14	3,150	21.7	2,500	17.2	1.75	44	.08	.11	56	51
518C-6	3/8	10	.64	16	3,000	20.7	2,250	15.5	2.00	51	.10	.14	56	51
518C-8	1/2	13	.81	21	3,000	20.7	2,250	15.5	3.00	76	.15	.22	56	51
518C-12	3/4	19	1.09	28	1,660	11.4	1,250	8.7	5.00	127	.21	.31	56	51
518C-16	1	25	1.32	34	1,330	9.2	1,000	6.9	8.00	203	.27	.40	56	51

Construction

Tube: Copolyester

Reinforcement: Fiber

Cover: Proprietary Blend (PFX)

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +212°F (100°C)
- Synthetic, synthetic blend, water, and water/oil emulsion hydraulic fluids limited to +135°F (+57°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure: (SAE requires 4:1 Design Factor)

- 4:1 Design Factor is required if hose failure will result in movement of aerial device
- 3:1 Design Factor is acceptable if hose failure will not result in movement of aerial device

Fittings

56 Series – pg. E-10 51 Series– pg. E-5

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

Orange

Notes

- Non-perforated cover
- Lay lines on this hose will have both ANSI and SAE maximum working pressure listed. ANSI A92.2 "Vehicle Mounted Elevating and Rotating Aerial Devices"
- *3/16" and 1/4" working pressure reduced to 3,000 and 2,750 psi respectively when using field attachable couplings
- 51 Series field attachable couplings are not intended for use on hose that has previously been in service

For detailed ordering information, please consult price list or contact Parflex Division.

518D – Non-Conductive Hose



Features

- Nylon core for maximum resistance to permeable fluids.
- 518D-4 offers heavier polyurethane jacket improving abrasion resistance and ease of splitting bonded constructions
- Super high density braid allows smaller braid O.D. (518D-4)
- Twin or multi-line constructions available.

Certifications

- Meets SAE J517 for less than 50 micro-amps leakage under 75,000 volts per ft.
- Meets/Exceeds SAE 100R7
- ANSI A92.2

Applications/Markets



- Medium pressure hydraulic service where hydraulic circuit exposure and contact with high voltage may be encountered
- Aerial lift equipment
- Hydraulic tools where exposure to high voltage may be encountered

Part Number	Nominal I.D.		Maximum O.D.		ANSI A92.2 Max. Working Pressure 73°F/ 23°C		SAE 100R7 Max. Working Pressure 73°F/ 23°C		Minimum Bend Radius		Weight		Permanent Fitting Series
#											lbs	kg	
	inch	mm	inch	mm	psi	MPa	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
518D-2	1/8	3	.34	9	3,150	21.7	3,000	21.0	0.50	13	.03	.05	56
518D-3	3/16	5	.43	11	3,250	22.4	3,250	22.4	0.75	19	.05	.07	56
518D-4	1/4	6	.47	12	3,150	21.7	3,000	20.7	1.50	38	.06	.09	56
518D-5	5/16	8	.57	14	3,150	21.7	2,500	17.2	1.75	44	.08	.11	56
518D-6	3/8	10	.64	16	3,000	20.7	2,250	15.5	2.00	51	.10	.14	56
518D-8	1/2	13	.81	21	3,000	20.7	2,250	15.5	3.00	76	.15	.22	56
518D-12	3/4	19	1.09	28	1,660	11.4	1,250	8.7	5.00	127	.21	.31	56

Construction

Tube: Nylon

Reinforcement: Fiber

Cover: Proprietary Blend (PFX)

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +212°F (100°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure: (SAE requires 4:1 Design Factor)

- 4:1 Design Factor is required if hose failure will result in movement of aerial device
- 3:1 Design Factor is acceptable if hose failure will not result in movement of aerial device

Fittings

56 Series – pg. E-10

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

Orange

Notes

- Non-perforated cover
- Lay lines on this hose will have both ANSI and SAE maximum working pressure listed. ANSI A92.2 "Vehicle Mounted Elevating and Rotating Aerial Devices"

515H – Compact/Light Weight Hose



Features

- Twin or multi-line available
- Compact O.D., light weight, flexible
- Special order colors for system color coding

Certifications

- MSHA Accepted

Applications/Markets



- Hydraulic and pneumatic systems where a small O.D. hose is necessary
- Pilot Lines
- Joystick Controls

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
515H-3*	3/16	5	.34	9	2,175	15.0	0.75	19	.03	.04	54
515H-4	1/4	6	.41	10	2,000	13.8	1.50	38	.04	.05	54
515H-5*	5/16	8	.49	12	1,750	12.0	1.75	44	.05	.07	54
515H-6	3/8	10	.56	14	1,500	10.3	2.00	51	.05	.08	54
515H-8*	1/2	13	.71	18	1,500	10.3	3.00	76	.11	.16	54

Construction

Tube: Copolyester

Reinforcement: Fiber

Cover: Polyurethane

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +212°F (100°C)
- Synthetic, synthetic blend, water, and water/oil emulsion hydraulic fluids limited to +135°F (+57°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

54 Series – pg. E-7

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

● Black

Notes

- *Factory-made assemblies only -3, -5 and -8
- Approved with rapid assembly fitting system
- Perforated cover

For detailed ordering information, please consult price list or contact Parflex Division.

520N/528N – General Hydraulic Hose



Features

- Twin and multi-line available
- Fast response, lighter and smaller O.D. than 100R2 hose

Certifications

- Meets/Exceeds SAE 100R8
- 520N MSHA Accepted
- 528N Meets SAE J517 for less than 50 micro-amps leakage under 75,000 volts per foot

Applications/Markets



- Hydraulic and pneumatic circuits and systems
- Hydraulic tool applications
- Ideal in hot water applications

Part Number		Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#	#									lbs	kg	
Natural	Non-Conductive	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
520N-3	528N-3	3/16	5	.43	11	5,000	34.5	1.50	38	.05	.07	56
520N-4	528N-4	1/4	6	.51	13	5,000	34.5	2.00	51	.07	.10	56
520N-5	528N-5	5/16	8	.57	14	4,500	31.0	2.50	64	.08	.12	56
520N-6	528N-6	3/8	10	.65	17	4,000	27.6	2.50	64	.08	.13	56
520N-8	528N-8	1/2	13	.81	21	3,500	24.1	4.00	102	.14	.20	56
-	528N-10	5/8	16	.92	23	2,750	19.0	6.00	152	.17	.25	56

Construction

Tube: Nylon

Reinforcement: Aramid Fiber

Cover: Polyurethane

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +212°F (100°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

56 Series – pg. E-10

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

- Black
- Orange (Non-Conductive)

Notes

- Perforated cover - 520N
- Non-perforated cover - 528N

526BA – Breathing Air Refill Hose



Features

- 6000 psi Constant Pressure

Certifications (Complies with:)

- CGA G7.1-1 Grade E Breathing Air Standards
- NFPA 1901

Applications/Markets

- Integrated containment fill stations
- Mobile and stationary systems with or without cascade controls
- Mobile Trailer/Truck Systems
- Portable SCBA Fill

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
526BA-3	3/16	5	.42	11	6,000	41.4	1.50	38	.05	.07	CG
526BA-4	1/4	6	.50	13	6,000	41.4	2.00	51	.07	.10	CG
526BA-6	3/8	10	.64	16	6,000	41.4	3.00	76	.09	.13	CG

Construction

Tube: Nylon

Reinforcement: Aramid Fiber

Cover: Polyurethane

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +180°F (82°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

CG Series – pg. E-53

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

Gray

Notes

- Perforated cover
- Not for use as part of a SCBA systems
- This hose is not for use between a pressure reducing regulator and breathing mask
- For fitting attachment lubricate only with water or non-toxic lubricant. Do not assemble with petroleum or hydrocarbon based lubricants. Do not flush with solvents of any kind
- This hose does not contain a conductive element; therefore, it should not be used with explosive gases such as pure oxygen and hydrogen
- Hose is compliant with CGA Grade E Breathing Air Standards, however air quality is dependent upon all system components

527BA – Breathing Air Refill Hose



Features

- 7000 psi constant pressure

Certifications (Complies with:)

- CGA G7.1-1 Grade E Breathing Air Standards
- NFPA 1901

Applications/Markets

- Integrated containment fill stations
- Mobile and stationary systems with or without cascade controls
- Mobile Trailer/Truck Systems
- Portable SCBA Fill

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#											
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
527BA-3	3/16	5	.43	11	7,000	48.3	1.50	38	.05	.07	CG
527BA-4	1/4	6	.52	13	7,000	48.3	2.00	51	.07	.11	CG

Construction

Tube: Nylon

Reinforcement: Aramid Fiber

Cover: Polyurethane

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +180°F (82°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

CG Series – pg. E-53

Connection configurations limited to:
-Male Pipe (01)
-Female Pipe (02)
-Male JIC (03, 3E)
-Female JIC Swivel (06, 37, 39, 41, L9)

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

Blue

Notes

- Perforated cover
- Not for use as part of a SCBA systems
- This hose is not for use between a pressure reducing regulator and breathing mask
- For fitting attachment lubricate only with water or non-toxic lubricant. Do not assemble with petroleum or hydrocarbon based lubricants. Do not flush with solvents of any kind
- This hose does not contain a conductive element; therefore, it should not be used with explosive gases such as pure oxygen and hydrogen
- Hose is compliant with CGA Grade E Breathing Air Standards, however air quality is dependent upon all system components

53DM/538DM – DuraMax™ Low Temperature



Features

- Low coefficient of friction cover
- Superior flexibility in cold temperature applications
- Better bend radius than SAE J517 and 100R7
- Smaller O.D. than 100R7 and 100R18
- 3000 psi constant pressure

Certifications

- Meets/Exceeds SAE 100R18
- 538DM Meets SAE J517 for less than 50 micro-amps leakage under 75,000 volts per foot

Applications/Markets



- Excellent over-the-sheave in lift truck applications
- Cold storage or refrigerated areas
- Construction and agriculture equipment in cold climates

Part Number		Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#	#									lbs	kg	
Natural	Non-Conductive	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
53DM-4	538DM-4	1/4	6	.49	12	3,000	20.7	1.25	32	.07	.10	56
53DM-6	538DM-6	3/8	10	.66	17	3,000	20.7	2.00	51	.11	.16	56
53DM-8	538DM-8	1/2	13	.84	21	3,000	20.7	3.50	89	.17	.26	56
53DM-10	538DM-10	5/8	16	1.03	26	3,000	20.7	4.00	102	.22	.33	56
53DM-12	-	3/4	19	1.13	29	3,000	20.7	6.50	165	.26	.39	CG

Construction

Tube: Copolyester
Reinforcement: Fiber
Cover: Copolyester

Operating Parameters

Temperature Range:

- -70°F (-57°C) to +212°F (100°C)
- Water/glycol hydraulic fluids limited to +135°F (+57°C)

Vacuum Rating: 28 inch Hg
Change in length at Max. Working Pressure: +/-2%
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

56 Series – pg. E-10 CG Series – pg. E-53

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

- Black
- Orange (Non-Conductive)

Notes

- Perforated cover - 53DM
- Non-perforated cover - 538DM

For detailed ordering information, please consult price list or contact Parflex Division.

540N – General Hydraulic Hose



Features

- Matte cover for low coefficient of friction
- Special order colors
- Twin or multi-line available
- Excellent chemical compatibility
- Good chemical compatibility

Certifications

- Meets/Exceeds SAE 100R7
- MSHA Accepted

Applications/Markets



- Hydraulic and pneumatic systems
- Agricultural Spraying
- Polyurethane Foam Mixers
- Hot Water

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#											
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
540N-2	1/8	3	.34	9	3,000	20.7	0.50	13	.03	.05	56
540N-3	3/16	5	.44	11	3,000	20.7	0.75	19	.04	.06	56
540N-4	1/4	6	.50	13	2,750	19.0	1.50	38	.07	.10	56
540N-5	5/16	8	.58	15	2,500	17.2	1.75	44	.07	.10	56
540N-6	3/8	10	.65	17	2,250	15.5	2.00	51	.09	.13	56
540N-8	1/2	13	.81	21	2,000	13.8	3.00	76	.13	.19	56
540N-12	3/4	19	1.05	27	1,250	8.6	6.00	152	.17	.25	56

Construction

Tube: Nylon

Reinforcement: Fiber

Cover: Polyurethane

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +212°F (100°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

56 Series – pg. E-10

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

● Black

Notes

Perforated cover

540P – Specialty Water Hose



Features

- Plasticizer free non-leaching core tube
- Low-moisture permeability

Certifications

- Meets/Exceeds SAE 100R7
- Core tube compliant with FDA Title 21

Applications/Markets



- Potable water delivery to remote sites
- Distilled and de-ionized water
- Polyurethane Foam Mixers
- Inert gas transfer

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
540P-4	1/4	6	.50	13	2,750	19.0	1.25	32	.05	.08	56
540P-6	3/8	10	.65	17	2,250	15.5	2.00	51	.09	.13	56
540P-8	1/2	13	.81	21	2,000	13.8	3.00	76	.13	.19	56
540P-12	3/4	19	1.05	27	1,250	8.6	5.00	127	.19	.28	56

Construction

Tube: Polyethylene

Reinforcement: Fiber

Cover: Polyurethane

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +150°F (66°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

56 Series – pg. E-10

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

Aqua

Notes

Perforated cover

55LT – Low Temperature Hose



Features

- Twin and multi-line available
- Superior flexibility in cold temperature applications

Certifications

- Meets/Exceeds SAE 100R7

Applications/Markets



- Hydraulic systems exposed to very low temperatures
- Excellent over-the-sheave in lift truck applications
- Cold storage or refrigerated areas
- Construction and agriculture equipment in cold climates

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
55LT-2	1/8	3	.34	9	3,000	20.7	0.50	13	.03	.05	56
55LT-3	3/16	5	.43	11	3,250	22.4	0.75	19	.05	.08	56
55LT-4	1/4	6	.51	13	3,000	20.7	1.25	32	.07	.10	56
55LT-5	5/16	8	.57	14	2,500	17.2	1.75	44	.09	.13	56
55LT-6	3/8	10	.66	17	2,250	15.5	2.00	51	.10	.14	56
55LT-8	1/2	13	.81	21	2,000	13.8	3.00	76	.14	.21	56

Construction

Tube: Copolyester

Reinforcement: Fiber

Cover: Copolyester

Operating Parameters

Temperature Range:

- -70°F (-57°C) to +212°F (100°C)
- Water/glycol hydraulic fluids limited to +135°F (+57°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

56 Series – pg. E-10

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

● Black

Notes

Perforated cover

56DH/568DH – Diagnostic Hose



Features

- Twin or multi-line available
- Compact O.D.
- Light weight
- Flexible

Certifications

- MSHA Accepted for -2 only

Applications/Markets



- Hydraulic and pneumatic systems where a small O.D. hose is necessary
- Diagnostic hydraulic lines

Part Number		Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#	#									lbs	kg	
Natural	Non-Conductive	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
56DH-1.5	568DH-1.5	.09	2	.20	5	6,000	41.4	0.25	6	.02	.01	SF
56DH-2	568DH-2	.14	4	.32	8	6,000	41.4	0.50	13	.03	.05	CY

Construction

Tube: Nylon
Reinforcement: Aramid Fiber
Cover: Polyurethane

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +200°F (93°C)

Vacuum Rating: 28 inch Hg
Change in length at Max. Working Pressure: +/-2%
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

CY Series - pg. E-59 SF Series - pg. E-64

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

- Black
- Orange (Non-Conductive)

Notes

- Perforated cover - 56DH
- Non-perforated cover - 568DH

For detailed ordering information, please consult price list or contact Parflex Division.

575X/575XN – Fast Response Hose



Features

- Light weight
- Low change in length under pressure
- Low volumetric expansion
- Fast response even over longer lengths
- 5000 psi constant pressure

Certifications

- MSHA Accepted for 575X only

Applications/Markets



- Marine, offshore drilling
- Applications requiring fast and accurate response time

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
575X-3	3/16	5	.43	11	5,000	34.5	1.50	38	.05	.07	CG
575X-4	1/4	6	.51	13	5,000	34.5	2.00	51	.07	.10	CG
575X-6	3/8	10	.64	16	5,000	34.5	3.00	76	.09	.13	CG
575XN-8	1/2	13	.81	21	5,000	34.5	4.00	102	.14	.21	CG
575X-12	3/4	19	1.15	29	5,000	34.5	8.00	203	.24	.36	CG
575X-16	1	25	1.59	40	5,000	34.5	10.00	254	.48	.70	CG

Construction

Tube: Nylon

Reinforcement: Fiber

Cover: Polyurethane; 575XN -8 Nylon

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +212°F (100°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

CG Series - pg. E-53

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

● Black

Notes

Non-perforated cover

580N/H580N/588N – High Pressure Hose



Features

- Twin and multi-line available
- Lighter weight and smaller O.D. than 100R2

Certifications

- Meets/Exceeds SAE 100R8
- 580N MSHA Approved
- 588N Meets SAE J517 for less than 50 micro-amps leakage under 75,000 volts per foot

Applications/Markets



- Hydraulic and pneumatic circuits and systems

Part Number		Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#	#									lbs	kg	
Natural	Non-Conductive	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
580N-8	588N-8*	1/2	13	.89	23	3,500	24.1	4.00	102	.21	.31	56
580N-10	588N-10*	5/8	16	.98	25	2,750	19.0	6.00	152	.21	.31	56
580N-12	588N-12*	3/4	19	1.15	29	2,250	15.5	8.00	203	.23	.35	56
580N-16	588N-16*	1	25	1.47	37	2,000	13.8	10.00	254	.38	.56	56
H580N-16*	-	1	25	1.58	40	3,000	20.7	10.00	254	.53	.79	CG

Construction

Tube: Nylon
Reinforcement: Fiber
Cover: Polyurethane

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +212°F (100°C)

Vacuum Rating: 28 inch Hg
Change in length at Max. Working Pressure: +/-2%
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

CG Series – pg. E-53

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-1

Colors

- Black
- Orange (Non-Conductive)

Notes

- Perforated cover - 580N
- *Non-perforated cover -588N, H580N-16

For detailed ordering information, please consult price list or contact Parflex Division.

83FR – DuraGard™ General Purpose Polyurethane



Features

- Weld spatter resistant
- Excellent abrasion resistance
- Excellent flexibility
- Compact bend radius
- Specially Formulated Polyurethane tube
- Twin-line or multi-line constructions available

Certifications

- MSHA Accepted
- Non-conductive per SAE J343 test procedures for thermoplastic hose
- UL94HB compliant

Applications/Markets



- General purpose air and water hose often used in robotic welding applications

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series	Push-Lok Fitting*
#									lbs	kg		
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.		
83FR-4	1/4	6	.48	12	300	2.1	1.00	25	.05	.07	56	82*
83FR-6	3/8	10	.60	15	300	2.1	2.00	51	.08	.11	56	82*
83FR-8	1/2	13	.76	19	300	2.1	2.50	64	.12	.17	56	82*
83FR-12	3/4	19	1.04	26	300	2.1	3.50	89	.19	.28	56	82*

Construction

Tube: Specially Formulated Polyurethane

Reinforcement: Fiber

Cover: Polyurethane

Operating Parameters

Temperature Range:

- -20°F (-29°C) to +200°F (93°C)

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

56 Series – pg. E-10

82 Series – Available from Parker Hose Products Division

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

- Black (BLK)
- Blue (BLU)
- Brown (BRN)
- Green (GRN)
- Gray (GRA)
- Red (RED)

Notes

- *Temperature and pressure reduced with 82 series Push-Lok Fitting:
  -20°F (-29°C) to +145°F (+63°C)
  175 psi maximum working pressure
- Non-perforated cover

1035HT – High Temperature Power Cleaning



Features

- Non-marring
- Broad temperature range

Applications/Markets

- Pressure Washers (low pressure)
- Carpet Cleaning

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
1035HT-4	1/4	6	.50	13	1,750	12.1	1.50	38	.06	.08	56
1035HT-6	3/8	10	.65	17	1,500	10.3	2.00	51	.09	.13	56

Construction

Tube: Nylon

Reinforcement: Fiber

Cover: Polyurethane

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +230°F (110°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

56 Series – pg. E-10

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

Yellow

Notes

- Perforated cover
- No chlorinated solvents should be used
- Also available with a blue jacket (1035HT-4-BLU) upon request
- HBR (Hose Bend Restrictor) suggested for carpet cleaning applications - See Hose Guard in Tooling Equipment and Accessories Section pg. F-18

For detailed ordering information, please consult price list or contact Parflex Division.

B9 - General Purpose Transfer Hose



Features

- Excellent flexibility
- Light Weight
- Specially Formulated Polyurethane core tube for good chemical compatibility

Applications/Markets



- Low pressure transmission of air, oil, water, and coolants

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series	Field Attachable Series
#									lbs	kg		
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.		
B903	3/16	5	.39	10	250	1.7	1.00	25	.04	.06	56	–
B904	1/4	6	.46	12	250	1.7	1.50	38	.05	.07	56	82*
B905	5/16	8	.55	14	250	1.7	2.00	51	.08	.12	56	–
B906	3/8	10	.64	16	250	1.7	3.00	76	.09	.13	56	82*
B908	1/2	13	.78	20	250	1.7	3.00	76	.13	.19	56	82*

Construction

Tube: Specially Formulated Polyurethane
Reinforcement: Fiber
Cover: Specially Formulated Polyurethane

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +200°F (93°C)
- Water/and water based fluids up to +130°F (+54°C)

Change in length at Max. Working Pressure: +/-2%
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

56 Series – pg. E-10
82 Series – Available from Parker Hose Products Division
For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource
Access instructions are on pg. G-14

Colors

- Red
- Black (BLK)

Notes

- *Temperature and pressure reduced with 82 series Push-Lok Fitting:
  -20°F to +100°F (-29°C to +38°C)
  100 psi maximum working pressure
- Non-perforated cover

5CNG – Electrically Conductive Compressed Natural Gas Hose



Features

- Twin constructions available

Certifications

Conforms to:

- ANSI CSA NGV 4.2
- NFPA 52
- ECE R110 (factory built only)
- CSA 12.52 Class A, Class D
- CSA Listing (Certificate # 1053249)

Applications/Markets



- CNG Dispenser/Refueling
- Fleet Transit/On-Vehicle
- CNG Fuel Transfer

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
5CNG-4	1/4	6	.55	14	5,000	34.5	2.00	51	.08	.11	CG
5CNG-6	3/8	10	.65	16	5,000	34.5	3.00	76	.09	.13	CG
5CNG-8	1/2	13	.90	23	5,000	34.5	4.00	102	.21	.31	CG
5CNG-12	3/4	19	1.19	30	5,000	34.5	7.50	191	.24	.36	CG
5CNG-16	1	25	1.59	40	5,000	34.5	10.00	254	.36	.53	CG

Construction

Tube: Electrically Conductive Nylon

Reinforcement: Fiber

Cover: Polyurethane

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +185°F (85°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

CG Series – pg. E-53

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Color

Red

Notes

- CNG hose must be assembled at the factory or by a Parflex approved facility
- Perforated cover
- Appropriate wire and vinyl guards must be used on ANSI/CSA compliant single-line and twin-line bonded hose assemblies. -4 to -8 SS wire guards - pg. F-19
  -12 & -16 Vinyl guards - pg. F-18

Accessories

- PSG - Wire spring guard
- CNGG - Vinyl hose guard

For detailed ordering information, please consult price list or contact Parflex Division.

CNGRP – Regulated Pressure Natural Gas Hose - Electrically Conductive



Features

- For use downstream of pressure regulator

Certifications

Conforms to:

- ANSI CSA NGV 3.1
- NFPA 52
- CSA 12.3, Class C
- CSA Listing (Certificate# 70102698)

Applications/Markets



- Fleet Transit/On-Vehicle

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
CNGRP-12	5/8	16	1.04	26	500	3.45	5.00	127	.42	.63	91N

Construction

Tube: Nylon

Reinforcement: Stainless Steel

Cover: TPV

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +248°F (120°C)

Change in length at Max. Working Pressure: +2%/-4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

91N Series – pg. E-31

Connection configurations limited to: 10691N-12-12C, 1JC91N-12-12C, 1TU91N-12-12C, 1AL91N-10-12C, 1AL91N-12-12C, 10691N-10-12C, 1TU91N-10-12C

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

Red

Notes

- For use with natural gas only
- CNG hose must be assembled at the factory or by a Parflex approved facility

HLB – Lubrication Line Hose



Features

- HLB remote lubrication system versus 1/4" rubber hoses can save money per line in reduced component and installation labor costs
- Unique GK bulkhead hose fittings with integrated nipple can save money per zerk connection in unnecessary adapter costs
- Compact 1/8" hoses save hundreds of dollars of waste in your operation by eliminating gallons of unnecessary "in-line" grease versus larger bore rubber hoses

Certifications

- MSHA Accepted

Applications/Markets



- Grease and lubrication lines
- Agriculture
- Construction
- Industrial
- Material Handling
- Mobile Equipment
- Transportation
- General purpose hydraulic systems

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series	Field Attachable Series
#									lbs	kg		
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.		
HLB02	1/8	3.2	.32	8	3,000	20.7	.50	13	.03	.04	CY	BU
HLB03	3/16	4.8	.41	10	3,000	20.7	.75	19	.06	.08	CY	BU

Construction

Tube: Copolyester
Reinforcement: Fiber
Cover: Polyurethane

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +212°F (100°C)
- Synthetic, synthetic blend, water, and water/oil emulsion hydraulic fluids limited to +135°F (+57°C)
- BU Series Field Attachable Fitting limited to 120°F (53°C)

Vacuum Rating: 28 inch Hg
Change in length at Max. Working Pressure: +/-3%
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

CY Series – pg. E-59 BU Series – pg. E-52
For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource
Access instructions are on pg. G-14

Colors

● Black

Notes

Not for use as a whip hose on hand-operated grease guns

For detailed ordering information, please consult price list or contact Parflex Division.

MSH – Marine Steering Fast Response Hose



Features

- Fast, accurate response
- Permanent or field attachable
- Salt water, corrosion resistant

Applications/Markets

- Marine hydraulic steering systems

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series	Field Attachable Series
#									lbs	kg		
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.		
MSH-5	5/16	8	.48	12	1,000	6.9	2.25	57	.05	.07	MS	MS
MSH-6	3/8	10	.59	15	1,000	6.9	3.00	76	.07	.11	MS	MS

Construction

Tube: Nylon
Reinforcement: Fiber
Cover: Polyurethane

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +200°F (93°C)

Vacuum Rating: 28 inch Hg
Change in length at Max. Working Pressure: +/-2%
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

MS Series – pg. E-62

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

● Black

Notes

- Non-perforated cover
- Bend restrictions are available only for permanent fittings
- HBR (Hose Bend Restrictor) available for Marine Steering Hose Assemblies. See Hose Guard in Tooling Equipment and Accessories Section pg. F-18

MSXL Marine Hydraulic Steering Hose



Features

- Fast, accurate response in marine steering systems
- Low volumetric expansion
- Salt water resistant cover

Applications/Markets

- Marine hydraulic steering systems

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#											
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
MSXL-5	5/16	8	.50	13	1,500	10.3	2-1/4	57	.05	.07	MS

Construction

Tube: Nylon
Reinforcement: Aramid Fiber
Cover: Polyurethane

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +185°F (85°C)

Vacuum Rating: 28 inch Hg
Change in length at Max. Working Pressure: +/-2%
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

MS Series Permanent Crimp – pg. E-62

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14


Colors

● Black

Notes

- MS Series Permanent Crimp Fittings only
- Non-perforated cover
- Optional HBR (Hose Bend Restrictor) available for Marine Steering Hose Assemblies

PTH – Marine Power Tilt Hose



Features

- Compact design
- Abrasion resistant polyurethane cover
- Excellent flexibility
- Corrosion resistant

Applications/Markets

- Power tilt mechanisms for outboard and stern drive engines
- Trim Tab assemblies
- Jack Plate assemblies

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#											
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
PTH-3	3/16	5	.43	11	3,000	20.7	0.75	19	.08	.11	92

Construction

Tube: Nylon

Reinforcement: Fiber and Stainless Steel Wire

Cover: Polyurethane

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +212°F (100°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

92 Series – pg. E-40

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

Clear

Notes

- Non-perforated cover
- Also available as custom order with black cover
- SS wire overbraid for enhanced kink resistance and cut through protection

S5N – Predator® Hose (Water Jetting/Lateral Cleaning)



Features

- Easily identified lime green cover signifies 4000 psi constant pressure
- Slim profile and light weight provide easy handling and routing

Certifications

- NSWMA (National Solid Waste Management Assoc.)
- WASTEC (Waste Equipment Technology Assoc.)
- WEMI (Waste Equipment Management Inst.)

Applications/Markets

- High-pressure water equipment for cleaning or debris removal in lateral sewer lines

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
S508N	1/2	13	.81	21	4000	28	4.00	102	.16	.24	56

Construction

Tube: Gray Nylon

Reinforcement: Aramid Fiber

Cover: Polyurethane

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +135°F (57°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure is 2.5x Max. Working Pressure at 73°F (23°C)

Fittings

56 Series – pg. E-10

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

Green

Notes

- All standard assembly lengths coupled with rigid male pipe each end
- Not for use in hydraulic applications
- Perforated cover

For detailed ordering information, please consult price list or contact Parflex Division.

S6 – Predator® Hose (Sewer Cleaning)



Features

- Easily identified orange cover signifies 2500 psi constant pressure
- Bonded construction provides excellent kink resistance and flexibility

Certifications

- NSWMA (National Solid Waste Management Assoc.)
- WASTEC (Waste Equipment Technology Assoc.)
- WEMI (Waste Equipment Management Inst.)

Applications/Markets

- High-pressure and high-volume water equipment for cleaning or debris removal in large sewer lines

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
S612	3/4	19	1.14	29	2,500	17.2	4.00	102	.29	.43	SQ/HY
S616	1	25	1.41	36	2,500	17.2	6.00	152	.38	.57	SQ/HY

Construction

Tube: Gray Copolyester

Reinforcement: Fiber

Cover: Polyurethane

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +135°F (57°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure is 2.5x Max. Working Pressure at 73°F (23°C)

Fittings

SQ Series (Swage Only)– pg. E-65

HY Series – Available from Parker Hose Products Division

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

Orange

Notes

- All standard assembly lengths coupled with rigid male pipe each end
- Not for use in hydraulic applications
- Perforated cover

S9 – Predator® Hose (Sewer Cleaning)



Features

- Easily identified blue cover signifies 3000 psi constant pressure
- Bonded construction provides excellent kink resistance and flexibility

Certifications

- NSWMA (National Solid Waste Management Assoc.)
- WASTEC (Waste Equipment Technology Assoc.)
- WEMI (Waste Equipment Management Inst.)

Applications/Markets



- High-pressure and high-volume water equipment for cleaning or debris removal in large sewer lines

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
S912	3/4	19	1.15	29	3,000	20.7	4.00	102	.30	.45	SQ/HY
S916	1	25	1.47	37	3,000	20.7	8.00	203	.46	.68	SQ/HY

Construction

Tube: Gray Copolyester
Reinforcement: Fiber
Cover: Polyurethane

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +135°F (57°C)

Vacuum Rating: 28 inch Hg
Change in length at Max. Working Pressure: +/-2%
Min. Burst Pressure is 2.5x Max. Working Pressure at 73°F (23°C)

Fittings

SQ Series (Swage Only)– pg. E-65
HY Series – Available from Parker Hose Products Division
For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource
Access instructions are on pg. G-14

Colors

● Blue

Notes

- All standard assembly lengths coupled with rigid male pipe each end
- Not for use in hydraulic applications
- Perforated cover

For detailed ordering information, please consult price list or contact Parflex Division.

SLH – Sewer Leader Hose



Features

- Easily identified black cover indicates termination of hose

Certifications

- NSWMA (National Solid Waste Management Assoc.)
- WASTEC (Waste Equipment Technology Assoc.)
- WEMI (Waste Equipment Management Inst.)

Applications/Markets

- Leader hose for S5N/S6/S9 high-pressure sewer cleaning hose

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
SLH-8	1/2	13	0.77	20	4,000	27.6	3.50	89	.25	.37	HY
SLH-12	3/4	19	1.08	27	3,000	20.7	4.80	122	.45	.67	HY
SLH-16	1	25	1.43	36	3,000	20.7	6.00	152	.80	1.19	HY

Construction

Tube: Gray Copolyester

Reinforcement: High Tensile Strength Wire

Cover: Smooth Synthetic Rubber

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +135°F (57°C)

Vacuum Rating: 28 inch Hg

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure is 2.5x Max. Working Pressure at 73°F (23°C)

Fittings

HY Series – Available from Parker Hose Products Division

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Color

● Black

Notes

- Not for use in hydraulic applications
- Non-perforated cover

DuraFlex™ Hydraulic Hose Coil, Non-Conductive



Features

- Bonded twin-line construction
- Self retracting coil design

Certifications

- Meets/Exceeds SAE 100R7
- Meets SAE J517 for less than 50 micro-amps leakage under 75,000 volts per foot

Applications/Markets

- Hydraulic tool hose for aerial lift applications
- General Hydraulics

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#									lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
548N-6	3/8	10	.65	17	2,250	15.5	2.00	51	.09	.13	CG

Nomenclature

HC-548N-06MP-06MP-10

Configuration
HC — twin-line hose coil
(blank) — twin-line straight hose

Hose Type (see specifications below)
548N — Med Pressure - straight or coiled

End Connectors
06MP — 3/8" Rigid Male Pipe
06FJ — 3/8" Female JIC Swivel

Effective Working Length
6 — 6 foot length
8 — 8 foot length
10 — 10 foot length
12 — 12 foot length

Notes
1) Part Number example shown is a stocked item.
2) Other combinations from this chart are readily available.
3) For options not shown, please consult Parflex Division.

Construction

Tube: Nylon
Reinforcement: Fiber
Cover: Polyurethane

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +212°F (100°C)

Vacuum Rating: 28 inch Hg
Change in length at Max. Working Pressure: +/-2%
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

CG Series – pg. E-53

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors


Orange (Non-Conductive)

Notes

Non-perforated cover

For detailed ordering information, please consult price list or contact Parflex Division.

919/919B – PTFE Hose



Features

- Excellent chemical compatibility
- Handles extreme temperatures to +450°F
- Environmentally safe
- Resists moisture
- Low friction minimizes pressure drops and deposits

Certifications

- Meets/Exceeds SAE 100R14A - 919
- Meets/Exceeds SAE 100R14B - 919B
- FDA CFR 177.1550 (Natural tube)

Applications/Markets



- Chemical Transfer Lines
- General Hydraulics
- Compressed Air/Gases
- Adhesive Dispensing
- Coolant Lines

Part Number		Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series	Field Attachable Series
#	#										lbs	kg		
Natural	Static-Dissipative	inch	mm	inch	mm	psi	MPa	inch	mm	inch	lbs./ft.	kg./mtr.		
919-4	919B-4	3/16	5	.32	8	3,000	20.7	2.00	50	28	.06	.09	91N	90
919-5	919B-5	1/4	6	.38	10	3,000	20.7	3.00	75	28	.09	.13	91N	90
919-6	919B-6	5/16	8	.44	11	2,500	17.2	4.00	100	28	.10	.15	91N	90
919-8	919B-8	13/32	10	.53	13	2,000	13.8	5.00	127	28	.13	.19	91N	90
919-10	-	1/2	13	.63	16	1,500	10.3	6.50	165	28	.15	.22	91N	90
919-12	-	5/8	16	.75	19	1,200	8.3	7.50	191	12	.19	.28	91N	90
919-16	-	7/8	22	1.03	26	1,000	6.9	9.00	229	14	.27	.40	91N	90
919-20	-	1-1/8	29	1.28	33	625	4.3	16.00	406	10	.39	.58	91	90

Construction

Tube: 919 - Natural FDA Compliant PTFE
919B - Black Static-Dissipative PTFE

Reinforcement: 304 Stainless Steel Braid

Operating Parameters

Temperature Range:

- -100°F (-73°C) to +450°F (232°C)

Change in length at Max. Working Pressure: +2% to -4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

90 Series – pg. E-26 91/91N Series – pg. E-31

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Notes

- Use hose type 919B with static-dissipative core tube when conveying non-conducting fluids such as oils, paints, fuels, steam, etc.
- Constructed with minimum .030 PTFE tube wall thickness

919J – Silicone Covered PTFE Hose



Features

- Silicone cover provides a clean, smooth cover to protect the stainless steel wire reinforcement against wear, fraying and contaminants
- Steam cleanable

Certifications

- Meets/Exceeds SAE 100R14A
- FDA CFR 177.1550

Applications/Markets



- Chemical Transfer Lines
- General Hydraulics
- Compressed Air/Gases
- Adhesive Dispensing
- Coolant Lines

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
#										lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	inch	lbs./ft.	kg./mtr.	
919J-4-RED	3/16	5	.45	11	3,000	20.7	2.00	50	28	.12	.18	91N
919J-5-RED	1/4	6	.52	13	3,000	20.7	3.00	75	28	.14	.21	91N
919J-6-RED	5/16	8	.58	15	2,500	17.2	4.00	100	28	.17	.25	91N
919J-8-RED	13/32	10	.68	17	2,000	13.8	5.00	127	28	.20	.30	91N
919J-10-RED	1/2	13	.78	20	1,500	10.3	6.50	165	28	.24	.35	91N
919J-12-RED	5/8	16	.91	23	1,200	8.3	7.50	191	12	.29	.43	91N

Construction

Tube: Natural FDA compliant PTFE
Reinforcement: 304 Stainless Steel Braid
Cover: Extruded Silicone

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +450°F (232°C)

Change in length at Max. Working Pressure: +2% to -4%
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

91N Series – pg. E-31

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

Red

Notes

- Cover must be skived prior to fitting attachment
- Constructed with minimum .030 PTFE tube wall thickness

919U – High Abrasion Resistance PTFE Hose



Features

- Non-Marring, abrasion resistant polyurethane cover protects the stainless steel wire reinforcement against wear, fraying and contaminants

Certifications

- Meets/Exceeds SAE 100R14A but operates at a temperature range of -40°F to +275°F
- FDA CFR 177.1550

Applications/Markets



- Chemical Transfer Lines
- General Hydraulics
- Compressed Air/Gases
- Adhesive Dispensing
- Coolant Lines

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
#										lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	inch	lbs./ft.	kg./mtr.	
919U-4	3/16	5	.37	9	3,000	20.7	2.00	50	28	.08	.13	91N
919U-6	5/16	8	.51	13	2,500	17.2	4.00	100	28	.13	.20	91N
919U-8	13/32	10	.61	15	2,000	13.8	5.00	127	28	.15	.22	91N
919U-12	5/8	16	.84	21	1,200	8.3	7.50	191	12	.22	.33	91N
919U-16	7/8	22	1.12	28	1,000	6.9	9.00	229	14	.31	.47	91N

Construction

Tube: Natural FDA compliant PTFE

Reinforcement: 304 Stainless Steel Braid

Cover: Polyurethane

Operating Parameters

Temperature Range:

- -40°F (-40°C) to +275°F (135°C)

Change in length at Max. Working Pressure: +2% to -4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

91N Series – pg. E-31

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14


Colors

● Black

Notes

- Cover must be skived prior to fitting attachment
- Other colors available upon request
- Constructed with minimum .030 PTFE tube wall thickness

929/929B – Heavy Wall PTFE Hose



Features

- Excellent kink resistance
- Enhanced resistance to gas permeation due to increased PTFE wall thickness (.040")

Certifications

- Meets/Exceeds SAE 100R14A - 929
- Meets/Exceeds SAE 100R14B - 929B
- FDA CFR 177.1550 (Natural tube)

Applications/Markets



- Chemical Transfer Lines
- General Hydraulics
- Compressed Air/Gases
- Adhesive Dispensing
- Coolant Lines

Part Number		Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
#	#										lbs	kg	
Natural	Static-Dissipative	inch	mm	inch	mm	psi	MPa	inch	mm	inch	lbs./ft.	kg./mtr.	
929-4	929B-4	3/16	5	.34	9	3,000	20.7	2.00	51	28	.08	.12	91N
929-6	929B-6	5/16	8	.47	12	2,500	17.2	4.00	102	28	.12	.18	91N
929-8	929B-8	13/32	10	.59	15	2,000	13.8	4.60	117	28	.16	.23	91N
-	929B-12	5/8	16	.81	21	1,200	8.3	6.50	165	12	.19	.28	91N
-	929B-16	7/8	22	1.14	29	1,250	8.6	7.40	188	12	.49	.73	91N

Construction

Tube: 929 - Natural FDA Compliant PTFE
929B - Black Static-Dissipative PTFE

Reinforcement: 304 Stainless Steel Braid

Operating Parameters

Temperature Range:

- -100°F (-73°C) to +450°F (232°C)

Change in length at Max. Working Pressure: +2% to -4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

91/91N Series – pg. E-31

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Notes

- Use hose type 929B with static-dissipative core tube when conveying non-conducting fluids such as oils, paints, fuels, steam, etc.
- Constructed with minimum .040 PTFE tube wall thickness

For detailed ordering information, please consult price list or contact Parflex Division.

929BJ – Silicone Covered PTFE Hose
(with Static-Dissipative Tube)



Features

- Silicone cover protects SS wire reinforcement against wear and fraying, up to 450°F
- Silicone cover provides clean, smooth cover and prevents contaminants from accumulating in braid
- Excellent kink resistance
- Enhanced resistance to gas permeation due to increased PTFE wall thickness
- Steam cleanable

Applications/Markets



- Vacuum lines for high temperature autoclaves
- General Hydraulics
- Compressed Air/Gases

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
#										lbs	kg	
	inch	mm	inch	mm	psi	MPa	inch	mm	inch	lbs./ft.	kg./mtr.	
929BJ-4	3/16	5	.58	15	3,000	20.7	2.00	51	28	.17	.25	91N
929BJ-6	5/16	8	.70	18	2,500	17.2	4.00	102	28	.23	.34	91N
929BJ-8	13/32	10	.81	20	2,000	13.8	4.60	117	28	.29	.43	91N
929BJ-12	5/8	16	1.04	27	1,200	8.3	6.50	165	12	.43	.64	91N
929BJ-16	7/8	22	1.36	35	1,250	8.6	7.40	188	12	.78	1.16	91N

Construction

Tube: Black Static-Dissipative PTFE
Reinforcement: 304 Stainless Steel Braid
Cover: Silicone

Operating Parameters

Temperature Range:

- -65°F (-54°C) to +450°F (232°C)

Change in length at Max. Working Pressure: +2% to -4%
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

91N Series – pg. E-31

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Colors

Brown

Notes

- Cover must be skived prior to fitting attachment
- Constructed with minimum .040 PTFE tube wall thickness

939/939B – Convoluted PTFE Hose



Features

- Excellent flexibility
- Exceptional kink resistance

Certifications

- FDA CFR 177.1550 (Natural tube)

Applications/Markets

- Chemical Transfer
- General Hydraulics
- Hose applications requiring tight routings

Part Number		Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Vac. Rating Hg./73˚F	Weight		Permanent Fitting Series
#	#										lbs	kg	
Natural	Static-Dissipative	inch	mm	inch	mm	psi	MPa	inch	mm	inch	lbs./ft.	kg./mtr.	
939-6	939B-6	3/8	10	.59	15	1,500	10.3	2.25	57	28	.12	.18	93N
939-8	939B-8	1/2	13	.79	20	1,350	9.3	2.88	73	28	.21	.31	93N
939-10	939B-10	5/8	16	.88	22	1,000	6.9	3.00	76	28	.24	.36	93N
939-12	939B-12	3/4	19	1.09	28	1,100	7.6	3.75	95	28	.32	.47	93N
939-16	939B-16	1	25	1.33	34	1,000	6.9	5.00	127	28	.45	.67	93N
939-20	939B-20	1-1/4	32	1.75	44	1,000	6.9	6.25	159	20*	.70	1.04	93N
939-24	939B-24	1-1/2	38	2.05	52	750	5.2	7.50	191	12*	.80	1.18	93N
939-32	939B-32	2	51	2.56	65	250	1.7	10.00	254	5*	1.01	1.50	93N

Construction

Tube: 939 - Natural FDA Compliant PTFE
939B - Black Static-Dissipative PTFE

Reinforcement: 304 Stainless Steel Braid

Operating Parameters

Temperature Range:

- -100°F (-73°C) to +450°F (232°C)

Change in length at Max. Working Pressure: +2% to -4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

93N Series – pg. E-41

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource


Access instructions are on pg. G-14

Notes

- Use hose type 939B with static-dissipative core tube when conveying non-conducting fluids such as oils, paints, fuels, steam, etc.
- *28 in/Hg can be obtained by using 2799 internal spring guard. See pg. F-20

For detailed ordering information, please consult price list or contact Parflex Division.

943B – 3,000 psi W.P. High Temp Hose



Features

- Excellent chemical compatibility
- Resists moisture
- Low friction minimizes pressure drops and deposits

Certifications

- Meets/Exceeds SAE 100R7/SAE 100R17

Applications/Markets



- High temp hydraulic applications
- Chemical Transfer
- Compressed Air/Gases
- Paint Striping

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight	
#										lbs	kg
	inch	mm	inch	mm	psi	MPa	inch	mm	inch	lbs./ft.	kg./mtr.
943B-6	5/16	8	.49	12	3,000	20.7	2.50	64	28	.18	.26
943B-8	13/32	10	.62	16	3,000	20.7	2.88	73	28	.24	.35
943B-10	1/2	13	.73	19	3,000	20.7	3.25	83	28	.32	.46
943B-12	5/8	16	.99	25	3,000	20.7	4.00	102	28	.70	1.01
943B-16	29/32	23	1.25	32	3,000	20.7	5.00	127	28	1.02	1.53

Construction

Tube: Black Static-Dissipative PTFE
Reinforcement: 304 Stainless Steel Braid

Operating Parameters

Temperature Range:

- -65°F (-54°C) to +400°F (204°C)

Change in length at Max. Working Pressure: +/-2%
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

94 Series – pg. E-44

Notes

- Factory-made assemblies only

944B – 4,000-4,500 psi W.P. High Temp Hose



Features

- Excellent chemical compatibility
- Resists moisture
- Low friction minimizes pressure drops and deposits

Applications/Markets



- General Hydraulics
- Chemical Transfer
- Compressed Air/Gases

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight	
#										lbs	kg
	inch	mm	inch	mm	psi	MPa	inch	mm	inch	lbs./ft.	kg./mtr.
944B-4	15/64	6	.39	10	4,500	31.0	1.50	38	28	.11	.16
944B-6	5/16	8	.49	12	4,500	31.0	2.50	64	28	.17	.24
944B-8	7/16	11	.62	16	4,500	31.0	2.88	73	28	.25	.35
944B-10	1/2	13	.73	19	4,000	27.6	3.25	83	28	.31	.45
944B-12	5/8	16	.99	25	4,000	27.6	4.00	102	28	.74	1.05
944B-16	29/32	23	1.25	32	4,000	27.6	5.00	127	28	1.09	1.55

Construction

Tube: Black Static-Dissipative PTFE

Reinforcement: 304 Stainless Steel Braid

Operating Parameters

Temperature Range:

- -65°F (-54°C) to +400°F (204°C)

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure is 3x Max. Working Pressure at 73°F (23°C)

Fittings

94 Series – pg. E-44

Notes

- Factory-made assemblies only
- Reduce pressure to 3,000 psi (20.7MPa) for pressure impulse applications

For detailed ordering information, please consult price list or contact Parflex Division.

950B – 4,000 psi W.P. High Temp Hose



Features

- Excellent chemical compatibility
- Resists moisture
- Low friction minimizes pressure drops and deposits

Applications/Markets



- High temp hydraulic applications
- Chemical Transfer
- Compressed Air/Gases
- Ground Support

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight	
#										lbs	kg
	inch	mm	inch	mm	psi	MPa	inch	mm	inch	lbs./ft.	kg./mtr.
950B-4	15/64	6	.50	13	4,000	27.6	3.00	76	28	.20	.27
950B-6	5/16	8	.62	16	4,000	27.6	5.00	127	28	.24	.36
950B-8	7/16	11	.75	19	4,000	27.6	5.75	146	28	.45	.68
950B-12	5/8	16	1.08	27	4,000	27.6	7.75	197	28	.96	1.43
950B-16	29/32	23	1.36	34	4,000	27.6	9.63	245	28	1.30	1.93

Construction

Tube: Black Static-Dissipative PTFE

Reinforcement: Multiple high density braids of 304 Stainless Steel

Operating Parameters

Temperature Range:

- -65°F (-54°C) to +400°F (204°C)

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

95 Series – pg. E-44

Notes

Factory-made assemblies only

955B – 5,500 psi W.P. High Temp Hose



Features

- Excellent chemical compatibility
- Resists moisture
- Low friction minimizes pressure drops and deposits

Applications/Markets



- General Hydraulics
- Chemical Transfer
- Compressed Air/Gases
- Ground Support

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight	
#										lbs	kg
	inch	mm	inch	mm	psi	MPa	inch	mm	inch	lbs./ft.	kg./mtr.
955B-4	15/64	6	.50	13	5,500	37.9	3.00	76	28	.23	.34
955B-6	5/16	8	.62	16	5,500	37.9	5.00	127	28	.24	.35
955B-8	7/16	11	.75	19	5,500	37.9	5.75	146	28	.46	.68
955B-10	1/2	13	.91	23	5,500	37.9	6.50	165	28	.91	1.34
955B-12	5/8	16	1.08	27	5,500	37.9	7.75	197	28	.92	1.36
955B-16	29/32	23	1.36	34	5,500	37.9	9.63	245	28	1.20	1.77

Construction

Tube: Black Static-Dissipative PTFE

Reinforcement: Multiple high density braids of 304 Stainless Steel

Operating Parameters

Temperature Range:

- -65°F (-54°C) to +400°F (204°C)

Change in length at Max. Working Pressure: +/-2%

Min. Burst Pressure is 16,000 psi at 73°F (23°C)

Fittings


95 Series – pg. E-44

Notes

- Factory-made assemblies only
- Reduce operating pressure to 4000 psi (27.6 MPa) for impulse service applications

For detailed ordering information, please consult price list or contact Parflex Division.

STW/STB - "TRUE BORE"
Smoothbore PTFE Hose, Stainless Steel Braid



Features

- High temperature hose
- Excellent chemical compatibility
- Resists moisture
- Low friction minimizes pressure drops and deposits

Compliances

- FDA 21 CFR 177.1550
- USP Class VI
- ISO 10993 Sections 5, 6, 10, 11

Applications/Markets



- Fluid Handling
- Chemical Transfer
- Paint
- Pharmaceutical
- Food & Beverage
- Cosmetics

Part Number		Nominal I.D.		Nominal O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
#	#										lbs	kg	
Natural	Static-Dissipative	inch	mm	inch	mm	psi	bar	inch	mm	inch	lbs./ft.	kg./mtr.	
04-STW	04-STB	1/4	6	.37	9	3,000	207	3	76	28	.08	.13	PAGE
06-STW	06-STB	3/8	10	.51	13	2,000	138	5	127	28	.11	.16	PAGE
08-STW	08-STB	1/2	13	.63	16	1,750	121	6.50	165	28	.16	.24	PAGE
12-STW	12-STB	3/4	19	.88	22	1,000	69	8.50	216	28	.20	.30	PAGE
16-STW	16-STB	1	25	1.13	29	1,000	69	12	305	20	.33	.49	PAGE
16Z-STW	16Z-STB	1	25	1.22	31	1,000	69	12	305	20	.56	.83	PAGE
20Z-STW	20Z-STB	1-1/4	32	1.52	38	1,000	69	14	356	18	.68	1.02	PAGE
24Z-STW	24Z-STB	1-1/2	38	1.73	44	900	62	15	381	15	.79	1.18	PAGE

Construction

Tube: STW - Natural FDA Compliant PTFE
STB - Black Static-Dissipative PTFE

Reinforcement: 304 Stainless Steel Braid

Operating Parameters

Temperature Range:

- -100°F (-73°C) to +450°F (232°C)

Change in length at Max. Working Pressure: +2% to -4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Pressure ratings based on 73°F (23°C)

Decrease working pressure 1% for every 2°F above 212°F

Fittings

PAGE Fittings – pg. E-45

Uses crimp collar ST300, see pg. E-46


For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Notes

- "Z" indicates double braid
- See pg. A-21 for part numbering system
- Cannot be used with 90 or 91N series fittings

SBFW - PAGE-flex™ SBF™
Extra Flexible Fluoropolymer Hose



Features

- Half the minimum bend radius of conventional smoothbore products
- Kink and vacuum resistant
- Easily cleaned
- Cooler outside temperatures reduces operator burns
- Reduces environment temperatures in confined areas
- Available with white Silicone cover

Compliances

- FDA 21 CFR 177.1550
- **USP Class VI Certified**
- ISO 10993 Sections 5, 6, 10, 11

Applications/Markets



- Fluid Handling
- Chemical Transfer
- Paint
- Pharmaceutical
- Food & Beverage
- Cosmetics



Part Number	Nominal I.D.		Nominal O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight	
#										lbs	kg
Natural	inch	mm	inch	mm	psi	bar	inch	mm	inch	lbs./ft.	kg./mtr.
06-SBFW	3/8	10	.63	16	300	21	2	51	28	.16	.24
08-SBFW	1/2	13	.76	19	300	21	2.50	64	28	.23	.34
12-SBFW	3/4	19	1.04	26	250	17	3	76	28	.37	.55
16-SBFW	1	25	1.29	33	250	17	4	102	28	.54	.80
24-SBFW	1-1/2	38	1.85	47	200	14	7	178	28	.83	1.23

Construction

Tube: SBFW - Natural PFA
Reinforcement: Bonded Wire Braid - Silicone - Textile Braided Composite with 316 Stainless Steel Braid

Operating Parameters

Temperature Range:

- -65°F (-54°C) to +325°F (163°C)

Change in length at Max. Working Pressure: +2% to -4%
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)
Pressure ratings based on 73°F (23°C)
Decrease working pressure 1% for every 2°F above 212°F

Fittings

PAGE Fittings – pg. E-45

Notes

- Factory-made assemblies only
- Available with white silicone cover
- See pg. A-21 for part numbering system

For detailed ordering information, please consult price list or contact Parflex Division.

SCW/SCB - Convoluted PTFE Hose
316 Stainless Steel Braid



Features

- High temperature hose
- Excellent corrosion resistance
- Seamless
- Open pitch
- Self draining
- Environmentally safe; low effusion

Compliances

- FDA 21 CFR 177.1550
- USP Class VI
- ISO 10993 Sections 5, 6, 10, 11

Applications/Markets



- Fluid Handling
- Chemical Transfer
- Semiconductor

Part Number		Nominal I.D.		Nominal O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
#	#										lbs	kg	
Natural	Static-Dissipative	inch	mm	inch	mm	psi	bar	inch	mm	inch	lbs./ft.	kg./mtr.	
04-SCW	04-SCB	1/4	6	.46	12	1,500	104	0.75	19	28	.08	.11	PAGE
06-SCW	06-SCB	3/8	10	.54	14	1,500	104	1	25	28	.14	.21	PAGE
08-SCW	08-SCB	1/2	13	.72	18	1,500	104	1.50	38	28	.16	.23	PAGE
12-SCW	12-SCB	3/4	19	1.02	26	1,200	83	2	51	28	.27	.40	PAGE
16-SCW	16-SCB	1	25	1.31	33	1,000	69	2.50	64	28	.37	.55	PAGE
20-SCW	20-SCB	1-1/4	32	1.73	44	750	52	3	76	28	.46	.68	PAGE
24-SCW	24-SCB	1-1/2	38	1.93	49	650	45	3.75	95	28	.55	.81	PAGE
32-SCW	32-SCB	2	51	2.42	62	450	31	4.75	121	28	.90	1.4	PAGE

Construction

Tube: SCW - Natural FDA Compliant PTFE
SCB - Black Static-Dissipative PTFE

Reinforcement: 316 Stainless Steel Braid

Operating Parameters

Temperature Range:

- -100°F (-73°C) to +500°F (260°C)

Change in length at Max. Working Pressure: +2% to -4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Pressure ratings based on 73°F (23°C)

Decrease working pressure 1% for every 2°F above 212°F

Fittings

PAGE Fittings – pg. E-45

Uses crimp collar ST300, see pg. E-46

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Notes

- See pg. A-21 for part numbering system
- Cannot be used with 93N series fittings

PCW/PCB - Convoluted PTFE Hose
Polypropylene Braid



Features

- Personal handling safety
- Excellent corrosion resistance
- Seamless
- Open pitch
- Self draining
- Environmentally safe; low effusion

Compliances

- FDA 21 CFR 177.1550
- USP Class VI
- ISO 10993 Sections 5, 6, 10, 11

Applications/Markets



- Fluid Handling
- Chemical Transfer
- Pharmaceutical
- Food & Beverage

Part Number		Nominal I.D.		Nominal O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
#	#										lbs	kg	
Natural	Static-Dissipative	inch	mm	inch	mm	psi	bar	inch	mm	inch	lbs./ft.	kg./mtr.	
04-PCW	04-PCB	1/4	6	.55	14	350	59	0.75	19	28	.03	.05	PAGE
06-PCW	06-PCB	3/8	10	.64	16	350	59	1	25	28	.06	.09	PAGE
08-PCW	08-PCB	1/2	13	.84	21	300	21	1.50	38	28	.15	.22	PAGE
12-PCW	12-PCB	3/4	19	1.15	29	250	17	2	51	28	.18	.27	PAGE
16-PCW	16-PCB	1	25	1.50	38	250	17	2.50	64	28	.26	.39	PAGE
20-PCW	20-PCB	1-1/4	32	1.92	49	200	14	3	76	28	.37	.55	PAGE
24-PCW	24-PCB	1-1/2	38	2.12	54	200	14	3.75	95	28	.42	.63	PAGE
32-PCW	32-PCB	2	51	2.65	67	200	14	4.75	121	28	.56	.83	PAGE

Construction

Tube: PCW - Natural FDA Compliant PTFE
PCB - Black Static-Dissipative PTFE

Reinforcement: Polypropylene

Operating Parameters

Temperature Range:

- -0°F (-18°C) to +212°F (100°C)

Change in length at Max. Working Pressure: +2% to -4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Pressure ratings based on 73°F (23°C)

Decrease working pressure 1% for every 2°F above 212°F

Fittings

PAGE Fittings – pg. E-45

Uses crimp collar PC300, see pg. E-46

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Notes

- See pg. A-21 for part numbering system
- Cannot be used with 93N series fittings

For detailed ordering information, please consult price list or contact Parflex Division.

SCWV/SCBV
Stainless Steel Braid, Heavy Wall Convoluted PTFE Hose



Features

- High temperature hose
- Open pitch
- Thicker wall
- Handles vacuum applications at elevated temperatures
- Excellent chemical compatibility
- Easy Cleaning

Applications/Markets

- Fluid Handling
- Chemical Transfer
- Semiconductor

Compliances

- FDA 21 CFR 177.1550
- USP Class VI
- ISO 10993 Sections 5, 6, 10, 11

Part Number		Nominal I.D.		Nominal O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight	
#	#										lbs	kg
Natural	Static-Dissipative	inch	mm	inch	mm	psi	bar	inch	mm	inch	lbs./ft.	kg./mtr.
08-SCWV	08-SCBV	1/2	13	.75	19	1,500	104	2	51	28	.17	.26
12-SCWV	12-SCBV	3/4	19	1.04	26	1,200	83	2.75	70	28	.33	.49
16-SCWV	16-SCBV	1	25	1.25	32	1,000	69	4	102	28	.37	.55
20-SCWV	20-SCBV	1-1/4	32	1.66	42	750	52	5.50	140	28	.56	.83
24-SCWV	24-SCBV	1-1/2	38	1.92	49	650	45	7	178	28	.64	.95
32-SCWV	32-SCBV	2	51	2.49	63	450	31	8.50	216	28	.84	1.24
40-SCWV	40-SCBV	2-1/2	64	3.25	83	200	14	12	305	28	1.52	2.26
48-SCWV	48-SCBV	3	76	3.80	97	175	12	14	356	28	1.82	2.71
64-SCWV	64-SCBV	4	102	4.76	121	150	10	16	406	28	2.10	3.13

Construction

Tube: SCWV - Natural FDA Compliant PTFE
SCBV - Black Static-Dissipative PTFE

Reinforcement: 316 Stainless Steel Braid

Operating Parameters

Temperature Range:

- -100°F (-73°C) to +500°F (260°C)

Change in length at Max. Working Pressure: +2% to -4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Pressure ratings based on 73°F (23°C)

Decrease working pressure 1% for every 2°F above 212°F

Fittings

PAGE Fittings – pg. E-45

Notes

- Factory-made assemblies only
- See pg. A-21 for part numbering system
- Cannot be used with 93N Series fittings
- Vacuum 5602 recommended for 2-1/2, 3 and 4 inch

PCWV/PCBV
Polypropylene Braid, Heavy Wall Convoluted PTFE Hose



Features
- Open pitch
- Thicker wall
- Handles vacuum applications at elevated temperatures
- Excellent chemical compatibility
- Easy Cleaning

Compliances
- FDA 21 CFR 177.1550
- USP Class VI
- ISO 10993 Sections 5, 6, 10, 11

Applications/Markets



- Fluid Handling
- Chemical Transfer
- Pharmaceutical
- Food & Beverage

Part Number		Nominal I.D.		Nominal O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight	
#	#										lbs	kg
Natural	Static-Dissipative	inch	mm	inch	mm	psi	bar	inch	mm	inch	lbs./ft.	kg./mtr.
08-PCWV	08-PCBV	1/2	13	.81	21	300	21	3	76	28	.14	.20
12-PCWV	12-PCBV	3/4	19	1.30	33	250	17	3.50	89	28	.22	.32
16-PCWV	16-PCBV	1	25	1.44	36	250	17	4.50	114	28	.32	.47
20-PCWV	20-PCBV	1-1/4	32	1.86	47	200	14	5	127	28	.40	.59
24-PCWV	24-PCBV	1-1/2	38	2.10	53	200	14	6	152	28	.49	.73
32-PCWV	32-PCBV	2	51	2.66	68	200	14	8.50	216	28	.66	.99
40-PCWV	40-PCBV	2-1/2	64	3.57	91	150	10	12	305	28	1.21	1.80
48-PCWV	48-PCBV	3	76	3.92	100	125	9	14	356	28	1.45	2.16
64-PCWV	64-PCBV	4	102	4.92	125	100	7	16	406	28	1.68	2.50

Construction
Tube: PCWV- Heavy Wall Natural FDA Compliant PTFE
PCBV - Heavy Wall Black Static-Dissipative PTFE
Reinforcement: Polypropylene

Operating Parameters
Temperature Range:
- -0°F (-18°C) to +212°F (100°C)

Change in length at Max. Working Pressure: +2% to -4%
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)
Pressure ratings based on 73°F (23°C)
Decrease working pressure 1% for every 2°F above 212°F

Fittings
PAGE Fittings – pg. E-45

Notes
- Factory-made assemblies only
- See pg. A-21 for part numbering system
- Cannot be used with 93N Series fittings

For detailed ordering information, please consult price list or contact Parflex Division.

SCWV-FS/SCBV-FS - Flare-Seal®
Stainless Steel Braid



Features

- Flare Seal fitting - Continuous PTFE through fitting; no area for bacterial entrapment
- Increased flow
- Thicker wall
- Excellent chemical compatibility
- Easy Cleaning

Compliances

- FDA 21 CFR 177.1550
- USP Class VI
- ISO 10993 Sections 5, 6, 10, 11

Applications/Markets



- Fluid Handling
- Chemical Transfer
- Pharmaceutical
- Food & Beverage

Part Number		Nominal I.D.		Nominal O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight	
#	#											
Natural	Static-Dissipative	inch	mm	inch	mm	psi	bar	inch	mm	inch	lbs./ft.	kg./mtr.
08-SCWV-FS	08-SCBV-FS	1/2	13	.75	19	500	35	2	51	28	.17	.26
12-SCWV-FS	12-SCBV-FS	3/4	19	1.04	26	425	29	2.75	70	28	.33	.49
16-SCWV-FS	16-SCBV-FS	1	25	1.25	32	350	24	4	102	28	.37	.55
20-SCWV-FS	20-SCBV-FS	1-1/4	32	1.66	42	325	22	5.50	140	28	.56	.83
24-SCWV-FS	24-SCBV-FS	1-1/2	38	1.92	49	300	21	7	178	28	.64	.95
32-SCWV-FS	32-SCBV-FS	2	51	2.49	63	250	17	8.50	216	28	.84	1.24
40-SCWV-FS	40-SCBV-FS	2-1/2	64	3.25	83	200	14	12	305	28	1.52	2.26
48-SCWV-FS	48-SCBV-FS	3	76	3.80	97	175	12	14	356	28	1.82	2.71
64-SCWV-FS	64-SCBV-FS	4	102	4.76	121	150	10	16	406	28	2.10	3.13

Construction

Tube: SCWV - Heavy Wall Natural FDA Compliant PTFE
SCBV - Heavy Wall Black Static-Dissipative PTFE

Reinforcement: 316 Stainless Steel Braid

Operating Parameters

Temperature Range:

- -100°F (-73°C) to +500°F (260°C)

Change in length at Max. Working Pressure: +2% to -4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Pressure ratings based on 73°F (23°C)

Decrease working pressure 1% for every 2°F above 212°F)


Fittings

PAGE Fittings – pg. E-45

Notes

- Factory-made assemblies only
- See pg. A-21 for part numbering system
- Cannot be used with 93N series fittings

PCWV-FS/PCBV-FS - Flare-Seal®
Polypropylene Braid



Features

- Flare Seal fitting - Continuous PTFE through fitting; no area for bacterial entrapment
- Increased flow
- Personal handling safety
- Good chemical compatibility
- Easy Cleaning

Compliances

- FDA 21 CFR 177.1550
- USP Class VI
- ISO 10993 Sections 5, 6, 10, 11

Applications/Markets



- Fluid Handling
- Chemical Transfer
- Pharmaceutical
- Food & Beverage

Part Number		Nominal I.D.		Nominal O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight	
#	#											
Natural	Static-Dissipative	inch	mm	inch	mm	psi	bar	inch	mm	inch	lbs./ft.	kg./mtr.
08-PCWV-FS	08-PCBV-FS	1/2	13	.810	21	300	21	3	76	28	.14	.20
12-PCWV-FS	12-PCBV-FS	3/4	19	1.10	28	250	17	3.50	89	28	.22	.32
16-PCWV-FS	16-PCBV-FS	1	25	1.44	36	250	17	4.50	114	28	.31	.47
20-PCWV-FS	20-PCBV-FS	1-1/4	32	1.86	47	200	14	5	127	28	.40	.59
24-PCWV-FS	24-PCBV-FS	1-1/2	38	2.10	53	200	14	6	152	28	.49	.73
32-PCWV-FS	32-PCBV-FS	2	51	2.66	68	200	14	8.50	216	28	.66	.99
40-PCWV-FS	40-PCBV-FS	2-1/2	64	3.42	87	150	10	12	305	28	1.21	1.80
48-PCWV-FS	48-PCBV-FS	3	76	3.92	100	125	9	14	356	28	1.45	2.16
64-PCWV-FS	64-PCBV-FS	4	102	4.92	125	100	7	16	406	28	1.68	2.50

Construction

Tube: PCWV - Heavy Wall Natural FDA Compliant PTFE
PCBV - Heavy Wall Black Static-Dissipative PTFE

Reinforcement: Polypropylene

Operating Parameters

Temperature Range:

- 0°F (-18°C) to +212°F (100°C)

Change in length at Max. Working Pressure: +2% to -4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Pressure ratings based on 73°F (23°C)

Decrease working pressure 1% for every 2°F above 212°F

Fittings


PAGE Fittings – pg. E-45

Notes

- Factory-made assemblies only
- See pg. A-21 for part numbering system
- Cannot be used with 93N series fittings

For detailed ordering information, please consult price list or contact Parflex Division.

NCW/NCB - Seamless Convoluted PTFE
with Nomex® Braid



Features

- Very light weight
- Superior flexibility
- Kink and vacuum resistant
- Eliminates RFI issues
- Factory assembly only

Compliances

- FDA 21 CFR 177.1550
- USP Class VI
- ISO 10993 Sections 5, 6, 10, 11

Applications/Markets



- Fluid Handling
- Chemical Transfer
- Paint
- Pharmaceutical
- Food & Beverage
- Cosmetics

Part Number		Nominal I.D.		Nominal O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight	
#	#										lbs	kg
Natural	Static-Dissipative	inch	mm	inch	mm	psi	bar	inch	mm	inch	lbs./ft.	kg./mtr.
04-NCW	04-NCB	.260	7	.460	12	725	50	1	25	30	.02	.03
06-NCW	06-NCB	.370	9	.560	14	400	28	1-1/2	38	30	.06	.09
08-NCW	08-NCB	.500	13	.740	19	280	19	2	51	30	.08	.12
12-NCW	12-NCB	.750	19	1.010	26	200	14	2-1/2	64	30	.14	.22
16-NCW	16-NCB	1.000	25	1.290	33	200	14	4	102	30	.22	.32

Construction

Tube: NCW - Natural PTFE
NCB - Black Static Dissipative PTFE

Reinforcement: Nomex® braid

Operating Parameters

Temperature Range:

- -100°F (-73°C) to +400°F (204°C)

Change in length at Max. Working Pressure: +2% to -4%
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)
Pressure ratings based on 73°F (23°C)
Decrease working pressure 1% for every 2°F above 212°F

Fittings

PAGE Fittings – pg. E-45

Notes

- Factory-made assemblies only
- NCB (Static Dissipative) tube I.D. surface only
- NCB Conductive Spec - Must conduct 20 microamps 1000 VDC potential 14" sample
- See pg. A-21 for part numbering system
- Cannot be used with 93N series fittings



Nomex® is a registered trademark of E. I. du Pont de Nemours and Company.

RCTW - EPDM Rubber Covered
Fluoropolymer Hose



Features

- Personal handling safety
- Handles full vacuum
- Good chemical compatibility
- Easy Cleaning

Compliances

- FDA 21 CFR 177.1550 (FEP core)
- **USP Class VI Certified**
- ISO 10993 Sections 5, 6, 10, 11

Applications/Markets



- Food & Beverage
- Pharmaceutical
- Fluid Handling
- Chemical
- Ground Support
- Industrial
- Paint
- Semiconductor

Part Number	Nominal I.D.		Nominal O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
#										lbs	kg	
Natural	inch	mm	inch	mm	psi	bar	inch	mm	inch	lbs./ft.	kg./mtr.	
08-RCTW	1/2	13	.95	24	500	35	2.50	64	28	.33	.49	PAGE
12-RCTW	3/4	19	1.25	32	500	35	3	76	28	.51	.76	PAGE
16-RCTW	1	25	1.53	39	450	31	4	102	28	.67	1.00	PAGE
20-RCTW	1-1/4	32	1.74	44	375	26	7	178	28	.72	1.07	PAGE
24-RCTW	1-1/2	38	2.13	54	375	26	9	229	28	1.10	1.51	PAGE
32-RCTW	2	51	2.68	68	280	21	10.50	267	28	1.54	2.28	PAGE
40-RCTW	2-1/2	64	3.28	84	200	14	15	381	28	2.07	3.09	PAGE
48-RCTW	3	76	3.88	99	200	14	18	457	28	2.99	4.46	PAGE
64-RCTW	4	102	4.98	127	150	10	22.50	572	28	4.33	6.46	PAGE

Construction

Tube: Natural FEP
Reinforcement: Double Wire Helix - Multi-layered Rubber
Cover: Textile Reinforced EPDM

Operating Parameters

Temperature Range:

- -40°F(-40°C) to +300°F (+149°C) Decrease working pressure one percent for every 2°F above 212°F

Operating pressures shown are for non-impulse service

Change in length at Max. Working Pressure: +2% to -4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Pressure ratings based on 73°F (23°C)

Decrease working pressure 1% for every 2°F above 212°F

Fittings

PAGE Fittings – pg. E-45

Uses crimp collar RC300, see pg. E-46

For most Parker products, Crimp Die Selection charts can be found online at www.parker.com/crimpsource

Access instructions are on pg. G-14

Notes

- See pg. A-21 for part numbering system
- Cannot be used with 91N or 93N series fittings

Metal Hose
9A, 9M, 9H, 9P

See CATALOG 4690MH for technical information



Features:

- Hydroformed annular core tube (9H incorporates helical core)
- High percentage braid coverage for better life cycle and protection against core damage
- 9A - General Purpose - up to 2700 psi working pressures
- 9M - Ultra Flexible - Compressed corrugations for increased flexibility, up to 2700 psi working pressure
- 9H - High Pressure - proprietary design yielding up to 5800 psi working pressure while maintaining flexibility
- 9P - High Pressure - up to 6000 psi working pressure, Parker's highest pressure metal hose construction

Applications/Markets



- Abrasion and over bending – as a protective cover over wires or other hoses to prevent these problems
- Chemical transfer
- Diesel engine exhaust
- Hot oil and lube lines
- Loading/unloading of light oils, gas, and chemicals
- Petrochemical
- Power Gen
  - Connections for the fuel rail to the combustion cans on gas turbine fuel lines
  - Pump connections
- Pulp & Paper
- Solvent and steam lines

Metal Hose Size and Performance Specifications				
Inside Diameter (in.)	9A	9M	9H	9P
1/4	●	●	●	●
3/8	●	●	●	
1/2	●	●	●	●
5/8	●	●	●	●
3/4	●	●	●	●
1	●	●	●	●
1-1/4	●	●	●	●
1-1/2	●	●	●	●
2	●	●		●
2-1/2 - 6	Contact Customer Service			

Construction

Tube: 300 series SS

Reinforcement: 300 series SS braid: 0, 1or 2 layers

Operating Parameters

Temperature Range:
-380°F (-228°C) to +1200°F (+648°C)
For carbon steel fittings:
-70°F (-57°C) to +900°F (+482°C)

Working Pressure
Reference individual pages and derating charts in CAT 4690MH

Notes

Hoses greater than 2" I.D. available - Contact the division

For technical information, download CAT 4690



See CATALOG 4690MH for technical information

Multitube® BOP Bundles, Electro-Hydraulic Umbilicals and Hotlines



Features:

- Dependability and Experience - Over 30 years of Oil & Gas thermoplastic hose design and engineering experience
- Field Tested - Over 750,000 feet of bundles and over 40 million feet of pilot hose produced for rigs
- Capabilities - BOP umbilical lengths up to 7,000+ ft and 90+ pilot hoses within 1 umbilical
- Extended Service Life - Compact pilot hose design allows for more spares to be installed in the bundle without increasing the O.D.

Applications/Markets



- Oil & Gas

For technical information, contact customer services



BOP Umbilicals with Velocity Hose

Parker offers premier hose solutions for every aspect of hydraulic BOP controls. Parker's BOP umbilicals are used on offshore drilling rigs to control the subsea BOP stack. They have a smaller O.D. which means Parker can produce BOP umbilicals with more pilot lines without increasing the O.D. of the umbilical. The umbilical is built with Velocity Hose to allow for precise control and faster response times when activating subsea valves on the BOP pod.



Electro-Hydraulic Umbilicals

Parker is an industry leader in designing short length electro-hydraulic umbilicals for offshore applications. We also produce high-pressure subsea hoses, (1/4", 3/8" and 1/2" I.D.) in compliance to API 17e and pressure ratings up to 15,000 psi. These hoses can be combined into an umbilical configuration with electrical power cables included.



Hotline Hose

Subsea Hotline's are the primary emergency hydraulic control line providing critical service for various subsea functions. Parker Hotline hoses are specially designed to provide fast response time and low volumetric expansion with length capability of 14,000 feet continuous.

A redundant jacket option is available for additional abrasion resistance and protection.

These hoses are custom engineered. For technical information, contact customer service.



For detailed ordering information, please consult price list or contact Parflex Division.

polyflex Ultra-High Pressure Hose

See CATALOG 4900 for technical information




Features:

- Working pressures up to 58,000 psi
- Wide range of hose sizes from 5/64" to 3" I.D.
- Very long continuous lengths available
- Multiple color options for ease of identification
- Wide range of core tube and jacket material options available

Applications/Markets



- Oil & Gas
- Water Blast/Water Jetting
- Hydraulic Tool



Oil & Gas Hose

With production plants in both the USA and Europe, supported by Parker's global sales and distribution network, customers can benefit from local service and the supply of quality parts wherever they are situated. ***polyflex*** Oil & Gas hoses are used in a wide variety of Oil & Gas applications, both onshore and offshore, and are available with seawater resistant cover materials.



Water Blast Hose

polyflex Water Blast Hoses are the highest quality ultra high pressure thermoplastic hoses on the market and are also ideal for construction applications such as hydrodemolition, industrial cleaning and surface preparation.



Hydraulic Tool Hose

polyflex hoses can be used to power hydraulic tools, such as torque wrenches and bolt tensioners. They are also used on rescue equipment such as the Jaws of Life and similar tools.

For technical information, download CAT 4900



See CATALOG 4900 for technical information

For detailed ordering information, please consult price list or contact Parflex Division.

Notes

Thermoplastic

Polyethylene

Nylon

Parprene™ TPE

Polypropylene

Polyurethane

Clear Vinyl

Fluoropolymer

PTFE

FEP

PFA

PVDF




Table of Contents

Thermoplastic Tubing

Introduction

Intro B-4
Tubing Compatibility Chart for Fittings B-8

PolyethyleneTubing

Fractional – Series E/EB B-12
Metric – Series E/EB B-14
Antimicrobial – Series EA B-16
Flame Resistant – Series PEFR B-18
High Density – Series HDPE B-20

Nylon Tubing

Fractional – Series N/NB B-22
Metric – Series N/NB B-24
Pure Air Tubing – Series PAT B-26
Semi-rigid Tubing – Series NR B-28
Series NTNA B-30

Parprene™ Tubing

General Industrial – Series G: B-32
Food & Dairy – Series F: B-34

Polypropylene Tubing

Laboratory Grade – Series PP/PPB B-36

Polyurethane Tubing

Fractional Polyether Base – Series U B-38
Metric Polyether Base – Series UM B-40
HUFR MicroWeld™ – Series HUFR B-42
Fractional – Series HU B-44
Metric – Series HUM B-46

Clear Vinyl Tubing

Clear Vinyl Tubing – Series PV B-48

For detailed ordering information, please consult price list or contact Parflex Division.
Parker Hannifin Corporation | Parflex Division | Ravenna, Ohio | **parker.com/pfd**

Fluoropolymer Tubing

Introduction

Intro B-52
Material Overview B-54
Fluoropolymer Nomenclature B-56

PTFE Tubing

Fractional – Series 101 ..... B-58
Metric – Series 201 ..... B-58
Fractional – Series TFS, TFT, TFL B-62
AWG – Series TFH, TFS, TFT, TFL B-64
Beading - Series TFB B-69
Spiral Cut Cable Wrap, TSWTF B-70
PTFE Fractional Heat Shrink - Series HS2TFS, HS2TFT, HS2TFL, HS2TFI B-72
PTFE AWG 2:1 Heat Shrink - Series HS2TFS, HS2TFT, HS2TFL B-74
PTFE AWG 4:1 Heat Shrink - Series HS4TFI B-78
Convoluted, Convo-Tex® - Series CV B-80
Low Profie, Heavy Wall - Series CVL, CVH B-82
SAE AS81914/1 and 2 - Series 81914 ..... B-84

FEP Tubing

Fractional – Series 103 ..... B-86
Metric – Series 203 ..... B-86
FEP 1.3:1 Heat Shrink - Series HS1.3FEP B-88
FEP 1.67:1 Heat Shrink - Series HS1.67FEP B-90
FEP Roll Cover - Series HS1.25FEP B-92
FEP/PTFE Double Shrink - Series TSSS, TSSL B-93
Convoluted- Series CV03, Convo-Flon™ B-94
SAE AS81914/3 and 4 - Series 81914 ..... B-96
Corrugated - Series CR03 ..... B-98
Retractable Coiled Tubing- Series 703 ..... B-100

PFA Tubing

Fractional – Series 104 ..... B-102
Metric – Series 204 ..... B-102

High Purity PFA Tubing

Fractional – Series 105 ..... B-104
Metric – Series 205 ..... B-104

PVDF Tubing

Flex™– Series 110 ..... B-106
Super-Flex® – Series 111 ..... B-106

Parflex Tubing Introduction

Parflex New, Tubing Product

Parflex has expanded the tubing line to include:



Antimicrobial Tubing

Antimicrobial Tubing for food and beverage applications. This tubing is specially formulated with Sanitized® to resist degradation from mildew, fungi and biofilm that can accumulate on the inside or outside of tubing in filling and processing applications. pg. B-16



Retail Packaging

EZ Pack 100 foot boxes are now available for Nylon and Polyurethane tubing in some sizes. Designed for easy storage and easy dispensing, these boxes are excellent for retail sales and fulfilling small quantity requirements.

Parflex Tubing Tutorial

- Review the general attributes of Parflex thermoplastic and fluoropolymer tubing – this provides an excellent overview for the tubing product line.
- Review the application symbols - this will help you clear up any questions you may have on the product tables within the section. The market/applications table identifies and provides a “good fit” summary.
- Review the pressure bar graph - provides relative pressure ratings for the entire line of thermoplastic tubing. For fluoropolymer tubing, please contact Customer Service.
- Review the STAMPED guide (Size, Temperature, Media, Application, Pressure, End Configuration, and Delivery Preferences) on pg. 13 to help narrow your search for the desired product.
- Specific nomenclature, features, advantages and benefits can be found at the beginning page of each product line.
- Text appears in 2 colors. The primary dimensions are in black. As a courtesy, the metric/inch equivalent has been added and appears in blue.

Tubing Introduction

Tube Line Fabrication Guide for Leak Free Systems

Every hydraulic, pneumatic and lubrication system requires some form of tube line fabrication and fitting installation for completion. Proper fabrication and installation are essential for the overall efficiency, leak free performance and general appearance of any system.

Start by planning ahead. After sizing the tube lines and selecting the appropriate style of fitting, consider the following in the design of your system:

- Accessibility of joints
- Proper routing of lines
- Adequate tube line supports
- Available fabricating tools

Routing of Lines

Routing of lines is probably the most difficult, yet most significant, of these system design considerations. Proper routing involves getting a connecting line from one point to another through the most logical path.

Always try to leave fitting joints as accessible as possible. Hard to reach joints are hard to assemble and tighten properly. Inaccessible joints are also more difficult and time consuming to service.

Applications/Markets


Fluid Handling


Construction


Transportation


Industrial Pneumatic


Electrical


Military


General Industrial


Compressed Gas


Medical


Semiconductor



Food & Beverage


Pharmaceutical

Multitube® Tubing Introduction

See CAT 4200 for technical information

The Multitube® instrumentation product line has produced thermal insulated and heat traced tubing for over 40 years. Tubing and tubing bundles transfer gas, fluids, steam and viscous materials through instrument lines, condensate return lines, cooling water lines, lubriction lines and refrigeration lines. Some of these products are available with heated elements to ensure maximum freeze protection during the winter. The products displayed on these pages are just a sampling of the types of products available in the Multitube line of products. See Catalog 4200 for a detailed review.



Applications/Markets



- Chemical Processing
- Oil & Gas
- Refineries
- Power Generation



MJ - Jacketed Metal Tubing

Bundled tubing is an ideal alternative for applications where multiple lengths of tubing are currently being installed independently. Manufactured with or without protective, galvanized steel armor and a protective outer jacket. Metal tubes are uniquely identified using a number code printed along the entire length of each tube.

MJ - Metal, Jacketed MA - Metal Armored MAJ - Metal, Armor, Jacketed



PJ - Jacketed Plastic Tubing

Bundled tubing is an ideal alternative for applications where multiple lengths of tubing are currently being installed independently. Manufactured with or without protective, galvanized steel armor and a protective outer jacket. Plastic tubes are uniquely identified using a number code printed along the entire length of each tube.


PJ - Plastic, Jacketed PA - Plastic Armored PAJ - Plastic, Armor, Jacketed



TT - Temptube® Preinsulated Tubing

Preinsulated tubing - Transfer of fluids or gases up to 400°F while maintaining an outer jacket surface temperature of 140°F. Insulated bundles rated up to 1200°F. Also available as a custom bundle.

Typically used in steam supply lines, condensate return lines, cooling water lines, lubrication lines, refrigeration lines and liquid nitrogen lines.



LT - Light Steam Trace

Temptrace® LT - Permits use of higher pressure steam to heat trace instrument lines. Single or multiple tubes designed to utilize saturated steam pressures to 230 PSIG (15.8 BAR) and 400°F without generating a process tube temperature in excess of 200°F or a jacket surface temperature greater than 140°F.



SL - Self Regulating Low Temperature Maintenance Bundles

Temptrace® SL - Maintain temperatures up to 150˚F and withstands maximum internal exposure to 185˚F. Designed to provide freeze protection and low temp. maintenance for gases, liquids or viscous materials. With outdoor temperatures of -40°F, SL-Temptrace™ will maintain a process fluid or gas at 40°F to 400°F while maintaining an outer jacket surface temp. of 140°F . Heated cables are available in 120V and 208-277 volt, with heat outputs of 3, 5, 8 and 10 watt/ft.



SH - Self Regulating High Temperature Maintenance Bundles

Temptrace® SH - Maintain temperatures up to 250˚F and withstands an internal exposure temp. of 400˚F. Designed to provide temp. maintenance for gases, liquids or other process materials. Has a max. temp. rating of 250°F (121.1°C), when power to the heating cable is on, and can be steam cleaned at 400°F (204°C), when power to the heating cable is off.



For technical information, download CAT 4200



Parflex Tubing Introduction

Tubing Compatibility Chart

Parker Tubing / Hose Capability with Parker FSC Fittings

		Parflex Thermoplastic and Thermo-elastomer Tubing											
		Industrial Tubing Series (Outside Diameter (O.D.) Shown)											
	Product Sizes (inch)	Polyethylene E, EA, & EB Inch (4,5,6,8,10) Metric (6,8,10,12)	Polyethylene PEFR Inch (2.5,4,6,8)	Polyethylene HDPE Inch (4,6)	Nylon N Inch (2,2.5,3,4,5,6,8)	Nylon PAT Inch (2,4,6,8,10,12)	Nylon NR Inch (2,3,4,5,6,8)	Polypropylene PP & PPB Inch (2,2.5,3,4,6,8,10)	Polyurethane U & UM (90 - 95 Shore A) Inch (2,3,4,6,8,9,12) Metric (4,6,8,10,12)	Polyurethane HU & HUM (>95 Shore A) Inch (2,2.5,4,6,8,12) Metric (4,6,8,10,12)	Polyurethane HUFR (Weld Tubing) Inch (4,6,8)	Clear Vinyl Inch (1/8" - 2 1/2")	Thermo-elastomer Tubing (TPE) Food Grade & Industrial - Inch (3/16" - 1")
Compression & Flare	Compression Inch (2,3,4,5,6,7,8,10,12)	PS TS	PS TS	PS TS	PS TS	PS TS	PS TS	PS TS					
	Compress-Align Inch (2,3,4,5,6,8,10,12,14,16)	TS	TS	TS	TS	TS	TS	TS					
	Metric Compression Metric (4,5,6,8,10,12,14,16,18,20,22,25,28)	TS			TS		TS	TS		TS			
	Poly-Tite Inch (4,5,6,8)				BS			BS					
	Hi-Duty Inch (2,3,4,5,6,8,10)	TS	TS	TS	TS	TS	TS	TS					
	45 degree flare Inch (2,3,4,5,6,8,10,12,14)												
	Inverted Flare Inch (2,3,4,5,6,8,10,12)												
	Fast & Tite Inch (4,5,6,8,10)								TS	TS		TS	
Push-to-Connect	Flow Controls Inch (2,2.5,4,5,6,8) Metric (4,6,8,10,12)												
	Prestolok Brass Inch (2,2.5,3,4,5,6,8)												
	Prestolok Composite Inch (2,2.5,3,4,5,6,8, 10) Metric (3,4,6,8,10,12,14,16)												
	Prestolok All-Metal Inch (2.5,4,5,6,8) Metric (4,6,8,10,12,14)												
	Prestolok Stainless Inch (2.5,3,4,5,6,8) Metric (4,6,8,10,12)												
	Liquifit Inch (2.5,4,6,8) Metric (4,6,8,10,12)												
	TrueSeal Inch (4,5,6,8)						MG		TS	TS		TS	
Barb	Par-Barb Inch (2,3,4,5,6,8,10,12,16,20,24) Inside Diameter								CL			CL	CL
	Dubl-Barb Inch (2.5,4,6,8)												
	Hose Barb Inch (2,3,4,5,6,8,10,12,16) Inside Diameter											CL	CL
	Garden Hose											CL	
DOT Transportation	NTA Inch (3,4,6,8,10,12)												
	Transmission Fittings Inch (2,2.5)												
	Air Brake Inch (4,6,8,10,12,16)												
	Air Brake Hose Inch (6,8)												
	Vibra-Lok Inch (2,3,4,5,6,8,10,12)												
	Prestomatic Inch (4,6,8,10) Metric (6,8,10,12,16)												
	PTC Inch (2.5,3,4,6,8,10,12)												
	SAE Cartridges Inch (4,6,8,10)												

For detailed ordering information, please consult price list or contact Parflex Division.

Tube Line Fabrication Guide for Leak Free Systems

Every hydraulic, pneumatic and lubrication system requires some form of tube line fabrication and fitting installation for completion. Proper fabrication and installation are essential for the overall efficiency, leak free performance, and general appearance of any system.

Start by planning ahead. After sizing the tube lines and selecting the appropriate style of fitting, consider the following in the design of your system:

1. Accessibility of joints
2. Proper routing of lines
3. Adequate tube line supports
4. Available fabricating tools

	Parflex Thermoplastic Tubing				Parflex Fluoropolymer Tubing					
	Transportation Tubing									
	PFT Air Brake (SAE J844) Inch (2,2.5,3,4,5,6,8,10,12)	Air Brake DIN 74324 (Nylon 12) Metric (4,6,8,10,12,15,16,18)	PFT Diesel Fuel Sizes 4,6,8,10,12	HTFL Diesel Fuel Sizes 4,6,8,10,12	PFA Fluoropolymer Inch (3/32" - 1") Metric (4mm - 12mm)	FEP Fluoropolymer Inch (1/8" - 1") Metric (3mm - 12mm)	PTFE Fluoropolymer Inch (3/32" - 1") Metric (3mm - 16mm)	PVDF Fluoropolymer Inch (2,3,4,5,6,8,10,12,16)	Product Sizes (inch)	
					PS TS	PS TS	PS TS	PS TS	Compression Inch (2,3,4,5,6,7,8,10,12)	Compression & Flare
					TS	TS	TS	TS	Compress-Align Inch (2,3,4,5,6,8,10,12,14,16)	Compression & Flare
					TS	TS	TS	TS	Metric Compression Metric (4,5,6,8,10,12,14,16,18,20,22,25,28)	Compression & Flare
									Poly-Tite Inch (4,5,6,8)	Compression & Flare
									Hi-Duty Inch (2,3,4,5,6,8,10)	Compression & Flare
									45 degree flare Inch (2,3,4,5,6,8,10,12)	Compression & Flare
									Inverted Flare Inch (2,3,4,5,6,8,10,12,14)	Compression & Flare
									Fast & Tite Inch (4,5,6,8,10)	Compression & Flare
						■			Flow Controls Inch (2,2.5,4,5,6,8) Metric (4,6,8,10,12)	Push-to-Connect
									Prestolok Brass Inch (2,2.5,3,4,5,6,8)	Push-to-Connect
						■			Prestolok Composite Inch (2,2.5,3,4,5,6,8, 10) Metric (3,4,6,8,10,12,14,16)	Push-to-Connect
						■			Prestolok All-Metal Inch (2.5,4,5,6,8) Metric (4,6,8,10,12,14)	Push-to-Connect
						■			Prestolok Stainless Inch (2.5,3,4,5,6,8) Metric (4,6,8,10,12)	Push-to-Connect
									Liquifit Inch (2.5,4,6,8) Metric (4,6,8,10,12)	Push-to-Connect
					MG	MG	MG	MG	TrueSeal Inch (4,5,6,8)	Push-to-Connect
									Par-Barb Inch (2,3,4,5,6,8,10,12,16,20,24) Inside Diameter	Barb
									Dubl-Barb Inch (2.5,4,6,8)	Barb
									Hose Barb Inch (2,3,4,5,6,8,10,12,16) Inside Diameter	Barb
									Garden Hose	Barb
	■		■	■					NTA Inch (3,4,6,8,10,12)	DOT Transportation
									Transmission Fittings Inch (2,2.5)	DOT Transportation
	TS								Air Brake Inch (4,6,8,10,12,16)	DOT Transportation
									Air Brake Hose Inch (6,8)	DOT Transportation
									Vibra-Lok Inch (2,3,4,5,6,8,10,12)	DOT Transportation
	■	■	■						Prestomatic Inch (4,6,8,10) Metric (6,8,10,12,16)	DOT Transportation
	■		■						PTC Inch (2.5,3,4,6,8,10,12)	DOT Transportation
	■		■						SAE Cartridges Inch (4,6,8,10)	DOT Transportation

PS	Plastic Sleeve & Tube Support Recommended
TS	Tube Support Is Recommended
BS	Brass Sleeve Recommended
CL	Clamp Required
MG	Metal Gripper Collet Recommended
■	Tube/Fitting Combination Compatible
	Tube/Fitting Combination NOT Compatible

For detailed ordering information, please consult price list or contact Parflex Division.

Thermoplastic Tubing

Polyethylene

- Parflex polyethylene tubing meets FDA, NSF Standard 51 for all food contact applications and NSF-61 for potable water applications.
- E-Series NSF tubing is made of 100% virgin resin material.
- Polyethylene tubing meets ASTM D-1693 (10% IGEPAL) for stress crack resistance.
- Parflex also offers special PE tubing: PEFR (flame retardant) and HDPE (high density).

Nylon

- Flexible nylon tubing is constructed of high-grade resins for strength and flexibility for routing in tight spaces.
- Semi-rigid high strength nylon is constructed of high-grade resins without the addition of plasticizers for higher pressure tubing applications.
- Pure Air Tubing (PAT) is the tubing choice for pure air systems (semiconductor) due to its cleanliness; in addition, it offers excellent chemical and UV light resistance.
- NTNA Tubing meets NSF Standard 51 for all food contact applications and may be used for instrumentation lines, lubrication and process piping systems and oil and refrigerant lines.

Parprene™ (thermoplastic elastomer)

- Excellent flexural fatigue resistance.
- Resistant to environmental stress cracking.
- Series F meets FDA, NSF Standard 51 and 3-A approved for all food contact applications.

Polypropylene

- Polypropylene tubing meets FDA, NSF Standard 51 for all food contact applications.
- Polypropylene tubing exhibits excellent chemical resistance to chlorinated water applications.
- Black Polypropylene tubing is commonly used in outdoor applications where UV light stabilization is required.

Polyurethane

- Polyurethane tubing is a flexible, kink-resistant and abrasion-resistant material commonly used in pneumatic applications.
- Polyurethane is available in multiple transparent and opaque colors for system color coding.
- Polyurethane is available in the following durometers (measurement of material hardness):
  Medium durometer: (90 – 95)
  High durometer: (>95) for higher pressures

Polyvinyl Chloride (PVC)

- PVC tubing is made from 100% virgin resin material and meets all FDA specifications for materials in contact with food and drugs.
- PVC tubing is a very flexible, 70 durometer tubing. It is crystal-clear and ideal for situations where visible fluid flow is necessary (i.e. sight gauges for tank identification).


All plastic tubing dimensions are laser monitored to ensure overall quality product.
Most tubing sizes are packaged in convenient 100-ft., 250-ft., 500-ft. and 1,000-ft. lengths.

Thermoplastic Tubing

Typical Applications

Product Family	Series	Suggested Markets and Applications
Polyethylene	E and EB	Potable water, chemical transfer, and low-cost, low-pressure pneumatics, NSF-51 & NSF- 61
	PEFR	Pneumatic controls in HVAC
	HDPE	Chemical transfer and low-cost pneumatics
	EA	Formulated with Sanitized® for food and beverage
Nylon	N	Pneumatic and petroleum-based chemical transfer
	PAT	Pure air and gas distribution systems, semiconductor
	NR	High pressure pneumatic, low pressure lubrication and hydraulic, marine control systems
	NTNA	Instrumentation lines, lubrication and process piping systems, oil and refrigerant lines, NSF-51
Polypropylene	PP and PPB	Food contact and chemical transfer applications, chlorinated water, NSF-51
Urethane	U and UM	Pneumatic controls requiring high flexibility, kink resistance and movement
	HU and HUM	High-pressure pneumatics requiring flexibility and kink resistance, robotics
Parprene™	TPE, Series G	Thermoplastic elastomer, black, general industrial tubing
	TPE, Series F	Thermoplastic elastomer, tan, food & dairy FDA compliant tubing
Vinyl	PV	Low-pressure chemical and medical applications requiring high clarity and flexibility, FDA


Tubing Pressure Ranges



Working pressures are at 73°F (23°C). Pressure ratings are also effected by diameter of tubing and wall thickness. Actual performance may vary with different media and working conditions. Use this information for comparison only.

Polyethylene Tubing

Series E: Instrument Grade – FDA, NSF Listed
Series EB: Ultraviolet Light Resistant



Features

- Made from 100% virgin resin material
- Chemically resistant and flexible
- High molecular weight resin provides increased dimensional stability, uniformity and long-term strength
- Economical system solution

Certifications

- FDA compliant for food contact
- ASTM D-1693 (10% IGEPAL) for stress crack resistance
- NSF – 51
- NSF – 61

Applications/Markets

- Potable water
- Chemical transfer
- Low-pressure pneumatics

Part Number	Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Package Quantity	Minimum Bend Radius		Weight	
#	#											Package quantities vary by size and color			lbs	kg
Natural	Black	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	feet	inch	mm	lbs./ft.	kg./mtr.
E-43-XXXX	EB-43-XXXX	1/4	6.4	.170	4.3	.040	1.0	120	8.3	480	33.1	0100, 0500, 1000	1.00	25.4	.011	.016
E-53-XXXX	EB-53-XXXX	5/16	7.9	.187	4.8	.062	1.6	145	10.0	580	40.0	0100, 0500	1.13	28.7	.020	.030
E-64-XXXX	EB-64-XXXX	3/8	9.5	.250	6.4	.062	1.6	125	8.6	500	34.5	0100, 0500	1.25	31.8	.025	.037
E-86-XXXX	EB-86-XXXX	1/2	12.7	.375	9.5	.062	1.6	90	6.2	360	24.8	0100, 0500	2.50	63.5	.034	.051
E-108-XXXX	EB-108-XXXX	5/8	15.9	.500	12.7	.062	1.6	70	4.8	280	19.3	0100	4.00	101.6	.044	.065

Standard black is not NSF approved.

For detailed ordering information, please consult price list or contact Parflex Division.

Order Information

Example: E-64-Y-0500

E-64-Y-0500 – **Polyethylene**

E-**6**4-Y-0500 – **Tube O.D.** in sixteenths of an inch **(3/8")**

E-6**4**-Y-0500 – **Tube I.D.** in sixteenths of an inch **(.250")**

E-64-**Y**-0500 – **Color,** i.e. **Yellow** (Omit for Natural and Black)
E-64-0500 – Natural Polyethylene
EB-64-0500 – Black Polyethylene


E-64-Y-**0500** – **Package Quantity** in feet **(500')**

Available in black as well as nine other colors, as suggested by the Instrument Society of America

Color Code		
	-	Natural
	-	Black
	B	Blue
	G	Green
	O	Orange
	P	Purple
	R	Red
	GRA	Gray
	Y	Yellow
	WHT	White

Polyethylene Tubing (Series E)

Maximum Working Pressure (psig)



Fittings

Parker fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 694-4614 FAX

FSC Product Families:

- Compression
- Compress-Align®
- Poly-Tite
- Hi-Duty
- Fast & Tite
- Flow Controls
- Prestolok Brass
- Prestolok Composite
- Prestolok Stainless
- Prestolok All-Metal
- Liquifit
- TrueSeal™
- Dubl-Barb®

For tube support use, reference Tubing/Fitting Compatibility Chart (pg. B-8/B-9) or contact Fluid System Connectors Division (269) 692-6555

Notes


- E series natural and colored tubing meet FDA, NSF-51 requirements for food contact applications and NSF-61 for potable water
- FDA, NSF-51 and NSF-61 compliant black polyethylene tubing is also available.
  Add -NSF suffix to the EB part number
  (ie. EB-64-0500-NSF)
- Resistant to environmental stress cracking exceeding that of ordinary polyethylene tubing as measured by ASTM D-1693 (10% IGEPAL)
- Black (EB) tubing is suggested for use in sunlit areas and in close proximity to high ultraviolet light sources
- All tubing conforms to ASTM D-1248, Type I, Class A, Category 4, Grade E5
- The operating temperature range for service at rated pressures with compatible fluids is -80˚F (-62˚C) to +150˚F (66˚C)

Colors

- See Color Code Table

Metric Polyethylene Tubing

Series E: Instrument Grade – FDA, NSF Listed
Series EB: Ultraviolet Light Resistant



Features

- Made from 100% virgin resin material
- Chemically resistant and flexible
- High molecular weight resin provides increased dimensional stability, uniformity and long-term strength
- Economical system solution

Certifications

- FDA compliant for food contact
- ASTM D-1693 (10% IGEPAL) for stress crack resistance
- NSF – 51
- NSF – 61

Applications/Markets





- Potable water
- Chemical transfer
- Low-pressure pneumatics

Part Number	Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Package Quantity	Minimum Bend Radius		Weight	
#	#														kg	lbs
Natural	Black	mm	inch	mm	inch	mm	inch	bar	psi	bar	psi	feet	mm	inch	kg./mtr.	lbs./ft.
E-6X1-0100	EB-6X1-0100	6	.236	4	.157	1.00	.039	8.6	125	34.5	500	0100	25	1.00	.019	.013
E-8X1-0100	EB-8X1-0100	8	.315	6	.236	1.00	.039	6.9	100	27.6	400	0100	38	1.50	.021	.014
E-10X1.5-0100	EB-10X1.5-0100	10	.393	7	.276	1.50	.059	8.6	125	34.5	500	0100	38	1.50	.039	.026
E-12X1.5-0100	EB-12X1.5-0100	12	.472	9	.354	1.50	.059	6.2	100	24.8	400	0100	63	2.50	.048	.032

Standard black is not NSF approved.

For detailed ordering information, please consult price list or contact Parflex Division.


Order Information

Example: E-8x1-0100

E-8x1-0100 – **Metric Polyethylene (Natural)**
EB-8x1-0100 – Metric Polyethylene (Black)
E-8x1-0100 – **Tube O.D.** in millimeters **(8 mm)**
E-8x**1**-0100 – **Tube Wall Thickness** in millimeters **(1 mm)**
E-8x1-**0100** – **Package Quantity** in feet **(100')**

Metric Polyethylene Tubing (Series E)

Maximum Working Pressure (bar)



Fitting Recommendations

Parker fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 694-4614 FAX

FSC Product Families:

- Compression Metric
- Flow Controls
- Prestolok Composite
- Prestolok All-Metal
- Prestolok Stainless
- Liquifit

For tube support use, reference Tubing/Fitting Compatibility Chart (pg. B-8/B-9) or contact Fluid System Connectors Division (269) 692-6555

Notes

- E series natural tubing listed below meet FDA, NSF-51 requirements for food contact applications and NSF-61 for potable water
- Resistant to environmental stress cracking exceeding that of ordinary polyethylene tubing as measured by ASTM D-1693 (10% IGEPAL)
- Black (EB) tubing is suggested for use in sunlit areas and in close proximity to high ultraviolet light sources
- All tubing conforms to ASTM D-1248, Type I, Class A, Category 4, Grade E5
- The operating temperature range for service at rated pressures with compatible fluids is -85˚F (-65˚C) to +150˚F (66˚C)


Colors

○ Natural

● Black

Antimicrobial Polyethylene Tubing

Series EA: Formulated with Sanitized®



Features

- Polyethylene treated with Sanitized® resist degradation from mildew, fungi and biofilm
- BPA and phthalate free
- Resistant to environmental stress cracking exceeding that of ordinary polyethylene tubing as measured per ASTM D-1693 (10% IGEPAL)
- Blue tube color allows quick identification
- Use with Parker antimicrobial filters to create a complete system
- Extensive range of compatible Parker fittings

Applications/Markets





- Food & Beverage
- Water systems
- Low pressure pneumatics

Certifications/Comliances

- U.S. FDA 21 CFR 177.1520
- NSF-51
- ASTM D-1248, Type I, Class A, Category 4, Grade E5
- ASTM D-1693 (10% IGEPAL)
- REACH and RoHS compliant

Part Number	Tube O.D.		Tube I.D.		Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Minimum Bend Radius		Weight per 100 feet	
#													lbs	kg
Natural	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	lbs./ft.	kg./mtr.
EA-43	1/4	6.35	0.170	4.32	0.040	1.02	120	8.3	480	33	1	25	1.05	.476
EA-64	3/8	9.52	0.250	6.35	0.062	1.57	125	8.6	500	34	1-1/4	42	2.45	1.11
EA-86	1/2	12.70	0.375	9.52	0.062	1.57	90	6.2	360	25	2-1/2	64	3.36	1.52





PARKER PARFLEX EA WITH SANITIZED® NSF-51 3/8 O.D

For detailed ordering information, please consult price list or contact Parflex Division.

Order Information

Example: EA-64-0100

EA-64-0100 – **Polyethylene**

E**A**-64-0100 – A**ntimicrobial**


EA-**6**4-0100 – **Tube O.D.** in sixteenths of an inch **(3/8")**

EA-6**4**-0100 – **Tube I.D.** in sixteenths of an inch **(.250")**

EA-64-**0100** – **Package Quantity** in feet **(100')**

Polyethylene Tubing (Series EA)

Maximum Working Pressure (psig)



Fittings

Parker fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 694-4614 FAX

FSC Product Families:

- Compression
- Compress-Align®
- Poly-Tite
- Hi-Duty
- Fast & Tite
- Flow Controls
- Prestolok Brass
- Prestolok Composite
- Prestolok Stainless
- Prestolok All-Metal
- Liquifit
- TrueSeal™
- Dubl-Barb®

For tube support use, reference Tubing/Fitting Compatibility Chart (pg. B-8/B-9) or contact Fluid System Connectors Division (269) 692-6555

Notes

- Packaged 100 foot coils - sealed clear polyethylene bag
  Special lengths available, contact Parflex division
- The operating temperature range for service at rated pressures with compatible fluids is -80°F (-62°C) to +120°F (48°C)


Color

● Arctic blue

. X .062 WALL WP 125 PSI TEMP 120 F MAX 44A15103724

Polyethylene Tubing

Series PEFR: Flame Resistant



Features

- Excellent stress crack resistance

Certifications

- UL 94 V-2
- ASTM D-1693 (10% IGEPAL) for stress crack resistance

Applications/Markets

- Pneumatic controls in HVAC applications

Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Package Quantity	Minimum Bend Radius		Weight	
#														lbs	kg
Black	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	feet	inch	mm	lbs./ft.	kg./mtr.
PEFR-2.5-XXXX	5/32	4.0	.096	2.4	.030	0.76	185	12.8	740	51.0	0500	.50	12.7	.006	.009
PEFR-4-XXXX	1/4	6.4	.170	4.3	.040	1.0	140	9.7	560	38.6	0500, 1000	.75	17.4	.012	.018
PEFR-6-XXXX	3/8	9.5	.250	6.4	.062	1.6	155	10.7	620	42.8	0500	1.50	36.1	.029	.043
PEFR-8-XXXX	1/2	12.7	.375	9.5	.062	1.6	100	6.9	400	27.6	0250	1.75	39.1	.041	.061

Order Information


Example: PEFR-4-0500

PEFR-4-0500 – **Flame Resistant Polyethylene**

PEFR-**4**-0500 – **Tube O.D.** in sixteenths of an inch **(1/4")**

PEFR-4-**0500** – **Package Quantity** in feet **(500')**

Flame Resistant Polyethylene Tubing (Series PEFR) Maximum Working Pressure (psig)



Fittings

Parker fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 694-4614 FAX

- FSC Product Families:
- Compression
- Compress-Align
- Hi-Duty
- Fast & Tite®
- Prestolok® Brass
- Dubl-Barb®

For tube support use, reference Tubing/Fitting Compatibility Chart (pg. B-8/B-9) or contact Fluid System Connectors Division (269) 692-6555

Notes

Using the same base linear low-density polyethylene (LLDPE) as the E-Series tubing, Parker Hannifin, Parflex Division's PEFR tubing has the following advantages:


- Resistant to environmental stress cracking exceeding that of ordinary polyethylene tubing as measured by ASTM D-1693 (10% IGEPAL)
- The operating temperature range for service at rated pressures with compatible fluids is -85°F (-65°C) to +150°F (66°C)

Colors

- Black

Polyethylene Tubing

Series HDPE: High Density



Features

- Manufactured from high strength, high density polyethylene
- Semi-rigid tubing that is inherently resistant to most chemicals, less easily cut or damaged and has a higher burst pressure rating than Series E tubing
- Economical system solution

Applications/Markets





- Chemical transfer
- Low-pressure pneumatics

Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Package Quantity	Minimum Bend Radius		Weight	
#														lbs	kg
Black	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	feet	inch	mm	lbs./ft.	kg./mtr.
HDPE-43-XXXX	1/4	6.4	.170	4.3	.040	1.0	300	20.7	1200	82.7	0250, 0500	1.50	38.1	.011	.016
HDPE-64-XXXX	3/8	8.5	.250	6.4	.062	1.6	300	20.7	1200	82.7	0250, 0500	2.50	63.5	.025	.037

Only available in black.

For detailed ordering information, please consult price list or contact Parflex Division.

Order Information

Example: HDPE-43-0500

HDPE-43-0500 – **High Density Polyethylene**


HDPE-**4**3-0500 – **Tube O.D.** in sixteenths of an inch **(1/4")**

HDPE-4**3**-0500 – **Tube I.D.** in sixteenths of an inch **(.170")**

HDPE-43-**0500** – **Package Quantity** in feet **(500')**

High Density Polyethylene Tubing (Series HDPE)

Maximum Working Pressure (psig)



Fittings

Parker fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 694-4614 FAX

- Compression
- Compress-Align
- Hi-Duty
- Fast & Tite®
- Prestolok® Brass
- Dubl-Barb®

For tube support use, reference Tubing/ Fitting Compatibility Chart (pg. B-8/B-9) or contact Fluid System Connectors Division (269) 692-6555


Notes

- Recommended operating temperature range for service at rated pressures with compatible fluids is -80°F (-62°C) to +175°F (80°C)

Colors

- Black

Nylon Tubing
Series N: Flexible



Features

- Flexible nylon tubing uses high-grade resins for strength and flexibility for routing in tight spaces
- Made from abrasion-resistant, heat and light-stabilized nylon
- Exhibits low-level water absorption
- Chemically resistant



Contact Customer Service for Retail Packaging Options

EZ Pack 100 foot boxes available for some sizes.

Applications/Markets

- Robotics
- Machine tool
- General pneumatics
- Lubrication
- Petroleum-based chemical transfer
- Pest control lines

Part Number	Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Reel Length	Minimum Bend Radius		Weight	
#	#														lbs	kg
Natural	Black	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	feet	inch	mm	lbs./ft.	kg./mtr.
NN-2-016	NB-2-016	1/8	3.2	.093	2.4	.016	0.41	250	17.2	1000	69.0	0100, 0250	.25	4.6	.003	.005
NN-2-031	NB-2-031	1/8	3.2	.064	1.6	.031	0.79	500	34.5	2000	137.9	0100, 0250	.25	4.6	.004	.006
NN-2.5-025	NB-2.5-025	5/32	4.0	.106	2.7	.025	0.64	300	20.7	1200	82.7	0100, 0250	.50	12.7	.005	.007
NN-3-025	NB-3-025	3/16	4.8	.138	3.5	.025	0.64	250	17.2	1000	69.0	0100, 0250	.63	16.0	.006	.009
NN-3-046	NB-3-046	3/16	4.8	.096	2.4	.046	1.2	500	34.5	2000	137.9	0100, 0250	.44	11.2	.009	.013
NN-4-035	NB-4-035	1/4	6.4	.180	4.6	.035	0.89	250	17.2	1000	69.0	0100, 0250	.88	22.4	.011	.016
NN-4-040	NB-4-040	1/4	6.4	.170	4.3	.040	1.0	310	21.4	1250	86.2	0100, 0250	.88	22.4	.012	.018
NN-4-062	NB-4-062	1/4	6.4	.127	3.2	.062	1.6	500	34.5	2000	137.9	0100, 0250	.50	12.7	.017	.025
NN-5-040	NB-5-040	5/16	7.9	.233	5.9	.040	1.0	250	17.2	1000	69.0	0100, 0250	1.13	28.7	.016	.024
NN-6-050	NB-6-050	3/8	9.5	.275	7.0	.050	1.3	250	17.2	1000	69.0	0100, 0250	1.13	28.7	.023	.034
NN-6-093	NB-6-093	3/8	9.5	.190	4.8	.093	2.4	500	34.5	2000	137.9	0100, 0250	.75	19.0	.038	.056
NN-8-062	NB-8-062	1/2	12.7	.375	9.5	.062	1.6	250	17.2	1000	69.0	0100, 0250	1.25	31.8	.039	.058
NN-8-124	NB-8-124	1/2	12.7	.253	6.4	.124	3.2	500	34.5	2000	137.9	0100, 0250	1.00	25.4	.067	.099

Order Information

Example: N-2-016-RED-0100

N-2-016-RED-0100 – **Nylon**

N-**2**-016-RED-0100 – **Tube O.D.** in sixteenths of an inch **(1/8")**

N-2-**016**-RED-0100 – **Wall Thickness** in inches **(.016")**

N-2-016-**RED**-0100 – **Colors** (Omit for Natural and Black)
NN-2-016-0100 - Natural Nylon
NB-2-016-0100 - Black Nylon


N-2-016-RED-**0100** – **Package Quantity** in feet **(100')**

(Omit quantity number after color for 250' reel length)

Color Code		
○	NN	Natural
●	NB	Black
●	BLU	Blue
●	GRN	Green
●	RED	Red
●	YEL	Yellow

Nylon Tubing (Series N)

Maximum Working Pressure (psig)



Fittings

Parker fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 694-4614 FAX

FSC Product Families:

- Compression
- Compress-Align®
- Poly-Tite
- Hi-Duty
- Fast & Tite
- Flow Controls
- Prestolok Brass
- Prestolok Composite
- Prestolok All-Metal
- Prestolok Stainless
- TrueSeal™
- NTA®
- Transmission

For tube support use, reference Tubing/Fitting Compatibility Chart (pg. B-8/B-9) or contact Fluid System Connectors Division (269) 692-6555

Notes

- The operating temperature range for service at rated pressures with compatible fluids, depending upon conditions, is -65°F (-54°C) to +200°F (93°C)
- Black tubing suggested for use in sunlit areas and in close proximity to high ultraviolet light sources

Colors

- See Color Code Table

Metric Nylon Tubing

Series N: Flexible



Features

- Flexible nylon tubing uses high-grade resins for strength and flexibility for routing in tight spaces
- Made from abrasion-resistant, heat and light-stabilized nylon
- Exhibits low-level water absorption
- Chemically resistant

Applications/Markets

- Robotics
- Machine tool
- General pneumatics
- Lubrication
- Petroleum-based chemical transfer
- Pest control lines

Part Number	Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Reel Length	Weight	
#	#													
Natural	Black	mm	inch	mm	inch	mm	inch	bar	psi	bar	psi	feet	kg./mtr.	lbs./ft.
NN4X.65	NB4X.65	4	.157	2.7	.107	0.65	.026	20.7	300	82.7	1200	100	.007	.005
NN6X1	NB6X1	6	.236	4.0	.157	1.00	.039	23.5	341	94	1363	100	.016	.011
NN8X1	NB8X1	8	.315	6.0	.236	1.00	.039	17.0	247	68	986	100	.024	.016
NN10X1	NB10X1	10	.393	8.0	.315	1.00	.039	12.5	181	50	725	100	030	.020
NN12X1	NB12X1	12	.472	10.0	.393	1.00	.039	11.0	160	44	638	100	.036	.024
NN14X1.5	NB14X1.5	14	.551	11.0	.433	1.50	.059	15.0	218	60	870	100	.063	.042
NN16X1.5	NB16X1.5	16	.630	13.0	.512	1.50	.059	12.5	181	50	725	100	.073	.049
NN18X1.5	NB18X1.5	18	.709	15.0	.591	1.50	.059	10.5	152	42	609	100	.082	.055
NN20X1.5	NB20X1.5	20	.787	17.0	.669	1.50	.059	9.5	138	38	551	100	.092	.062

For detailed ordering information, please consult price list or contact Parflex Division.

Order Information

Example: NN4x.65

NN4x.65 – **Natural Nylon**

NN**4**x.65 – **Tube O.D.** in millimeters **(4mm)**

NN4x**.65** – **Wall Thickness** in millimeters **(0.65mm)**

Fittings

Parker fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 694-4614 FAX

FSC Product Families:

- Metric Compression
- Flow Controls
- Prestolok Composite
- Prestolok All-Metal
- Prestolok Stainless

For tube support use, reference Tubing/ Fitting Compatibility Chart (pg. B-8/B-9) or contact Fluid System Connectors Division (269) 692-6555

Notes

- The operating temperature range for service at rated pressures with compatible fluids, depending upon conditions, is -65°F (-54°C) to +200°F (93°C)
- Black tubing suggested for use in sunlit areas and in close proximity to high ultraviolet light sources


Colors

○ Natural

● Black


Metric Nylon Tubing (Series N)

Maximum Working Pressure (bar)



Nylon Pure Air Tubing

Series PAT: Ultra Pure, UV Resistant



Features

- The tubing choice for pure air systems (semiconductor) due to its cleanliness and excellent chemical and UV light resistance
- Maintains good resistance to high ambient temperatures with low moisture absorption
- Manufactured from a specially formulated nylon for use in pure air and gas distribution systems
- Provides high tensile strength with excellent coupling retention in high pressure, temperature and vibration environments
- Sizes -2 and -4 are single wall tubing construction
- Sizes -6 through -12 are reinforced tubing construction

Applications/Markets




- Pure air and gas distribution systems
- Semi-conductor



Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Reel Length	Minimum Bend Radius		Weight	
#														lbs	kg
	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	feet	inch	mm	lbs./ft.	kg./mtr.
PAT2	1/8	3.2	.079	2.0	.023	0.58	250	17.2	1000	69.0	1000	.37	9.4	.035	.052
PAT4	1/4	6.4	.170	4.3	.040	1.0	300	20.7	1200	82.7	1000	1.00	25.4	.124	.185
PAT6	3/8	9.5	.251	6.4	.062	1.6	350	24.1	1400	96.4	500	1.50	38.1	.282	.420
PAT8	1/2	12.7	.376	9.6	.062	1.6	235	16.2	950	65.5	500	2.00	50.8	.395	.588
PAT10	5/8	15.9	.441	11.2	.092	2.3	225	15.5	900	62.1	250	2.50	63.5	.702	1.04
PAT12	3/4	19.1	.566	14.4	.092	2.3	200	13.8	800	55.2	250	3.00	76.2	.872	1.30

For detailed ordering information, please consult price list or contact Parflex Division.

Order Information

Example: PAT4-BLK-0250

PAT4-BLK-0250 – **Pure Air Tubing**

PAT**4**-BLK-0250 – **Tube O.D.** in sixteenths of an inch **(1/4")**


PAT4-**BLK**-0250 – **Color (Black)**

PAT4-BLK-**0250** – **Package Quantity** in feet **(250')**

Color Code		
●	BLK	Black
●	BRN	Brown
●	SIL	Silver

Pure Air Nylon Tubing (Series PAT)

Maximum Working Pressure (psig)



Fittings

Parker fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 694-4614 FAX

FSC Product Families:

- Compression
- Compress-Align®
- Hi-Duty
- Fast & Tite
- NTA®

For tube support use, reference Tubing/ Fitting Compatibility Chart (pg. B-8/B-9) or contact Fluid System Connectors Division (269) 692-6555

Notes


- Packaged on corrugated plastic reel with ends capped and shipped in a plastic-lined container
- The operating temperature range for service at rated pressures with compatible fluids is -70°F (-57°C) to +200°F (93°C)
- PAT tubing is rated for full vacuum service at 28 inch Hg

Colors

- See Color Code Table

Nylon Tubing

Series NR: Semi-rigid High Strength



Features

- High grade nylon resins without the addition of plasticizers for higher pressure tubing applications
- Chemical resistant, good resistance to high ambient temperature and low moisture absorption
- High tensile strength and excellent coupling retention in high pressure, temperature and vibration environments
- Better dimensional stability at elevated temperatures than N Series

Applications/Markets



- High-pressure pneumatics and oils
- Lubrication systems
- Marine control systems
- Process lines for chemicals

Part Number	Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Reel Length	Minimum Bend Radius		Weight	
#	#														lbs	kg
Natural	Black	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	feet	inch	mm	lbs./ft.	kg./mtr.
NNR-2-017	NBR-2-017	1/8	3.2	.091	2.3	.017	0.43	425	29.3	1700	117.2	0100, 0500	.50	12.7	.003	.005
NNR-2-026	NBR-2-026	1/8	3.2	.073	1.9	.026	0.66	625	43.1	2500	172.4	0100, 0500	.38	9.7	.004	.006
NNR-3-024	NBR-3-024	3/16	4.8	.140	3.6	.024	0.61	425	29.3	1700	117.2	0100, 0500	.75	19.0	.006	.009
NNR-3-039	NBR-3-039	3/16	4.8	.110	2.8	.039	0.99	625	43.1	2500	172.4	0100, 0500	.63	16.0	.008	.012
NNR-4-035	NBR-4-035	1/4	6.4	.180	4.6	.035	0.89	425	29.3	1700	117.2	0100, 0250	1.00	25.4	.011	.016
NNR-4-050	NBR-4-050	1/4	6.4	.150	3.9	.050	1.3	625	43.1	2500	172.4	0100, 0250	.88	22.3	.014	.021
NNR-5-040	NBR-5-040	5/16	7.9	.233	5.9	.040	1.0	425	29.3	1700	117.2	0100, 0250	1.50	38.1	.015	.022
NNR-6-048	NBR-6-048	3/8	9.5	.279	7.1	.048	1.2	425	29.3	1700	117.2	0100, 0250	1.75	44.5	.022	.033
NNR-6-075	NBR-6-075	3/8	9.5	.225	5.7	.075	1.9	625	43.1	2500	172.4	0100, 0250	1.50	38.1	.032	.048
NNR-8-062	NBR-8-062	1/2	12.7	.375	9.5	.062	1.6	375	26	1500	103.4	0100, 0250	2.38	60.5	.038	.057
NNR-8-075	NBR-8-075	1/2	12.7	.350	8.9	.075	1.9	625	43.1	2500	172.4	0100, 0250	2.50	63.5	.045	.067

For detailed ordering information, please consult price list or contact Parflex Division.

Order Information

Example: NBR-2-017-0100

NBR-2-017-0100 – **Nylon**

N**B**R-2-017-0100 – **Color** (Black)

NB**R**-2-017-0100 – **Rigid**

NBR-**2**-017-0100 – **Tube O.D.** in sixteenths of an inch **(1/8")**


NBR-2-**017**-0100 – **Wall Thickness** in inches **(.017")**

NBR-2-017-**0100** – **Package Quantity** in feet **(100')**

(Omit for other package quantities)

Semi-rigid Nylon Tubing (Series NR)

Maximum Working Pressure (psig)



Fittings

Parker fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 694-4614 FAX

FSC Product Families:

- Compress-Align®
- Compression
- Fast & Tite®
- Flow Controls
- Hi-Duty
- Prestolok® All-Metal
- Prestolok® Brass
- Prestolok® Composite
- Prestolok® Stainless
- TrueSeal™

For tube support use, reference Tubing/ Fitting Compatibility Chart (pg. B-8/B-9) or contact Fluid System Connectors Division (269) 692-6555

Notes

- The operating temperature range for service at rated pressures with compatible fluids is -60°F (-51°C) to +200°F (93°C)

Colors

○ Natural

● Black

Nylon Tubing

Series NTNA: Semi-rigid Nylon Tubing



Features

- High grade nylon resins without the addition of plasticizers
- High tensile strength and excellent coupling retention in high pressure, temperature and vibration environments
- Excellent chemical resistance
- Rugged construction resists vermin attack

Certifications

- NSF-51

Applications/Markets



- Instrumentation lines
- Lubrication systems
- Process piping systems
- Refrigerant lines

Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Reel Length	Minimum Bend Radius		Weight	
#														lbs	kg
	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	feet	inch	mm	lbs./ft.	kg./mtr.
22NTNA	1/8	3.2	.091	2.3	.017	0.4	375	25.9	1,500	103.4	500	0.50	12.7	.003	.005
532NTNA	5/32	4.0	.113	2.9	.022	0.6	375	25.9	1,500	103.4	500	0.63	16.0	.004	.006
33NTNA	3/16	4.8	.139	3.5	.024	0.6	375	25.9	1,500	103.4	350	0.75	19.0	.006	.009
44NTNA	1/4	6.4	.184	4.7	.033	0.8	375	25.9	1,500	103.4	200	1.00	25.4	.010	.015
55NTNA	5/16	7.9	.232	5.8	.040	1.0	375	25.9	1,500	103.4	150	1.50	38.1	.015	.022
66NTNA	3/8	9.5	.282	7.1	.048	1.2	375	25.9	1,500	103.4	100	1.75	44.4	.022	.033
88NTNA	1/2	12.7	.375	9.5	.062	1.6	375	25.9	1,500	103.4	100	2.38	60.5	.032	.048

For detailed ordering information, please consult price list or contact Parflex Division.

Order Information

Example: 44NTNA

44NTNA – **Tube O.D.** in sixteenths of an inch **(1/4")**

44**NT**NA – **Nylon Tubing**

44NT**NA** – **Color** (Natural)

Fittings

Parker fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 694-4614 FAX

Notes


- The operating temperature range for service at rated pressures with compatible fluids is -60°F (-51°C) to +212°F (100°C)

Colors

○ Natural

Semi-rigid Nylon Tubing (Series NTNA)

Maximum Working Pressure (psig)



TPE Parprene™ Tubing

Series G: General Industrial



Features

- Excellent flexural fatigue resistance
- Ozone and UV light resistant
- Temperatures from (-75°F to 275°F)
- Abrasion resistant
- Resistant to environmental stress cracking
- Lot-to-lot traceability
- Chemically compatible with common sanitizers and cleaners
- Extensive range of compatible Parker fittings and couplers

Applications/Markets



- Wastewater Sampling
- Cable Insulation
- Caustic Dispensing
- Ink and toner feed lines
- Chemical Transfer

Part Number	Tube O.D. (Ref.)		Tube I.D.		Wall Thickness		Maximum Working Pressure		Minimum Bend Radius		Standard Coil		Weight per 100 feet	
#													lbs	kg
	inch	mm	inch	mm	inch	mm	psi	bar	inch	mm	feet	mtr.	lb.	kg.
G64-31	0.188	5	0.062	2	0.062	1.59	34	2.34	1/4	6	50	15.2	1.03	0.47
G64-42	0.250	6	0.125	3	0.062	1.59	19	1.31	1/2	13	50	15.2	1.55	0.70
G64-53	0.312	8	0.188	5	0.062	1.59	13	0.90	3/4	19	50	15.2	2.06	0.93
G64-64	0.375	10	0.250	6	0.062	1.59	10	0.69	1-1/4	32	50	15.2	2.58	1.17
G64-75	0.438	11	0.312	8	0.062	1.59	8	0.55	1-1/2	38	50	15.2	3.10	1.41
G64-84	0.500	13	0.250	6	0.125	3.18	19	1.31	3/4	19	50	15.2	6.19	2.81
G64-86	0.500	13	0.375	10	0.062	1.59	7	0.48	2-1/4	57	50	15.2	3.61	1.64
G64-106	0.625	16	0.375	10	0.125	3.18	13	0.90	1-1/4	32	50	15.2	8.26	3.75
G64-128	0.750	19	0.500	13	0.125	3.18	10	0.69	2	51	50	15.2	10.32	4.68
G64-1410	0.875	22	0.625	16	0.125	3.18	8	0.55	3-1/4	83	50	15.2	12.39	5.62
G64-1612	1.000	25	0.750	19	0.125	3.18	7	0.48	4	102	50	15.2	14.45	6.56

For detailed ordering information, please consult price list or contact Parflex Division.

Order Information

Example: G64-31

G64-31 – **TPE, General Series**

G**64**-31 – **Hardness Durometer (64 Shore A)**

G64-**3**1 – **Tube O.D.** in sixteenths of an inch **(3/16")**

G64-3**1** – **Tube I.D.** in sixteenths of an inch **(1/16")**

Fittings

Parker fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 694-4614 FAX

FSC Product Families:

- Par-Barb® Thermoplastic
- Dubl-Barb®
- Hose Barb

For tube support use, reference Tubing/ Fitting Compatibility Chart (pg. B-8/B-9) or contact Fluid System Connectors Division (269) 692-6555

Couplings

Parker couplings available from:
Quick Coupling Division
Minneapolis, MN
(763) 544-7781
(763) 544-3418 FAX

QCD Product Families:

- Spectrum Series
- PPM Series
- PPL Series

Notes


- TPE is a thermoplastic elastomer formulated to withstand the rigors of peristaltic pump applications and yet, be safe enough for food and beverage applications.
- The operating temperature range for service at rated pressures with compatible fluids is -75°F (-59°C) to +275°F (135°C)
- Packaged 50 foot coils - sealed clear polyethylene bag, barcoded, 1 per box for lot traceability
- Special lengths available, contact Parflex division

Colors

● Black

TPE Parprene™ Tubing

Series F: Food & Dairy



Features

- Excellent flexural fatigue resistance
- Ozone and UV light resistant
- Temperatures from (-75°F to 275°F)
- Abrasion resistant
- Resistant to environmental stress cracking
- Lot-to-lot traceability
- Chemically compatible with common sanitizers and cleaners
- Extensive range of compatible Parker fittings and couplers
- Latex free material

Applications/Markets

- Hot/Cold beverage dispensing
- Food and dairy processing lines
- Chemical transfer
- Water purification lines
- Soap dispensing

Certifications

- FDA compliant for food contact
- NSF-51 Approved
- 3-A Approved

Part Number	Tube O.D. (Ref.)		Tube I.D.		Wall Thickness		Maximum Working Pressure		Minimum Bend Radius		Standard Coil		Weight per 100 feet	
#													lbs	kg
	inch	mm	inch	mm	inch	mm	psi	bar	inch	mm	feet	mtr.	lb.	kg.
F64-31	0.188	5	0.062	2	0.062	1.59	34	2.34	1/4	6	50	15.2	1.03	0.47
F64-42	0.250	6	0.125	3	0.062	1.59	19	1.31	1/2	13	50	15.2	1.55	0.70
F64-53	0.312	8	0.188	5	0.062	1.59	13	0.90	3/4	19	50	15.2	2.06	0.93
F64-64	0.375	10	0.250	6	0.062	1.59	10	0.69	1-1/4	32	50	15.2	2.58	1.17
F64-75	0.438	11	0.312	8	0.062	1.59	19	1.31	1-1/2	38	50	15.2	3.10	1.41
F64-84	0.500	13	0.250	6	0.125	3.18	8	0.55	3/4	19	50	15.2	6.19	2.81
F64-86	0.500	13	0.375	10	0.062	1.59	7	0.48	2-1/4	57	50	15.2	3.61	1.64
F64-106	0.625	16	0.375	10	0.125	3.18	13	0.90	1-1/4	32	50	15.2	8.26	3.75
F64-128	0.750	19	0.500	13	0.125	3.18	10	0.69	2	51	50	15.2	10.32	4.68
F64-1410	0.875	22	0.625	16	0.125	3.18	8	0.55	3-1/4	83	50	15.2	12.39	5.62
F64-1612	1.000	25	0.750	19	0.125	3.18	7	0.48	4	102	50	15.2	14.45	6.56

For detailed ordering information, please consult price list or contact Parflex Division.

Order Information

Example: F64-31

F64-31 – **TPE, General Series**

F**64**-31 – **Hardness Durometer (64 Shore A)**

F64-**3**1 – **Tube O.D.** in sixteenths of an inch **(3/16")**

F64-3**1** – **Tube I.D.** in sixteenths of an inch **(1/16")**

Fittings

Parker fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 694-4614 FAX

FSC Product Families:

- Par-Barb® Thermoplastic
- Dubl-Barb®
- Hose Barb

For tube support use, reference Tubing/ Fitting Compatibility Chart (pg. B-8/B-9) or contact Fluid System Connectors Division (269) 692-6555

Couplings

Parker couplings available from:
Quick Coupling Division
Minneapolis, MN
(763) 544-7781
(763) 544-3418 FAX

QCD Product Families:

- Spectrum Series
- PPM Series
- PPL Series

Notes


- TPE is a thermoplastic elastomer formulated to withstand the rigors of peristaltic pump applications and yet, be safe enough for food and beverage applications.
- The operating temperature range for service at rated pressures with compatible fluids is -75°F (-59°C) to +275°F (135°C)
- Packaged 50 foot coils - sealed clear polyethylene bag, barcoded, 1 per box for lot traceability
- Special lengths available, contact Parflex division

Colors

- Tan

Polypropylene Tubing

Series PP: Laboratory Grade – FDA, NSF Listed
Series PPB: Ultraviolet Light Resistant



Features

- Acid and chemically resistant
- May be used in higher temperatures and working pressures than polyethylene tubing
- Excellent compatibility with high temperature water
- Low water absorption (less than .01%)
- Good compatibility with vegetable oils
- Excellent resistance to environmental stress cracking

Certifications

- FDA
- NSF-51

Both in white; NSF also in special black part numbers

Applications/Markets



- Food contact - White only
- Chemical transfer
- Chlorinated water



Part Number	Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Reel Length	Minimum Bend Radius		Weight	
#	#															
White	Black	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	feet	inch	mm	lbs./ft.	kg./mtr.
PP-21-1000	PPB-21-1000	1/8	3.2	.079	2.0	.023	0.58	350	24.1	1400	96.4	1000	.50	12.7	.003	.005
PP-32-0500	PPB-32-0500	3/16	4.8	.120	3.1	.034	0.86	350	24.1	1400	96.4	0500	.75	14.4	.006	.009
PP-43-0500	PPB-43-0500	1/4	6.4	.170	4.3	.040	1.0	300	20.7	1200	82.7	0500	1.00	25.4	.010	.019
PP-53-0500	PPB-53-0500	5/16	7.9	.188	4.8	.062	1.6	350	24.1	1400	96.4	0500	1.25	31.8	.019	.028
PP-64-0500	PPB-64-0500	3/8	9.5	.250	6.4	.062	1.6	300	20.7	1200	82.7	0500	1.25	31.8	.024	.036
PP-86-0250	PPB-86-0250	1/2	12.7	.375	9.5	.062	1.6	225	15.5	900	62.1	0250	2.50	63.5	.033	.049
PP-108-0100	PPB-108-0100	5/8	15.9	.500	12.7	.062	1.6	175	12.1	700	48.3	0100	4.00	101.6	.042	.062

Order Information

Example: PP-86-0250

PP-86-0250 – **Polypropylene**


PP-**8**6-0250 – **Tube O.D.** in sixteenths of an inch **(1/2")**

PP-8**6**-0250 – **Tube I.D.** in sixteenths of an inch **(.375")**

PP-86-**0250** – **Package Quantity** in feet **(250')**

Polypropylene Tubing (Series PP & PPB)

Maximum Working Pressure (psig)



Fittings

Parker fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 694-4614 FAX

FSC Product Families:

- Compression
- Compress-Align®
- Poly-Tite
- Hi-Duty
- Fast & Tite
- Prestolok Brass
- TrueSeal™

For tube support use, reference Tubing/Fitting Compatibility Chart (pg. B-8/B-9) or contact Fluid System Connectors Division (269) 692-6555

Notes

- NSF black polypropylene tubing is available upon special request. Add -FDA suffix to PPB part number
- The operating temperature range for service at rated pressures with compatible fluids is 0°F (-18°C) to +200°F (93°C)


Colors

○ White

● Black

Polyurethane Tubing

Series U: Polyether Base



Features

- 90 to 95 Shore A durometer
- Excellent kink and abrasion resistance
- Excellent hydrolytic stability
- Flexible and easy to assemble onto designated fittings
- Polyurethane tubing exhibits the elongation and recovery characteristics of rubber and the chemical resistance associated with plastics

Applications/Markets



- Pneumatic controls
- Robotics
- Machine tools
- General pneumatics
- Vacuum equipment
- Analytical instrumentation
- Semiconductor equipment
- Medical and laboratory applications

Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Reel Length	Weight	
#												lbs	kg
Natural	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	feet	lbs./ft.	kg./mtr.
U-21-XXXX	1/8	3.2	.063	1.6	.031	0.79	125	8.6	375	25.9	0050, 0250, 0500, 1000	.005	.007
U-32-XXXX	3/16	4.8	.125	3.2	.031	0.79	125	8.6	375	25.9	0050, 0250, 0500	.008	.012
U-42-XXXX	1/4	6.4	.125	3.2	.063	1.6	125	8.6	375	25.9	0050, 0250, 0500, 1000	.018	.027
U-64-XXXX	3/8	9.5	.250	6.4	.063	1.6	125	8.6	375	25.9	0050, 0250, 0500, 1000	.030	.045
U-85-XXXX	1/2	12.7	.328	8.3	.086	2.2	125	8.6	375	25.9	0050, 0250, 0500	.044	.065
U-86-XXXX	1/2	12.7	.375	9.5	.063	1.6	85	5.9	255	17.6	0050, 0250, 0500	.042	.062
U-96-XXXX	9/16	14.3	.375	9.5	.094	2.4	125	8.6	375	25.9	0050, 0100	.068	.101
U-128-XXXX	3/4	19.1	.500	12.7	.125	3.2	125	8.6	375	25.9	0050, 0100	.120	.179

Also available in coils



Contact Customer Service for Retail Packaging Options

EZ Pack 100 foot boxes available for some sizes.

For detailed ordering information, please consult price list or contact Parflex Division.

Order Information

Example: U-21-BLK-0500

U-21-BLK-0500 – **Polyurethane**

U-**2**1-BLK-0500 – **Tube O.D.** in sixteenths of an inch **(1/8")**

U-2**1**-BLK-0500 – **Tube I.D.** in sixteenths of an inch **(.063")**

U-21-**BLK**-0500 – **Color (Black)** (Omit for Natural)


U-21-BLK-**0500** – **Package Quantity** in feet **(500')**

Opaque Color Code		
○	-	Natural
●	BLK	Black
●	BLU	Blue
●	GRA	Gray
●	GRN	Green
●	ORG	Orange
●	RED	Red
○	WHT	White
●	YEL	Yellow

Transparent Color Code		
●	TBLU	Transparent Blue
●	TGRN	Transparent Green
●	TORG	Transparent Orange
●	TRED	Transparent Red
●	TYEL	Transparent Yellow

Polyurethane Tubing (Series U)

Maximum Working Pressure (psig)



Fittings

Parker fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 694-4614 FAX

FSC Product Families:

- Fast & Tite
- TrueSeal™
- Par-Barb®

For tube support use, reference Tubing/ Fitting Compatibility Chart (pg. B-8/B-9) or contact Fluid System Connectors Division (269) 692-6555

Notes


- The operating temperature range for service at rated pressures with compatible fluids is -40°F (-40°C) to +180°F (82°C)

Colors

- See Color Code Table

Metric Polyurethane Tubing

Series UM: Polyether Base



Features

- 90 to 95 Shore A durometer
- Excellent kink and abrasion resistance
- Excellent hydrolytic stability
- Flexible and easy to assemble onto designated fittings
- Polyurethane tubing exhibits the elongation and recovery characteristics of rubber and the chemical resistance associated with plastics

Applications/Markets



- Pneumatic controls
- Robotics
- Machine tools
- General pneumatics
- Vacuum equipment
- Analytical instrumentation
- Semiconductor equipment
- Medical and laboratory applications

Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Reel Length	Weight	
#												kg	lbs
Natural	mm	inch	mm	inch	mm	inch	bar	psi	bar	psi	feet	kg./mtr.	lbs./ft.
UM4x2.5-XXXX	4	.157	2.5	.098	0.75	.030	9.0	131	26.0	377	0100, 0250, 0500	.009	.006
UM6x4-XXXX	6	.236	4.0	.157	1.00	.039	9.0	131	26.0	377	0100, 0250, 0500	.018	.012
UM8x5-XXXX	8	.315	5.0	.196	1.50	.059	9.0	131	26.0	377	0100, 0250, 0500	.036	.024
UM10x6.5-XXXX	10	.393	6.5	.256	1.75	.069	9.0	131	26.0	377	0100, 0250	.053	.036
UM12x8-XXXX	12	.472	8.0	.315	2.00	.079	9.0	131	26.0	377	0100, 0250	.073	.049

Order Information

Example: UM6x4-BLK-0100

UM6X4-BLK-0100 – **Polyurethane Metric**

UM**6**X4-BLK-0100 – **Tube O.D.** in millimeters **(6 mm)**

UM6X**4**-BLK-0100 – **Tube I.D.** in millimeters **(4 mm)**

UM6X4-**BLK**-0100 – **Color (Black)** (Omit for Natural)

UM6X4-BLK-**0100** – **Package Quantity** in feet **(100')**

Opaque Color Code		
○	-	Natural
●	BLK	Black
●	BLU	Blue
●	GRA	Gray
●	GRN	Green
●	ORG	Orange
●	RED	Red
●	YEL	Yellow

Transparent Color Code		
●	TBLU	Transparent Blue
●	TGRN	Transparent Green
●	TORG	Transparent Orange
●	TRED	Transparent Red
●	TYEL	Transparent Yellow

Fittings

Parker fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 694-4614 FAX

FSC Product Families:

- Prestolok Brass
- Par-Barb

For tube support use, reference Tubing/ Fitting Compatibility Chart (pg. B-8/B-9) or contact Fluid System Connectors Division (269) 692-6555

Notes


- The operating temperature range for service at rated pressures with compatible fluids is -40°F (-40°C) to +180°F (82°C)

Colors

- See Color Code Table


Metric Polyurethane Tubing (Series UM)

Maximum Working Pressure (bar)



For detailed ordering information, please consult price list or contact Parflex Division.

HUFR MicroWeld™ Tubing



Features

- Mono-wall construction eliminates the need for skiving tools or knives, reducing installation time
- Excellent abrasion resistance
- Silicone and halogen free
- Weighs 36% less than equivalent covered tubing

Certifications

- UL 94 V2 compliant

Applications/Markets



- Robotics
- Welding
- General automation

Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Reel Length	Minimum Bend Radius		Weight	
#														lbs	kg
	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	feet	inch	mm	lbs./ft.	kg./mtr.
HUFR-4-045-XX-0500	1/4	6.4	.160	4.1	.045	1.1	175	12.1	525	36.2	0500	.50	12.7	.016	.024
HUFR-6-062-XX-0500	3/8	9.5	.251	6.4	.062	1.6	150	10.3	450	31.0	0500	.75	19.1	.033	.049
HUFR-8-090-XX-0250	1/2	12.7	.320	8.1	.090	2.3	160	11.0	475	32.7	0250	1.00	25.4	.063	.094

For detailed ordering information, please consult price list or contact Parflex Division.

Order Information

Example: HUFR-4-045-BL-0500

HUFR-4-045-BL-0500 – **MicroWeld™ Polyurethane**
HUFR-**4**-045-BL-0500 – **Tube O.D.** in sixteenths of an inch **(1/4")**
HUFR-4-**045**-BL-0500 – **Wall Thickness** in inches **(.045")**
HUFR-4-045-**BL**-0500 – **Color (Blue)**
HUFR-4-045-BL-**0500** – **Package Quantity** in feet **(500')**

Color Code		
●	BK	Black
●	BL	Blue
●	GN	Green
●	RD	Red
○	WH	White

Fittings

Parker fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 694-4614 FAX

FSC Product Families:

- Prestolok All-Metal
- Prestolok Stainless

For tube support use, reference Tubing/ Fitting Compatibility Chart (pg. B-8/B-9) or contact Fluid System Connectors Division (269) 692-6555

Notes


- The operating temperature range for service at rated pressures with compatible fluids is -40°F (-40°C) to +180°F (82°C)

Colors

- See Color Code Table

MicroWeld™ Tubing (Series HUFR)

Maximum Working Pressure (psig)



Polyurethane Tubing

Series HU: High Durometer Polyether Base



Features

- 95 Shore A durometer or greater
- Excellent kink and abrasion resistance
- Excellent hydrolytic stability
- Flexible and easy to assemble onto designated fittings
- Polyurethane tubing exhibits the elongation and recovery characteristics of rubber and the chemical resistance associated with plastics

Applications/Markets



- Pneumatic controls
- Robotics
- Machine tools
- General pneumatics
- Vacuum equipment
- Analytical instrumentation
- Semiconductor equipment
- Medical and laboratory applications

Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Reel Length	Weight	
#												lbs	kg
	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	feet	lbs./ft.	kg./mtr.
HU-2-XXXX	1/8	3.2	.063	1.6	.031	0.79	300	20.7	900	62.1	0100, 0250, 0500	.005	.007
HU-2.5-XXXX	5/32	4.0	.094	2.4	.031	0.79	210	14.5	630	43.4	0100, 0500	.006	.009
HU-4-XXXX	1/4	6.4	.160	4.1	.045	1.1	180	12.4	540	37.2	0100, 0500	.014	.021
HU-6-XXXX	3/8	9.5	.250	6.4	.062	1.6	180	12.4	540	37.2	0100, 0500	.030	.045
HU-8-XXXX	1/2	12.7	.320	8.1	.090	2.3	180	12.4	540	37.2	0100, 0250	.057	.085
HU-12-XXXX	3/4	19.1	.467	11.9	.142	3.6	180	12.4	540	37.2	0100, 0250	.133	.198

Order Information

Example: HU-2-BLK-0500

HU-2-BLK-0500 – **High Durometer Polyurethane**

HU-**2**-BLK-0500 – **Tube O.D.** in sixteenths of an inch **(1/8")**

HU-2-**BLK**-0500 – **Color (Black)**

HU-2-BLK-**0500** – **Package Quantity** in feet **(500')**

Color Code		
●	BLK	Black
●	BLU	Blue
●	DBL	Dark Blue
●	RED	Red
●	YEL	Yellow

Fittings

Parker fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 694-4614 FAX

FSC Product Families:

- Metric Compression
- Fast & Tite
- Flow Controls
- Prestolok Brass
- Prestolok Composite
- Prestolok All-Metal
- Prestolok Stainless
- TrueSeal™

For tube support use, reference Tubing/ Fitting Compatibility Chart (pg. B-8/B-9) or contact Fluid System Connectors Division (269) 692-6555

Notes


- The operating temperature range for service at rated pressures with compatible fluids is -40°F (-40°C) to +180˚F (82˚C)

Colors

- See Color Code Table

Polyurethane Tubing (Series HU)

Maximum Working Pressure (psig)



Metric Polyurethane Tubing

Series HUM: High Durometer (Metric) Polyether Base



Features

- 95 Shore A durometer or greater
- Excellent kink and abrasion resistance
- Excellent hydrolytic stability
- Flexible and easy to assemble onto designated fittings
- Polyurethane tubing exhibits the elongation and recovery characteristics of rubber and the chemical resistance associated with plastics

Applications/Markets



- Pneumatic controls
- Robotics
- Machine tools
- General pneumatics
- Vacuum equipment
- Analytical instrumentation
- Semiconductor equipment
- Medical and laboratory applications

Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Reel Length	Weight	
#													
	mm	inch	mm	inch	mm	inch	bar	psi	bar	psi	feet	kg./mtr.	lbs./ft.
HUM-4-XXXX	4	.157	2.4	.094	0.80	.031	12.4	180	37.2	540	0100, 0500	.009	.006
HUM-6-XXXX	6	.236	4.0	.157	1.00	.039	12.4	180	37.2	540	0100, 0500	.018	.012
HUM-8-XXXX	8	.315	5.0	.196	1.50	.059	12.4	180	37.2	540	0100, 0500	.036	.024
HUM-10-XXXX	10	.393	6.5	.256	1.75	.069	12.4	180	37.2	540	0100, 0250	.053	.036
HUM-12-XXXX	12	.472	8.0	.315	2.00	.079	12.4	180	37.2	540	0100, 0250	.073	.049

For detailed ordering information, please consult price list or contact Parflex Division.

Order Information

Example: HUM-6-BLK-0100

HUM-6-BLK-0100 – **High Durometer Metric Polyurethane**

HUM-**6**-BLK-0100 – **Tube O.D.** in millimeters **(6mm)**

HUM-6-**BLK**-0100 – **Color (Black)**

HUM-6-BLK-**0100** – **Package Quantity** in feet **(100')**

Fittings

Parker fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 694-4614 FAX

FSC Product Families:

- Metric Compression
- Flow Controls
- Prestolok Composite
- Prestolok All-Metal
- Prestolok Stainless

For tube support use, reference Tubing/ Fitting Compatibility Chart (pg. B-8/B-9) or contact Fluid System Connectors Division (269) 692-6555

Notes

- The operating temperature range for service at rated pressures with compatible fluids is -40°F (-40°C) to +180°F (82°C)


Colors

○ Natural

● Black

Metric Polyurethane Tubing (Series HUM)


Maximum Working Pressure (bar)



HUM (All Sizes)

Vinyl Tubing

Series PV: Clear Vinyl Tubing



Features

- Made from a virgin clear PVC (polyvinyl chloride) resin; specifically formulated for exceptional purity, clarity and flexibility
- 70 durometer for soft, easy handling and bending without tubing collapse

Certifications

- FDA compliant

Applications/Markets




- Low-pressure chemicals
- Pneumatics
- Low-pressure sight flow indicator

Order Information

Example: PV108-1

PV108-1 – **Poly-Vinyl Tubing**

PV**10**8-1 – **Tube O.D.** in sixteenths of an inch **(5/8")**

PV10**8**-1 – **Tube I.D.** in sixteenths of an inch **(1/2")**

PV108-**1** – **Formula V-1 FDA Approved Formulation**

Fittings

Parker fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 694-4614 FAX

FSC Product Families:

- Poly-Tite
- Fast & Tite
- TrueSeal™
- Par-Barb®
- Hose Barb
- Garden Hose

For tube support use, reference Tubing/Fitting Compatibility Chart (pg. B-8/B-9) or contact Fluid System Connectors Division (269) 692-6555

Notes

- Formula V-1 tubing fully meets all specifications called out by the United States Food and Drug Administration (FDA) for materials in contact with food and drugs for human consumption
- The operating temperature range for service at rated pressures with compatible fluids is -40°F (-40°C) to +150°F (65°C)

For detailed ordering information, please consult price list or contact Parflex Division.

Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Std. Coil	Weight	
#										lbs	kg
	inch	mm	inch	mm	inch	mm	psi	bar	feet	lbs./ft.	kg./mtr.
PV21-1	1/8	3.2	.063	1.6	.031	.79	35	2.4	100	.005	.007
PV32-1	.170	4.3	.125	3.2	.025	.64	35	2.4	100	.006	.009
PV42-1	1/4	6.4	.125	3.2	.063	1.6	65	4.5	100	.025	.037
PV43-1	1/4	6.4	.170	4.3	.040	1.2	55	3.8	100	.014	.021
PV403-1	1/4	6.4	.188	4.8	.031	.79	22	1.5	100	.011	.016
PV53-1	5/16	7.9	.188	4.8	.063	1.6	55	3.8	100	.025	.037
PV63-1	3/8	9.5	.188	4.8	.094	2.4	65	4.5	100	.043	.064
PV73-1	7/16	11.1	.188	4.8	.125	3.2	75	5.2	100	.063	.094
PV54-1	5/16	7.9	.250	6.4	.031	.79	20	1.4	100	.014	.021
PV64-1	3/8	9.5	.250	6.4	.064	1.6	55	3.8	100	.032	.048
PV74-1	7/16	11.1	.250	6.4	.094	2.4	60	4.1	100	.052	.077
PV84-1	1/2	12.7	.250	6.4	.125	3.2	70	4.8	100	.076	.113
PV75-1	7/16	11.1	.313	7.9	.063	1.6	50	3.4	100	.038	.057
PV85-1	1/2	12.7	.313	7.9	.094	2.4	60	4.1	100	.062	.092
PV95-1	9/16	14.3	.313	7.9	.125	3.2	70	4.8	100	.088	.131
PV86-1	1/2	12.7	.375	9.5	.063	1.6	45	3.1	100	.044	.065
PV96-1	9/16	14.3	.375	9.5	.094	2.4	50	3.4	100	.071	.106
PV106-1	5/8	15.9	.375	9.5	.125	3.2	60	4.1	100	.101	.150
PV97-1	9/16	14.3	.438	11.1	.063	1.6	40	2.8	100	.050	.074
PV107-1	5/8	15.9	.438	11.1	.094	2.4	45	3.1	100	.080	.119
PV117-1	11/16	17.5	.438	11.1	.125	3.2	50	3.4	100	.115	.171
PV108-1	5/8	15.9	.500	12.7	.063	1.6	30	2.1	100	.057	.085
PV118-1	11/16	17.5	.500	12.7	.094	2.4	40	2.8	100	.089	.132
PV128-1	3/4	19.1	.500	12.7	.125	3.2	45	3.1	100	.126	.187
PV138-1	13/16	20.7	.500	12.7	.156	4.0	60	4.1	100	.167	.248
PV129-1	3/4	19.1	.563	14.3	.094	2.4	40	2.8	100	.099	.147
PV139-1	13/16	20.7	.563	14.3	.125	3.2	45	3.1	100	.138	.205

Vinyl Tubing (cont.)

Series PV: Clear Vinyl Tubing

Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Std. Coil	Weight	
#										lbs	kg
	inch	mm	inch	mm	inch	mm	psi	bar	feet	lbs./ft.	kg./mtr.
PV1310-1	13/16	20.7	.625	15.9	.094	2.4	35	2.4	100	.108	.161
PV1410-1	7/8	22.2	.625	15.9	.125	3.2	40	2.8	100	.151	.225
PV1510-1	15/16	23.8	.625	15.9	.156	4.0	50	3.5	100	.196	.292
PV1411-1	7/8	22.2	.688	17.5	.094	2.4	30	2.1	100	.118	.176
PV1611-1	1	25.4	.688	17.5	.156	4.0	45	3.1	100	.213	.317
PV1612-1	1	25.4	.750	19.1	.125	3.2	35	2.4	100	.176	.262
PV1712-1	1-1/16	27.0	.750	19.1	.156	4.0	35	2.4	100	.228	.339
PV1812-1	1-1/8	28.6	.750	19.1	.188	4.8	50	3.5	100	.283	.421
PV2012-1	1-1/4	31.8	.750	19.1	.250	6.4	55	3.8	50	.409	.609
PV1814-1	1-1/8	28.6	.875	22.2	.125	3.2	30	2.1	50	.201	.299
PV1914-1	1-3/16	30.2	.875	22.2	.156	4.0	35	2.4	100	.259	.385
PV2014-1	1-1/4	31.8	.875	22.2	.188	4.8	45	3.1	50	.321	.478
PV2016-1	1-1/4	31.8	1.000	25.4	.125	3.2	25	1.7	50	.230	.342
PV2116-1	1-5/16	33.4	1.000	25.4	.156	4.0	30	2.1	50	.291	.433
PV2216-1	1-3/8	34.9	1.000	25.4	.188	4.8	40	2.8	50	.359	.534
PV2416-1	1-1/2	38.1	1.000	25.4	.250	6.4	45	3.1	50	.514	.765
PV2218-1	1-3/8	34.9	1.125	28.6	.125	3.2	25	1.7	50	.252	.375
PV2420-1	1-1/2	38.1	1.250	31.8	.125	3.2	20	1.4	50	.277	.412
PV2620-1	1-5/8	41.3	1.250	31.8	.188	4.8	35	2.4	50	.434	.646
PV2820-1	1-3/4	44.4	1.250	31.8	.250	6.4	45	3.1	50	.604	.899
PV3024-1	1-7/8	47.6	1.500	38.1	.188	4.8	30	2.1	50	.510	.759
PV3224-1	2	50.8	1.500	38.1	.250	6.4	40	2.8	50	.705	1.05
PV3628-1	2-1/4	57.2	1.750	11.1	.250	6.4	30	2.1	50	.806	1.20
PV4032-1	2-1/2	63.5	2.000	50.8	.250	6.4	35	2.4	50	.906	1.35

Notes

Fluoropolymer Tubing

Fluoropolymer tubing features a low coefficient of friction and anti-stick properties, high temperature capabilities and the most corrosion and chemical resistance of all polymers. Within normal use temperatures, fluoropolymers are attacked by so few chemicals that it is easier to describe the exceptions rather than list the chemicals they are compatible with (see Chemical Resistance Summary, pg. B-54). These chemically inert tubes are non-wetting and non-leaching, making them ideal for a wide range of fluid and material handling applications.

Parker fluoropolymer tubing is available in PTFE, FEP, PFA and PVDF with some materials operating at temperatures up to 500°F (260°C). Each material has specific dominant characteristics, but all operate in high-temperature, corrosive environments.

- Parflex PTFE, FEP, PFA and PVDF tubing complies with European Standard RoHs and are also FDA compliant to FDA regulation 21 CFR 177.1550, making these products suitable for use in food and beverage applications.
- Parflex PTFE, FEP and PFA are listed VW-1 in the burning test for Underwriters Laboratories and pass the UL-83 vertical flame test. In a flame situation, PTFE, FEP and PFA tubing resist combustion and do not promote flame spread.

All fluoropolymer tubing dimensions are continuosly monitored to ensure an overall quality product.
Most tubing sizes are packaged in convenient 25-ft., 50-ft., 100-ft. and 1,000-ft. lengths.

PTFE

- PTFE (Polytetrafluoroethylene) is offered in beading, smoothbore tubing, heat shrinkable, spiral wrap and convoluted tubing.
- PTFE tubing features unmatched chemical resistance and a non-stick surface that facilitates flow and eliminates media buildup.

FEP

- FEP (Fluorinated Ethylene Propylene) is available in smoothbore tubing, heat shrinkable, convoluted, corrugated and retractable coil tubing.
- FEP tubing offers the highest clarity in the fluoropolymer market and is a close second to PTFE in chemical resistance.
- FEP is available in long, continuous lengths (1,000 feet and longer) whereas the longest lengths for PTFE range from 200 to 1,000 feet depending on size and wall thickness.

PFA

- PFA (Perfluoroalkoxy) is available in smoothbore tubing.
- When temperature and clarity are both factors, PFA is the resin of choice because it offers the high-temperature attributes of PTFE, long continuous lengths, and almost as much clarity as FEP.
- High purity resins available.
- Low permeability.

Fluoropolymer Tubing

Product Family	Type	Series		Suggested Applications		Suggested Markets
PTFE	Beading	TFB		Pull Cord O-Ring Seals	Spacers Woven Filter	Chemical High-Temp Food Instrumentation Laboratory Gas Sampling Electrical Insulation Fluid Handling Industrial Equipment Ground Support
	Smoothbore	TFH TFS	TFT TFL	Electrical Insulation Protective Cover	Circuit Board Wire Insulation	
	Smoothbore	101	201	Electrical Insulation Fluid Transfer	Gas Sampling Laboratory	
	Heat Shrink	HS2T	HS4T TSSS/L	Electrical Insulation Protective Cover	Circuit Board Rollers	
	Convoluted	CV CVL	CVH 81914	Fluid Transport Wire Harness	Protection/Cable Core Robotics	
	Spiral Wrap	TSWTF		Cable Harnessing	Wiring closets	Aerospace Automotive
FEP	Smoothbore	103	203	Nitrogen Filling Downhole Pump Ozone Sampling	Hearing Aid Optical Sensors	UV Applications Chemical Instrumentation Laboratory Gas Dispensing Gas Sampling Robotics Fluid Handling Food & Beverage Semiconductor Pharmaceutical Electrical Industrial Equipment Medical
	Heat Shrink	HS1.3 HS1.6 HS1.25	TSSS TSSL	Protective Covering UV Light Covering Product Testing	Paper Rollers Ink Rollers	
	Convoluted	CV	81914	Fluid Transport Wire Harness	Protection/Cable Core Robotics	
	Corrugated	CR		Vacuum Applications Wet Bench DNA Sequencer	Fluid Transfer Robotics	
	Retractable	703		Lab Equipment Gas Dispensing	Wet Bench Dual Containment	
PFA	Smoothbore	104	204	Air Sampling Gas Purge Wet Bench	Flow Monitoring Steam Plant	Chemical Laboratory Semiconductor Instrumentation Food Environmental Fluid Handling Gas Service Pharmaceutical Medical
H.P. PFA	Smoothbore	105	205	Flow Monitoring Systems High Purity Apps. DI Water Dispensers	DI Recirculators Heat Exchangers Pure Chemical Dispensers	
PFA H.P. PFA	Retractable	704	705	Lab Equipment Gas Dispensing	Wet Bench Dual Containment	
PVDF	Smoothbore	110	111	Outdoor/Extreme Conditions Applications with long cycle life	Thermal Cycling Water Systems	Chemical Food Gas/Environmental

High Purity PFA

- H.P. PFA (Perfluoroalkoxy) has the highest molecular weight available.
- Withstands corrosive surfactants for longer periods of time than standard products.
- Lowest level of extractables.

PVDF

- PVDF (Polyvinylidene Fluoride) is available in flexible and super flexible smoothbore tubing.
- PVDF offers a combination of properties beneficial for use in many critical applications requiring chemical resistance with low permeability.
- ▪ PVDF exhibits low extractable levels while providing high mechanical strength and abrasion resistance.

Fluoropolymer Tubing

Fluoropolymer - Quick Reference

PTFE (Polytetrafluoroethylene)
Working Temperature: 500°F (260°C)
Color: Opaque to translucent

- Chemically inert
- Lowest coefficient of friction
- Superior dielectric strength
- Exceptional heat resistance
- Self extinguishing
- Non-wetting
- Excellent flexlife
- Laser markable

PFA (Perfluoroalkoxy)
Working Temperature: 500°F (260°C)
Color: Clear with light blue or tint

- High purity resins available
- Low permeation resins available
- Use when you need the temperature range of PTFE and the clarity of FEP
- Exceptional heat resistance
- Self extinguishing
- Non-wetting
- Good flexlife

FEP (Fluorinated Ethylene Propylene)
Working Temperature: 400°F (204°C)
Color: Clear

- Excellent chemical resistance
- Non-wetting
- Weldable
- Tubes can be sealed by melting
- Long continuous lengths
- Low refractive index
- Improved clarity over PFA
- Lower cost alternative to PFA

PVDF (Polyvinylidene Fluoride)
Working Temperature: 265°F (130°C)
Color: Varies

- Very good chemical resistance
- Excellent resistance to creep and fatigue
- UV Resistant
- Weldable
- Exceptional corrosion resistance for chlorine, fluorine, or bromine environments

Chemical Resistance Summary

Within normal use, temperatures, fluoropolymers are attacked by so few chemicals that it is easier to describe the exceptions rather than list the chemicals they are compatible with.

DO NOT USE FLUOROPLASTICS WITH THE FOLLOWING:

- Alkali metals such as elemental sodium, potassium, lithium, etc. The alkali metals remove fluorine from the polymer molecule.
- Extremely potent oxidizers, fluorine (F2) and related compounds (e.g., chlorine trifluoride, CIF3). These can be handled by fluoropolymers, but only with great care, as fluorine is absorbed into the resins, and the mixture becomes sensitive to a source of ignition such as impact.
- 80% NaOH (Sodium Hydroxide) or KOH (Potassium Hydroxide), metal hydrides such as Borances (e.g., B2H6), Aluminum Chloride, Ammonia (NH3), certain Amines (R-NH2) and imines (R=NH) and 70% Nitric Acid at temperatures near the suggested service limit.

WARNING

FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS AND/OR SYSTEMS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.

This document and other information from Parker Hannifin Corporation, its subsidiaries and authorized distributors provide product and/or system options for further investigation by users having technical expertise. It is important that you analyze all aspects of your application and review the information concerning the product or system in the current product catalog. Due to the variety of operating conditions and applications for these products or systems, the user, through its own analysis and testing, is solely responsible for making the final selection of the products and systems and assuring that all performance, safety and warning requirements of the application are met.

The products described herein, including without limitation, product features, specifications, designs, availability and pricing, are subject to change by Parker Hannifin Corporation and its subsidiaries at any time without notice.

Fluoropolymer Tubing

The table below lists a generally accepted summary of properties that we believe to be reliable. Please note that many of these resins are produced in several varieties and property characteristics may vary. Therefore, determination of resin is dependent on the application and this table is only meant to serve as a general guideline.

Properties*	ASTM or Unit	PTFE	FEP	PFA	High Purity PFA	PVDF	ETFE
MECHANICAL PROPERTIES							
Specific Gravity	D792 D3307	2.13-2.22 -	2.12-2.17 -	2.12-2.17 -	- 2.14-2.16	1.76-1.82 -	1.74 -
Elongation %	D638 D3307	200-450 -	250-330 -	280-400 -	- 370	100-800 -	430 -
Tensile Strength (psi)	D638(psi) D3307(psi)	2000-7000 -	2800-4000 -	4000-5000 -	- 4693	2000-5000 -	6962 -
Flexural Strength (psi)	D790	no break	no break	no break	no break	1500-5000	5500
Compressive Strength (psi)	D695	700-900	725-2200	725-810	na	2000-6000	2500
Tensile Elastic Modulus (Young's Modulus) (psi)	D638	57,000 -	50,000 -	72,500- 87,000	 na	35,000-220,000	116,030
Flexural Modulus	D790(psi) D790 103MPa (103kgf/cm2)	71,000-85,000 0.5-0.6 (5.0-6.0)	78,000-92,000 0.5-0.6 (5.5-6.4)	94,000-99,000 0.6-0.7 (6.6-7.0)	- 647-686 -	90,000-168,000 280,00-110,000	130,534 - -
Flex Life (MIT cycles)	D2176	>1,000,000	5,000-80,000	10,000-500,000	2000 x 10^3	na	na
Hardness Durometer Shore D	D2240	D50-65	D55	D55-D60	D60	D55-D75	D67
Coefficient of Friction	(on steel)	0.02	0.05	0.04-0.06	0.05	0.33-0.49	0.20
Abrasion Resistance 1000 cycles	Taber	8-90	14-20	0.00-96.75	na	16-33	0.005
Impact Strength IZO.D. 73°F (23°C) notched ft/lbs/in	D256	3	no break	no break	no break	4	no break
THERMAL PROPERTIES							
Melting Point	°C °F	327 621	260 500	305 582	305 582	125 257	260 500
Upper Service Temperature(20000h)	°C °F	260 500	204 400	260 500	260 500	130 265	180 356
Flammability	UL 94	V-0	V-0	V-0	V-0	V-0	V-0
Thermal Conductivity BTU-in/hr-ft^2, °F		1.7-2.08	1.4	1.3	na	1.00-1.25	1.65
Thermal Conductivity Cal-cm/sec-cm^2, °C		6 x 10-4	6 x 10-4	6 x 10-6	na	na	5.7 x 10-4
Linear Coefficient of Thermal Expansion Min/in°F 73.4-140°F	D696	55.6	46.1-58.3	66.7	na	7.00-10.8	9.4 (10^{-5}/°C)
Heat of Fusion	BTU/LB	29-37	4-35	13	na	0.28-0.36	20
Heat of Combustion	BTU/LB °F	2200	2200	2300	na	na	8100
Low Temperature Embrittlement	°C °F	-268 -450	-268 -450	-268 -450	-268 -450	-62 -80	-76 -105
ELECTRICAL PROPERTIES							
Dielectric Constant	D150/10^3Hz D150/10^6Hz	2.1 2.1	2.1 2.1	2.1 2.1	2.1 2.1	3.5 10.6	2.6
Dielectric Strength	D149/125 MIL D149/10 MIL	500 ≥1400	508 >610	500 ≥1400	500 - 600 na	0.8 1.5	na
Volume Resistivity	D257/ohm-cm	>10^{18}	>10^{18}	>10^{18}	na	2 x 10^{14}	10^{17}
Surface Resistivity	D257/ohm-cm	>10^{18}	>10^{17}	>10^{17}	na	5 x 10^{14}	>10^{15}
GENERAL PROPERTIES							
Chemical/Solvent Resistance	D543	Excellent	Excellent	Excellent	Excellent	Very Good	Excellent
Refractive Index		1.35	1.338	1.34	1.34	1.42	1.447
Limiting Oxygen Index, %	D2868	>95	>95	≥95	na	42/75[2]	31
Water Contact Angle	Angle to Level	110	114	115	na	92	na
Water Absorption 24h,%	D570	<0.01	<0.01	<0.03	<0.01	0.03-0.05	0.03
Weatherability		Excellent	Excellent	Excellent	Excellent	Excellent	Excellent

*General resin properties; Tubing properties may vary.

Tubing Pressure Ranges

Tubing pressures vary by material, tubing size and wall thickness. Please contact Customer Service for specific pressures.

Fluoropolymer Tubing

Fluoropolymer Tubing Nomenclature

Smoothbore Fractional and Metric Tubing

105- 0250 062 - N T - 100

Product Family

1	=	Fractional
2	=	Metric
7	=	Retractable Coil
9	=	Custom

Resin Family

01	=	PTFE
03	=	FEP
04	=	PFA
05	=	PFA High Purity
10	=	PVDF: Flex™
11	=	PVDF: Super-Flex™
12	=	ETFE NONSTANDARD

Outside Diameter

0250	=	.250 inch
0700	=	7 mm

Wall Thickness

062	=	.062 inch
100	=	1 mm

Tubing Color Options*

N	=	Natural
0	=	Black
1	=	Brown
2	=	Red
3	=	Orange
4	=	Yellow
5	=	Green
6	=	Blue
7	=	Violet
8	=	Gray
9	=	White

Tube Packaging

T	=	Bulk Default Configuration
C	=	Tube Cut Job (followed by cut length in inches)

Configuration

Blank	=	No color
C	=	Colored Solid Tube
S	=	Colored Stripe on Tube
L	=	Laser Marked

Length

25	=	25 ft coil
50	=	50 ft coil
100	=	100 ft coil
1000	=	1000 ft coil
Blank	=	No cut
xx.xxx	=	Length (inch)

Convoluted and Corrugated Tubing

CV 01- 1/8ID- 88- 1.5-2C

Convolution Profile

CV	=	Convoluted
CVW	=	Convoluted w/wire
CR	=	Corrugated
CVL	=	Low Profile
CVH	=	Heavy Wall
CVHW	=	Heavy Wall w/wire
CVLW	=	Low Profile W/wire

Resin Family

01	=	PTFE
03	=	FEP
04	=	PFA
05	=	PFA High Purity

Tubing I.D. or O.D. Size

x/x	=	below 1"
x.xx	=	1" and up

Overall Length in inches

Cuff Length in inches

Cuff and Options

Blank	=	No cuffs
XX.XXX-1C	=	1 Cuff
XX.XXX-2C	=	2 Cuffs

Special Configuration

Blank	=	Default
FC	=	Fully Conductive
CI	=	Conductive I.D.

For detailed ordering information, please consult price list or contact Parflex Division.

Fluoropolymer Tubing Nomenclature

Heat Shrink, Electrical Insulation Tubing and Beading

HS2** T F T 1/8 - N T***

Special Configurations

Blank if Smooth Bore
HS2 = 2:1 Ratio PTFE
HS4 = 4:1 Ratio PTFE
HS1.3 = 1.3/1:1 Ratio FEP
HS1.6 = 1.67:1 Ratio FEP
HS1.25 = 1.25:1 Ratio FEP

Resin Family

TF = PTFE
FP = FEP
PF = PFA
ET = ETFE

Tubing Configurations

H = Heavy Wall
S = Standard Wall
T = Thin Wall
L = Light Wall
I = Industrial Wall
B = Beading

Tubing Sizes**

XX for AWG size 0-30
X/X for Fractional sizes 1/8 to 1.00 inch

Tubing Color Options*

N = Natural
0 = Black
1 = Brown
2 = Red
3 = Orange
4 = Yellow
5 = Green
6 = Blue
7 = Violet
8 = Gray
9 = White

Tube Packaging

T = Bulk Default Configuration
C = Tube Cut Job (followed by cut length in inches -if cut, go to Other Options)

Configuration

Blank = No color
C = Colored Solid Tube
S = Colored Stripe on Tube

Other Options

Blank = Not required
xx.xxx = Add cut length in inches

*When ordering coiled tubing in colors, the color code is always followed by TC; when ordering cut lengths, the color code is followed by CC....i.e.,HS2TFT1/8-2TC ..i.e.,HS1.3FEP24-0CC48.000


**This first configuration is only used for heat shrinkable tubing or spiral wrap. For example, electrical insulation tubing part number would read TFT-1/8-NT.

***When changing to cut length, replace the T with C and specify the length in inches. If this part was cut to 4 feet, part number would read TFT-1/8-NC48.000.

****Sizes for heat shrink designate the size of the heat shrink tube as stated by the applicable specification. The actual O.D. of the tubing does not always match the size. Review actual tables to see the true expanded dimension of the tube.

PTFE Tubing

Series Fractional & Metric: 101, 201



Features

- Virgin Polytetrafluoroethylene resin
- Chemically inert
- Lowest coefficient of friction
- Superior dielectric strength
- Exceptional heat resistance
- Self extinguishing
- Non-wetting
- Excellent flexlife
- Laser markable

Applications/Markets



- Cable Liner
- Electrical Insulation
- Oxygen Sensor
- Paint Transfer
- Gas Sampling
- Laboratory

Certifications/Compliance

- AMS 3653E
- VW1, UL-83 (natural)
- FDA Compliant
- USP Class VI Compliant

Order Information

Example: 101-0188062-0TC-100

101-0188062-0TC-100 – **PTFE**
101-**0188**062-0TC-100 – **Tube O.D.** in inches **(3/16")**
101-0188**062**-0TC-100 – **Tube Wall Thickness** in inches **(.062")**
101-0188062-**0**TC-100 – **Black**
101-0188062-0**T**C-100 – **Bulk Tubing**
101-0188062-0T**C**-100 – **Solid Color Tube**
101-0188062-0TC-**100** – **Package Quantity** in feet **(100')**

Notes

- Working Temperature: 500°F (260°C)
- Working pressure calculated using a Design Factor of 4
- Custom packaging and sizes are quoted upon request
- Package quantities are not continuous

Colors

- ○ Natural, Translucent
- Colors available as custom run, see color code table

Color Code					
○	N	Natural	●	5	Green
●	0	Black	●	6	Blue
●	1	Brown	●	7	Violet
●	2	Red	●	8	Gray
●	3	Orange	○	9	White
●	4	Yellow			

Fittings

Fittings available for sizes 3/32" up to 1.1"

Parker Fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 692-6634 FAX

FSC Product Families:

- Compression
- Compress-Align®
- Metric Compression
- TrueSeal™

For detailed ordering information, please consult price list or contact Parflex Division.

101 PTFE Industrial Wall Fractional Size Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure		Burst Pressure		Min. Bend Radius		Vac. Rating	Weight	
#																				
	inch	inch	tol.	mm	tol.	inch	tol.	mm	tol.	inch	mm	psi 73°F	bar 23°C	psi 73°F	bar 23°C	inch	mm	at 73°F	lb. per ft.	kg. per m.
101-0094031	3/32	0.094	± 0.005	2.40	± 0.13	0.031	± 0.002	0.79	± 0.05	0.031	0.79	390	27	1560	108	0.500	13	28	0.006	0.009
101-0125031	1/8	0.125	± 0.005	3.18	± 0.13	0.063	± 0.003	1.57	± 0.05	0.031	0.79	290	20	1160	80	0.500	13	28	0.009	0.013
101-0156031	5/32	0.156	± 0.005	3.99	± 0.13	0.094	± 0.004	2.39	± 0.08	0.031	0.79	220	15	880	61	0.625	16	28	0.011	0.017
101-0188031	3/16	0.188	± 0.005	4.78	± 0.13	0.125	± 0.005	3.18	± 0.13	0.031	0.79	180	12	720	50	0.750	19	28	0.014	0.021
101-0250031	1/4	0.250	± 0.005	6.35	± 0.13	0.190	± 0.005	4.83	± 0.13	0.031	0.79	130	9	520	36	1.000	25	28	0.020	0.030
101-0312031	5/16	0.312	± 0.005	7.92	± 0.13	0.250	± 0.007	6.35	± 0.18	0.031	0.79	100	7	400	28	2.250	57	28	0.026	0.038
101-0375031	3/8	0.375	± 0.005	9.52	± 0.13	0.312	± 0.006	7.92	± 0.15	0.031	0.79	80	6	320	22	2.750	70	28	0.032	0.047
101-0438031	7/16	0.438	± 0.005	11.13	± 0.13	0.375	± 0.007	9.52	± 0.18	0.031	0.79	70	5	280	19	4.000	102	28	0.037	0.056
101-0500031	1/2	0.500	± 0.006	12.70	± 0.15	0.438	± 0.008	11.13	± 0.20	0.031	0.79	60	4	240	17	4.000	102	28	0.043	0.064
101-0563031	9/16	0.563	± 0.007	14.30	± 0.18	0.500	± 0.010	12.70	± 0.25	0.031	0.79	55	4	220	15	5.000	127	28	0.049	0.073
101-0625031	5/8	0.625	± 0.007	15.88	± 0.18	0.563	± 0.010	14.30	± 0.25	0.031	0.79	50	3	200	14	5.500	140	28	0.054	0.081
101-0688031	11/16	0.688	± 0.010	17.48	± 0.25	0.625	± 0.012	15.88	± 0.31	0.031	0.79	45	3	180	12	6.250	159	28	0.060	0.090
101-0750032	3/4	0.750	± 0.010	19.05	± 0.25	0.688	± 0.012	17.48	± 0.31	0.032	0.81	40	3	160	11	6.500	165	28	0.068	0.101
101-0830040	0.830	0.830	± 0.014	21.08	± 0.36	0.750	± 0.014	19.05	± 0.36	0.040	1.02	45	3	180	12	8.000	203	28	0.093	0.139
101-0965045	0.965	0.965	± 0.016	24.51	± 0.41	0.875	± 0.016	22.22	± 0.41	0.045	1.14	45	3	180	12	12.000	305	28	0.122	0.182
101-1100050	1.100	1.100	±0 .020	27.94	± 0.51	1.000	± 0.020	25.40	± 0.51	0.050	1.27	40	3	160	11	18.000	457	28	0.155	0.231

Continued on next page

PTFE Tubing

Series Fractional & Metric: 101, 201 (cont.)

101 PTFE Heavy Wall Fractional Size Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure		Burst Pressure		Min. Bend Radius		Vac. Rating	Weight	
#																			lbs	kgs
	inch	inch	tol.	mm	tol.	inch	tol.	mm	tol.	inch	mm	psi 73˚F	bar 23˚C	psi 73˚F	bar 23˚C	inch	mm	at 73˚F	lb. per ft.	kg. per m.
101-0188062	3/16	.188	± .005	4.78	± 0.13	0.063	± 0.003	1.57	± 0.05	0.062	1.57	390	27	1560	108	0.250	6	28	0.023	0.034
101-0250047	1/4	.250	± .005	6.35	± 0.13	0.157	± 0.005	3.99	± 0.13	0.047	1.19	210	14	840	58	0.625	16	28	0.028	0.042
101-0250062	1/4	.250	± .005	6.35	± 0.13	0.125	± 0.005	3.18	± 0.13	0.062	1.57	290	20	1160	80	0.500	13	28	0.034	0.051
101-0312062	5/16	.312	± .005	7.92	± 0.13	0.188	± 0.006	4.76	± 0.15	0.062	1.57	222	15	888	61	0.875	22	28	0.046	0.068
101-0375062	3/8	.375	± .005	9.52	± 0.13	0.250	± 0.005	6.35	± 0.13	0.062	1.57	180	12	720	50	1.000	25	28	0.057	0.085
101-0438062	7/16	.438	± .005	11.13	± 0.13	0.312	± 0.007	7.92	± 0.18	0.062	1.57	150	10	600	41	2.250	57	28	0.069	0.103
101-0500062	1/2	.500	± .005	12.70	± 0.13	0.375	± 0.005	9.52	± 0.13	0.062	1.57	130	9	520	36	2.250	57	28	0.080	0.120
101-0563062	9/16	.563	± .007	14.30	± 0.18	0.437	± 0.008	11.13	± 0.20	0.062	1.57	110	8	440	30	2.750	70	28	0.092	0.137
101-0625062	5/8	.625	± .007	15.88	± 0.18	0.500	± 0.010	12.70	± 0.25	0.062	1.57	100	7	400	28	3.000	76	28	0.103	0.154
101-0688062	11/16	.688	± .010	17.48	± 0.25	0.563	± 0.010	14.30	± 0.25	0.062	1.57	90	6	360	25	5.000	127	28	0.115	0.171
101-0750062	3/4	.750	± .010	19.05	± 0.25	0.625	± 0.010	15.88	± 0.25	0.062	1.57	80	6	320	22	6.000	152	28	0.126	0.188
101-0875062	7/8	.875	± .014	22.22	± 0.36	0.750	± 0.014	19.05	± 0.36	0.062	1.57	70	5	280	19	7.250	184	28	0.149	0.222
101-1000062	1	1.000	± .016	25.40	± 0.25	0.875	± 0.016	22.22	± 0.36	0.062	1.57	100	6.9	400	28	8.000	203	28	0.172	0.256


For detailed ordering information, please consult price list or contact Parflex Division.

201 Metric PTFE Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure		Burst Pressure		Min. Bend Radius		Vac. Rating	Weight	
#																				
	mm	mm	tol.	inch	tol.	mm	tol.	inch	tol.	mm	inch	bar 23°C	psi 73°F	bar 23°C	psi 73°F	mm	inch	at 73°F	kg. per m.	lb. per ft.
201-0300100	3	3	± 0.11	0.118	± 0.004	1	± 0.11	0.039	± 0.004	1	0.039	27	390	108	1560	13	0.500	28	0.014	0.009
201-0400100	4	4	± 0.11	0.157	± 0.004	2	± 0.11	0.074	± 0.004	1	0.039	20	290	80	1160	13	0.500	28	0.020	0.014
201-0500100	5	5	± 0.11	0.197	± 0.004	3	± 0.11	0.118	± 0.004	1	0.039	15	220	61	880	19	0.750	28	0.027	0.018
201-0600100	6	6	± 0.13	0.236	± 0.005	4	± 0.13	0.157	± 0.005	1	0.039	12	180	50	720	25	1.000	28	0.034	0.023
201-0700100	7	7	± 0.13	0.276	± 0.005	5	± 0.13	0.197	± 0.005	1	0.039	10	150	41	600	38	1.500	28	0.041	0.027
201-0800100	8	8	± 0.13	0.315	± 0.005	6	± 0.13	0.236	± 0.005	1	0.039	9	130	36	520	51	2.000	28	0.048	0.032
201-0900100	9	9	± 0.13	0.354	± 0.005	7	± 0.13	0.276	± 0.005	1	0.039	8	110	30	440	57	2.250	28	0.055	0.037
201-1000100	10	10	± 0.13	0.394	± 0.005	8	± 0.13	0.315	± 0.005	1	0.039	7	100	28	400	64	2.500	28	0.061	0.041
201-1200100	12	12	± 0.15	0.472	± 0.006	10	± 0.15	0.394	± 0.006	1	0.039	6	80	22	320	76	3.000	28	0.075	0.050
201-1400100	14	14	± 0.15	0.551	± 0.006	12	± 0.15	0.472	± 0.006	1	0.039	5	70	19	280	89	3.500	28	0.089	0.060
201-1600100	16	16	± 0.15	0.630	± 0.006	14	± 0.15	0.551	± 0.006	1	0.039	4	60	17	240	108	4.250	28	0.102	0.069

PTFE Tubing

Series Fractional: TFL, TFS, TFT



Features

- Virgin Polytetrafluoroethylene resin
- Chemically inert
- Lowest coefficient of friction
- Superior dielectric strength
- Exceptional heat resistance
- Self extinguishing
- Non-wetting
- Excellent flexlife
- Laser markable

Applications/Markets



- Electrical Insulation
- Protective Cover
- Cable Liner
- Spacer

Certifications/Compliance

- AMS 3653E
- VW1, UL-83 (natural)
- FDA Compliant
- USP Class VI Compliant
- **Light Wall** (TFL) – ASTM D3295 Class 1, AMS 3654C
- **Thin Wall** (TFT) – ASTM D3295 Class 2, AMS 3655B
- **Standard Wall** (TFS) – ASTM D3295 Class 3, MIL-I-22129C

Order Information

Example: TFS1/2-NT

TFS1/2-NT – **PTFE**
TF**S**1/2-NT – **Standard Wall**
TFS**1/2**-NT – **Tube O.D.** in inches **(1/2")**
TFS1/2-**N**T – **Natural**
TFS1/2-N**T** – **Bulk Tubing**

Notes

- Working Temperature: 500°F (260°C)
- Package quantities are not continuous - Fractional tubing is supplied in random length coils, with a minimum coil length of 15 feet.
- Custom packaging, sizes and lengths are quoted upon request.

Colors

- ○ Natural, Translucent
- Colors available as custom run, see color code table

Fittings

Fittings available for sizes 3/32" up to 1.1"

Parker Fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 692-6634 FAX

FSC Product Families:

- TrueSeal™

Color Code					
○	N	Natural	●	5	Green
●	0	Black	●	6	Blue
●	1	Brown	●	7	Violet
●	2	Red	●	8	Gray
●	3	Orange	○	9	White
●	4	Yellow			


For detailed ordering information, please consult price list or contact Parflex Division.

TFS, TFT & TFL PTFE Fractional Tubing

Size	Nominal I.D.		Standard Wall			Thin Wall			Light Wall			Standard Packaging
			Part Number	Nominal Wall		Part Number	Nominal Wall		Part Number	Nominal Wall		
			#			#			#			
inch	inch	mm	Natural	inch	mm	Natural	inch	mm	Natural	inch	mm	
1/8	0.125	3.18	TFS1/8	0.020	0.51	TFT1/8	0.015	0.38	TFL1/8	0.008	0.20	Random Length Coil
3/16	0.188	4.78	TFS3/16	0.020	0.51	TFT3/16	0.015	0.38	TFL3/16	0.010	0.25	Random Length Coil
1/4	0.250	6.35	TFS1/4	0.020	0.51	TFT1/4	0.015	0.38	TFL1/4	0.010	0.25	Random Length Coil
5/16	0.318	7.92	TFS5/16	0.020	0.51	TFT5/16	0.015	0.38	TFL5/16	0.012	0.30	Random Length Coil
3/8	0.381	9.52	TFS3/8	0.025	0.64	TFT3/8	0.015	0.38	TFL3/8	0.015	0.38	Random Length Coil
7/16	0.444	11.13	TFS7/16	0.025	0.64	TFT7/16	0.018	0.46	TFL7/16	0.018	0.46	Random Length Coil
1/2	0.507	12.70	TFS1/2	0.025	0.64	TFT1/2	0.018	0.46	TFL1/2	0.018	0.46	Random Length Coil
5/8	0.632	15.88	TFS5/8	0.025	0.64	TFT5/8	0.020	0.51	-	-	-	Random Length Coil
3/4	0.760	19.05	TFS3/4	0.030	0.76	TFT3/4	0.025	0.64	-	-	-	Random Length Coil
7/8	0.885	22.22	TFS7/8	0.035	0.89	-	-	-	-	-	-	Random Length Coil
1	1.010	25.40	TFS1.00	0.035	0.89	-	-	-	-	-	-	Random Length Coil

PTFE Tubing

Series AWG: TFH, TFS, TFT, TFL



Features

- Virgin Polytetrafluoroethylene resin
- Chemically inert
- Lowest coefficient of friction
- Superior dielectric strength
- Exceptional heat resistance
- Self extinguishing
- Non-wetting
- Excellent flexlife
- Laser markable

Applications/Markets



- Electrical Insulation
- Protective Cover
- Circuit Board
- Wire Insulation
- Strain Relief
- Introducer
- Stent Delivery

Certifications/Compliance

- AMS 3653E
- VW1, UL-83 (natural)
- FDA Compliant
- USP Class VI Compliant
- **Light Wall** (TFL) – ASTM D3295 Class 1, AMS 3654C UL-224 150V 200°C
- **Thin Wall** (TFT) – ASTM D3295 Class 2, AMS 3655B, UL-224 300V 200°C, CSA 9032-01 300V
- **Standard Wall** (TFS) – ASTM D3295 Class 3, MIL-I-22129C, UL-224 600V 200°C, CSA 9032-01 600V
- **Heavy Wall** (TFH) – ASTM D3295, Class 4

Order Information

Example: TFH13-2TC

TFH13-2TC – **PTFE**
TF**H**13-2TC – **Heavy Wall**
TFH**13**-2TC – **AWG Size**
TFH13-**2**TC – **Red**
TFH13-2**T**C – **Bulk Tubing**
TFH13-2T**C** – **Solid Color Tube**

Colors

- ○ Natural, Translucent
- Colors available as custom run, see color code table

Color Code					
○	N	Natural	●	5	Green
●	0	Black	●	6	Blue
●	1	Brown	●	7	Violet
●	2	Red	●	8	Gray
●	3	Orange	○	9	White
●	4	Yellow			

Notes

- Working Temperature: 500°F (260°C)
- AWG Spaghetti tubing is supplied in random lengths with a minimum length of 25 feet
- Continuous lengths and colors quoted upon request
- AWG spaghetti tubing is also available in FEP and PFA
- Consult factory for pricing and minimum lengths

For detailed ordering information, please consult price list or contact Parflex Division.

TFH PTFE AWG Heavy Wall

Part Number	Order Size	Nominal I.D.		Minimum I.D.		Maximum I.D.		Nominal Wall		Standard Packaging
#										
	AWG	inch	mm	inch	mm	inch	mm	inch	mm	
TFH24	24	0.022	0.56	0.020	0.51	0.026	0.66	0.016 ± 0.003	0.41 ± 0.08	1,000 ft. Spool
TFH23	23	0.026	0.66	0.023	0.58	0.029	0.74	0.016 ± 0.003	0.41 ± 0.08	1,000 ft. Spool
TFH22	22	0.028	0.71	0.025	0.64	0.032	0.81	0.016 ± 0.003	0.41 ± 0.08	1,000 ft. Spool
TFH21	21	0.032	0.81	0.029	0.74	0.035	0.89	0.016 ± 0.003	.0.41 ± 0.08	1,000 ft. Spool
TFH20	20	0.034	0.86	0.032	0.81	0.040	1.02	0.018 ± 0.003	0.46 ± 0.08	1,000 ft. Spool
TFH19	19	0.038	0.97	0.036	0.91	0.044	1.12	0.020 ± 0.004	0.51 ± 0.10	1,000 ft. Spool
TFH18	18	0.042	1.07	0.040	1.02	0.049	1.25	0.020 ± 0.004	0.51 ± 0.10	1,000 ft. Spool
TFH17	17	0.048	1.22	0.045	1.14	0.054	1.37	0.020 ± 0.004	0.51 ± 0.10	1,000 ft. Spool
TFH16	16	0.053	1.35	0.051	1.30	0.061	1.55	0.020 ± 0.004	0.51 ± 0.10	1,000 ft. Spool
TFH15	15	0.059	1.50	0.057	1.45	0.067	1.70	0.020 ± 0.004	0.51 ± 0.10	1,000 ft. Spool
TFH14	14	0.066	1.68	0.064	1.63	0.074	1.88	0.020 ± 0.004	0.51 ± 0.10	500 ft. Spool
TFH13	13	0.076	1.93	0.072	1.83	0.082	2.08	0.020 ± 0.004	0.51 ± 0.10	500 ft. Spool
TFH12	12	0.085	2.16	0.081	2.06	0.091	2.31	0.020 ± 0.004	0.51 ± 0.10	500 ft. Spool
TFH11	11	0.095	2.41	0.091	2.31	0.101	2.57	0.020 ± 0.004	0.51 ± 0.10	500 ft. Spool
TFH10	10	0.106	2.69	0.102	2.59	0.112	2.84	0.025 ± 0.005	0.64 ± 0.13	500 ft. Spool
TFH09	9	0.118	3.00	0.114	2.90	0.124	3.15	0.025 ± 0.005	0.64 ± 0.13	500 ft. Spool
TFH08	8	0.133	3.38	0.129	3.28	0.141	3.58	0.030 ± 0.005	0.76 ± 0.13	Random Length Coil
TFH07	7	0.148	3.76	0.144	3.66	0.158	4.01	0.030 ± 0.005	0.76 ± 0.13	Random Length Coil
TFH06	6	0.166	4.22	0.162	4.11	0.178	4.52	0.030 ± 0.005	0.76 ± 0.13	Random Length Coil
TFH05	5	0.185	4.70	0.182	4.62	0.196	4.98	0.032 ± 0.005	0.81 ± 0.13	Random Length Coil

Certifications

- ASTM D3295 Class 4
- AMS 3653E
- FDA Compliant
- USP Class VI Compliant

PTFE Tubing

Series AWG: TFH, TFL, TFS, TFT (cont.)

TFS PTFE AWG Standard Wall

Part Number	Order Size	Nominal I.D.		Minimum I.D.		Maximum I.D.		Nominal Wall		Standard Packaging
#		◎		◎		◎		◎←		
	AWG	inch	mm	inch	mm	inch	mm	inch	mm	
TFS30	30	0.012	0.31	0.010	0.25	0.015	0.38	.009 ± .002	0.23 ± 0.05	1,000 ft. Spool
TFS28	28	0.015	0.38	0.013	0.33	0.018	0.46	.009 ± .002	0.23 ± 0.05	1,000 ft. Spool
TFS26	26	0.018	0.46	0.016	0.41	0.022	0.56	.009 ± .002	0.23 ± 0.05	1,000 ft. Spool
TFS24	24	0.022	0.56	0.020	0.51	0.026	0.66	.012 ± .003	0.31 ± 0.08	1,000 ft. Spool
TFS23	23	0.026	0.66	0.023	0.58	0.029	0.74	.012 ± .003	0.31 ± 0.08	1,000 ft. Spool
TFS22	22	0.028	0.71	0.025	0.64	0.032	0.81	.012 ± .003	0.31 ± 0.08	1,000 ft. Spool
TFS21	21	0.032	0.81	0.029	0.74	0.035	0.89	.012 ± .003	0.31 ± 0.08	1,000 ft. Spool
TFS20	20	0.034	0.86	0.032	0.81	0.040	1.02	.016 ± .003	0.41 ± .0.08	1,000 ft. Spool
TFS19	19	0.038	0.97	0.036	0.91	0.044	1.12	.016 ± .003	0.41 ± .0.08	1,000 ft. Spool
TFS18	18	0.042	1.07	0.040	1.02	0.049	1.25	.016 ± .003	0.41 ± .0.08	1,000 ft. Spool
TFS17	17	0.048	1.22	0.045	1.14	0.054	1.37	.016 ± .003	0.41 ± .0.08	1,000 ft. Spool
TFS16	16	0.053	1.35	0.051	1.30	0.061	1.55	.016 ± .003	0.41 ± .0.08	1,000 ft. Spool
TFS15	15	0.059	1.50	0.057	1.45	0.067	1.70	.016 ± .003	0.41 ± .0.08	500 ft. Spool
TFS14	14	0.066	1.68	0.064	1.63	0.074	1.88	.016 ± .003	0.41 ± .0.08	500 ft. Spool
TFS13	13	0.076	1.93	0.072	1.83	0.082	2.08	.016 ± .003	0.41 ± .0.08	500 ft. Spool
TFS12	12	0.085	2.16	0.081	2.06	0.091	2.31	.016 ± .003	0.41 ± .0.08	500 ft. Spool
TFS11	11	0.095	2.41	0.091	2.31	0.101	2.57	.016 ± .003	0.41 ± .0.08	500 ft. Spool
TFS10	10	0.106	2.69	0.102	2.59	0.112	2.84	.016 ± .003	0.41 ± .0.08	500 ft. Spool
TFS09	9	0.118	3.00	0.114	2.90	0.124	3.15	.020 ± .004	0.51 ± .0.10	Random Length Coil
TFS08	8	0.133	3.38	0.129	3.28	0.141	3.58	.020 ± .004	0.51 ± .0.10	Random Length Coil
TFS07	7	0.148	3.76	0.144	3.66	0.158	4.01	.020 ± .004	0.51 ± .0.10	Random Length Coil
TFS06	6	0.166	4.22	0.162	4.11	0.178	4.52	.020 ± .004	0.51 ± .0.10	Random Length Coil
TFS05	5	0.185	4.70	0.182	4.62	0.196	4.98	.020 ± .004	0.51 ± .0.10	Random Length Coil
TFS04	4	0.208	5.28	0.204	5.18	0.224	5.69	.020 ± .004	0.51 ± .0.10	Random Length Coil
TFS03	3	0.234	5.94	0.229	5.82	0.249	6.32	.020 ± .004	0.51 ± .0.10	Random Length Coil
TFS02	2	0.263	6.68	0.258	6.55	0.278	7.06	.020 ± .004	0.51 ± .0.10	Random Length Coil
TFS01	1	0.294	7.47	0.289	7.34	0.311	7.90	.020 ± .004	0.51 ± .0.10	Random Length Coil
TFS00	0	0.330	8.38	0.325	8.25	0.347	8.81	.020 ± .004	0.51 ± .0.10	Random Length Coil

Certifications

- ASTM D3295 Class 3
- MIL-I-22129C
- AMS 3653E
- UL-224 600V 200°C
- CSA 9032-01 600V
- FDA Compliant

TFT PTFE AWG Thin Wall

Part Number	Order Size	Nominal I.D.		Minimum I.D.		Maximum I.D.		Nominal Wall		Standard Packaging
#										
	AWG	inch	mm	inch	mm	inch	mm	inch	mm	
TFT32	32	.010	0.25	.008	0.20	.012	0.31	0.007 ± 0.002	0.18 ± 0.05	1,000 ft. Spool Only
TFT30	30	.012	0.31	.010	0.25	.015	0.38	0.009 ± 0.002	0.23 ± 0.05	1,000 ft. Spool
TFT28	28	.015	0.38	.013	0.33	.018	0.46	0.009 ± 0.002	0.23 ± 0.05	1,000 ft. Spool
TFT26	26	.018	0.46	.016	0.41	.022	0.56	0.009 ± 0.002	0.23 ± 0.05	1,000 ft. Spool
TFT24	24	.022	0.56	.020	0.51	.026	0.66	0.010 ± 0.003	0.25 ± 0.08	1,000 ft. Spool
TFT23	23	.026	0.66	.023	0.58	.029	0.74	0.010 ± 0.003	0.25 ± 0.08	1,000 ft. Spool
TFT22	22	.028	0.71	.025	0.64	.032	0.81	0.010 ± 0.003	0.25 ± 0.08	1,000 ft. Spool
TFT21	21	.032	0.81	.029	0.74	.035	0.89	0.010 ± 0.003	0.25 ± 0.08	1,000 ft. Spool
TFT20	20	.034	0.86	.032	0.81	.040	1.02	0.012 ± 0.003	0.31 ± 0.08	1,000 ft. Spool
TFT19	19	.038	0.97	.036	0.91	.044	1.12	0.012 ± 0.003	0.31 ± 0.08	1,000 ft. Spool
TFT18	18	.042	1.07	.040	1.02	.049	1.25	0.012 ± 0.003	0.31 ± 0.08	1,000 ft. Spool
TFT17	17	.048	1.22	.045	1.14	.054	1.37	0.012 ± 0.003	0.31 ± 0.08	1,000 ft. Spool
TFT16	16	.053	1.35	.051	1.30	.061	1.55	0.012 ± 0.003	0.31 ± 0.08	1,000 ft. Spool
TFT15	15	.059	1.50	.057	1.45	.067	1.70	0.012 ± 0.003	0.31 ± 0.08	1,000 ft. Spool
TFT14	14	.066	1.68	.064	1.63	.074	1.88	0.012 ± 0.003	0.31 ± 0.08	500 ft. Spool
TFT13	13	.076	1.93	.072	1.83	.082	2.08	0.012 ± 0.003	0.31 ± 0.08	500 ft. Spool
TFT12	12	.085	2.16	.081	2.06	.091	2.31	0.012 ± 0.003	0.31 ± 0.08	500 ft. Spool
TFT11	11	.095	2.41	.091	2.31	.101	2.57	0.012 ± 0.003	0.31 ± 0.08	500 ft. Spool
TFT10	10	.106	2.69	.102	2.59	.112	2.84	0.012 ± 0.003	0.31 ± 0.08	500 ft. Spool
TFT09	9	.118	3.00	.114	2.90	.124	3.15	0.015 ± 0.003	0.38 ± 0.08	500 ft. Spool
TFT08	8	.133	3.38	.129	3.28	.141	3.58	0.015 ± 0.003	0.38 ± 0.08	Random Length Coil
TFT07	7	.148	3.76	.144	3.66	.158	4.01	0.015 ± 0.003	0.38 ± 0.08	Random Length Coil
TFT06	6	.166	4.22	.162	4.11	.178	4.52	0.015 ± 0.003	0.38 ± 0.08	Random Length Coil
TFT05	5	.185	4.70	.182	4.62	.196	4.98	0.015 ± 0.003	0.38 ± 0.08	Random Length Coil
TFT04	4	.208	5.28	.204	5.18	.224	5.69	0.015 ± 0.003	0.38 ± 0.08	Random Length Coil
TFT03	3	.234	5.94	.229	5.82	.249	6.32	0.015 ± 0.003	0.38 ± 0.08	Random Length Coil
TFT02	2	.263	6.68	.258	6.55	.278	7.06	0.015 ± 0.003	0.38 ± 0.08	Random Length Coil
TFT01	1	.294	7.47	.289	7.34	.311	7.90	0.015 ± 0.003	0.38 ± 0.08	Random Length Coil
TFT00	0	.330	8.38	.325	8.25	.347	8.81	0.015 ± 0.003	0.38 ± 0.08	Random Length Coil

Certifications

- ASTM D3295 Class 2
- AMS 3653E
- AMS 3655B
- UL-224 300V 200°C
- CSA 9032-01 300V
- FDA Compliant
- USP Class VI Compliant

For detailed ordering information, please consult price list or contact Parflex Division.

PTFE Tubing

Series AWG: TFH, TFL, TFS, TFT (cont.)

TFL PTFE AWG Light Wall


Part Number	Order Size	Nominal I.D.		Minimum I.D.		Maximum I.D.		Nominal Wall		Standard Packaging
#										
	AWG	inch	mm	inch	mm	inch	mm	inch	mm	
TFL32	32	0.010	0.25	0.008	0.20	0.012	0.31	0.005 ± 0.002	0.13 ± 0.05	1,000 ft. Spool Only
TFL30	30	0.012	0.31	0.010	0.25	0.015	0.38	0.006 ± 0.002	0.13 ± 0.05	1,000 ft. Spool
TFL28	28	0.015	0.38	0.013	0.33	0.018	0.46	0.006 ± 0.002	0.13 ± 0.05	1,000 ft. Spool
TFL26	26	0.018	0.46	0.016	0.41	0.022	0.56	0.006 ± 0.002	0.13 ± 0.05	1,000 ft. Spool
TFL24	24	0.022	0.56	0.020	0.51	0.026	0.66	0.006 ± 0.002	0.13 ± 0.05	1,000 ft. Spool
TFL23	23	0.026	0.66	0.023	0.58	0.029	0.74	0.006 ± 0.002	0.13 ± 0.05	1,000 ft. Spool
TFL22	22	0.028	0.71	0.025	0.64	0.032	0.81	0.006 ± 0.002	0.13 ± 0.05	1,000 ft. Spool
TFL21	21	0.032	0.81	0.029	0.74	0.035	0.89	0.006 ± 0.002	0.13 ± 0.05	1,000 ft. Spool
TFL20	20	0.034	0.86	0.032	0.81	0.040	1.02	0.006 ± 0.002	0.13 ± 0.05	1,000 ft. Spool
TFL19	19	0.038	0.97	0.036	0.91	0.044	1.12	0.006 ± 0.002	0.13 ± 0.05	1,000 ft. Spool
TFL18	18	0.042	1.07	0.040	1.02	0.049	1.25	0.006 ± 0.002	0.13 ± 0.05	1,000 ft. Spool
TFL17	17	0.048	1.22	0.045	1.14	0.054	1.37	0.006 ± 0.002	0.13 ± 0.05	1,000 ft. Spool
TFL16	16	0.053	1.35	0.051	1.30	0.061	1.55	0.006 ± 0.002	0.13 ± 0.05	1,000 ft. Spool
TFL15	15	0.059	1.50	0.057	1.45	0.067	1.70	0.006 ± 0.002	0.13 ± 0.05	1,000 ft. Spool
TFL14	14	0.066	1.68	0.064	1.63	0.074	1.88	0.008 ± 0.002	0.20 ± 0.05	500 ft. Spool
TFL13	13	0.076	1.93	0.072	1.83	0.082	2.08	0.008 ± 0.002	0.20 ± 0.05	500 ft. Spool
TFL12	12	0.085	2.16	0.081	2.06	0.091	2.31	0.008 ± 0.002	0.20 ± 0.05	500 ft. Spool
TFL11	11	0.095	2.41	0.091	2.31	0.101	2.57	0.008 ± 0.002	0.20 ± 0.05	500 ft. Spool
TFL10	10	0.106	2.69	0.102	2.59	0.112	2.84	0.008 ± 0.002	0.20 ± 0.05	500 ft. Spool
TFL09	9	0.118	3.00	0.114	2.90	0.124	3.15	0.008 ± 0.002	0.20 ± 0.05	500 ft. Spool
TFL08	8	0.133	3.38	0.129	3.28	0.141	3.58	0.008 ± 0.002	0.20 ± 0.05	Random Length Coil
TFL07	7	0.148	3.76	0.144	3.66	0.158	4.01	0.008 ± 0.002	0.20 ± 0.05	Random Length Coil
TFL06	6	0.166	4.22	0.162	4.11	0.178	4.52	0.010 ± 0.003	0.25 ± 0.08	Random Length Coil
TFL05	5	0.185	4.70	0.182	4.62	0.196	4.98	0.010 ± 0.003	0.25 ± 0.08	Random Length Coil
TFL04	4	0.208	5.28	0.204	5.18	0.224	5.69	0.010 ± 0.003	0.25 ± 0.08	Random Length Coil
TFL03	3	0.234	5.94	0.229	5.82	0.249	6.32	0.010 ± 0.003	0.25 ± 0.08	Random Length Coil
TFL02	2	0.263	6.68	0.258	6.55	0.278	7.06	0.010 ± 0.003	0.25 ± 0.08	Random Length Coil
TFL01	1	0.294	7.47	0.289	7.34	0.311	7.90	0.012 ± 0.003	0.31 ± 0.08	Random Length Coil
TFL00	0	0.330	8.38	0.325	8.25	0.347	8.81	0.012 ± 0.003	0.31 ± 0.08	Random Length Coil

Certifications

- ASTM D3295 Class 1
- AMS 3653E
- AMS 3654C
- UL-224 150V 200°C
- FDA Compliant
- USP Class VI Compliant

PTFE Beading

Series Fractional: TFB



Features

- Virgin Polytetrafluoroethylene resin
- Chemically inert
- Lowest coefficient of friction
- Superior dielectric strength
- Exceptional heat resistance
- Self extinguishing
- Non-wetting
- Excellent flexlife
- Laser markable

Applications/Markets





- Pull Cord
- O-ring Seals
- Spacers
- Woven Filter

Certifications

- ASTM D1710, Type 1, Grade 1, Class B
- ASTM D3295
- VW1, UL-83 (natural)
- FDA Compliant
- USP Class VI Compliant

TFB PTFE Beading

Part Number	Diameter		Tolerance		Standard Packaging
#	◎				
	inch	mm	inch	mm	
TFB015	0.015	0.38	± 0.002	± 0.05	1,000 ft. Spool
TFB020	0.020	0.51	± 0.002	± 0.05	1,000 ft. Spool
TFB025	0.025	0.64	± 0.002	± 0.05	1,000 ft. Spool
TFB028	0.028	0.71	± 0.002	± 0.05	1,000 ft. Spool
TFB031	0.031	0.79	± 0.002	± 0.05	1,000 ft. Spool
TFB035	0.035	0.89	± 0.002	± 0.05	1,000 ft. Spool
TFB039	0.039	0.99	± 0.002	± 0.05	1,000 ft. Spool
TFB043	0.043	1.09	± 0.002	± 0.05	1,000 ft. Spool
TFB047	0.047	1.19	± 0.002	± 0.05	1,000 ft. Spool
TFB050	0.050	1.27	± 0.002	± 0.05	1,000 ft. Spool
TFB055	0.055	1.40	± 0.003	± 0.08	1,000 ft. Spool
TFB060	0.060	1.52	± 0.003	± 0.08	1,000 ft. Spool
TFB062	0.062	1.57	± 0.003	± 0.08	1,000 ft. Spool
TFB070	0.070	1.78	± 0.003	± 0.08	1,000 ft. Spool
TFB072	0.072	1.83	± 0.003	± 0.08	1,000 ft. Spool
TFB078	0.078	1.98	± 0.004	± 0.10	500 ft. Spool
TFB080	0.080	2.03	± 0.004	± 0.10	500 ft. Spool
TFB084	0.084	2.13	± 0.004	± 0.10	500 ft. Spool
TFB090	0.090	2.29	± 0.004	± 0.10	500 ft. Spool
TFB094	0.094	2.39	± 0.004	± 0.10	500 ft. Spool
TFB100	0.100	2.54	± 0.004	± 0.10	500 ft. Spool
TFB109	0.109	2.77	± 0.004	± 0.10	500 ft. Spool
TFB115	0.115	2.92	± 0.004	± 0.10	500 ft. Spool
TFB125	0.125	3.18	± 0.004	± 0.10	Random Length
TFB150	0.150	3.81	± 0.004	± 0.10	Random Length
TFB188	0.188	4.78	± 0.004	± 0.10	Random Length

Notes

- Working Temperature: -100°F to 500°F (-75°C to 260°C)
- Package quantities are not continuous

Colors

- ○ Natural, Translucent
- Colors available as custom run, see color code table

Color Code					
○	N	Natural	●	5	Green
●	0	Black	●	6	Blue
●	1	Brown	●	7	Violet
●	2	Red	●	8	Gray
●	3	Orange	○	9	White
●	4	Yellow			

Order Information

Example: TFB028-NT

TFB028-NT – **PTFE Beading**

TFB**028**-NT – **Beading O.D.** in inches **(.028")**


TFB028-**NT** – **Natural**

TFB028-N**T** – **Bulk Tubing**

For detailed ordering information, please consult price list or contact Parflex Division.

PTFE Spiral Cut Cable Wrap

Series: TSWTF



Features

- Provides harnessing for wires and cable while allowing leads at various points
- Exceptional heat resistance
- Self extinguishing
- Flexible
- Superior dielectric strength

Certifications

- A-A-59602
- AMS 3653E
- ASTM D3295
- VW1, UL-83 (natural)

Applications/Markets



- Cable harnessing
- Wiring closets
- Aerospace
- Automotive

Notes

- Available in left- or right-hand cut. Please specify with proper suffix at end of part number (i.e. TSWTF-18-NT-R)
- Working Temperature: 500°F (260°C)
- 100 ft. is the minimum item quantity sold
- Stock packaging for sizes 1/8" to 1/2" is 100- and 500-ft. non-continuous spools and, for sizes greater than 1/2", 100-ft. non-continuous spools
- Custom packaging, sizes and colors are available upon request
- Spiral cut cable wrap is also quoted in FEP upon request
- Package quantities are not continuous
- Colors available as custom run, see color code table

Order Information

Example: TSWTF-3/8-5T

TSWTF-3/8-5T – **Spiral Wrap**

TSW**TF**-3/8-5T – **Material (PTFE)**

TSWTF-**3/8**-5T – **O.D.** in inches **(.375")**

TSWTF-3/8-**5**T – **Green**

TSWTF-3/8-5**T** – **Bulk Tubing**

Colors


- ○ Natural, Translucent
- Colors available as custom run, see color code table

Color Code					
○	N	Natural	●	5	Green
●	0	Black	●	6	Blue
●	1	Brown	●	7	Violet
●	2	Red	●	8	Gray
●	3	Orange	○	9	White
●	4	Yellow			


For detailed ordering information, please consult price list or contact Parflex Division.

PTFE Spiral Wrap


Part Number	O.D. "A"		tolerance O.D.		Wall "B"		tolerance Wall		Pitch "D"		tolerance Pitch		Max Bundle O.D. "C"	
#														
	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
TSWTF-1/8-NT	0.125	3.18	± 0.005	0.127	0.020	0.508	± 0.008	0.203	0.212	5.38	± 0.015	0.381	1/2	12.70
TSWTF-3/16-NT	0.188	4.78	± 0.005	0.127	0.030	0.762	± 0.008	0.203	0.312	7.92	± 0.015	0.381	1	25.40
TSWTF-1/4-NT	0.250	6.35	± 0.005	0.127	0.030	0.762	± 0.008	0.203	0.375	9.52	± 0.015	0.381	2	50.80
TSWTF-3/8-NT	0.375	9.52	± 0.005	0.127	0.030	0.762	± 0.008	0.203	0.437	11.10	± 0.015	0.381	2-1/2	63.50
TSWTF-1/2-NT	0.500	12.70	± 0.005	0.127	0.030	0.762	± 0.008	0.203	0.562	14.27	± 0.015	0.381	3	76.20
TSWTF-3/4-NT	0.750	19.05	± 0.005	0.127	0.040	1.02	± 0.008	0.203	0.875	22.22	± 0.015	0.381	4	101.60
TSWTF-1.00-NT	1	25.40	± 0.005	0.127	0.040	1.02	± 0.008	0.203	1	25.40	± 0.015	0.381	6	152.40



TOP SECTION CUT



DEPICTS RIGHT HAND CUT



PTFE Heat Shrinkable Tubing

Series 2:1 Fractional: HS2TFS, HS2TFT, HS2TFL, HS2TFI



Features

- Virgin Polytetrafluoroethylene resin
- 2:1 Shrink Ratio
- Chemically inert
- Lowest coefficient of friction
- Superior dielectric strength
- Exceptional heat resistance
- Self extinguishing
- Non-wetting

Applications/Markets



- Electrical Insulation
- Protective Cover
- Electronic Harness
- Laboratory

Certifications

- ASTM D2902 Type I
- AMS 3653E
- VW1, UL-83 (natural)
- FDA Compliant
- USP Class VI Compliant
- **Light Wall** (HS2TFL) – AMS-DTL-23053/12A Class 4
- **Thin Wall** (HS2TFT) – AMS-DTL-23053/12A Class 3, AMS 3585
- **Standard Wall** (HS2TFS) – AMS-DTL-23053/12A Class 2, AMS 3586
- **Heavy Wall** (HS2TFH) – AMS-DTL-23053/12A Class 1 (Custom Order only)

Order Information

Example: HS2TFI7/8-NT

HS2TFI7/8-NT – **Heat Shrink**
HS**2**TFI7/8-NT – **Shrink Ratio (2:1)**
HS2**TF**I7/8-NT – **PTFE**
HS2TFI7/8-NT – **Wall Type (Industrial Wall)**
HS2TFI**7/8**-NT – **Heat Shrink Size** in inches **(7/8")**
HS2TFI7/8-**N**T – **Natural**
HS2TFI7/8-NT – **Bulk Tubing**

Colors

- ○ Natural, Opaque to translucent
- Colors available as custom run, see color code table

When ordering coiled tubing in colors, the color code is always followed by TC; when ordering cut lengths, the color code is followed by CC

i.e.,HS2TFI7/8-2TC i.e.,HS2TFI7/8-0CC48.000

Color Code					
○	N	Natural	●	5	Green
●	0	Black	●	6	Blue
●	1	Brown	●	7	Violet
●	2	Red	●	8	Gray
●	3	Orange	○	9	White
●	4	Yellow			

Notes

- Working Temperature: -100°F (-75°C) to +500°F (260°C)
- Shrink Temperature: 662°F (350°C) for 10 minutes per AMS-DTL-23053/12A
- *Dielectric Strength: ≥ 1,400 V/M, per ASTM D 149 short term test of 10 MIL thickness (Volts/MIL)
- PTFE Fractional Heat Shrink tubing is available in stock packaging of 4-ft. straight lengths
- Minimum quantities may apply
- Custom packaging, sizes, lengths and colors are quoted upon request


For detailed ordering information, please consult price list or contact Parflex Division.

HS2TFS & HS2TFT PTFE Fractional Heat Shrink Tubing (2:1) SW & TW

Order Size	Minimum Expanded I.D.		Maximum Recovered I.D.		Standard Wall				Thin Wall			
					Mil Spec*	Part Number	Nominal Recovered Wall		Mil Spec*	Part Number	Nominal Recovered Wall	
inch	inch	mm	inch	mm			inch	mm			inch	mm
1/8	0.215	05.5	0.130	3.3	23053/12A-215	HS2TFS1/8	0.020 ± 0.004	0.51 ± 0.10	23053/12A-319	HS2TFT1/8	0.015 ± 0.003	0.38 ± 0.08
1/4	0.410	10.4	0.260	6.6	23053/12A-222	HS2TFS1/4	0.020 ± 0.004	0.51 ± 0.10	23053/12A-326	HS2TFT1/4	0.015 ± 0.004	0.38 ± 0.10
5/16	0.470	11.9	0.329	8.4	23053/12A-225	HS2TFS5/16	0.020 ± 0.004	0.51 ± 0.10	23053/12A-329	HS2TFT5/16	0.015 ± 0.004	0.38 ± 0.10
3/8	0.560	14.2	0.399	10.1	23053/12A-228	HS2TFS3/8	0.025 ± 0.006	0.64 ± 0.15	-	HS2TF 3/8	0.015 ± 0.004	0.38 ± 0.10
7/16	0.655	16.6	0.462	11.7	23053/12A-229	HS2TFS7/16	0.025 ± 0.006	0.64 ± 0.15	-	HS2TFT7/16	0.018 ± 0.004	0.46 ± 0.10
1/2	0.750	19.1	0.524	13.3	23053/12A-230	HS2TFS1/2	0.025 ± 0.006	0.64 ± 0.15	-	HS2TFT1/2	0.018 ± 0.004	0.46 ± 0.10
5/8	0.930	23.6	0.655	16.6	23053/12A-231	HS2TFS5/8	0.030 ± 0.006	0.76 ± 0.15	-	HS2TF 5/8	0.020 ± 0.004	0.51 ± 0.10
3/4	1.125	28.6	0.786	20.0	23053/12A-232	HS2TFS3/4	0.035 ± 0.008	0.89 ± 0.20	-	HS2TFT3/4	0.025 ± 0.004	0.64 ± 0.10
7/8	1.130	28.7	0.911	23.1	23053/12A-233	HS2TFS7/8	0.035 ± 0.008	0.89 ± 0.20	-	HS2TFT7/8	0.025 ± 0.004	0.64 ± 0.10
1	1.500	38.1	1.036	26.3	23053/12A-234	HS2TFS1.00	0.035 ± 0.008	0.89 ± 0.20	-	HS2TFT1.00	0.025 ± 0.004	0.64 ± 0.10

HS2TFL PTFE Fractional Heat Shrink Tubing (2:1) LW

Order Size	Minimum Expanded I.D.		Maximum Recovered I.D.		Light Wall			
					Mil Spec*	Part Number	Nominal Recovered Wall	
inch	inch	mm	inch	mm			inch	mm
1/8	0.215	5.5	0.130	3.3	23053/12A-415	HS2TFL1/8	0.008 ± 0.002	0.20 ± 0.05
1/4	0.410	10.4	0.260	6.6	23053/12A-422	HS2TFL1/4	0.010 ± 0.003	0.25 ± 0.08
5/16	0.470	11.9	0.329	8.4	23053/12A-425	HS2TFL5/16	0.012 ± 0.003	0.31 ± 0.08




HS2TFI PTFE Fractional Heat Shrink Tubing (2:1), Ind. Heavy Wall

Part Number	Order Size	Mil Spec*	Minimum Expanded I.D.		Maximum Recovered I.D.		Nominal Recovered Wall	
	inch		inch	mm	inch	mm	inch	mm
HS2TFI1/8	1/8	23053/12A-101	0.166	4.2	0.130	3.3	0.030 ± 0.005	0.76 ± 0.13
HS2TFI3/16	3/16	23053/12A-102	0.250	6.4	0.193	4.9	0.030 ± 0.005	0.76 ± 0.13
HS2TFI1/4	1/4	23053/12A-103	0.333	8.4	0.257	6.5	0.030 ± 0.005	0.76 ± 0.13
HS2TFI5/16	5/16	23053/12A-104	0.415	10.5	0.320	8.1	0.030 ± 0.005	0.76 ± 0.13
HS2TFI3/8	3/8	23053/12A-105	0.498	12.6	0.383	9.7	0.030 ± 0.005	0.76 ± 0.13
HS2TFI7/16	7/16	23053/12A-106	0.580	14.7	0.448	11.4	0.030 ± 0.006	0.76 ± 0.15
HS2TFI1/2	1/2	23053/12A-107	0.666	16.9	0.510	13.0	0.030 ± 0.006	0.76 ± 0.15
HS2TFI9/16	9/16	23053/12A-108	0.748	19.0	0.572	14.5	0.030 ± 0.006	0.76 ± 0.15
HS2TFI5/8	5/8	23053/12A-109	0.830	21.1	0.637	16.2	0.030 ± 0.006	0.76 ± 0.15
HS2TFI11/16	11/16	23053/12A-110	0.915	23.2	0.700	17.8	0.032 ± 0.006	0.81 ± 0.15
HS2TFI3/4	3/4	23053/12A-111	1.000	25.4	0.764	19.4	0.040 ± 0.007	1.02 ± 0.18
HS2TFI7/8	7/8	23053/12A-112	1.170	29.7	0.891	22.6	0.045 ± 0.007	1.14 ± 0.18
HS2TFI1.00	1	23053/12A-113	1.330	33.8	1.020	25.9	0.050 ± 0.008	1.27 ± 0.20

For detailed ordering information, please consult price list or contact Parflex Division.

PTFE Heat ShrinkableTubing

Series 2:1 AWG: HS2TFS, HS2TFT, HS2TFL



Features

- Virgin Polytetrafluoroethylene resin
- 2:1 Shrink Ratio
- Chemically inert
- Lowest coefficient of friction
- Superior dielectric strength
- Exceptional heat resistance
- Self extinguishing
- Non-wetting

Certifications

- ASTM D2902 Type I
- AMS 3653E
- VW1, UL-83 (natural)
- FDA Compliant
- USP Class VI Compliant
- **Light Wall** (HS2TFL) – AMS-DTL-23053/12A Class 4
- **Thin Wall** (HS2TFT) – AMS-DTL-23053/12A Class 3, AMS 3585
- **Standard Wall** (HS2TFS) – AMS-DTL-23053/12A Class 2, AMS 3586
- **Heavy Wall** (HS2TFH) – AMS-DTL-23053/12A Class 1 (Custom Order only)

Applications/Markets



- Electrical Insulation
- Protective Cover
- Electronic Harness
- Laboratory

Order Information

Example: HS2TFS15-4TC-500

HS2TFS15-4TC-500 – **Heat Shrink**
HS**2**TFS15-4TC-500 – **Shrink Ratio (2:1)**
HS2**TF**S15-4TC-500 – **PTFE**
HS2TF**S**15-4TC-500 – **Wall Type (Standard Wall)**
HS2TFS**15**-4TC-500 – **Heat Shrink Size** in AWG **(AWG15)**
HS2TFS15-**4**TC-500 – **Yellow**
HS2TFS15-4**T**C-500 – **Bulk Tubing**
HS2TFS15-4T**C**-500 – **Solid Color**
HS2TFS15-4TC-**500** – **Package Quantity** in feet **(500')**

Colors

- ○ Natural, Opaque to translucent
- Colors available as custom run, see color code table

When ordering coiled tubing in colors, the color code is always followed by TC; when ordering cut lengths, the color code is followed by CC

i.e.,HS2TFS15-2TC i.e., HS2TFS15-0CC48.000

Color Code					
○	N	Natural	●	5	Green
●	0	Black	●	6	Blue
●	1	Brown	●	7	Violet
●	2	Red	●	8	Gray
●	3	Orange	○	9	White
●	4	Yellow			

Notes

- Working Temperature: -100°F (-75°C) to +500°F (260°C)
- Shrink Temperature: 662°F (350°C) for 10 minutes AMS-DTL-23053/12A
- *Dielectric Strength: ≥ 1,400 V/M, per ASTM D 149 short term test of 10 MIL thickness (Volts/MIL)
- PTFE AWG Heat Shrink tubing is available in stock packaging of 4-ft. straight lengths
- Minimum quantities may apply
- Custom packaging, sizes, lengths and colors are quoted upon request


For detailed ordering information, please consult price list or contact Parflex Division.

HS2TFS Standard Wall (2:1)

Part Number	Order Size	Mil Spec*	Minimum Expanded I.D.		Maximum Recovered I.D.		Nominal Recovered Wall	
	AWG		inch	mm	inch	mm	inch	mm
HS2TFS24	24	23053/12A-201	0.050	1.27	0.027	0.69	0.012 ± 0.002	0.31 ± 0.05
HS2TFS22	22	23053/12A-202	0.055	1.40	0.032	0.81	0.012 ± 0.002	0.31 ± 0.05
HS2TFS20	20	23053/12A-203	0.060	1.52	0.039	0.99	0.016 ± 0.003	0.41 ± 0.08
HS2TFS19	19	23053/12A-204	0.065	1.65	0.043	1.09	0.016 ± 0.003	0.41 ± 0.08
HS2TFS18	18	23053/12A-205	0.076	1.93	0.049	1.25	0.016 ± 0.003	0.41 ± 0.08
HS2TFS17	17	23053/12A-206	0.085	2.16	0.054	1.37	0.016 ± 0.003	0.41 ± 0.08
HS2TFS16	16	-	0.093	2.36	0.061	1.55	0.016 ± 0.003	0.41 ± 0.08
HS2TFS15	15	23053/12A-207	0.110	2.79	0.067	1.70	0.016 ± 0.003	0.41 ± 0.08
HS2TFS14	14	23053/12A-208	0.120	3.05	0.072	1.83	0.016 ± 0.003	0.41 ± 0.08
HS2TFS13	13	23053/12A-210	0.140	3.56	0.080	2.03	0.016 ± 0.003	0.41 ± 0.08
HS2TFS12	12	23053/12A-211	0.150	3.81	0.089	2.26	0.016 ± 0.003	0.41 ± 0.08
HS2TFS11	11	23053/12A-212	0.170	4.32	0.101	2.57	0.016 ± 0.003	0.41 ± 0.08
HS2TFS10	10	23053/12A-213	0.191	4.85	0.112	2.84	0.016 ± 0.003	0.41 ± 0.08
HS2TFS09	9	23053/12A-214	0.205	5.21	0.124	3.15	0.020 ± 0.004	0.51 ± 0.10
HS2TFS08	8	23053/12A-216	0.240	6.10	0.141	3.58	0.020 ± 0.004	0.51 ± 0.10
HS2TFS07	7	23053/12A-217	0.270	6.86	0.158	4.01	0.020 ± 0.004	0.51 ± 0.10
HS2TFS06	6	23053/12A-218	0.302	7.67	0.178	4.52	0.020 ± 0.004	0.51 ± 0.10
HS2TFS05	5	23053/12A-219	0.320	8.13	0.198	5.03	0.020 ± 0.004	0.51 ± 0.10
HS2TFS04	4	23053/12A-220	0.370	9.40	0.224	5.69	0.020 ± 0.004	0.51 ± 0.10
HS2TFS03	3	23053/12A-221	0.390	9.91	0.249	6.32	0.020 ± 0.004	0.51 ± 0.10
HS2TFS02	2	23053/12A-223	0.430	10.9	0.278	7.06	0.020 ± 0.004	0.51 ± 0.10
HS2TFS01	1	23053/12A-224	0.450	11.4	0.311	7.90	0.020 ± 0.004	0.51 ± 0.10
HS2TFS00	0	23053/12A-226	0.470	11.9	0.347	8.81	0.020 ± 0.004	0.51 ± 0.10

Certifications

- AMS-DTL-23053/12A, Class 3
- AMS 3585
- ASTM D2902 Type I
- FDA Compliant
- USP Class VI Compliant



PTFE Heat ShrinkableTubing

Series 2:1 AWG: HS2TFS, HS2TFT, HS2TFL (cont.)

HS2TFT Thin Wall (2:1)

Part Number	Order Size AWG	Mil Spec**	Minimum Expanded I.D.		Maximum Recovered I.D.		Nominal Recovered Wall	
			inch	mm	inch	mm	inch	mm
HS2TFT30	30	23053/12A-301	0.034	0.86	0.015	0.38	0.009 ± 0.002	0.23 ± 0.05
HS2TFT28	28	23053/12A-302	0.038	0.97	0.018	0.46	0.009 ± 0.002	0.23 ± 0.05
HS2TFT26	26	23053/12A-303	0.046	1.16	0.022	0.56	0.010 ± 0.003	0.25 ± 0.08
HS2TFT24	24	23053/12A-304	0.050	1.27	0.027	0.69	0.010 ± 0.002	0.25 ± 0.08
HS2TFT22	22	23053/12A-305	0.055	1.40	0.032	0.81	0.012 ± 0.003	0.31 ± 0.08
HS2TFT20	20	23053/12A-306	0.060	1.52	0.039	0.99	0.012 ± 0.003	0.31 ± 0.08
HS2TFT19	19	23053/12A-307	0.065	1.65	0.043	1.09	0.012 ± 0.003	0.31 ± 0.08
HS2TFT18	18	23053/12A-308	0.076	1.93	0.049	1.25	0.012 ± 0.003	0.31 ± 0.08
HS2TFT17	17	23053/12A-309	0.085	2.16	0.054	1.37	0.012 ± 0.003	0.31 ± 0.08
HS2TFT16	16	23053/12A-310	0.093	2.36	0.061	1.55	0.012 ± 0.003	0.31 ± 0.08
HS2TFT15	15	23053/12A-311	0.110	2.79	0.067	1.70	0.012 ± 0.003	0.31 ± 0.08
HS2TFT14	14	23053/12A-312	0.120	3.05	0.072	1.83	0.012 ± 0.003	0.31 ± 0.08
HS2TFT13	13	23053/12A-313	0.140	3.56	0.080	2.03	0.012 ± 0.003	0.31 ± 0.08
HS2TFT12	12	23053/12A-314	0.150	3.81	0.089	2.26	0.012 ± 0.003	0.31 ± 0.08
HS2TFT11	11	23053/12A-316	0.170	4.32	0.101	2.57	0.012 ± 0.003	0.31 ± 0.08
HS2TFT10	10	23053/12A-317	0.191	4.85	0.112	2.84	0.012 ± 0.003	0.31 ± 0.08
HS2TFT09	9	23053/12A-318	0.205	5.21	0.124	3.15	0.015 ± 0.004	0.38 ± 0.10
HS2TFT08	8	23053/12A-320	0.240	6.10	0.141	3.58	0.015 ± 0.004	0.38 ± 0.10
HS2TFT07	7	23053/12A-321	0.270	6.86	0.158	4.01	0.015 ± 0.004	0.38 ± 0.10
HS2TFT06	6	23053/12A-322	0.302	7.67	0.178	4.52	0.015 ± 0.004	0.38 ± 0.10
HS2TFT05	5	23053/12A-323	0.320	8.13	0.198	5.03	0.015 ± 0.004	0.38 ± 0.10
HS2TFT04	4	23053/12A-324	0.370	9.40	0.224	5.69	0.015 ± 0.004	0.38 ± 0.10
HS2TFT03	3	23053/12A-325	0.390	9.91	0.249	6.32	0.015 ± 0.004	0.38 ± 0.10
HS2TFT02	2	23053/12A-327	0.430	10.9	0.278	7.06	0.015 ± 0.004	0.38 ± 0.10
HS2TFT01	1	23053/12A-328	0.450	11.4	0.311	7.90	0.015 ± 0.004	0.38 ± 0.10
HS2TFT00	0	23053/12A-330	0.470	11.9	0.347	8.81	0.015 ± 0.004	0.38 ± 0.10

*Dielectric Strength: ≥ 1,400 V/M, per ASTM D 149 short term test of 10 MIL thickness (Volts/MIL)

Certifications

- AMS-DTL-23053/12A, Class 3
- AMS 3585
- ASTM D2902 Type I
- FDA Compliant
- USP Class VI Compliant

HS2TFL Light Wall (2:1)

Part Number	Order Size AWG	Mil Spec**	Minimum Expanded I.D.		Maximum Recovered I.D.		Nominal Recovered Wall	
			inch	mm	inch	mm	inch	mm
HS2TFL24	24	23053/12A-404	0.050	1.27	0.025	0.64	0.006 ± 0.002	0.15 ± 0.05
HS2TFL22	22	23053/12A-405	0.055	1.40	0.031	0.79	0.006 ± 0.002	0.15 ± 0.05
HS2TFL20	20	23053/12A-406	0.060	1.52	0.038	0.97	0.006 ± 0.002	0.15 ± 0.05
HS2TFL19	19	23053/12A-407	0.065	1.65	0.043	1.09	0.006 ± 0.002	0.15 ± 0.05
HS2TFL18	18	23053/12A-408	0.076	1.93	0.046	1.17	0.006 ± 0.002	0.15 ± 0.05
HS2TFL17	17	23053/12A-409	0.085	2.16	0.054	1.37	0.006 ± 0.002	0.15 ± 0.05
HS2TFL16	16	23053/12A-410	0.093	2.36	0.057	1.45	0.006 ± 0.002	0.15 ± 0.05
HS2TFL15	15	23053/12A-411	0.110	2.79	0.063	1.60	0.006 ± 0.002	0.15 ± 0.05
HS2TFL14	14	23053/12A-412	0.120	3.05	0.072	1.83	0.008 ± 0.002	0.20 ± 0.05
HS2TFL13	13	23053/12A-413	0.140	3.56	0.080	2.03	0.008 ± 0.002	0.20 ± 0.05
HS2TFL12	12	23053/12A-414	0.150	3.81	0.089	2.26	0.008 ± 0.002	0.20 ± 0.05
HS2TFL11	11	23053/12A-416	0.170	4.32	0.099	2.51	0.008 ± 0.002	0.20 ± 0.05
HS2TFL10	10	23053/12A-417	0.191	4.85	0.110	2.79	0.008 ± 0.002	0.20 ± 0.05
HS2TFL09	9	23053/12A-418	0.205	5.21	0.122	3.10	0.008 ± 0.002	0.20 ± 0.05
HS2TFL08	8	23053/12A-420	0.240	6.10	0.139	3.53	0.008 ± 0.002	0.20 ± 0.05
HS2TFL07	7	23053/12A-421	0.270	6.86	0.154	3.91	0.008 ± 0.002	0.20 ± 0.05
HS2TFL06	6	23053/12A-422	0.302	7.67	0.172	4.37	0.010 ± 0.003	0.25 ± 0.08
HS2TFL05	5	23053/12A-423	0.320	8.13	0.192	4.88	0.010 ± 0.003	0.25 ± 0.08
HS2TFL04	4	23053/12A-424	0.370	9.40	0.214	5.44	0.010 ± 0.003	0.25 ± 0.08
HS2TFL03	3	23053/12A-425	0.390	9.91	0.241	6.12	0.010 ± 0.003	0.25 ± 0.08
HS2TFL02	2	23053/12A-427	0.430	10.9	0.270	6.88	0.010 ± 0.003	0.25 ± 0.08
HS2TFL01	1	23053/12A-428	0.450	11.4	0.301	7.65	0.010 ± 0.003	0.25 ± 0.08
HS2TFL00	0	23053/12A-430	0.470	11.9	0.347	8.81	0.012 ± 0.003	0.31 ± 0.08


*Dielectric Strength: ≥ 1,400 V/M, per ASTM D 149 short term test of 10 MIL thickness (Volts/MIL)

Certifications

- AMS-DTL-23053/12A, Class 4
- ASTM D2902 Type I
- FDA Compliant
- USP Class VI Compliant

PTFE Heat ShrinkableTubing

Series 4:1 HS4TFI



Features

- Virgin Polytetrafluoroethylene resin
- 4:1 Shrink Ratio
- Chemically inert
- Lowest coefficient of friction
- Superior dielectric strength
- Exceptional heat resistance
- Self extinguishing
- Non-wetting

Applications/Markets





- Electrical Insulation
- Protective Cover
- Rollers
- Bulb Protection

Certifications

- AMS-DTL-23053/12A, Class 5
- ASTM D2902 Type I
- AMS 3584A
- VW1, UL-83 (natural)
- FDA Compliant
- USP Class VI Compliant

Order Information

Example: HS4TFI5/8-NT

HS4TFI5/8-NT – **Heat Shrink**
HS**4**TFI5/8-NT – **Shrink Ratio (4:1)**
HS4**TF**I5/8-NT – **PTFE**
HS4TF**I**5/8-NT – **Wall Type (Industrial Wall)**
HS4TFI**5/8**-NT – **Heat Shrink Size** in inches **(5/8")**
HS4TFI5/8-**N**T – **Natural**
HS4TFI5/8-N**T** – **Bulk Tubing**

Colors

- ○ Natural, Opaque to translucent
- Colors available as custom run, see color code table

When ordering coiled tubing in colors, the color code is always followed by TC; when ordering cut lengths, the color code is followed by CC

i.e.,HS4TFI5/8-2TC i.e.,HS4TFI5/8-0CC48.0000

Color Code					
○	N	Natural	●	5	Green
●	0	Black	●	6	Blue
●	1	Brown	●	7	Violet
●	2	Red	●	8	Gray
●	3	Orange	○	9	White
●	4	Yellow			


Notes

- Working Temperature: -500°F (260°C)
- Shrink Temperature: 662°F (350°C) for 10 minutes AMS-DTL-23053/12A
- For full recovery, expanded diameter should be 50% larger than the diameter of the object to be recovered over
- *Dielectric Strength: ≥ 1,400 V/M, per ASTM D 149 short term test of 10 MIL thickness (Volts/MIL)
- PTFE Fractional Heat Shrink tubing is available in stock packaging of 4-ft. straight lengths
- Minimum quantities may apply
- Custom packaging, sizes, lengths and colors are quoted upon request

For detailed ordering information, please consult price list or contact Parflex Division.


HS4TFI PTFE Industrial Wall Heat Shrink Tubing (4:1)

Part Number	Order Size	Mil Spec**	Minimum Expanded I.D.		Maximum Recovered I.D.		Nominal Recovered Wall	
	inch		inch	mm	inch	mm	inch	mm
HS4TFI5/64	5/64	23053/12A-501	0.078	1.98	0.025	0.64	0.009 ± 0.002	0.23 ± 0.05
HS4TFI1/8	1/8	23053/12A-502	0.125	3.18	0.037	0.94	0.012 ± 0.002	0.31 ± 0.05
HS4TFI3/16	3/16	23053/12A-503	0.187	4.75	0.050	1.27	0.012 ± 0.002	0.31 ± 0.05
HS4TFI1/4	1/4	23053/12A-504	0.250	6.35	0.063	1.60	0.012 ± 0.002	0.31 ± 0.05
HS4TFI5/16	5/16	23053/12A-505	0.312	7.92	0.078	1.98	0.012 ± 0.002	0.31 ± 0.05
HS4TFI3/8	3/8	23053/12A-506	0.375	9.52	0.096	2.44	0.012 ± 0.002	0.31 ± 0.05
HS4TFI7/16	7/16	23053/12A-507	0.438	11.1	0.112	2.84	0.012 ± 0.002	0.31 ± 0.05
HS4TFI1/2	1/2	23053/12A-508	0.500	12.7	0.144	3.66	0.015 ± 0.004	0.38 ± 0.10
HS4TFI5/8	5/8	23053/12A-510	0.625	15.9	0.178	4.52	0.015 ± 0.004	0.38 ± 0.10
HS4TFI3/4	3/4	23053/12A-512	0.750	19.1	0.224	5.70	0.015 ± 0.004	0.38 ± 0.10
HS4TFI7/8	7/8	23053/12A-513	0.875	22.2	0.244	6.20	0.015 ± 0.004	0.38 ± 0.10
HS4TFI1.00	1	23053/12A-514	1.000	25.4	0.278	7.06	0.015 ± 0.004	0.38 ± 0.10
HS4TFI1.25	1-1/4	23053/12A-515	1.250	31.8	0.347	8.81	0.015 ± 0.004	0.38 ± 0.10



PTFE Convoluted

Series Convo-Tex®



Features

- Chemically inert
- Low coefficient of friction
- Very flexible
- Self extinguishing
- Non-wetting

Certifications

- AMS 3653E
- VW1, UL-83 (natural)
- FDA Compliant
- USP Class VI Compliant

Applications/Markets



- Fluid Transport
- Wire Harness
- Protection/Cable Core
- Robotics

Order Information

Example: CV01-1/8-NT

CV01-1/8-NT – **Convoluted**
CV**01-**1/8-NT – **PTFE**
CV01-**1/8**-NT – **Size to Order (1/8")**
CV01-1/8-**NT** – **Color (N=Natural)**
CV01-1/8-N**T**– **"T" is bulk (**for cuffed tubing, remove "T" and add length, ie. CV01-1/8-N1200 = 1" Convo, natural, cut 12" long)

Colors

- ○ Natural, Opaque to Translucent
- Colors available as custom run, see color code table

Color Code					
○	N	Natural	●	5	Green
●	0	Black	●	6	Blue
●	1	Brown	●	7	Violet
●	2	Red	●	8	Gray
●	3	Orange	○	9	White
●	4	Yellow			

Notes

- Working Temperature: -100°F (-75°C) to +500°F (260°C)
- Standard cuffs for Convo-Tex are sized on the Inside Diameter
- Wire wrap reinforcement can be added for increased pressure applications or when a tighter bend radius is needed
- Minimum quantities may apply
- Custom packaging, sizes, lengths and colors are quoted upon request

For detailed ordering information, please consult price list or contact Parflex Division.

PTFE Convo-Tex® Convoluted


(Standard tubing is natural)

Part Number	Size To Order	Standard Cuff I.D. "A"		Standard Cuff Length "B"		Wall Thickness "C"		Min. Inside Diameter "D"		Max. Inside Diameter "D"		Max. Outside Diameter "E"		**Min. Bend Radius	
		inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
CV01-1/8-NT	CONV-2	1/8	3.18	3/4	19.1	0.010	0.25	0.130	3.3	0.140	3.6	0.235	5.9	3/8	9.5
CV01-1/4-NT	CONV-4	1/4	6.35	3/4	19.1	0.015	0.38	0.181	4.6	0.188	4.8	0.320	8.1	1/2	12.7
CV01-5/16-NT	CONV-5	5/16	7.94	1	25.4	0.020	0.51	0.273	6.9	0.281	7.1	0.414	10.5	3/4	19.1
CV01-3/8-NT	CONV-6	3/8	9.53	1	25.4	0.020	0.51	0.303	7.7	0.312	7.9	0.450	11.4	1-3/4	44.4
CV01-1/2-NT	CONV-8	1/2	12.7	1	25.4	0.020	0.51	0.425	10.8	0.437	11.1	0.590	15.0	1-1/4	31.2
CV01-5/8-NT	CONV-10	5/8	15.9	1-1/4	31.8	0.025	0.64	0.485	12.3	0.500	12.7	0.660	16.8	1-1/2	38.1
CV01-3/4-NT	CONV-12	3/4	19.1	1-1/2	38.1	0.023	0.58	0.608	15.4	0.625	15.9	0.780	19.8	1-3/4	44.4
CV01-1.00-NT	CONV-16	1	25.4	2	50.8	0.030	0.76	0.849	21.6	0.875	22.2	1.100	27.9	2-1/4	57.2
CV01-1.25-NT	CONV-20	1-1/4	31.8	2-1/2	63.5	0.035	0.89	1.150	29.2	1.190	30.2	1.560	39.6	2-3/4	69.9
CV01-1.50-NT	CONV-24	1-1/2	38.1	2-1/2	63.5	0.040	1.02	1.410	35.8	1.490	37.8	1.910	48.5	3	76.2
CV01-2.00-NT	CONV-32	2	50.8	2-1/2	63.5	0.043	1.09	1.955	49.7	1.985	50.4	2.450	62.2	4-1/4	107.9
CV01-2.50-NT	CONV-40	2-1/2	63.5	2-1/2	63.5	0.062	1.57	2.460	62.5	2.540	64.5	3.210	81.6	5	127
CV01-3.00-NT	CONV-48	3	76.2	2-1/2	63.5	0.070	1.78	2.940	74.7	3.060	77.7	3.750	95.3	7	177.8
CV01-4.00-NT	CONV-64	4	101.6	2-1/2	63.5	0.070	1.78	3.940	100.1	4.060	103.1	4.750	120.6	9	228.6

** Minimum 36" length.




Standard Cuffs for **Convo-Tex®** are sized on the **I.D.**





PTFE Convoluted

Series Low Profile and Heavy Wall



Features

- Chemically inert
- Low coefficient of friction
- Very flexible
- Self extinguishing
- Non-wetting

Low Profile

- Larger inside diameter
- Increased Flow

Heavy Wall

- Reinforces the strength of the tube allowing for braiding or covering, flanging or flaring
- Handles higher vacuum

Applications/Markets



- Fluid Handling
- Harnesses
- Lab Equipment
- Robotics

Certifications

- AMS 3653E
- VW1, UL-83
- FDA Compliant
- USP Class VI Compliant

Order Information

Example: CVH01-1/8-NT

CVH01-1/8-NT – **CVH - Heavywall Convoluted**
– **CVL Low Profile Convoluted**
CVH**01-**1/8-NT – **PTFE**
CVH01-**1/8**-NT – **Size to Order (1/8")**
CVH01-1/8-**NT** – **Color (N=Natural)**
CVH01-1/8-NT– **"T" is bulk (**for cuffed tubing, remove "T" and add length, ie. CVH01-1/8-N1200 = 1"Heavy Wall Convo, natural, cut 12" long)

Colors

- ○ Natural, Opaque to Translucent
- Colors available as custom run, see color code table

Color Code					
○	N	Natural	●	5	Green
●	0	Black	●	6	Blue
●	1	Brown	●	7	Violet
●	2	Red	●	8	Gray
●	3	Orange	○	9	White
●	4	Yellow			

Notes

- Working Temperature: 500°F (260°C)
- Standard cuffs for Convo-Tex are sized on the Inside Diameter
- Wire wrap reinforcement can be added for increased pressure applications or when a tighter bend radius is needed
- Minimum quantities may apply
- Custom packaging, sizes, lengths, cuffs and colors are quoted upon request

For detailed ordering information, please consult price list or contact Parflex Division.


PTFE Low Profile Convoluted

(Standard tubing is natural)

Part Number	Size To Order	Min. Inside Diameter		Max. Inside Diameter		Max. Outside Diameter		Wall Thickness		**Min. Bend Radius	
		inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
CVL01-3/8-NT	3/8	0.394	10.0	0.406	10.3	0.560	14.2	0.023	0.58	1/2	13
CVL01-1/2-NT	1/2	0.490	12.5	0.510	13.0	0.700	17.8	0.025	0.64	3/4	19
CVL01-3/4-NT	3/4	0.740	18.8	0.760	19.3	0.980	24.9	0.035	0.89	1.88	48
CVL01-1.00-NT	1	0.990	25.1	1.010	25.7	1.260	32.0	0.035	0.89	2-1/4	57
CVL01-1.25-NT	1-1/4	1.210	30.7	1.250	31.8	1.539	39.1	0.035	0.89	3	76
CVL01-1.50-NT	1-1/2	1.520	38.6	1.540	39.1	1.870	47.5	0.044	1.12	3-1/2	89
CVL01-1.75-NT	1-3/4	1.690	42.9	1.750	44.5	2.100	53.3	0.040	1.02	4-1/4	108
CVL01-2.00-NT	2	2.010	51.1	2.030	51.6	2.370	60.2	0.043	1.09	4-3/4	121

** Minimum 36 length.

Standard Cuffs for **Low Profile** and **Heavy Wall** are sized on the **I.D.**



PTFE Heavy Wall Convoluted

(Standard tubing is natural)

Part Number	Size To Order	Min. Inside Diameter		Max. Inside Diameter		Max. Outside Diameter		Wall Thickness		**Min. Bend Radius	
		inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
CVH01-1/4-NT	1/4	0.257	6.5	0.265	6.7	0.415	10.5	0.025	0.38	3/4	19
CVH01-3/8-NT	3/8	0.335	8.5	0.345	8.8	0.510	13.0	0.025	0.64	1	25
CVH01-1/2-NT	1/2	0.454	11.5	0.466	11.8	0.700	17.8	0.035	0.89	1-1/2	38
CVH01-3/4-NT	3/4	0.683	17.4	0.701	17.8	1.010	25.7	0.050	1.27	1.88	48
CVH01-1.00-NT	1	0.841	21.4	0.859	21.8	1.210	30.7	0.053	1.35	2-1/2	64
CVH01-1.25-NT	1-1/4	1.125	28.6	1.145	29.1	1.610	40.9	0.062	1.57	3.13	79
CVH01-1.50-NT	1-1/2	1.420	36.1	1.480	37.6	1.880	47.8	0.062	1.57	3-3/4	95
CVH01-1.75-NT	1-3/4	1.540	39.1	1.600	40.6	2.100	53.3	0.062	1.57	4-1/2	114
CVH01-2.00-NT	2	1.770	45.0	1.830	46.5	2.432	61.8	0.062	1.57	4-3/4	120
CVH01-2.50-NT	2-1/2	2.460	62.5	2.540	64.5	3.210	81.5	0.062	1.57	5	127
CVH01-3.00-NT	3	2.940	74.7	3.060	77.7	3.750	95.3	0.062	1.57	7	178
CVH01-4.00-NT	4	3.90	100	4.060	103	4.750	121	0.070	1.77	9	229

** Minimum 36 length.

PTFE Convoluted

Series SAE AS81914/1 and SAE AS81914/2



Features

- Chemically inert
- Low coefficient of friction
- Very flexible
- Self extinguishing
- Non-wetting

Certifications

- AMS 3653E
- SAE AS81914/1
- SAE AS81914/2
- FDA Compliant

Applications/Markets

- Fluid Handling
- Harnesses
- Crush Resistant Cover
- Robotics

Order Information

Example: 81914/1-1010-0TC

81914/1-1010-0TC – **SAE AS81914 Convoluted**
81914/**1**-1010-0TC – **PTFE**
81914/1-**10**10-0TC – **Helical Convolutions**
81914/1-10**10**-0TC – **Size (10=1.000")**
81914/1-1010-**0**TC – **Color (0=Black)**
81914/1-1010-0**TC** – **"T" is bulk - (**for cuffed tubing, remove "T" and add length, ie. 81914/1-1010-01200 = 187" Convo, black, cut 12" long

Notes

- Working Temperature: 500°F (260°C)
- Tubing is provided in black without cuffs direct from inventory
- Stock packaging is random coils
- Also availabe in close convolution 81914/2
- Minimum quantities may apply
- Custom packaging, sizes, lengths, cuffs and colors are quoted upon request

Colors

- ● Black
- Colors available as custom run, see color code table

When ordering convoluted tubing in colors, the "N" designation for natural should be replaced by the correct color designator;

i.e.,81914/1-101-0T (black bulk tubing)
i.e.,81914/1-101-01200 (black tubing - 12 inches long)

Color Code					
○	N	Natural	●	5	Green
●	0	Black	●	6	Blue
●	1	Brown	●	7	Violet
●	2	Red	●	8	Gray
●	3	Orange	○	9	White
●	4	Yellow			

For detailed ordering information, please consult price list or contact Parflex Division.

PTFE Convoluted Tubing (SAE AS81914/1)

(Standard tubing is black)

Part Number	MIL Spec*	Maximum Inside Diameter		Minimum Inside Diameter		Maximum Outside Diameter		Maximum Wall Thickness		Minimum Bend Radius		Pitch	Weight	
		inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	±1	lb./100 ft.	kg./100 mtr.
81914/1-1001-0TC	-1	0.188	4.78	0.181	4.6	0.320	8.13	0.023	0.584	1/2	13	8	2	2.98
81914/1-1002-0TC	-2	0.281	7.14	0.273	6.93	0.414	10.5	0.027	0.686	3/4	19	7.5	2.9	4.31
81914/1-1003-0TC	-3	0.312	7.93	0.303	7.7	0.450	11.4	0.027	0.686	7/8	22	7.5	3.6	5.36
81914/1-1004-0TC	-4	0.375	9.53	0.364	9.25	0.530	13.5	0.029	0.737	1	25	7	4.2	6.25
81914/1-1005-0TC	-5	0.437	11.1	0.425	10.8	0.590	15.0	0.029	0.737	1-1/4	32	7	4.9	7.29
81914/1-1006-0TC	-6	0.500	12.7	0.485	12.3	0.660	16.8	0.029	0.737	1-1/2	38	7	5.2	7.74
81914/1-1007-0TC	-7	0.625	15.9	0.608	15.4	0.780	19.9	0.035	0.889	1-3/4	44	7	6.9	10.3
81914/1-1008-0TC	-8	0.750	19.1	0.730	18.5	0.975	24.8	0.035	0.889	1.88	48	6	10.4	15.5
81914/1-1009-0TC	-9	0.875	22.2	0.850	21.6	1.100	27.9	0.035	0.889	2-1/4	57	6	11.3	16.8
81914/1-1010-0TC	-10	1.000	25.4	0.975	24.8	1.260	32.0	0.035	0.889	2-1/2	64	4.5	12.6	18.8
81914/1-1011-0TC	-11	1.125	28.6	1.100	27.9	1.390	35.3	0.035	0.889	2-3/4	70	4.5	13.8	20.5
81914/1-1012-0TC	-12	1.250	31.8	1.210	30.7	1.539	39.1	0.035	0.889	3	76	4	15.5	23.1
81914/1-1013-0TC	-13	1.500	38.1	1.440	36.6	1.850	47.0	0.040	1.020	3.75	95	4	21.7	32.3
81914/1-1014-0TC	-14	1.750	44.5	1.690	42.9	2.100	53.3	0.045	1.140	4.25	108	4	25.3	37.6
81914/1-1015-0TC	-15	2.000	50.8	1.940	49.3	2.350	59.7	0.045	1.140	4.75	121	4	29	43.2

*PTFE convoluted tubing is provided in BLACK without cuffs direct from the factory. Black part numbers are designated with "0T" and Natural part numbers are designated with "NT" after the Mil Spec number (i.e.,81914/1-1014-0T).

Standard Cuffs for **81914/1** are sized on the **I.D.**




Without Cuffs



With Cuffs

FEP Tubing

Series Fractional & Metric: 103, 203



Features

- Virgin Fluorinated Ethylene Propylene resin
- Translucent
- Chemically inert
- Long continuous lengths
- Low coefficient of friction
- Self extinguishing
- Non-wetting
- Weldable

Certifications/Compliance

- ASTM D2116-07
- VW-1, UL-83 (natural)
- FDA Compliant
- USP Class VI Compliant

Applications/Markets



- Nitrogen Transfer
- Ozone Sampling
- Optical Sensor
- Laboratory
- Down Hole Pump
- Food & Beverage
- Catheter Repair
- Syringe Tips

Order Information

Example: 103-0250031-NT-100

103-0250031-NT-100 – **Fractional**

103-0250031-NT-100 – **FEP**

103-**0250**031-NT-100 – **Tube O.D.** in inches **(1/4")**

103-0250**031**-NT-100 – **Tube Wall Thickness** in inches **(.031")**

103-0250031-**NT**-100 – **Natural**

103-0250031-NT-**100** – **Package Quantity** in feet **(100')**

Fittings

Fittings available for sizes 1/8" up to 1"

Parker Fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 692-6634 FAX

FSC Product Families:

FSC Product Families:

- Compression
- Compress-Align®
- Metric Compression
- Flow-Controls
- Prestolok Composite
- Prestolok All-Metal
- Prestolok Stainless
- TrueSeal™

Notes

- Working Temperature:
  -100°F (-75°C) to +400°F (204°C)
- Working pressure calculated using a Design Factor of 4 at 73°F (23°C)
- Custom packaging and sizes are quoted upon request
- Package quantities are not continuous

Options

- Smoothbore
- Convoluted
- Corrugated
- Retractable Coils
- Paratubing

Colors

- ○ Natural, Translucent
- Colors available as custom run, see color code table

Color Code					
○	N	Natural	●	5	Green
●	0	Black	●	6	Blue
●	1	Brown	●	7	Violet
●	2	Red	●	8	Gray
●	3	Orange	○	9	White
●	4	Yellow			

For detailed ordering information, please consult price list or contact Parflex Division.

103 FEP Industrial Wall Fractional Size Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure		Burst Pressure		Min. Bend Radius		Vac. Rating	Weight	
#																				
	inch	inch	tol.	mm	tol.	inch	tol.	mm	tol.	inch	mm	psi 73°F	bar 23°C	psi 73°F	bar 23°C	inch	mm	at 73°F	lb. per ft.	kg. per m.
103-0094031	3/32	0.094	± 0.005	2.40	± 0.127	0.031	± 0.002	0.79	± 0.051	0.031	0.79	630	43	2520	174	0.500	13	28	0.006	0.009
103-0125031	1/8	0.125	± 0.003	3.18	± 0.076	0.062	± 0.003	1.57	± 0.076	0.031	0.79	470	32	1880	130	0.375	10	28	0.009	0.013
103-0156031	5/32	0.157	± 0.005	3.99	± 0.127	0.094	± 0.005	2.39	± 0.127	0.031	0.79	360	25	1440	99	0.375	10	28	0.011	0.017
103-0188031	3/16	0.188	± 0.005	4.78	± 0.127	0.125	± 0.005	3.18	± 0.127	0.031	0.79	290	20	1160	80	0.750	19	28	0.014	0.021
103-0250031	1/4	0.250	± 0.005	6.35	± 0.127	0.188	± 0.005	4.78	± 0.127	0.031	0.79	210	14	840	58	1.750	44	28	0.020	0.030
103-0312031	5/16	0.312	± 0.005	7.92	± 0.127	0.250	± 0.005	6.35	± 0.127	0.031	0.79	160	11	640	44	2.250	57	28	0.025	0.038
103-0375031	3/8	0.375	± 0.005	9.52	± 0.127	0.312	± 0.005	7.92	± 0.127	0.031	0.79	130	9	520	36	2.750	70	28	0.031	0.047
103-0438031	7/16	0.438	± 0.005	11.13	± 0.127	0.375	± 0.005	9.52	± 0.127	0.031	0.79	110	8	440	30	4.000	102	28	0.037	0.055
103-0500031	1/2	0.500	± 0.006	12.70	± 0.152	0.438	± 0.006	11.13	± 0.152	0.031	0.79	90	6	360	25	4.000	102	28	0.043	0.063
103-0563031	9/16	0.563	± 0.006	14.30	± 0.152	0.500	± 0.006	12.70	± 0.152	0.031	0.79	80	6	320	22	5.000	127	28	0.054	0.080

103 FEP Heavy Wall Fractional Size Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure		Burst Pressure		Min. Bend Radius		Vac. Rating	Weight	
#																				
	inch	inch	tol.	mm	tol.	inch	tol.	mm	tol.	inch	mm	psi 73°F	bar 23°C	psi 73°F	bar 23°C	inch	mm	at 73°F	lb. per ft.	kg. per m.
103-0188062	3/16	0.188	± 0.005	4.78	± 0.127	0.064	± 0.005	1.63	± 0.127	0.062	1.57	630	43	2520	174	0.250	6	28	0.023	0.034
103-0250040	1/4	0.250	± 0.005	6.35	± 0.127	0.170	± 0.005	4.32	± 0.127	0.040	1.02	280	19	1120	77	1.250	32	28	0.025	0.037
103-0250047	1/4	0.250	± 0.005	6.35	± 0.127	0.156	± 0.005	3.96	± 0.127	0.047	1.19	340	23	1360	94	0.750	19	28	0.028	0.042
103-0250062	1/4	0.250	± 0.005	6.35	± 0.127	0.125	± 0.005	3.18	± 0.127	0.062	1.57	470	32	1880	130	0.750	19	28	0.034	0.051
103-0312062	5/16	0.312	± 0.005	7.92	± 0.127	0.188	± 0.005	4.78	± 0.127	0.062	1.57	360	25	1440	99	1.375	35	28	0.045	0.068
103-0375062	3/8	0.375	± 0.005	9.52	± 0.127	0.250	± 0.005	6.35	± 0.127	0.062	1.57	290	20	1160	80	1.500	38	28	0.057	0.085
103-0438062	7/16	0.438	± 0.005	11.13	± 0.127	0.312	± 0.005	7.92	± 0.127	0.062	1.57	250	17	1000	69	2.625	67	28	0.068	0.102
103-0500062	1/2	0.500	± 0.005	12.70	± 0.127	0.375	± 0.005	9.53	± 0.127	0.062	1.57	210	14	840	58	2.125	54	28	0.079	0.119
103-0625062	5/8	0.625	± 0.006	15.88	± 0.152	0.500	± 0.006	12.70	± 0.152	0.062	1.57	160	11	640	44	3.000	76	28	0.102	0.152
103-0750062	3/4	0.750	± 0.006	19.05	± 0.152	0.625	± 0.006	15.88	± 0.152	0.062	1.57	130	9	520	36	6.000	152	28	0.125	0.186
103-1000062	1	1.000	± 0.010	25.40	± 0.254	0.875	± 0.010	22.22	± 0.254	0.062	1.57	90	6	360	25	8.000	203	28	0.170	0.254


203 Metric FEP Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure		Burst Pressure		Min. Bend Radius		Vac. Rating	Weight	
#																				
	mm	mm	tol.	inch	tol.	mm	tol.	inch	tol.	mm	inch	bar 23°C	psi 73°F	bar 23°C	psi 73°F	mm	inch	at 73°F	kg. per m.	lb. per ft.
203-0300100	3	3	± 0.11	0.118	± 0.004	1	± 0.11	0.039	± 0.004	1	0.039	27	390	108	1560	6	0.250	28	0.014	0.009
203-0400100	4	4	± 0.11	0.157	± 0.004	2	± 0.11	0.079	± 0.004	1	0.039	20	290	80	1160	13	0.500	28	0.020	0.014
203-0500100	5	**5**	± 0.11	0.197	± 0.004	3	± 0.11	0.118	± 0.004	1	0.039	15	220	61	880	19	0.750	28	0.027	0.018
203-0600100	6	6	± 0.13	0.236	± 0.005	4	± 0.13	0.157	± 0.005	1	0.039	12	180	50	720	29	1.125	28	0.034	0.023
203-0700100	7	7	± 0.13	0.276	± 0.005	5	± 0.13	0.197	± 0.005	1	0.039	10	150	41	600	44	1.750	28	0.041	0.027
203-0800100	8	8	± 0.13	0.315	± 0.005	6	± 0.13	0.236	± 0.005	1	0.039	9	130	36	520	51	2.000	28	0.047	0.032
203-0900100	9	9	± 0.13	0.354	± 0.005	7	± 0.13	0.275	± 0.005	1	0.039	8	110	30	440	54	2.125	28	0.054	0.036
203-1000100	10	10	± 0.13	0.393	± 0.005	8	± 0.13	0.315	± 0.005	1	0.039	7	100	28	400	70	2.750	28	0.061	0.041
203-1200100	12	12	± 0.15	0.472	± 0.006	10	± 0.15	0.394	± 0.006	1	0.039	6	80	22	320	76	3.000	28	0.074	0.050

For detailed ordering information, please consult price list or contact Parflex Division.

FEP Heat ShrinkableTubing

Series 1.3:1 HS1.3FEP



Features

- Easier to shrink than PTFE
- Chemically inert
- Low coefficient of friction
- Superior dielectric strength
- Good heat resistance
- Self extinguishing
- Non-wetting

Certifications

- AMS-DTL-23053/11A, Class 1
- ASTM D2902 Type II
- ASTM D3296-03
- VW-1, UL-83 (natural)
- FDA Compliant
- USP Class VI Compliant

Applications/Markets

- Protective Cover
- UV Light Covering
- Product Testing
- Rollers

Order Information

Example: HS1.3FEP24-0CC48.000

HS1.3FEP24-0CC48.000 – **Heat Shrink**
HS**1.3**FEP24-0CC48.000 – **Shrink Ratio (1.3:1)**
HS1.3**FEP**24-0CC48.000 – **FEP**
HS1.3FEP**24**-0CC48.000 – **Heat Shrink Size** in AWG **(AWG 24) (For inch size use** inch **(3/8")**
HS1.3FEP24-**0CC**48.000 – **Black**
HS1.3FEP24-0CC**48.000** – **Package Quantity** in feet **(48")**

Colors

- ○ Natural, Translucent
- Colors available as custom run, see color code table

When ordering coiled tubing in colors, the color code is always followed by TC; when ordering cut lengths, the color code is followed by CC
i.e.,HS1.3FEP24-2TC
i.e.,HS1.3FEP24-0CC48.000

Color Code					
○	N	Natural	●	5	Green
●	0	Black	●	6	Blue
●	1	Brown	●	7	Violet
●	2	Red	●	8	Gray
●	3	Orange	○	9	White
●	4	Yellow			


Notes

- Working Temperature: 400°F (204°C)
- Shrink Temperature:
  1" Dia. and below : 410°F (210°C)
  Over 1" Dia. : 430°F (221°C)
- *Dielectric Strength: ≥ 2,000 V/M, per ASTM D 149 short term test of 10 MIL thickness (Volts/MIL)
- Heat Shrink tubing is available in stock packaging of 4-ft. straight lengths
- Minimum quantities may apply
- Custom packaging, sizes, lengths and colors are quoted upon request

For detailed ordering information, please consult price list or contact Parflex Division.

HS1.3FEP AWG Heat Shrink Tubing (1.3:1)

Part Number	Order Size AWG	Mil Spec*	Minimum Expanded I.D.		Maximum Recovered I.D.		Nominal Recovered Wall	
			inch	mm	inch	mm	inch	mm
HS1.3FEP24	24	23053/11A-101	0.031	0.79	0.027	0.69	0.008 ± 0.002	0.20 ± 0.05
HS1.3FEP22	22	23053/11A-102	0.036	0.91	0.032	0.81	0.008 ± 0.002	0.20 ± 0.05
HS1.3FEP20	20	23053/11A-103	0.045	1.14	0.039	0.99	0.008 ± 0.002	0.20 ± 0.05
HS1.3FEP18	18	23053/11A-104	0.060	1.52	0.049	1.25	0.008 ± 0.002	0.20 ± 0.05
HS1.3FEP16	16	23053/11A-105	0.075	1.90	0.061	1.55	0.009 ± 0.002	0.23 ± 0.05
HS1.3FEP14	14	23053/11A-106	0.092	2.34	0.072	1.83	0.009 ± 0.002	0.23 ± 0.05
HS1.3FEP12	12	23053/11A-107	0.115	2.92	0.089	2.26	0.009 ± 0.002	0.23 ± 0.05
HS1.3FEP10	10	23053/11A-108	0.141	3.58	0.114	2.90	0.010 ± 0.003	0.25 ± 0.08
HS1.3FEP09	9	23053/11A-109	0.158	4.01	0.124	3.15	0.010 ± 0.003	0.25 ± 0.08
HS1.3FEP08	8	23053/11A-110	0.180	4.57	0.143	3.63	0.010 ± 0.003	0.25 ± 0.08
HS1.3FEP07	7	23053/11A-111	0.197	5.00	0.158	4.01	0.011 ± 0.004	0.28 ± 0.10
HS1.3FEP06	6	23053/11A-112	0.225	5.72	0.180	4.57	0.011 ± 0.004	0.28 ± 0.10
HS1.3FEP05	5	23053/11A-113	0.248	6.30	0.198	5.03	0.011 ± 0.004	0.28 ± 0.10
HS1.3FEP04	4	23053/11A-114	0.290	7.37	0.226	5.74	0.011 ± 0.004	0.28 ± 0.10
HS1.3FEP03	3	23053/11A-115	0.310	7.87	0.249	6.32	0.011 ± 0.003	0.28 ± 0.08
HS1.3FEP02	2	23053/11A-116	0.365	9.27	0.280	7.11	0.012 ± 0.004	0.31 ± 0.10
HS1.3FEP01	1	23053/11A-117	0.400	10.2	0.311	7.90	0.012 ± 0.004	0.31 ± 0.10
HS1.3FEP00	0	23053/11A-118	0.440	11.2	0.349	8.86	0.012 ± 0.004	0.31 ± 0.10




HS1.3FEP Fractional Heat Shrink Tubing (1.3:1)

Part Number	Order Size inch	Mil Spec*	Minimum Expanded I.D.		Maximum Recovered I.D.		Nominal Recovered Wall	
			inch	mm	inch	mm	inch	mm
HS1.3FEP3/8	3/8	23053/11A-119	0.500	12.7	0.383	9.73	0.015 ± 0.004	0.38 ± 0.10
HS1.3FEP7/16	7/16	23053/11A-120	0.580	14.7	0.448	11.4	0.020 ± 0.004	0.51 ± 0.10
HS1.3FEP1/2	1/2	23053/11A-121	0.666	16.9	0.510	13.0	0.020 ± 0.004	0.51 ± 0.10
HS1.3FEP5/8	5/8	23053/11A-122	0.830	21.1	0.637	16.2	0.025 ± 0.004	0.64 ± 0.10
HS1.3FEP3/4	3/4	23053/11A-123	1.000	25.4	0.764	19.4	0.030 ± 0.004	0.76 ± 0.10
HS1.3FEP7/8	7/8	23053/11A-124	1.170	29.7	0.891	22.6	0.035 ± 0.004	0.89 ± 0.10
HS1.3FEP1.00	1	23053/11A-126	1.330	33.8	1.020	25.9	0.035 ± 0.004	0.89 ± 0.10
HS1.3FEP1.13	1-1/8	23053/11A-133	1.500	38.1	1.145	29.1	0.035 ± 0.004	0.89 ± 0.10
HS1.3FEP1.25	1-1/4	23053/11A-134	1.666	42.3	1.270	32.3	0.035 ± 0.004	0.89 ± 0.10
HS1.3FEP1.38	1-3/8	23053/11A-135	1.833	46.6	1.390	35.3	0.035 ± 0.004	0.89 ± 0.10
HS1.3FEP1.50	1-1/2	23053/11A-136	2.000	50.8	1.520	38.6	0.035 ± 0.004	0.89 ± 0.10

FEP Heat ShrinkableTubing

Series 1.67:1 HS1.6FEP



Features

- Easier to shrink than PTFE
- Chemically inert
- Low coefficient of friction
- Superior dielectric strength
- Good heat resistance
- Self extinguishing
- Non-wetting

Certifications

- AMS-DTL-23053/11A, Class 2
- ASTM 2902 Type II
- ASTM D3296-03
- VW-1, UL-83 (natural)
- FDA Compliant
- USP Class VI Compliant

Applications/Markets

- Protective Cover
- UV Light Covering
- Product Testing
- Rollers

Order Information

Example: HS1.6FEP3/32-NC48.000

HS1.6FEP3/32-NC48.000 – **Heat Shrink**
HS**1.6**FEP3/32-NC48.000 – **Shrink Ratio (1.67:1)**
HS1.6**FEP**3/32-NC48.000 – **FEP**
HS1.6FEP**3/32**-NC48.000 – **Heat Shrink Size** in inches **(3/32")**
HS1.6FEP3/32-**N**C48.000 – **Natural**
HS1.6FEP3/32-N**C**48.000 – **Cut Tubing**
HS1.6FEP3/32-NC**48.000** – **Package Quantity** in feet **(48")**

Colors

- ○ Natural, Translucent
- Colors available as custom run, see color code table

When ordering coiled tubing in colors, the color code is always followed by TC; when ordering cut lengths, the color code is followed by CC
i.e.,HS1.6FEP3/32-2TC
i.e.,HS1.6FEP3/32-0CC48.000

Color Code					
○	N	Natural	●	5	Green
●	0	Black	●	6	Blue
●	1	Brown	●	7	Violet
●	2	Red	●	8	Gray
●	3	Orange	○	9	White
●	4	Yellow			


Notes

- Working Temperature: 400°F (204°C)
- Shrink Temperature:
  1" Dia. and below: 410°F (210°C)
  Over 1" Dia.: 430°F (221°C)
- *Dielectric Strength: ≥ 2,000 V/M, per ASTM D 149 short term test of 10 MIL thickness (Volts/MIL)
- Heat Shrink tubing is available in stock packaging of 4-ft. straight lengths
- Minimum quantities may apply
- Custom packaging, sizes, lengths and colors are quoted upon request

For detailed ordering information, please consult price list or contact Parflex Division.


HS1.6FEP Fractional Heat Shrink Tubing (1.67:1)

Part Number	Order Size inch	Mil Spec*	Minimum Expanded I.D.		Maximum Recovered I.D.		Nominal Recovered Wall	
			inch	mm	inch	mm	inch	mm
HS1.6FEP3/32	3/32	23053/11A-201	0.093	2.36	0.056	1.42	0.008 ± 0.003	0.20 ± 0.08
HS1.6FEP1/8	1/8	23053/11A-202	0.125	3.18	0.075	1.90	0.010 ± 0.003	0.25 ± 0.08
HS1.6FEP3/16	3/16	23053/11A-203	0.188	4.78	0.115	2.92	0.010 ± 0.003	0.25 ± 0.08
HS1.6FEP1/4	1/4	23053/11A-204	0.250	6.35	0.150	3.81	0.010 ± 0.003	0.25 ± 0.08
HS1.6FEP3/8	3/8	23053/11A-205	0.375	9.52	0.225	5.72	0.012 ± 0.003	0.31 ± 0.08
HS1.6FEP1/2	1/2	23053/11A-206	0.500	12.7	0.300	7.62	0.015 ± 0.004	0.38 ± 0.10
HS1.6FEP3/4	3/4	23053/11A-207	0.750	19.1	0.450	11.4	0.020 ± 0.004	0.51 ± 0.10
HS1.6FEP1.00	1	23053/11A-208	1.000	25.4	0.600	15.2	0.025 ± 0.005	0.64 ± 0.13
HS1.6FEP1.50	1-1/2	23053/11A-209	1.500	38.1	0.900	22.9	0.030 ± 0.005	0.76 ± 0.13
HS1.6FEP2.00	2	23053/11A-210	2.000	50.8	1.200	30.5	0.030 ± 0.005	0.76 ± 0.13



FEP Heat Shrinkable Roll Cover

Series 1.25:1 HS1.25FEP



Features

- Extends roller life
- Eliiminates roller build up and picking
- Low coefficient of friction
- Flexible
- Good heat resistance

Certifications

- ASTM D2902 Type II
- VW-1, UL-83 (natural)

Applications/Markets



- Protective Cover
- Rollers

Order Information

Example: HS1.25FEP3.50-NC48.000

HS1.25FEP3.50-NC48.000 – **Heat Shrink**
HS**1.25**FEP3.50-NC48.000 – **Shrink Ratio (1.25:1)**
HS1.25**FEP**3.50-NC48.000 – **FEP**
HS1.25FEP**3.50**-NC48.000 – **Heat Shrink Expanded Size** inches **(3 1/2 in)**
HS1.25FEP3.50-**N**C48.000 – **Natural**
HS1.25FEP3.50-N**C**48.000 – **Cut Tubing**
HS1.25FEP3.50-NC**48.000** – **Package Quantity** in feet **(48")**

Notes

- Working Temperature: 400°F (204°C)
- Shrink Temperature:
  347°F (175°C) for 10 minutes - For high temperatures 500°F (260°C), PFA roll covers are available
- Dielectric Strength: ≥ 2,000 V/M, per ASTM D 149 short term test of 10 MIL thickness (Volts/MIL)
- Roll Cover is available in stock packaging of 4-ft. straight lengths
- Custom packaging, sizes, lengths and colors are quoted upon request
- For adhesion purposes, roll covers must be etched; Etching is available on the inside diameter, outside diameter or both
- Minimum quantities may apply

Colors

- ○ Natural, Translucent


HS1.25.1 FEP Roll Cover

Part Number	Order Size	Minimum Expanded I.D.		Maximum Recovered I.D.		Nominal Recovered Wall	
	inch	inch	mm	inch	mm	inch	mm
HS1.25FEP1/2	1/2	0.550	14.0	0.440	11.2	0.020 ± 0.004	0.508 ±0.10
HS1.25FEP5/8	5/8	0.700	17.8	0.540	13.7	0.020 ± 0.004	0.508 ±0.10
HS1.25FEP3/4	3/4	0.800	20.3	0.640	16.3	0.020 ± 0.004	0.508 ±0.10
HS1.25FEP7/8	7/8	0.950	24.1	0.760	19.3	0.020 ± 0.004	0.508 ±0.10
HS1.25FEP1.00	1	1.100	27.9	0.880	22.4	0.020 ± 0.004	0.508 ±0.10
HS1.25FEP1.25	1 1/4	1.300	33.0	1.000	25.4	0.020 ± 0.004	0.508 ±0.10
HS1.25FEP1.50	1-1/2	1.700	43.2	1.300	33.0	0.020 ± 0.004	0.508 ±0.10
HS1.25FEP2.00	2	2.100	53.3	1.700	43.2	0.020 ± 0.004	0.508 ±0.10
HS1.25FEP2.25	2-1/4	2.260	59.7	2.000	50.8	0.020 ± 0.004	0.508 ±0.10
HS1.25FEP2.50	2-1/2	2.600	66.0	2.100	53.3	0.020 ± 0.004	0.508 ±0.10
HS1.25FEP3.00	3	3.100	78.7	2.600	66.0	0.020 ± 0.004	0.508 ±0.10
HS1.25FEP3.50	3-1/2	3.500	88.9	3.100	78.7	0.020 ± 0.004	0.508 ±0.10
HS1.25FEP4.00	4	4.300	109.2	3.500	88.9	0.020 ± 0.004	0.508 ±0.10
HS1.25FEP5.00	5	5.200	132.1	4.300	109.3	0.020 ± 0.004	0.508 ±0.10
HS1.25FEP6.00	6	6.200	157.5	5.200	132.1	0.020 ± 0.004	0.508 ±0.10
HS1.25FEP7.00	7	7.200	182.9	6.200	157.5	0.020 ± 0.004	0.508 ±0.10
HS1.25FEP8.00	8	8.300	210.8	7.200	182.9	0.020 ± 0.004	0.508 ±0.10

For detailed ordering information, please consult price list or contact Parflex Division.

FEP/PTFE Heat Shrinkable Double Shrink

Series TSSS and TSSL



Features

- Double Shrink encapsulates your parts as the FEP melts during the PTFE shrinking process
- Protects cables, tubes and other objects from moisture and dirt
- Self extinguishing

Certifications

- VW-1, UL-83 (natural)

Applications/Markets

- Wire splices
- Encapsulates fittings

FEP/PTFE Double Shrink Tubing

Part Number	Minimum Expanded I.D.		Maximum Recovered I.D.		Nominal Recovered Wall	
	inch	mm	inch	mm	inch	mm
Standard Wall						
TSSS036	0.036	0.91	0.00	0.00	0.023	0.584
TSSS060	0.060	1.52	0.00	0.00	0.028	0.711
TSSS130	0.130	3.30	0.00	0.00	0.032	0.813
TSSS160	0.160	4.06	0.00	0.00	0.032	0.813
TSSS190	0.190	4.83	0.061	1.55	0.035	0.889
TSSS250	0.250	6.35	0.125	3.18	0.035	0.889
TSSS350	0.350	8.89	0.190	4.83	0.035	0.889
TSSS450	0.450	11.4	0.312	7.92	0.055	1.400
TSSS700	0.700	17.8	0.440	11.2	0.055	1.400
TSSS950	0.950	24.1	0.680	17.3	0.065	1.650
Light Wall						
TSSL065	0.065	1.65	0.00	0.00	0.015	0.381
TSSL115	0.115	2.92	0.045	1.14	0.015	0.381
TSSL130	0.130	3.30	0.060	1.52	0.015	0.381
TSSL180	0.180	4.57	0.065	1.65	0.015	0.381
TSSL190	0.190	4.83	0.070	1.78	0.015	0.381
TSSL240	0.240	6.10	0.150	3.81	0.020	0.508
TSSL350	0.350	8.89	0.210	5.33	0.025	0.635
TSSL480	0.480	12.2	0.315	8.00	0.032	0.813
TSSL700	0.700	17.8	0.500	12.7	0.040	1.020
TSSL1000	1	25.4	0.700	17.8	0.045	1.140

Order Information

Example: TSSL036-NC48.000

TSSL036-NC48.000 – **Double Shrink**
TSS**L**036-NC48.000 – **Light Wall**
TSSL**036-**NC48.000 – **Size** in inches **(0.036")**
TSSL036-**N**C48.**0**00 – **Natural**
TSSL036-N**C**48.0**0**0 – **Cut Tubing**
TSSL036-NC**48.000** – **Package Quantity** in feet **(48")**

Notes


- Working Temperature: 450°F (231°C)
- Shrink Temperature: 680°F (360°C)
- Longitudinal Change: +/- 10%
- Heat Shrink tubing is available in stock packaging of 4-ft. straight lengths
- Custom packaging, sizes, lengths and colors are quoted upon request
- Minimum quantities may apply

Colors

- ○ Natural, Translucent

FEP Convoluted Tubing

Series: CV03 and Convo-Flon™



Features

- Cuffs are sized on the I.D.
- Very flexible
- Long continuous lengths
- Translucent
- Chemically inert
- Good flexlife

Certifications/Compliance

- ASTM D3296-03
- VW-1, UL-83 (natural)

Applications/Markets



- Fluid Transport
- Vascular Graft
- Laboratory
- Robotics

Order Information

Example: CV03-1-1/2-NT

CV03-1-1/2-NT – **Convoluted Tubing**
CV**03**-1-1/2-NT – **FEP**
CV03-**1-1/2**-NT – **Tube Size** in inches **(1-1/2")**
CV03-1-1/2-**NT**– **Natural**

Notes

- Working Temperature: -100°F (-75°C) to +400°F (204°C)

Colors

- ○ Natural, Translucent

For detailed ordering information, please consult price list or contact Parflex Division.


FEP Convoluted

(Standard tubing is natural)


Part Number	Order Size	Standard Cuff I.D. "A"		Standard Cuff Length "B"		Wall Thickness "C"		Min. Inside Diameter "D"		Max. Inside Diameter "D"		Max. Outside Diameter "E"		**Min. Bend Radius	
	inch	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
CV03-1/4-NT	1/4	1/4	6.35	3/4	19.1	0.020	0.508	0.251	6.38	0.265	6.73	0.405	10.3	0.365	9
CV03-5/16-NT	5/16	5/16	7.94	1	25.4	0.023	0.584	0.273	6.93	0.281	7.14	0.424	10.8	0.500	13
CV03-3/8-NT	3/8	3/8	9.53	1	25.4	0.023	0.584	0.364	9.25	0.375	9.53	0.530	13.5	0.875	22
CV03-1/2-NT	1/2	1/2	12.7	1	25.4	0.025	0.635	0.485	12.3	0.500	12.7	0.660	16.8	0.625	16
CV03-5/8-NT	5/8	5/8	15.9	1-1/4	31.8	0.025	0.635	0.609	15.5	0.625	15.9	0.780	19.8	1.500	38
CV03-3/4-NT	3/4	3/4	19.1	1-1/2	38.1	0.025	0.635	0.730	18.5	0.750	19.1	0.975	24.8	3.500	89
CV03-1.00-NT	1	1	25.4	2	50.8	0.030	0.762	0.975	24.8	1.000	25.4	1.260	32.0	2.250	57
CV03-1.25-NT	1-1/4	1-1/4	31.8	2-1/2	63.5	0.040	1.02	1.210	30.7	1.250	31.8	1.540	39.1	2.500	64
CV03-1.50-NT	1-1/2	1-1/2	38.1	2-1/2	63.5	0.045	1.14	1.490	37.8	1.530	38.9	1.940	49.2	3.000	76
CV03-2.00-NT	2	2	50.8	2-1/2	63.5	0.045	1.14	1.990	50.5	2.020	51.3	2.370	60.2	4.250	108
CV03-2.50-NT	2-1/2	2-1/2	63.5	3	73.2	0.065	1.65	2.440	61.9	2.500	63.5	3.000	76.2	6.500	165
CV03-3.00-NT	3	3	76.2	3	73.2	0.065	1.65	2.92	74.2	3.02	76.7	3.74	95.0	7.50	191

** Minimum 36" length.

Standard Cuffs for **FEP Convo** are sized on the **I.D.**




Without Cuffs



With Cuffs

Standard Cuffs for **FEP Convo-Flon™** are sized on the **O.D.**



Without Cuffs



With Cuffs

FEP Convo-Flon™ Convoluted

(Standard tubing is natural)


Part Number	Order Size	Standard Cuff O.D. "A"		Standard Cuff Length "E"		Wall Thickness "C"		Min. Inside Diameter "B"		Max. Inside Diameter "B"		Max. Outside Diameter "A"		**Min. Bend Radius	
	inch	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
Contact Customer Service	1/4 x 3/8	1/4	6.35	3/4	19.1	0.020	0.508	0.251	6.38	0.265	6.73	0.375	9.53	0.625	16
	3/8 x 1/2	5/16	7.94	1	25.4	0.023	0.584	0.364	9.25	0.375	9.53	0.500	12.7	0.875	22
	1/2 x 5/8	3/8	9.53	1	25.4	0.025	0.635	0.480	12.2	0.500	12.7	0.625	15.9	1.250	32
	5/8 x 3/4	1	25.4	2	50.8	0.025	0.635	0.609	15.5	0.625	15.9	0.750	19.1	1.500	38
	3/4 x 7/8	1-1/4	31.8	2-1/2	63.5	0.025	0.635	0.730	18.5	0.750	19.1	0.875	22.2	1.750	44
	.800 x 1	1-1/2	38.1	2-1/2	63.5	0.030	0.762	0.800	20.3	0.820	2.80	1.000	25.4	2.250	57
	1-1/4 1-1/2	Contact Customer Service for actual dimensions.													

** Minimum 36" length.

For detailed ordering information, please consult price list or contact Parflex Division.

FEP Convoluted

Series SAE AS81914/3 and SAE AS81914/4



Features

- Longer lengths than PTFE
- Excellent clarity
- Chemically inert
- Low coefficient of friction
- Superior dielectric strength
- Good heat resistance
- Self extinguishing
- Non-wetting

Applications/Markets



- Fluid Handling
- Harnesses
- Lab Equipment
- Robotics

Certifications

- SAE AS81914/3
- SAE AS81914/4
- ASTM D3296-03
- FDA Compliant
- USP Class VI Compliant
- VW-1, UL-83 (natural)

Order Information

Example: 81914/3-1001-NT

81914/3-1001-NT – **SAE AS81914 Convoluted**
81914/**3**-1001-NT – **FEP**
81914/3-**10**01-NT – **Helical Convolutions**
81914/3-10**01**-NT – **Size (01=0.187")**
81914/3-1001-**N**T – **Color (N=Natural)**
81914/3-1001-N**T** – **"T" is bulk** (for cut tubing remove "T", add length, ie. 81914/3-1001-N1200 = 187" Convo, natural, cut 12" long)

Notes

- Working Temperature: 392°F (200°C)
- Tubing is provided in natural without cuffs direct from inventory
- Stock packaging is random coils
- Also availabe in close convolution 81914/4
- Minimum quantities may apply
- Custom packaging, sizes, lengths,cuffs and colors are quoted upon request

Colors

- ○ Natural, Translucent
- Colors available as custom run, see color code table

When ordering convoluted tubing in colors, the "N" designation for natural should be replaced by the correct color designator;

i.e.,81914/3-1001-0T (black bulk tubing)
i.e.,81914/3-1001-01200 (black tubing - 12 inches long)

Color Code					
○	N	Natural	●	5	Green
●	0	Black	●	6	Blue
●	1	Brown	●	7	Violet
●	2	Red	●	8	Gray
●	3	Orange	○	9	White
●	4	Yellow			

For detailed ordering information, please consult price list or contact Parflex Division.


FEP Convoluted Tubing (SAE AS81914/3)

(Standard tubing is natural)

Part Number	MIL Spec	Maximum Inside Diameter		Minimum Inside Diameter		Maximum Outside Diameter		Maximum Wall Thickness		Minimum Bend Radius		Pitch	Weight	
		inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	±1	lb./100 ft.	kg./100 mtr.
81914/3-1001-NT	-01	0.187	4.75	0.181	4.60	0.320	8.13	0.018	0.457	1/2	13	8	1.5	2.23
81914/3-1002-NT	-02	0.281	7.14	0.273	6.93	0.414	10.5	0.018	0.457	3/4	19	8	1.7	2.53
81914/3-1003-NT	-03	0.312	7.93	0.306	7.77	0.450	11.4	0.018	0.457	3/4	19	8	1.9	2.83
81914/3-1004-NT	-04	0.375	9.53	0.364	9.25	0.510	13.0	0.018	0.457	7/8	22	8	2.2	3.27
81914/3-1005-NT	-05	0.437	11.1	0.427	10.9	0.571	14.5	0.018	0.457	7/8	22	8	3.1	4.61
81914/3-1006-NT	-06	0.500	12.7	0.485	12.3	0.650	16.5	0.023	0.584	1-1/4	32	7	4.0	5.95
81914/3-1007-NT	-07	0.625	15.9	0.608	15.4	0.770	19.6	0.023	0.584	1-1/2	38	7	4.8	7.14
81914/3-1008-NT	-08	0.750	19.1	0.730	18.5	0.930	23.6	0.023	0.584	1-3/4	44	6	6.1	9.07
81914/3-1009-NT	-09	0.875	22.2	0.860	21.8	1.073	27.3	0.023	0.584	2	51	5	7.0	10.4
81914/3-1010-NT	-10	1.000	25.4	0.975	24.8	1.226	31.1	0.023	0.584	2.370	60	5	8.5	12.7
81914/3-1011-NT	-11	1.125	28.6	1.105	28.1	1.390	35.3	0.023	0.584	2.370	60	5	9.3	13.8
81914/3-1012-NT	-12	1.250	31.8	1.210	30.7	1.539	39.1	0.023	0.584	2-3/4	70	4	10.9	16.2
81914/3-1013-NT	-13	1.500	38.1	1.437	36.5	1.832	46.5	0.023	0.584	3.380	86	4	12.6	18.8
81914/3-1014-NT	-14	1.750	44.5	1.688	42.9	2.082	52.9	0.023	0.584	3.880	98	4	14.8	22.0
81914/3-1015-NT	-15	2.000	50.8	1.937	49.2	2.332	59.2	0.023	0.584	4.250	108	4	16.8	25.0

FEP convoluted tubing is provided in NATURAL without cuffs direct from the factory. Natural part numbers are designated with “NT” after the Mil Spec number (i.e.,81914/3-1014-NT).

Standard Cuffs for **81914/3** are sized on the **I.D.**



Without Cuffs



With Cuffs

FEP/PFA Corrugated

Extra Flexible Fluoropolymer Tubing, Series CR03



Features

- Capable of turning sharp corners without reducing the inside diameter of the tube
- Extremely flexible
- Kink resistant
- Non stick surface allows for easy cleaning
- Excellent clarity
- Chemically inert
- Available in FEP, PFA and High Purity PFA

Applications/Markets



- Vacuum Applications
- Robotics
- Instrumentation
- DNA Sequencer
- Fluid Transfer
- Pharmaceutical
- Wet Bench

Certifications

- FEP - ASTM D3296-03
- PFA - ASTM D3307-10
- FDA Compliant
- USP Class VI Compliant
- VW-1, UL-83 (natural)

Order Information

Example: CR03-3/4-NT

CR03-3/4-NT – **Corrugated Tubing**

CR**03**-3/4-NT – **FEP**

CR03-**3/4**-NT – T**ube I.D. when cuffed** in inches **(3/4")**

CR03-3/4-**N**T – **Color (N=Natural)**

CR03-3/4-N**T** – **"T" is bulk - for cuffed tubing add length, ie. CR03-3/4-N1200 = 1" Corr, natural, cut 12" long**

Colors

- ○ Natural, Translucent


Notes

- Working Temperature: 200°F (93°C) @ 0 pressure - For higher temperatures, request PFA Corrugated 300°F (148°C) @ 0 pressure
- Vacuum Service: 29.9 IN. Hg (759M Hg)
- Extension-Compression Length Ratio: Approximately 2:1
- Tubing is provided in natural without cuffs direct from inventory or with cuffs, as requested at time of order
- Stock packaging is random coils
- Minimum quantities may apply
- Corrugated tubing is also available in specialty configurations where corrugated and straight tubing run intermittently along the tube
- Custom packaging, sizes, lengths and colors are quoted upon request

For detailed ordering information, please consult price list or contact Parflex Division.


FEP Tex-Flex® Corrugated

Part Number	Size To Order	Maximum Cuff I.D. "A"		Standard Cuff Length "B"		Wall Thickness "C"		Ref. Outside Diameter "D"		Corrugated Length "E"	Minimum Bend Radius	
		inch	mm	inch	mm	inch	mm	inch	mm	±1	inch	mm
CR03-1/4-NT	1/4	0.250	6.35	3/4	19.1	0.015	0.38	0.375	9.53	To be specified at time of order	0.125	3.18
CR03-3/8-NT	3/8	0.375	9.53	1	25.4	0.020	0.51	0.625	15.9		0.187	4.76
CR03-1/2-NT	1/2	0.500	12.7	1	25.4	0.025	0.64	0.750	19.0		0.250	6.35
CR03-5/8-NT	5/8	0.625	15.9	1	25.4	0.025	0.64	0.938	23.8		0.312	7.94
CR03-3/4-NT	3/4	0.750	19.1	1-1/2	38.1	0.030	0.76	1.063	26.9		0.375	9.53
CR03-7/8-NT	7/8	0.875	22.2	1-1/2	38.1	0.030	0.76	1.250	31.8		0.438	11.1
CR03-1.00-NT	1	1.000	24.8	2	50.8	0.035	0.89	1.438	36.5		0.500	12.7
CR03-1.25-NT	1-1/4	1.250	31.8	2	50.8	0.035	0.89	1.625	41.3		0.625	15.9
CR03-1.50-NT	1-1/2	1.500	38.1	2	50.8	0.035	0.89	1.813	46.1		0.750	19.1
CR03-2.00-NT	2	2.000	50.8	2	50.8	0.040	1.02	2.625	66.7		1.000	25.4
CR03-2.50-NT	2-1/2	2.5000	63.8	2-1/2	63.5	0.070	1.78	3.360	85.3		2.500	63.5



Retractable Coiled Tubing

Single or Dual Containment, Series 703, 704, 705



Features

- Extremely flexible
- Excellent clarity
- Chemically inert
- Low coefficient of friction
- Self extinguishing
- Non-wetting
- Available in FEP, PFA and High Purity PFA

Certifications

- FEP - ASTM D3296-03
- PFA - ASTM D3307-10
- FDA Compliant
- USP Class VI Compliant
- VW-1, UL-83 (natural)

Applications/Markets



- Fluid Handling
- Wet Bench
- Lab Equipment
- Gas Dispensing
- Medical

Order Information

Example: 704-0312062-xx0012

704-0312062-xx0012 – **Retractable tubing**
704-**0312**062-xx0012 – **Tube O.D.** in inches **(3/16")**
704-0312**062-**xx0012 – **Wall (0.062")**
704-0312062-**xx**0012 – **Custom Options** (when needed)
704-0312062-xx**0012** – **Length 12"**

Colors

- ○ Natural, Translucent

Notes

- Working Temperature: 200°F (93°C) @ 0 pressure - For higher temperatures, request PFA 300°F (148°C) @ 0 pressure; above these temperatures, the coils dimensions are not stable and the coils will lose their shape
- Wall thickness of tubing .062"/1.57mm
- "X" denotes resin type - Replace "X" with 3 for FEP, 4 for PFA and 5 for HP PFA
- "xx" denotes custom options - Use when needed
- Standard left/right tail length is 6 inches
- Minimum quantities may apply
- Custom packaging, sizes, lengths and colors are quoted upon request

Fittings

Fittings available for sizes 3/16" up to 1/2"

Parker Fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 692-6634 FAX


FSC Product Families:

- Compression
- Compress-Align®
- TrueSeal™

For detailed ordering information, please consult price list or contact Parflex Division.

Retractable Tubing

Part Number	Size To Order O.D. x I.D.	Coil Inside Diameter		Retracted Length "A"		Extended Length	
		inch	mm	inch	mm	inch	mm
70X-0188062-xx0003	3/16" x 1/16"	0.750	19.1	3	76	12	305
70X-0188062-xx0006	3/16" x 1/16"	0.750	19.1	6	152	24	610
70X-0188062-xx0012	3/16" x 1/16"	0.750	19.1	12	305	48	1219
70X-0188062-xx0018	3/16" x 1/16"	0.750	19.1	18	457	72	1829
70X-0250062-xx0003	1/4" x 1/8"	1	25.4	3	76	12	305
70X-0250062-xx0006	1/4" x 1/8"	1	25.4	6	152	24	610
70X-0250062-xx0012	1/4" x 1/8"	1	25.4	12	305	48	1219
70X-0250062-xx0018	1/4" x 1/8"	1	25.4	18	457	72	1829
70X-0312062-xx0003	5/16" x 3/16"	1.625	41.3	3	76	12	305
70X-0312062-xx0006	5/16" x 3/16"	1.625	41.3	6	152	24	610
70X-0312062-xx0012	5/16" x 3/16"	1.625	41.3	12	305	48	1219
70X-0312062-xx0018	5/16" x 3/16"	1.625	41.3	18	457	72	1829
70X-0375062-xx0003	3/8" x 1/4"	1.625	41.3	3	76	12	305
70X-0375062-xx0006	3/8" x 1/4"	1.625	41.3	6	152	24	610
70X-0375062-xx0012	3/8" x 1/4"	1.625	41.3	12	305	48	1219
70X-0375062-xx0018	3/8" x 1/4"	1.625	41.3	18	457	72	1829
70X-0438062-xx0003	7/16" x 5/16"	3	76.2	3	76	12	305
70X-0438062-xx0006	7/16" x 5/16"	3	76.2	6	152	24	610
70X-0438062-xx0012	7/16" x 5/16"	3	76.2	12	305	48	1219
70X-0500062-xx0003	1/2" x 3/8"	3	76.2	3	76	12	305
70X-0500062-xx0006	1/2" x 3/8"	3	76.2	6	152	24	610
70X-0500062-xx0012	1/2" x 3/8"	3	76.2	12	305	48	1219






For detailed ordering information, please consult price list or contact Parflex Division.

PFA Tubing

Series Fractional & Metric: 104, 204



Features

- Virgin Perfluoroalkoxy
- Translucent
- High purity resins available
- Low permeability
- Exceptional heat resistance
- Chemically inert
- Long continuous lengths
- Low coefficient of friction
- Self extinguishing
- Non-wetting
- Non leaching

Certifications/Compliance

- ASTM D3307-10
- VW-1, UL-83 (natural)
- FDA Compliant
- USP Class VI Compliant

Applications/Markets



- Air Sampling
- Gas Sampling
- Fluid Transfer
- Laboratory
- Wet Bench
- Flow Monitoring
- Steam Plant

Order Information

Example: 104-0188062-NT-100

104-0188062-NT-100 – **Fractional**

104-0188062-NT-100 – **PFA**

104-**0188**062-NT-100 – **Tube O.D.** in inches **(3/16")**

104-0188**062**-NT-100 – **Tube Wall Thickness** in inches **(.062")**

104-0188062-**NT**-100 – **Natural**

104-0188062-NT-**100** – **Package Quantity** in feet **(100')**

Fittings

Fittings available for sizes 3/32" up to 1"

Parker Fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 692-6634 FAX

FSC Product Families:

- Compression
- Compress-Align®
- Metric Compression
- TrueSeal

Notes

- Working Temperature: -100°F (-75°C) to +500°F (260°C)
- Working pressure calculated using a Design Factor of 4 at 73°F (23°C)
- Custom packaging and sizes are quoted upon request
- Package quantities are not continuous

Options

- Smoothbore
- Convoluted
- Corrugated
- Retractable Coils
- Heat Shrink

Colors

- ○ Natural, Translucent
- Colors available as custom run, see color code table

Color Code					
○	N	Natural	●	5	Green
●	0	Black	●	6	Blue
●	1	Brown	●	7	Violet
●	2	Red	●	8	Gray
●	3	Orange	○	9	White
●	4	Yellow			

For detailed ordering information, please consult price list or contact Parflex Division.

104 PFA Industrial Wall Fractional Size Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure		Burst Pressure		Min. Bend Radius		Vac. Rating	Weight	
#																			lbs	kgs
	inch	inch	tol.	mm	tol.	inch	tol.	mm	tol.	inch	mm	psi 73°F	bar 23°C	psi 73°F	bar 23°C	inch	mm	at 73°F	lb. per ft.	kg. per m.
104-0094031	3/32	0.094	± 0.004	2.40	± 0.102	0.031	± 0.002	0.79	± 0.051	0.031	0.79	680	47	2720	188	0.250	6	28	0.006	0.009
104-0125031	1/8	0.125	± 0.004	3.18	± 0.102	0.064	± 0.004	1.63	± 0.102	0.031	0.79	500	34	2000	138	0.375	10	28	0.009	0.013
104-0156031	5/32	0.157	± 0.005	3.99	± 0.127	0.094	± 0.003	2.39	± 0.076	0.031	0.79	390	27	1560	108	0.625	16	28	0.011	0.017
104-0188031	3/16	0.188	± 0.005	4.78	± 0.127	0.125	± 0.005	3.18	± 0.127	0.031	0.79	320	22	1280	88	0.625	16	28	0.014	0.021
104-0250031	1/4	0.250	± 0.005	6.35	± 0.127	0.188	± 0.005	4.78	± 0.127	0.031	0.79	230	16	920	63	0.875	22	28	0.020	0.030
104-0312031	5/16	0.312	± 0.005	7.92	± 0.127	0.250	± 0.005	6.35	± 0.127	0.031	0.79	180	12	720	50	1.750	44	28	0.025	0.038
104-0375031	3/8	0.375	± 0.005	9.52	± 0.127	0.312	± 0.005	7.92	± 0.127	0.031	0.79	140	10	560	39	3.250	83	28	0.031	0.047
104-0438031	7/16	0.438	± 0.005	11.13	± 0.127	0.375	± 0.005	9.53	± 0.127	0.031	0.79	120	8	480	33	3.250	83	28	0.037	0.055
104-0500031	1/2	0.500	± 0.005	12.70	± 0.127	0.438	± 0.005	11.13	± 0.127	0.031	0.79	100	7	400	28	4.750	121	28	0.043	0.063
104-0563031	9/16	0.563	± 0.006	14.30	± 0.152	0.500	± 0.006	12.70	± 0.152	0.031	0.79	80	6	320	22	5.000	127	28	0.048	0.072

104 PFA Heavy Wall Fractional Size Tubing


Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure		Burst Pressure		Min. Bend Radius		Vac. Rating	Weight	
#																			lbs	kgs
	inch	inch	tol.	mm	tol.	inch	tol.	mm	tol.	inch	mm	psi 73°F	bar 23°C	psi 73°F	bar 23°C	inch	mm	at 73°F	lb. per ft.	kg. per m.
104-0188062	3/16	0.188	± 0.005	4.78	± 0.127	0.062	± 0.005	1.57	± 0.127	0.062	1.57	680	47	2720	188	0.500	13	28	0.023	0.034
104-0250040	1/4	0.250	± 0.005	6.35	± 0.127	0.170	± 0.005	4.32	± 0.127	0.040	1.02	300	21	1200	83	0.875	22	28	0.025	0.037
104-0250047	1/4	0.250	± 0.005	6.35	± 0.127	0.156	± 0.005	3.96	± 0.127	0.047	1.19	370	26	1480	102	1.000	25	28	0.028	0.042
104-0250062	1/4	0.250	± 0.005	6.35	± 0.127	0.125	± 0.005	3.18	± 0.127	0.062	1.57	500	34	2000	138	0.500	13	28	0.034	0.051
104-0312062	5/16	0.312	± 0.005	7.92	± 0.127	0.188	± 0.005	4.78	± 0.127	0.062	1.57	390	27	1560	108	0.750	19	28	0.045	0.068
104-0375062	3/8	0.375	± 0.005	9.52	± 0.127	0.250	± 0.005	6.35	± 0.127	0.062	1.57	320	22	1280	88	1.250	32	28	0.057	0.085
104-0438062	7/16	0.438	± 0.005	11.13	± 0.127	0.312	± 0.005	7.92	± 0.127	0.062	1.57	270	19	1080	74	2.625	67	28	0.068	0.102
104-0500062	1/2	0.500	± 0.005	12.70	± 0.127	0.375	± 0.005	9.53	± 0.127	0.062	1.57	230	16	920	63	3.000	76	28	0.079	0.119
104-0750062	3/4	0.750	± 0.006	19.05	± 0.152	0.625	± 0.006	15.88	± 0.152	0.062	1.57	140	10	560	39	6.000	152	28	0.125	0.186
104-1000062	1	1.000	± 0.010	25.40	± 0.254	0.875	± 0.010	22.22	± 0.254	0.062	1.57	100	7	400	28	8.000	203	28	0.170	0.254

204 Metric PFA Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure		Burst Pressure		Min. Bend Radius		Vac. Rating	Weight	
#																			kgs	lbs
	mm	mm	tol.	inch	tol.	mm	tol.	inch	tol.	mm	inch	bar 23°C	psi 73°F	bar 23°C	psi 73°F	mm	inch	at 73°F	kg. per m.	lb. per ft.
204-0400100	4	4	± 0.11	.157	± 0.004	2	± 0.11	.079	0.250	1	0.039	34	500	138	2000	6	0.250	28	0.020	0.014
204-0600100	6	6	± 0.11	.236	± 0.004	4	± 0.11	.157	± 0.004	1	0.039	22	320	88	1280	25	1.000	28	0.034	0.023
204-0800100	8	8	± 0.11	.315	± 0.004	6	± 0.11	.236	± 0.004	1	0.039	16	230	63	920	51	2.000	28	0.047	0.032
204-1000100	10	10	± 0.11	.393	± 0.004	8	± 0.11	.315	± 0.004	1	0.039	12	180	50	720	70	2.750	28	0.061	0.041
204-1200100	12	12	± 0.15	.472	± 0.006	10	± 0.15	.393	± 0.006	1	0.039	10	140	39	560	89	3.500	28	0.074	0.050

High Purity PFA Tubing

Series Fractional & Metric: 105, 205



Features

- Withstands corrosive surfactants for longer periods of time
- Highest molecular weight available
- Lowest level of extractables
- Low permeability
- Exceptional heat resistance
- Chemically inert
- Long continuous lengths
- Low coefficient of friction
- Self extinguishing
- Non leaching

Certifications/Compliance

- ASTM D3307-10
- VW-1, UL-83 (natural)
- FDA Compliant
- USP Class VI Compliant

Applications/Markets



- Flow Monitoring
- Gas Transfer
- Food
- Wet Bench
- DI Water Dispensers
- DI Recirculators
- Heat Exchangers
- Pure Chemical Dispensers
- High Purity Applications

Order Information

Example: 105-0375031-NT-100

105-0375031-NT-100 – **Fractional**

105-0375031-NT-100 – **High Purity PFA**

105-**0375**031-NT-100 – **Tube O.D.** in millimeters **(3/8")**

105-0375**031**-NT-100 – **Tube Wall Thickness** in millimeters **(.031")**

105-0375031-**NT**-100 – **Natural**

105-0375031-NT-**100** – **Package Quantity** in feet **(100')**

Notes

- Working Temperature: -100°F (-75°C) to +500°F (260°C)
- Working pressure calculated using a Design Factor of 4 at 73°F (23°C)
- Custom packaging and sizes are quoted upon request
- Package quantities are not continuous

Options

- Smoothbore
- Convoluted
- Corrugated
- Retractable Coils

Colors

○ Natural, Translucent

Fittings

Fittings available for sizes 4mm up to 12mm

Parker Fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 692-6634 FAX

FSC Product Families:

- Compression
- Compress-Align®
- Metric Compression
- TrueSeal

For detailed ordering information, please consult price list or contact Parflex Division.

105 High Purity PFA Industrial Wall Fractional Size Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure		Burst Pressure		Min. Bend Radius		Vac. Rating	Weight	
#																				
	inch	inch	tol.	mm	tol.	inch	tol.	mm	tol.	inch	mm	psi 73°F	bar 23°C	psi 73°F	bar 23°C	inch	mm	at 73°F	lb. per ft.	kg. per m.
105-0125031	1/8	0.125	± 0.004	3.18	± 0.102	0.064	± 0.004	1.63	± 0.102	0.031	0.79	500	34	2000	138	0.500	13	28	0.009	0.013
105-0188031	3/16	0.188	± 0.005	4.78	± 0.127	0.125	± 0.005	3.18	± 0.127	0.031	0.79	320	22	1280	88	0.750	19	28	0.014	0.021
105-0250031	1/4	0.250	± 0.005	6.35	± 0.127	0.188	± 0.005	4.78	± 0.127	0.031	0.79	230	16	920	63	1.000	25	28	0.020	0.030
105-0375031	3/8	0.375	± 0.005	9.52	± 0.127	0.312	± 0.005	7.92	± 0.127	0.031	0.79	140	10	560	39	3.500	89	28	0.031	0.047

105 High Purity PFA Heavy Wall Fractional Size Tubing


Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure		Burst Pressure		Min. Bend Radius		Vac. Rating	Weight	
#																				
	inch	inch	tol.	mm	tol.	inch	tol.	mm	tol.	inch	mm	psi 73°F	bar 23°C	psi 73°F	bar 23°C	inch	mm	at 73°F	lb. per ft.	kg. per m.
105-0250040	1/4	0.250	± 0.005	6.35	± 0.127	0.170	± 0.005	4.32	± 0.127	0.040	1.02	300	21	1200	83	0.938	24	28	0.025	0.037
105-0250047	1/4	0.250	± 0.005	6.35	± 0.127	0.156	± 0.005	3.96	± 0.127	0.047	1.19	370	26	1480	102	0.500	13	28	0.028	0.042
105-0250062	1/4	0.250	± 0.005	6.35	± 0.127	0.125	± 0.005	3.18	± 0.127	0.062	1.57	500	34	2000	138	0.625	16	28	0.034	0.051
105-0375062	3/8	0.375	± 0.005	9.52	± 0.127	0.250	± 0.005	6.35	± 0.127	0.062	1.57	320	22	1280	88	1.125	29	28	0.057	0.085
105-0500062	1/2	0.500	± 0.005	12.70	± 0.127	0.375	± 0.005	9.53	± 0.127	0.062	1.57	230	16	920	63	2.250	57	28	0.079	0.119
105-0750062	3/4	0.750	± 0.006	19.05	± 0.152	0.625	± 0.006	15.88	± 0.152	0.062	1.57	140	10	560	39	4.250	108	28	0.125	0.186
105-1000062	1	1.000	± 0.010	25.40	± 0.254	0.875	± 0.010	22.22	± 0.254	0.062	1.57	100	7	400	28	8.000	203	*	0.170	0.254

205 Metric High PFA Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure		Burst Pressure		Min. Bend Radius		Vac. Rating	Weight	
#																				
	mm	mm	tol.	inch	tol.	mm	tol.	inch	tol.	mm	inch	bar 23°C	psi 73°F	bar 23°C	psi 73°F	mm	inch	at 73°F	kg. per m.	lb. per ft.
205-0300100	3	3	± 0.11	0.118	± 0.004	1	± 0.11	0.039	± 0.004	1	0.039	47	680	188	2720	13	0.500	28	0.014	0.009
205-0400100	4	4	± 0.11	0.157	± 0.004	2	± 0.11	0.079	± 0.004	1	0.039	34	500	138	2000	13	0.500	28	0.020	0.020
205-0600100	6	6	± 0.11	0.236	± 0.004	4	± 0.11	0.157	± 0.004	1	0.039	22	320	88	1280	22	0.875	28	0.034	0.023
205-0800100	8	8	± 0.11	0.315	± 0.004	6	± 0.11	0.236	± 0.004	1	0.039	16	230	63	920	35	1.375	28	0.047	0.032
205-1000100	10	10	± 0.11	0.393	± 0.004	8	± 0.11	0.315	± 0.004	1	0.039	12	180	50	720	51	2.000	28	0.061	0.041
205-1200100	12	12	± 0.15	0.472	± 0.006	10	± 0.15	0.394	± 0.006	1	0.039	10	140	39	560	89	3.500	28	0.074	0.050

PVDF Tubing Polyvinylidene Fluoride

Series PVDF Flex™: 110, Series PVDF Super-Flex™: 111



Features

- Low extractable levels
- High mechanical strength
- Good chemical resistance
- High abrasion resistance
- Exceptional thermal stability
- Low permeability
- Self extinguishing
- Weather resistant

Certifications

- ASTM D3222
- FDA Compliant

Applications/Markets



- Applications with long cycle life
- Gas
- Food
- Thermal cycling
- Outdoor/extreme conditions
- Water systems
- Ground water monitoring
- Fluid and handling

Order Information

Example: 110-0312062-NT-100

110-0312062-NT-100 – **PVDF Flex**
110-**0312**062-NT-100 – **Tube O.D.** in inches **(5/16")**
110-0312**062**-NT-100 – **Tube Wall Thickness** in inches **(.062")**
110-0312062-**N**T-100 – **Natural**
110-0312062-N**T**-100 – **Bulk Tubing**
110-0312062-NT-**100** – **Package Quantity** in feet **(100')**

Notes

- Working Temperature: -80°F (-62°C) to +265°F (130°C)
- Working pressure calculated using a Design Factor of 4 at 73°F (23°C)
- Custom packaging and sizes are quoted upon request

Colors

- ○ Off-white

Fittings

Fittings available for sizes 1/8" up to 1"

Parker Fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 692-6634 FAX

FSC Product Families:

- Compression
- Compress-Align®
- Metric Compression
- TrueSeal

Color Code					
○	N	Natural	●	5	Green
●	0	Black	●	6	Blue
●	1	Brown	●	7	Violet
●	2	Red	●	8	Gray
●	3	Orange	○	9	White
●	4	Yellow			

For detailed ordering information, please consult price list or contact Parflex Division.

110 PVDF Flex™ Industrial Wall Fractional Size Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure		Burst Pressure		Min. Bend Radius		Vac. Rating	Weight	
#																				
	inch	inch	tol.	mm	tol.	inch	tol.	mm	tol.	inch	mm	psi 73°F	bar 23°C	psi 73°F	bar 23°C	inch	mm	at 73°F	lb. per ft.	kg. per m.
110-0125031	1/8	0.125	± 0.005	3.18	± 0.13	0.062	± 0.005	1.57	± 0.13	0.031	0.79	267	18.4	1068	73.6	0.500	13	28	0.007	0.011
110-0188031	3/16	0.188	± 0.005	4.78	± 0.13	0.125	± 0.005	3.18	± 0.13	0.031	0.79	180	12.4	720	49.6	0.750	19	28	0.012	0.018
110-0250031	1/4	0.250	± 0.005	6.35	± 0.13	0.188	± 0.005	4.78	± 0.13	0.031	0.79	170	11.7	680	46.8	1.000	25	28	0.016	0.025
110-0375031	3/8	0.375	± 0.005	9.52	± 0.13	0.312	± 0.005	7.92	± 0.13	0.031	0.79	93	6.4	372	25.6	2.500	64	28	0.026	0.039
110-0500031	1/2	0.500	± 0.005	12.70	± 0.13	0.438	± 0.005	11.13	± 0.13	0.031	0.79	83	5.7	332	22.9	4.000	102	28	0.035	0.053

110 PVDF Flex™ Heavy Wall Fractional Size Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure		Burst Pressure		Min. Bend Radius		Vac. Rating	Weight	
#																				
	inch	inch	tol.	mm	tol.	inch	tol.	mm	tol.	inch	mm	psi 73°F	bar 23°C	psi 73°F	bar 23°C	inch	mm	at 73°F	lb. per ft.	kg. per m.
110-0250047	1/4	0.250	± 0.005	6.35	± 0.13	0.156	± 0.005	3.96	± 0.13	.047	1.19	208	14.3	832	57.4	0.750	19	28	0.023	0.034
110-0250062	1/4	0.250	± 0.005	6.35	± 0.13	0.125	± 0.005	3.18	± 0.13	.062	1.57	330	22.8	1320	91.0	0.500	13	28	0.028	0.042
110-0312062	5/16	0.312	± 0.005	7.92	± 0.13	0.188	± 0.005	4.78	± 0.13	.062	1.57	219	15.1	876	60.4	0.875	22	28	0.038	0.056
110-0375062	3/8	0.375	± 0.005	9.52	± 0.13	0.250	± 0.005	6.35	± 0.13	.062	1.57	224	15.4	896	61.8	1.000	25	28	0.047	0.070
110-0500062	1/2	0.500	± 0.005	12.70	± 0.13	0.370	± 0.005	9.40	± 0.13	.062	1.57	169	11.7	676	46.6	2.000	51	28	0.066	0.098
110-0625062	5/8	0.625	± 0.005	15.88	± 0.13	0.500	± 0.005	12.70	± 0.13	.062	1.57	136	9.3	544	37.5	3.000	76	28	0.085	0.126
110-0750062	3/4	0.750	± 0.006	19.05	± 0.15	0.625	± 0.006	15.88	± 0.15	.062	1.57	114	7.9	456	31.4	6.000	152	28	0.103	0.154
110-1000062	1	1.000	± 0.010	25.40	± 0.25	0.875	± 0.008	22.22	± 0.25	.062	1.57	86	5.9	344	23.7	8.000	203	28	0.141	0.210

111 PVDF Super-Flex™ Industrial Wall Fractional Size Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure		Burst Pressure		Min. Bend Radius		Vac. Rating	Weight	
#																				
	inch	inch	tol.	mm	tol.	inch	tol.	mm	tol.	inch	mm	psi 73°F	bar 23°C	psi 73°F	bar 23°C	inch	mm	at 73°F	lb. per ft.	kg. per m.
111-0188031	3/16	0.188	± 0.005	4.78	± 0.13	0.125	± 0.005	3.18	± 0.13	0.031	0.79	180	12.4	720	50	0.750	19	28	0.012	0.018
111-0250031	1/4	0.250	± 0.005	6.35	± 0.13	0.188	± 0.005	4.78	± 0.13	0.031	0.79	170	11.7	680	47	0.750	19	28	0.016	0.025
111-0375031	3/8	0.375	± 0.005	9.53	± 0.13	0.312	± 0.005	7.92	± 0.13	0.031	0.79	93	6.4	372	26	2.500	64	28	0.026	0.039

111 PVDF Super-Flex™ Heavy Wall Fractional Size Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure		Burst Pressure		Min. Bend Radius		Vac. Rating	Weight	
#																				
	inch	inch	tol.	mm	tol.	inch	tol.	mm	tol.	inch	mm	psi 73°F	bar 23°C	psi 73°F	bar 23°C	inch	mm	at 73°F	lb. per ft.	kg. per m.
111-0250062	1/4	0.250	± 0.005	6.35	± 0.13	0.125	± 0.005	3.18	± 0.13	0.062	1.57	330	22.8	1320	91	0.375	10	28	0.028	0.042
111-0375062	3/8	0.375	± 0.005	9.52	± 0.13	0.250	± 0.005	6.35	± 0.13	0.062	1.57	224	15.4	896	62	0.750	19	28	0.038	0.056
111-0500062	1/2	0.500	± 0.005	12.7	± 0.13	0.375	± 0.005	9.52	± 0.13	0.062	1.57	169	11.7	676	47	1.500	38	28	0.066	0.098

For detailed ordering information, please consult price list or contact Parflex Division.

Notes

Air Hose and Fittings

Fast-Stor®

NoMar® Fast-Stor®

Ultra-Lite Superbraid®



Table of Contents

Hose & Tubing

Introduction C-4

Fast-Stor® Air Hose ..... C-8 : C-9
- Fast-Stor® Air Hose Assemblies, A0 ..... C-8
- Bulk Air Hose, FS C-9

NoMar® Fast-Stor® Urethane Coiled Assemblies, AUFS ..... C-14 : C-15

NoMar® Fast-Stor® High Durometer Urethane Coiled Assemblies, AHUFS C-17

NoMar® Fast-Stor® Coils, UFS C-16

Ultra-Lite Superbraid® Hose ..... C-20 : C-21

Fittings

Fast-Stor® Fittings ..... C-10 : C-12

Fast-Stor® Replacement Parts ..... C-12 : C-13

NoMar® Fast-Stor® Fittings ..... C-18 : C-19

Technical

Assembly Instructions NoMar® Fast-Stor® Fittings C-19

Assembly Instructions Fast-Stor® Hose C-13

Measuring Fast-Stor® Bulk Hose ..... C-6 : C-7

Size Selection Procedure C-5

Coiled Air Hose Visual Index

Fast-Stor® Coiled Air Hose Assembly

Air Hose Assembly



C-8

Fast-Stor® Coiled Air Hose (Bulk)

Air Hose Bulk



C-9

Fast-Stor® Fittings & Replacement Parts

MC Male Connector



C-10

ME Male Elbow



C-10

ML Live Male Pipe Swivel



C-11

FC Female Connector




C-11

FL Female Pipe Swivel

C-11

UC Union Connector



C-12

FN Brass Nut



C-12

FR Plastic Ferrule



C-12

SG Steel Spring Guard



C-13

TS Tube Support



C-13

NoMar® Fast-Stor® Assemblies & Coils

AUFS Assemblies



C-14 : C-15


UFS Coils



C-16


NoMar® Fast-Stor® Fittings

MCB Male Pipe Rigid



C-18

MLB Male Pipe Swivel



C-19

Ultra-Lite Superbraid Air Hose

Assemblies



C-20 : C-21

AHUFS Coils

AHUFS Assemblies



C-17

Air Hose

Every hydraulic, pneumatic and lubrication system requires some form of tube line fabrication and fitting installation for completion. Proper fabrication and installation are essential for the overall efficiency, leak free performance, and general appearance of any system.

Start by planning ahead. After sizing the tube lines and selecting the appropriate style of fitting, consider the following in the design of your system:

- Accessibility of joints
- Proper routing of lines
- Adequate tube line supports
- Available fabricating tools

Routing of Lines

Routing of lines is probably the most difficult, yet most significant, of these system design considerations. Proper routing involves getting a connecting line from one point to another through the most logical path.

Always try to leave fitting joints as accessible as possible. Hard to reach joints are hard to assemble and tighten properly. Inaccessible joints are also more difficult and time consuming to service.



For detailed ordering information, please consult price list or contact Parflex Division.

Size Selection Procedure

Proper size selection is extremely important in choosing any air hose in order to prevent "starvation" of the air tool and to ensure maximum torque and tool speed. Starved tools don't produce!

Steps in size selection:


1. Determine air flow rate and pressure required by following air-tool manufacturers recommendations.

2. Refer to "Air Flow Characteristics" graphs, shown below. Find air flow requirement in standard cubic feet per minute (SCFM) on vertical line to left of graph. Now follow horizontal line on same graph to determine total extended length of hose required. Follow vertical line above hose length to intersection with the horizontal air flow SCFM line.


3. Note pressure drop above curve nearest to intersection of SCFM and hose length lines. Pressure drop, subtracted from line pressure, equals "available pressure" at the selected SCFM flow rate and hose length.

4. If "available pressure" is below the tool manufacturers' recommendations, refer to chart for successively larger hose sizes until an acceptable "available pressure" is found. Choose this size Fast-Stor® Air Hose for your application.


5. Refer to "working pressure vs. temperature" chart (pg. B-11) to be sure your application falls within the working range of Fast-Stor® Air Hose.




3/16" 4 20 60 10 40




1/4" 4 20 60 10 40



3/8" 4 20 60 10 40



1/2" 4 20 60 10 40



3/4" 4 20 60 10 40


Actual working pressure charts are located in the tubing section on the specific product page.

Measuring Fast-Stor® Bulk Hose


Measuring Fast-Stor® hose is quick and easy and may be accomplished by either of two accurate methods:


1. Counting

Total Length of Hose			Number of Coils Needed to Obtain Required Net Extended Length +3%				
			3/16 I.D. Fast-Stor®	1/4 I.D. Fast-Stor®	3/8 I.D. Fast-Stor®	1/2 I.D. Fast-Stor®	3/4 I.D. Fast-Stor®
ft.	inch	mtr.	coils	coils	coils	coils	coils
3	36	.91	5-1/8	3-1/2	2-1/4	1-5/8	7/8
3	36	.91	5-1/8	3-1/2	2-1/4	1-5/8	7/8
5	60	1.52	8-1/2	5-3/4	3-7/8	2-5/8	1-1/2
7	84	2.13	12	8-1/8	5-3/4	3-3/4	1-1/8
10	120	3.05	17-1/8	11-1/2	7-3/4	5-3/8	3
12	144	3.66	20-1/2	13-7/8	9-1/4	6-1/2	3-1/2
15	180	4.57	25-3/4	17-3/8	11-1/2	8	4-1/2
16	192	4.88	27-3/8	18-1/2	12-3/8	8-5/8	4-3/4
17	204	5.18	29-1/8	19-5/8	13-1/8	9-1/8	5
19	216	5.79	30-7/8	20-3/4	13-7/8	9-5/8	5-3/8
20	240	6.10	34-1/4	23-1/8	15-3/8	10-3/4	6
25	300	7.62	42-7/8	28-7/8	19-1/4	13-3/8	7-1/2
30	360	9.14	51-3/8	34-5/8	23-1/8	16-1/8	8-7/8
33	396	10.06	56-1/2	38-1/8	25-3/8	17-3/4	9-3/4
50	600	15.24	85-5/8	57-3/4	38-1/2	26-7/8	14-7/8



1 Full 360° Coil






For detailed ordering information, please consult price list or contact Parflex Division.

2. Division into Even Numbers of Lengths

Bulk retracted lengths of Fast-Stor® hose are always exactly 100 feet long when shipped from the factory. Some diameter expansion of the coils may occur in shipment due to temperature and storage conditions. This may appear to have shortened a given 100 foot retracted length slightly in relation to other 100 foot retracted lengths in the same master carton. The shorter appearance should not be mistaken for any actual shortage in extended length. A bulk retracted length may be easily divided into smaller lengths by first measuring the tightly retracted length in inches, and dividing by 4 to determine the cut-off length for 25 feet, by 3 for 33 feet, by 8 for 12-1/2 feet, etc. Pieces should be tagged with their proper length before returning to storage.

Cutting Bulk Length Coils

To cut bulk length coils, position coils on work table extending away from you, cut end-up in 12 o'clock position.



Fast-Stor® Air Hose



Features

- Manufactured from tough, abrasion-resistant nylon
- Excellent memory characteristics over a wide temperature range
- Long service life in rugged applications
- Desirable Safety Yellow color per U.S. Government OSHA directives
- Optimal retail packaging available*

Applications/Markets



- Blow Guns
- Construction
- Mfg. Air Drops
- Machine Tool Lubrication
- Water Hose

Fast-Stor® Assemblies

Popular Stock Assemblies

Assembly Part Number	Hose I.D.		Total Length		Working Length		Nominal Compact Length		Coil I.D.		Maximum Working Pressure 73°F/23°C		Minimum Burst at 73°F/23°C		End Fittings
#															
	inch	mm	ft.	mtr.	ft.	mtr.	inch	mm	inch	mm	psi	MPa	psi	MPa	
A0312-MC4-ML4	3/16	5	12	3.7	9	2.7	4.8	122	2	51	225	1.55	680	4.69	1/4" NPT
A0325-MC4-ML4	3/16	5	25	7.6	18	5.5	9.6	244	2	51	225	1.55	680	4.69	1/4" NPT
A0350-MC4-ML4	3/16	5	50	15.2	38	11.6	20.2	513	2	51	225	1.55	680	4.69	1/4" NPT
A0412-MC4-ML4*	1/4	6	12	3.7	9	2.7	4.3	109	3	76	225	1.55	680	4.69	1/4" NPT
A0425-MC4-ML4*	1/4	6	25	7.6	18	5.5	8.6	218	3	76	225	1.55	680	4.69	1/4" NPT
A0450-MC4-ML4	1/4	6	50	15.2	38	11.6	18.1	460	3	76	225	1.55	680	4.69	1/4" NPT
A0612-MC6-ML6*	3/8	10	12	3.7	9	2.7	4.3	109	4.5	114	225	1.55	680	4.69	3/8" NPT
A0625-MC6-ML6	3/8	10	25	7.6	18	5.5	8.5	216	4.5	114	225	1.55	680	4.69	3/8" NPT
A0650-MC6-ML6	3/8	10	50	15.2	38	11.6	17.9	455	4.5	114	225	1.55	680	4.69	3/8" NPT
A0812-MC8-ML8	1/2	13	12	3.7	9	2.7	4.3	109	6.5	165	225	1.55	680	4.69	1/2" NPT
A0825-MC8-ML8	1/2	13	25	7.6	18	5.5	8.5	216	6.5	165	225	1.55	680	4.69	1/2" NPT
A0850-MC8-ML8	1/2	13	50	15.2	38	11.6	16.8	427	6.5	165	225	1.55	680	4.69	1/2" NPT

Construction

Tube: Yellow PFX Nylon
Spring Guard: Steel
Fittings: Brass

Operating Parameters

Service temperature range:
-40°F (-40°C) to +200°F (93°C)

Maximum working pressure based on safety factor of 3:1 over burst

Notes

*Retail packaging available - Add "R" suffix when ordering

For detailed ordering information, please consult price list or contact Parflex Division.

Fast-Stor® Bulk Air Hose



Assembly Part Number	Nominal Tube I.D.		Nominal Tube O.D.		Tube Wall Thickness		Coil I.D.		Coil O.D.		Total Length		Working Length		Master Carton Quantity		Maximum Working Pressure 73°F/23°C		Minimum Burst at 73°F/23°C	
#																				
	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	ft.	mtr.	ft.	mtr.	ft.	mtr.	psi	MPa	psi	MPa
FS-03-100	3/16	5	.233	6	.023	.58	2	51	2.5	64	100	30.5	75	22.9	600	183	225	160	680	469
FS-04-100	1/4	6	.310	8	.030	.76	3	76	3.7	94	100	30.5	75	22.9	600	183	225	160	680	469
FS-06-100	3/8	10	.460	12	.045	1.1	4.5	114	5.5	140	100	30.5	75	22.9	400	122	225	160	680	469
FS-08-100	1/2	13	.620	16	.062	1.6	6.5	165	7.8	198	100	30.5	75	22.9	400	122	225	160	680	469
FS-12-100	3/4	19	.897	23	.075	1.9	11	305	13.0	330	100	30.5	75	22.9	100	30	200	140	600	414

Construction

Tube: Yellow PFX Nylon

Operating Parameters

Service temperature range: -40°F (-40°C) to +200°F (93°C)

Maximum working pressure based on safety factor of 3:1 over burst

Order Information

Example: A0412-MC4-ML4

A0412-MC4-ML4 – **Assembly**


A**04**12-MC4-ML4 – **Tube ID (1/4")**

A04**12**-MC4-ML4 – **Total Length (12')**

A0412-**MC4**-ML4 – **End 1 Fitting Size & Type (1/4" Male NPT)**

A0412-MC4-**ML4** – **End 2 Fitting Size & Type (1/4" Male NPT, Swivel)**

Working Pressure to Temperature




Fast-Stor® Fittings

Fittings for Fast-Stor® hose are constructed from heavy duty brass with built in insert-supports. Fitting bodies are SAE Standard sizes. Hose entry length into the fittings is the longest in the industry due to Parflex's SAE body design and size standardization, assuring a strong grip on the hose.

All fitting part numbers include body, nut, ferrule and spring guard. For body only, use Prefix B.


MC – Male Connector



Part Number	Thread Size	Hose I.D.		L		B Hex		C Hex	
#									
		inch	mm	inch	mm	inch	mm	inch	mm
MC-03-2	1/8	3/16	5	1-3/8	35	9/16	14	1/2	13
MC-03-4	1/4	3/16	5	1-9/16	40	9/16	14	1/2	13
MC-04-2	1/8	1/4	6	1-3/8	35	9/16	14	9/16	14
MC-04-4	1/4	1/4	6	1-9/16	40	9/16	14	9/16	14
MC-06-6	3/8	3/8	10	1-13/16	46	11/16	17	13/16	21
MC-08-6	3/8	1/2	13	2-1/8	54	7/8	22	15/16	24
MC-08-8	1/2	1/2	13	2-1/8	54	7/8	22	15/16	24
*MC-12-12	3/4	3/4	19	2-1/4	57	1-1/4	32	1-3/8	35

*No spring guard required.


ME – Male 90° Elbow



Part Number	Thread Size	Hose I.D.		L		N		C Hex	
#									
		inch	mm	inch	mm	inch	mm	inch	mm
ME-03-4	1/4	3/16	5	1-1/4	32	15/16	24	9/16	14
ME-04-4	1/4	1/4	6	1-13/16	46	15/16	24	9/16	14
ME-06-6	3/8	3/8	10	1-9/16	40	1-1/8	29	13/16	21
ME-08-8	1/2	1/2	13	1-3/4	44	1-3/8	35	15/16	24


For detailed ordering information, please consult price list or contact Parflex Division.

ML – Live Male Pipe Swivel




Part Number	Thread Size	Hose I.D.		L		B Hex		C Hex	
#									
		inch	mm	inch	mm	inch	mm	inch	mm
ML-03-4	1/4	3/16	5	1-1/16	27	9/16	14	1/2	13
ML-04-4	1/4	1/4	6	1-9/16	40	9/16	14	9/16	14
ML-06-6	3/8	3/8	10	1-7/8	47	3/4	19	13/16	21
ML-08-8	1/2	1/2	13	2-3/8	60	7/8	22	15/16	24

FC – Female Connector FPT



Part Number	Thread Size	Hose I.D.		L		B Hex		C Hex	
#									
		inch	mm	inch	mm	inch	mm	inch	mm
FC-04-4	1/4	1/4	6	1-9/16	40	11/16	17	9/16	14
FC-06-6	3/8	3/8	10	1-3/4	44	13/16	21	13/16	21

FL – Female Pipe Swivel*




Part Number	Thread Size	Hose I.D.		L		B Hex		C Hex		Box Quantity
#										
		inch	mm	inch	mm	inch	mm	inch	mm	
FL-04-4	1/4	1/4	6	1-3/4	44	5/8	16	9/16	14	20

*Fitting does not swivel after assembly.

Fast-Stor® Union Connector


UC – Union Connector



Part Number	Thread Size	Hose I.D.		L		B Hex		C Hex	
#									
		inch	mm	inch	mm	inch	mm	inch	mm
UC-04-4	1/4 x 1/4 I.D.	1/4	6	1-7/8	48	1/2	13	9/16	14
UC-06-6	3/8 x 3/8 I.D.	3/8	10	2-5/8	67	11/16	17	13/16	21


Fast-Stor® Replacement Parts

FN – Brass Nut



Part Number	Hose I.D.	
#		
	inch	mm
FN-03	3/16	5
FN-04	1/4	6
FN-06	3/8	10
FN-08	1/2	13
FN-12	3/4	19

FR – Plastic Ferrule



Part Number	Hose I.D.	
#		
	inch	mm
FR-03	3/16	5
FR-04	1/4	6
FR-06	3/8	10
FR-08	1/2	13
FR-12*	3/4	19

* Brass.


For detailed ordering information, please consult price list or contact Parflex Division.

SG – Steel Spring Guard



Part Number	Hose I.D.	
#	⊙	
	inch	mm
SG-03	3/16	5
SG-04	1/4	6
SG-06	3/8	10
SG-08	1/2	13


TS – Tube Support



Part Number	Hose I.D.	
#	⊙	
	inch	mm
TS-03	3/16	5
TS-04	1/4	6
TS-06	3/8	10
TS-08	1/2	13
TS-12	3/4	19

How to Assemble Fast-Stor® Hose

1. Using a Parker HTC hand cutter, PTC tubing cutter or other sharp cutting tool, cut hose squarely to correct length.
2. Install SG spring guard on hose as shown. A guard is not required on size -12 hose.
3. Slide FN nut on hose. Then slide FR plastic ferrule over hose with taper side toward cut end of hose. Size -12 hose uses a brass ferrule and requires the hose end to be dipped in lean water for lubrication.
4. Insert TS tube support.
5. Push hose into fitting body until bottomed. Slide nut and ferrule up to fitting body and tighten nut by hand. With a wrench, tighten the nut additional 2 to 2-1/2 turns.
6. Slide spring guard over nut until the lead coil snaps between the nut and fitting body hex.



Parflex NoMar® Fast-Stor® Assemblies AUFS



Features

- Manufactured from durable, abrasion-resistant Polyurethane
- Excellent memory characteristics over a wide temperature range
- Field-attachable fittings
- Available in bulk or factory-made assemblies

Applications/Markets



- Auto Repair
- Blow Guns
- Construction
- Carpentry
- Furniture Manufacturing
- Mfg. Air Drops
- Marine
- Water Hose

Urethane Fast-Stor® Assemblies

Includes live male end and rigid male end

Assembly Part Number	Hose O.D.		Hose I.D.		Working Length		Nominal Compact Length		Nominal Coil I.D.		Maximum Working Pressure 73°F/23°C		Minimum Burst at 73°F/23°C		End Fittings
#															
	inch	mm	inch	mm	ft.	mtr.	inch	mm	inch	mm	psi	MPa	psi	MPa	
AUFS-32-TBLU-010**	3/16	5	1/8	3	10	3.0	6.6	167	3/4	19	135	.93	405	2.79	1/8" NPT
AUFS-32-TBLU-025**	3/16	5	1/8	3	25	7.6	19	482	3/4	19	135	.93	405	2.79	1/8" NPT
AUFS-42-TBLU-010	1/4	6	1/8	3	10	3.0	8.3	210	3/4	19	175	1.21	525	3.62	1/4" NPT
AUFS-42-TBLU-025	1/4	6	1/8	3	25	7.6	23.9	607	3/4	19	175	1.21	525	3.62	1/4" NPT
AUFS-64-TBLU-010*	3/8	10	1/4	6	10	3.0	5.6	142	1-3/4	44	180	1.24	540	3.72	1/4" NPT
AUFS-64-TBLU-015*	3/8	10	1/4	6	15	4.6	9.3	236	1-3/4	44	180	1.24	540	3.72	1/4" NPT
AUFS-64-TBLU-020	3/8	10	1/4	6	20	6.1	13	330	1-3/4	44	180	1.24	540	3.72	1/4" NPT
AUFS-64-TBLU-025*	3/8	10	1/4	6	25	7.6	16	406	1-3/4	44	180	1.24	540	3.72	1/4" NPT
AUFS-85-TBLU-010	1/2	13	21/64	8	10	3.0	5.5	140	2-1/2	64	150	1.03	450	3.10	3./8" NPT
AUFS-85-TBLU-015	1/2	13	21/64	8	15	4.6	9	229	2-1/2	64	150	1.03	450	3.10	3./8" NPT
AUFS-85-TBLU-020	1/2	13	21/64	8	20	6.1	12.5	317	2-1/2	64	150	1.03	450	3.10	3./8" NPT
AUFS-85-TBLU-025	1/2	13	21/64	8	25	7.6	16	406	2-1/2	64	150	1.03	450	3.10	3./8" NPT
AUFS-86-TBLU-010	1/2	13	3/8	10	10	3.0	5.5	140	2-1/2	64	110	.76	330	2.28	3/8" NPT
AUFS-86-TBLU-020	1/2	13	3/8	10	20	6.1	12.5	317	2-1/2	64	110	.76	330	2.28	3/8" NPT
AUFS-96-TBLU-010	9/16	14	3/8	10	10	3.0	6.1	155	2-1/2	64	140	.97	420	2.90	3/8" NPT
AUFS-96-TBLU-015	9/16	14	3/8	10	15	4.6	9.9	251	2-1/2	64	140	.97	420	2.90	3/8" NPT
AUFS-96-TBLU-020	9/16	14	3/8	10	20	6.1	13.7	348	2-1/2	64	140	.97	420	2.90	3/8" NPT
AUFS-96-TBLU-025	9/16	14	3/8	10	25	7.6	17.5	444	2-1/2	64	140	.97	420	2.90	3/8" NPT

For detailed ordering information, please consult price list or contact Parflex Division.

Assembly Part Number	Hose O.D.		Hose I.D.		Working Length		Nominal Compact Length		Nominal Coil I.D.		Maximum Working Pressure 73°F/23°C		Minimum Burst at 73°F/23°C		End Fittings
#															
	inch	mm	inch	mm	ft.	mtr.	inch	mm	inch	mm	psi	MPa	psi	MPa	
AUFS-128-TBLU-010	3/4	19	1/2	13	10	3.0	7.5	190	3	76	125	.86	375	2.59	1/2" NPT
AUFS-128-TBLU-015	3/4	19	1/2	13	15	4.6	11.2	284	3	76	125	.86	375	2.59	1/2" NPT
AUFS-128-TBLU-020	3/4	19	1/2	13	20	6.1	15	381	3	76	125	.86	375	2.59	1/2" NPT
AUFS-128-TBLU-025	3/4	19	1/2	13	25	7.6	19.5	495	3	76	125	.86	375	2.59	1/2" NPT

Construction

Tube: Transparent Blue Polyurethane
Fittings: Brass

Operating Parameters

Service temperature range: -40°F (-40°C) to +180°F (82°C)

Notes

Pigtail Lengths – 16" swivel end, 8" rigid end
*Retail packaging available - Add "R" suffix when ordering
**Size -32 comes standard with two rigid ends

Other sizes available upon request

Colors

Color Code		
●	TBLU	Transparent Blue


Other colors available upon request - consult factory

Order Information

Example: AUFS-64-TBLU-025

AUFS-64-TBLU-025 – **Assembled Urethane Fast-Stor**
AUFS-**6**4-TBLU-025 – **Tube OD (3/8")**
AUFS-6**4**-TBLU-025 – **Tube ID (1/4")**
AUFS-64-**TBLU**-025 – **Color (Transparent Blue)**
AUFS-64-TBLU-**025** – **Total Length (25')**

Parflex NoMar® Fast-Stor® Coiled Tubing UFS



Features

- Manufactured from durable, abrasion-resistant Polyurethane
- Excellent memory characteristics over a wide temperature range
- Long service life in rugged applications

Applications/Markets



- Auto Repair
- Blow Guns
- Construction
- Carpentry
- Furniture Manufacturing
- Mfg. Air Drops
- Marine
- Water Hose

Assembly Part Number	Hose O.D.		Hose I.D.		Working Length	Nominal Coil I.D.		Maximum Working Pressure 73°F/23°C		Minimum Burst at 73°F/23°C	
#											
	inch	mm	inch	mm	feet	inch	mm	psi	MPa	psi	MPa
UFS-32-TBLU-xxx	3/16	5	1/8	3	010, 025	3/4	19	135	.93	405	2.79
UFS-42-TBLU-xxx	1/4	6	1/8	3	010, 025	3/4	19	175	1.21	525	3.62
UFS-64-TBLU-xxx	3/8	10	1/4	6	010, 015, 020, 025	1-3/4	44	180	1.24	540	3.72
UFS-85-TBLU-xxx	1/2	13	21/64	8	010, 015, 020, 025	2-1/2	64	150	1.03	450	3.10
UFS-86-TBLU-xxx	1/2	13	3/8	10	010, 020	2-1/2	64	110	.76	330	2.28
UFS-96-TBLU-xxx	9/16	17	3/8	10	010, 015, 020, 025	2-1/2	64	140	.97	420	2.90
UFS-128-TBLU-xxx	3/4	19	1/2	13	010, 015, 020, 025	3	76	125	.86	375	2.59

Construction

Tube: Transparent Blue Polyurethane

Operating Parameters

Service temperature range: -40°F (-40°C) to +180°F (82°C)
Maximum working pressure based on safety factor of 3:1 over burst

Notes

xxx- Denotes Hose Length (feet)
Pigtail Lengths – 16" swivel end, 8" rigid end
Other sizes available upon request

Order Information

Example: UFS-86-TBLU-010

UFS-86-TBLU-010 – **Assembled NoMar® Fast-Stor®**
UFS-**8**6-TBLU-010 – **Tube OD (1/2")**
UFS-8**6**-TBLU-010 – **Tube ID (3/8")**
UFS-86-**TBLU**-010 – **Color (Transparent Blue)**
UFS-86-TBLU-**010** – **Total Length (10')**

Colors

Color Code		
●	TBLU	Transparent Blue

Other colors available upon request - consult factory

For detailed ordering information, please consult price list or contact Parflex Division.

Parflex NoMar® Fast-Stor® Coiled Assembly AHUFS



Features

- Manufactured from durable, abrasion-resistant 98 Durometer Polyurethane
- Excellent memory characteristics over a wide temperature range
- Long service life in rugged applications

Applications/Markets



- Auto Repair
- Blow Guns
- Construction
- Carpentry
- Furniture Manufacturing
- Mfg. Air Drops
- Marine
- Water Hose

Includes live male end and rigid male end

Assembly Part Number	Hose O.D.		Hose I.D.		Working Length		Nominal Compact Length		Coil I.D.		Maximum Working Pressure 73°F/23°C		Minimum Burst at 73°F/23°C		End Fittings
#															
	inch	mm	inch	mm	ft.	mtr.	inch	mm	inch	mm	psi	MPa	psi	MPa	
AHUFS-6-xxx-015	3/8	10	1/4	6	15	4.6	13	330	1-1/4	32	180	1.24	540	3.72	1/4"
AHUFS-6-xxx-025	3/8	10	1/4	6	25	6.7	22	559	1-1/4	32	180	1.24	540	3.72	1/4"

Construction

Tube: 98 Durometer Polyurethane
Fitting: Brass

Operating Parameters

Service temperature range: -40°F (-40°C) to +180°F (82°C)

Maximum working pressure based on safety factor of 3:1 over burst.

Notes

xxx- Denotes Color
Retail packaging available - Add "R" suffix when ordering
Pigtail Lengths – 16" swivel end, 8" rigid end
Other sizes available upon request

Colors

Color Code		
●	BLK	Black
●	BLU	Blue
●	RED	Red
●	YEL	Yellow

Other colors available upon request - consult factory

Order Information


Example: AHUFS-6-BLK-015

AHUFS-6-BLK-015 – **Assembled High Durometer Urethane Fast-Stor**
AHUFS-**6**-BLK-015 – **Tube OD (3/8")**
AHUFS-6-**BLK**-015 – **Color (Black)**
AHUFS-6-BLK-**015** – **Total Length (15')**

Parflex NoMar® Fast-Stor® Fittings

Parflex NoMar® Fast-Stor® fittings are manufactured from a heavy brass construction utilizing all standards for NPTF pipe threads. The engineered barb design generates the maximum gripping and sealing power when combined with the socket.


MCB Male Pipe Rigid



Part Number	Hose Part Number	Thread Size	Hose I.D.		L		Cutoff M		C Hex		F Hex	
#	#											
			inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
MCB-3x2-2	UFS-32	1/8 NPT	0.11	2.8	0.94	23.8	0.72	18.3	7/16	11	7/16	11
MCB-4x2-2	UFS-42	1/8 NPT	0.12	3.0	1.00	25.4	0.74	18.8	7/16	11	7/16	11
MCB-4x2-4	UFS-42	1/4 NPT	0.12	3.0	1.16	29.5	0.90	22.9	9/16	14	7/16	11
MCB-6x4-4	UFS-64	1/4 NPT	0.23	5.8	1.16	29.5	0.90	22.9	5/8	16	5/8	16
MCB-6x4-6	UFS-64	3/8 NPT	0.23	5.8	1.20	30.5	0.94	23.9	3/4	19	5/8	16
MCB-8x5-6	UFS-85	3/8 NPT	0.27	6.9	1.29	32.8	0.99	25.1	3/4	19	3/4	19
MCB-8x6-4	UFS-86	1/4 NPT	0.28	7.1	1.29	32.8	1.03	26.1	3/4	19	3/4	19
MCB-8x6-6	UFS-86	3/8 NPT	0.34	6.6	1.30	33.0	1.04	26.4	3/4	19	3/4	19
MCB-9x6-6	UFS-96	3/8 NPT	0.31	7.9	1.47	37.3	1.10	27.9	7/8	22	7/8	22
MCB-9x6-8	UFS-96	1/2 NPT	0.32	8.1	1.61	40.9	1.24	31.5	7/8	22	7/8	22
MCB-12x8-8	UFS-128	1/2 NPT	0.42	10.7	1.98	50.0	0.94	24.0	1	25	1	25


For detailed ordering information, please consult price list or contact Parflex Division.

MLB Male Live Swivel



Part Number	Hose Part Number	Thread Size	Hose I.D.		L		Cutoff M		C Hex		E Hex		F Hex	
#	#													
			inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
MLB-4x2-4	UFS-42	1/4 NPT	0.12	3.0	1.37	34.8	1.11	28.2	9/16	14	7/16	11	9/16	14
MLB-6x4-4	UFS-64	1/4 NPT	0.22	5.6	1.37	34.8	1.11	28.2	9/16	14	5/8	16	5/8	16
MLB-6x4-6	UFS-64	3/8 NPT	0.23	5.8	1.58	40.1	1.32	33.5	3/4	19	5/8	16	5/8	16
MLB-8x5-6	UFS-85	3/8 NPT	0.27	6.9	1.68	42.7	1.38	35.1	3/4	19	3/4	19	3/4	19
MLB-8x6-6	UFS-86	3/8 NPT	0.33	8.4	1.71	43.4	1.45	36.8	3/4	19	3/4	19	3/4	19
MLB-9x6-6	UFS-96	3/8 NPT	0.31	7.9	1.87	47.5	1.50	38.1	3/4	19	7/8	22	7/8	22
MLB-9x6-8	UFS-96	1/2 NPT	0.31	7.9	1.95	49.5	1.58	40.1	15/16	24	7/8	22	7/8	22
MLB-12x8-8	UFS-128	1/2 NPT	0.42	10.7	2.30	56.5	1.26	32.0	7/8	22	1	25	1	25

Assembly Instructions



1. Slide the socket on the tubing with threads facing the end of the tubing.
2. Press the tubing over the Tube Support portion of the fitting until the tube bottoms out. Do not use a lubricant.
3. Push the socket up to meet the mating threads on the fitting, finger tighten the socket onto the fitting.
4. Tighten the fitting and socket until the fitting hex and socket hex meet.

Ultra-Lite Superbraid® Hose



Features

- More than 20% lighter than similar braided polyurethane hoses
- Extremely tough and abrasion resistant
- State-of-the-art strain relief system allows the hose to bend freely without kinking at the fitting
- Features lightweight, non-marring jacket

Applications/Markets



- Auto Repair
- Blow Guns
- Construction
- Carpentry
- Furniture Manufacturing
- Mfg. Air Drops
- Marine
- Water Hose

Part Number	Nominal I.D.		Nominal O.D.		Total Length	Maximum Working Pressure 73°F/23°C		Fitting Size & Type
#								
	inch	mm	inch	mm	feet	psi	MPa	
SB-4-B-xxx-ML4 SB-4-Y-xxx-ML4	1/4	6	3/8	10	025, 050, 100	220	1.52	1/4" Male NPT, Swivel
SB-5-B-xxx-ML6 SB-5-Y-xxx-ML6	5/16	8	15/32	12	025, 050, 100	185	1.28	3/8" Male NPT, Swivel
SB-6-Y-xxx-ML4	3/8	10	.515	13	025, 050, 100	200	1.38	1/4" Male NPT, Swivel
SB-6-Y-xxx-ML6	3/8	10	.515	13	025, 050, 100	200	1.38	3/8" Male NPT, Swivel
SB-6-Y-xxx-MC4	3/8	10	.515	13	025, 050, 100	200	1.38	1/4" Male NPT, Rigid
SB-6-Y-xxx-MC6	3/8	10	.515	13	025, 050, 100	200	1.38	3/8" Male NPT, Rigid

Construction

Tube: Polyurethane
Reinforcement: Polyester
Cover: Polyurethane
Fittings: Brass
O-rings: Buna-N
Strain Relief Sleeves: Acetal

Operating Parameters

Temperature Range:
-40°F (-40°C) to +165°F (74°C)

Notes

xxx- Denotes Hose Length

Fittings

Parker Fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 694-4614 FAX

Field Attachable Fittings

Hose Size	Fitting Size	Fitting Type	F.A. Fitting	F.A. Fitting & Strain Relief
Inch	Inch		Part Number*	Part Number**
1/4	1/4	Male NPT, Swivel	06244S	07244S
5/16	1/4	Male NPT, Swivel	06254S	-
5/16	3/8	Male NPT, Swivel	06256S	-
3/8	1/4	Male NPT, Rigid	06264RU	07264RU
3/8	1/4	Male NPT, Swivel	06264SU	07264SU
3/8	3/8	Male NPT, Swivel	06266SU	07266SU
1/4	-	Hose Splicer	06244-HS	-
3/8	-	Hose Splicer	06266-HSU	-

* Includes Fitting & Nut (No Strain Relief).
** Includes Fitting & Nut with permanently attached strain relief.



Parflex Field Attachable Fittings do not require inserts or ferrules that become deformed during installation, so the fittings can be used over again without replacing any components. In addition, only two wrenches are needed to complete a safe and secure connection, making fitting replacement quick and easy!

For detailed ordering information, please consult price list or contact Parflex Division.

SB – Bulk Hose Without Fittings

Part Number	Nominal I.D.		Nominal O.D.		Working Length	Maximum Working Pressure	
#							
	inch	mm	inch	mm	feet	psi	MPa
SB-4-B-xxx SB-4-Y-xxx	1/4	6	3/8	10	025, 050,100, 500	220	1.52
SB-5-B-xxx SB-5-Y-xxx	5/16	8	15/32	12	025, 050,100, 300	185	1.28
SB-6-Y-xxx	3/8	10	.515	13	025, 050,100, 500	200	1.38

Order Information

Example: SB-4-Y-050-ML4

SB-4-Y-050-ML4 – **Super Braid**

SB-**4**-Y-050-ML4 – **Hose ID (1/4")**

SB-4-**Y**-050-ML4 – **Color (Yellow)**

SB-4-Y-**050**-ML4 – **Total Length (50')**

SB-4-Y-050-**ML4** – **Fittings Size & Type (1/4" Male NPT, Swivel)**

Color Code		
●	TBLU	Transparent Blue
●	YEL	Yellow

Notes

Parker




Table of Contents

Air Brake Tubing D-4
BRAKCoil® D-8
Cut Tubes D-13
Duo-Coil™ D-9
DollyCoil™ D-10
Fifth Wheel Slider D-12
FLR Diesel Fuel Tubing, Quick Connect Fittings D-7
Formed Assemblies D-13
Formed Harnesses D-13
Formed Tubes and Hoses D-13
HTFL Diesel Fuel Tubing, High Temp D-6
Jacketed Bundles D-13
PFT-FL Diesel Fuel Tubing D-5
SCR Hose ..... D-14 : D-15
SliderCoil™ D-11
Straight Harnesses D-13

Transportation Visual Index

Transportation Products

Air Brake Tubing	PFT-FL Diesel Fuel Tubing	HTFL High-Temperature Diesel Fuel Tubing	FLR Quick Connect Diesel Fuel Tubing	BRAKCoil®
 D-4	 D-5	 D-6	 D-7	 D-8
Duo-Coil®	**DollyCoil™**	**SliderCoil™**	**Fifth Wheel Slider**	**Cut Tubes**
 D-9	 D-10	 D-11	 D-12	 D-13
Formed Tubes & Hoses	**Jacketed Bundles**	**Straight Harnesses**	**Formed Harnesses**	**SCR Hose**
 D-13	 D-13	 D-13	 D-13	 D-14 : D-15

For detailed ordering information, please consult price list or contact Parflex Division.

Parflex Transportation Products



Formed Dash Harnesses
Transmission Air Shift Bundles
Cab Tilt Lines

Air Brake Tubing
Air Brake Harnesses



Slider Coils
Tire Inflation Hoses



Brake Coils




Heated SCR Hose
Fuel Tubing
High Temp Fuel Lines



Formed Diesel Fuel Tubing
Compressor Discharge Lines
Formed Power Steering Hoses
Transmission Oil Cooler Lines

Nylon Air Brake Tubing



Features

- 100% pressure tested
- Excellent UV stability
- Abrasion resistant
- Kink resistant

Certifications

- Meets SAE Specification J844
- Meets DOT FMVSS 49CFR 571.106
  *2A, 3A, and 5A are not DOT sizes

Applications/Markets

- Air brake lines

Part Number	Tube O.D.	Outside Diameter		Inside Diameter		Nominal Wall Thickness		Burst Pressure at 73°F /23°C		Minimum Bend Radius		Weight		Standard Reel		Standard Pallet	
#												lbs	kg				
	inch	inch	mm	inch	mm	inch	mm	psi	bar	inch	mm	lbs./100 ft.	kg./31 mtr.	feet	meter	feet	meter
PFT-2A-XXX-1000*	1/8	.125	3.2	.079	2.0	.023	0.6	1000	69.0	.370	9.4	.340	.154	1000	305	24,000	7315
PFT-2.5-XXX-1000	5/32	.156	4.0	.092	2.3	.032	0.8	1200	82.7	.500	12.7	.570	.259	1000	305	24,000	7315
PFT-3A-XXX-1000*	3/16	.188	4.8	.118	3.0	.035	0.9	1200	82.7	.750	19.1	.770	.349	1000	305	24,000	7315
1120-4A-XXX-1000	1/4	.250	6.4	.170	4.3	.040	1.0	1200	82.7	1.00	25.4	1.21	.549	1000	305	24,000	7315
PFT-5A-BLK-500*	5/16	.313	7.9	.232	5.9	.040	1.0	1000	69.0	1.25	31.8	1.57	.712	500	152	12,000	3658
1120-6B-XXX-500	3/8	.375	9.5	.251	6.4	.062	1.6	1400	96.5	1.50	38.1	2.70	1.22	500	152	12,000	3658
1120-8B-XXX-500	1/2	.500	12.7	.376	9.6	.062	1.6	950	65.5	2.00	50.8	3.90	1.77	500	152	6,000	3658
1120-10B-XXX-250	5/8	.625	15.9	.441	11.2	.092	2.3	900	62.1	2.50	63.5	7.00	3.18	250	76	3,000	914
1120-12B-XXX-250	3/4	.750	19.1	.566	14.4	.092	2.3	800	55.2	3.00	76.2	8.60	3.90	250	76	3,000	914

Note: *2A, 3A, and 5A are not DOT sizes XXX represents color code

Construction

Material:
Type A – Single-wall extruded Nylon (polyamide)

Type B – Nylon (polyamide) core, fiber reinforcement, Nylon (polyamide) cover/sheath

Operating Parameters

Temperature Range:
-40˚F (-40˚C) to +200˚F (93˚C)
Working Pressure: 150 psi (10.3 bar)

Fittings

Parker Fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 694-4614 FAX


FSC Product Families:

- NTA
- Air Brake
- Prestomatic
- PMT
- PTC

Colors

Color Code		
●	BLK	Black
●	BLU	Blue
●	BRN	Brown
●	GRN	Green
●	ORG	Orange
●	PUR	Purple
●	RED	Red
●	SIL	Silver
●	TAN	Tan
●	YEL	Yellow
○	WHT	White

Parflex Diesel Fuel Tubing



Features

- Nylon tubing designed for use in tractor, trailer and other mobile fuel systems
- Heat and light stabilized
- 100% quality controlled – 100% pressure tested
- Saves weight and labor in comparison with hose and hard-line tubing

Approvals

- Compatible with JP-5 (MIL-DTL-5624) and JP-8 (MIL-DTL-83133)
- Compatible with Biodiesel per Parflex PPB PL-18 hard-line tubing

Applications/Markets

- D.O.T. diesel fuel applications

Part Number	Nominal Tube O.D.		Nominal Tube I.D.		Minimum Bend Radius		Weight		Standard Reel	
#							lbs	kg		
	inch	mm	inch	mm	inch	mm	lbs./ft.	kg./mtr.	feet	meter
PFT-4A-XXX-1000-FL	1/4	6	.170	4	1	25	.012	.017	1000	305
PFT-6B-XXX-500-FL	3/8	10	.251	6	1-1/2	38	.027	.040	500	152
PFT-8B-XXX-500-FL	1/2	13	.376	10	2	51	.039	.058	500	152
PFT-10B-XXX-250-FL	5/8	16	.441	11	2-1/2	64	.070	.104	250	76
PFT-12B-XXX-250-FL	3/4	19	.566	14	3	76	.086	.128	250	76

XXX represents color code.

Construction

Heat and light stabilized seamless extruded nylon core reinforced with fibrous reinforcement and bonded with a protective blue nylon cover sheath

Operating Parameters

Temperature Range:
-40˚F (-40˚C) to +200˚F (93˚C)

Maximum Working Pressure: 150 psi (10.3 bar)

Do not exceed temperature and pressure ranges

Color

● BLU

Blue is standard
Consult division for additional colors

Fittings

Parker Fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 694-4614 FAX

FSC Product Families:

- NTA
- DF (Diesel Fuel Only)

Notes

Contact Parflex Division for application review

HTFL Diesel Fuel Line Tubing (High-Temperature)



Features

- Heat and UV stabilized
- For use in high temperature applications
- 100% pressure tested
- Light weight
- Pre-formed tubes available

Applications/Markets

Part Number	Nominal Tube O.D.		Nominal Tube I.D.		Nominal Wall Thickness		Working Pressure		Minimum Burst at 73°F /23°C		Minimum Bend Radius		Weight		Standard Reel	
#													lbs	kg		
	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	lbs./ ft.	kg./ mtr	feet	meter
HTFL-6B-BRN-500	3/8	10	.251	6	.062	1.6	175	12.1	1,400	96.5	1-1/2	38	.028	.041	500	152
HTFL-8B-BRN-500	1/2	13	.376	10	.062	1.6	155	10.7	950	65.5	2	51	.039	.058	500	152
HTFL-10B-BRN-250	5/8	16	.441	11	.092	2.3	140	9.7	900	62.1	2-7/8	73	.071	.106	250	76
HTFL-12B-BRN-250	3/4	19	.566	14	.092	2.3	150	10.3	800	55.1	3	76	.086	.128	250	76

Construction

Tube: High-temperature and chemical-resistant special polyamide

Reinforcement: High-strength yarn fiber

Cover: High-temperature and UV-resistant special polyamide

Operating Parameters

Temperature Range:
-50˚F (-46˚C) to +266˚F (130˚C)

Vacuum Rating: 28 inch Hg

Fittings

Parker Fittings available from:
Fluid System Connectors Division
Otsego, MI
(269) 692-6555
(269) 694-4614 FAX

FSC Product Families:

NTA

Color

● BRN

Brown is standard
Consult division for additional colors

Notes

Compatible with JP-5 (MIL-DTL-5624) and JP-8 (MIL-DTL-83133)

Compatible with Biodiesel per Parflex PPB PL-18

For detailed ordering information, please consult price list or contact Parflex Division.

FLR Diesel Fuel Tubing
J2044 Quick Connect Ready



Features

- Utilizes SAE 2044 Safe-Lock™ Quick Connect Fittings
- Easy to assemble
- Heat and UV stabilized
- 100% pressure tested
- Light weight
- Pre-formed tubes available
- Tested to select SAE J844, SAE J2044, and SAE J2045 liquid fuel assembly specifications

Applications/Markets

- General diesel fuel applications

Compliance

- SAE J2045, Section 4.2, Fitting Pull-Off for liquid fuel assemblies, at room temperature and at 250°F
- SAE J2045, Section 4.8, Burst Strength for liquid fuel assemblies, at room temperature and at 250°F
- SAE J2044, Section 7.5, Life Cycle Test for liquid fuel assemblies
- SAE J844, Section 9.13, Collapse Resistance, at 250°F

Part Number	Nominal Tube O.D.		Nominal Tube I.D.		Minimum Supported Bend Radius		Minimum Unsupported Bend Radius		Weight	
#									lbs	kg
	inch	mm	inch	mm	inch	mm	inch	mm	lbs./ ft.	kg./ mtr
FLR-6	0.434	11.0	0.320	8.1	1.75	44	2.25	57	0.030	0.045
FLR-8	0.559	14.2	0.425	10.8	2.25	57	2.75	70	0.046	0.068
FLR-10	0.660	16.8	0.500	12.7	2.75	70	3.25	83	0.064	0.095

Construction

Tube: High-temperature and chemical-resistant special polyamide

Color

● Black

Operating Parameters

Temperature Range:
Use in environments less than +239°F (+115°C)
Maximum Working Pressure: -7.2 psi to +72 psi (-0.50 bar to + 5 bar)
Do not exceed temperature and pressure ranges

Note

- Factory-made assemblies only
- Colors available upon request

Fittings


- Available SAE J2044 Quick Connect Fitting sizes include 3/8", 1/2", and 5/8"
- SAE J2044 Quick Connect Fittings available in 90° and 180° configurations.

J2044 Quick Connect Fittings available from
Parker Hannifin Fluid System Connectors Division

Phone: 269 692 6555 Fax: 269 694 4614

www.parker.com/fsc

BRAKCOIL®



Features

- Tractor-to-trailer coiled nylon air-brake connections
- Maintenance-free performance - designed for trouble-free service on your rig
- Years of city delivery and line haul testing
- Heavy-duty plated spring guards are rust-resistant for added protection
- More coils offer you maximum working lengths
- No need for pogo sticks or spring hangers
- Color coding gives you mistake-free hook-ups – blue for service, red for emergency

Certifications

- Meets or exceeds SAE J844 and D.O.T. FMVSS 106 Specifications at -70°F to +200°F

Applications/Markets

- Tractor to Trailer

Kit Coil Number	Individual Coil Part Number	Tube O.D.		Valve Tail Length		Brass Male Ends (NPT)				Working Length		Number of Coils
						Valve		Gladhand				
#	#											
		inch	mm	inch	mm	inch	mm	inch	mm	feet	meter	
731516	731512-RED 731512-BLU	-8	13	12	305	1/2	13	1/2	13	15	4.6	21-1/2
751597	731611-RED 731611-BLU	-8	13	12	305	3/8	10	1/2	13	15	4.6	21-1/2
731522	731513-RED 731513-BLU	-8	13	40	1016	1/2	13	1/2	13	15	4.6	21-1/2
741526	731612-RED 731612-BLU	-8	13	40	1016	3/8	10	1/2	13	15	4.6	21-1/2
751641	741590-RED 741590-BLU	-8	13	6	152	1/2	13	1/2	13	12	3.7	18-1/2
751655	751656-Blk Black Only	-8	13	6	152	3/8	10	1/2	13	12	3.7	18-1/2

Order Information

BRAKCOIL® kits are supplied complete – **Parker pre-assembled**, with everything needed, including spring guards and male pipe NTA brass fittings, **ready to install**. Special pipe thread sealant is factory applied. No cutting or assembly necessary. Just attach the gladhands (sold separately or pre-assembled). They are available in kits or as separate lines. A kit consists of both a red and blue tube assembly.

Construction

Tube: Coiled Nylon Air Brake Tubing

Operating Parameters

Temperature Range:
-70˚F (-57˚C) to +200˚F (93˚C)

Options


Extended BRAKCOIL® handle available, part no. 771164

Gladhands available

- BLU – Part # GH9211
- RED – Part # GH9212

For detailed ordering information, please consult price list or contact Parflex Division.

Duo-Coil™ Features



Features

- Duo-Coil combines both tractor-to-trailer lines (service and emergency) into a strong single unit
- Designed for quick hook-up and trouble-free service on your rig
- Reverse winding of the coiled air brake lines eliminates the possibility of tangling
- Installation swivel fittings make hook-up a snap
- The inner red emergency coil is wound inside the blue service coil offering added protection to the driver
- The single unit provides clean and neat installation

Certifications

- Meets or exceeds SAE J844 and D.O.T. FMVSS 106 Specifications at -70°F to +200°F

Applications/Markets

- Tractor to Trailer

Kit Coil Number	Tube O.D.		Valve Tail Length		Brass Male Ends (NPT)				Working Length		Number of Coils
					Valve		Gladhand				
#											
	inch	mm	inch	mm	inch	mm	inch	mm	feet	meter	
801048	-8	13	12	305	1/2	13	1/2	13	15	4.6	21-1/2
801632	-8	13	6	152	1/2	13	1/2	13	12	3.7	18-1/2
801595	-8	13	40	1016	1/2	13	1/2	13	15	4.6	21-1/2

Order Information

Duo-Coil™ kits are supplied complete – **Parker pre-assembled**, with everything needed, including spring guards and pipe end NTA fittings, **ready to install**. Special pipe thread sealant is factory applied. No cutting or fitting assembly is necessary. Just attach the gladhands (sold separately or pre-assembled).

Construction

Tube: Coiled Nylon Air Brake Tubing

Operating Parameters

Temperature Range:
-70˚F (-57˚C) to +200˚F (93˚C)


Options

Extended BRAKCOIL® handle available, part no. 771164

Gladhands available

- Blue – Part # GH9211
- Red – Part # GH9212

DollyCoil™



Features

- No need to install springs or hangers
- Will retract to its original shape even after long periods of extended use

Certifications

- Meets or exceeds SAE J844 and D.O.T. FMVSS 106 Specifications at -70°F to +200°F

Applications/Markets




- Multiple Trailers
- Converter Dollies

Kit Coil Number	Tube O.D.		Valve Tail Length		Brass Male Ends (NPT)				Standard Working Length		Number of Coils
					Valve 90° End		Gladhand 180° End				
#	◯										
	inch	mm	inch	mm	inch	mm	inch	mm	feet	meter	
751634	-8	13	8	13	1/2	13	1/2	13	6	1.83	12

Order Information

DollyCoil™ kits are supplied complete – **Parker pre-assembled**, with everything needed, including spring guards and male pipe end NTA fittings, **ready to install**. Special pipe thread sealant is factory applied. No cutting or assembly necessary. Just attach the gladhands (sold separately or pre-assembled). They are available in kits or as separate lines. A kit consists of both a red and blue tube assembly.

Construction

Tube: Coiled Nylon Air Brake Tubing

Operating Parameters

Temperature Range:
-70˚F (-57˚C) to +200˚F (93˚C)

Options


Extended BRAKCOIL® handle available, part no. 771164

Gladhands available

- Blue – Part # GH9211
- Red – Part # GH9212

For detailed ordering information, please consult price list or contact Parflex Division.

SliderCoil™



Features

- Used between an adjustable rear trailer axle and the final point on a trailer chassis
- No need to install springs or hangers
- Will retract to its original shape even after long periods of extended use

Certifications

- Meets or exceeds SAE J844 and D.O.T. FMVSS 106 Specifications at -70°F to +200°F

Applications/Markets




- Tractor Trailers (Sliding)
- Tractor Trailers (Axles)

Kit Coil Number	Individual Coil Part Number	Tube O.D.		Valve Tail Length		Brass Male Ends (NPT)				Working Length		Number of Coils
						Valve 90° End		Gladhand 180° End				
#	#	◯										
		inch	mm	inch	mm	inch	mm	inch	mm	feet	meter	
751657	751657-BLU, 751657-RED	-8	13	8	13	1/4	6	1/4	6	9	2.7	13-1/2
751659	751659-BLU, 751659-RED	-8	13	8	13	3/8	10	3/8	10	9	2.7	13-1/2

Order Information

SliderCoil™ kits are supplied complete – **Parker pre-assembled**, with everything needed, including spring guards and male pipe end NTA fittings, **ready to install**. Special pipe thread sealant is factory applied. No cutting or assembly necessary. They are available in kits or as separate lines. A kit consists of both a red and blue coil assemblies.

Construction

Tube: Coiled Nylon Air Brake Tubing

Operating Parameters

Temperature Range:
-70˚F (-57˚C) to +200˚F (93˚C)

Color

- Blue
- Red

Options

Extended BRAKCOIL® handle available, part no. 771164

Fifth Wheel Slider Coil



Features

- Clutter-free hook-up and maintenance-free performance of adjustable length pneumatic tubing for fifth wheel sliding action
- Self-adjusts from 10" to fully extended 74" working length
- Universal, ready for immediate installation
- No maintenance required - stays on the job at peak performance through years of trouble-free life
- Coil set is strong and permanent - Even after prolonged use in fully extended position, coils will retract to shorter length without sagging and eliminating hazards of chafing and wear

Certifications

- Conforms to SAE Specification J844 Type A
- Meets D.O.T. FMVSS 106

Applications/Markets

- Double Trailers
- Convert, Dollies

Part Number	Fittings	Pigtail Length		Maximum Extended Length		Retracted Length	
#							
		inch	mm	inch	mm	inch	mm
811537	(2)68NTA-4-4	2	51	74	1880	10	254
811537-NF-BLK	-	2	51	74	1880	10	254

Order Information

Fifth Wheel Slider Coil part# 811537 comes complete with fittings. Part# 811537-NF-BLK does not include fittings.

Construction

Tube: 1/4" O.D. extruded Nylon, heat and light stabilized, single wall

Operating Parameters

Temperature Range:
-40˚F (-40˚C) to +200˚F (93˚C)

Color

SIL

Options

Available with or without fittings

For detailed ordering information, please consult price list or contact Parflex Division.

Custom Harness, Bundles & Tubing

Order Information

Several different harnesses may be required on a single unit depending upon the model of the vehicle, wheel base and options available. To determine your harness application needs:

1. **Recognize the cost savings** available to you through the use of harnesses. How many dollars will be saved on tubing installation alone? On scrap reduction?
2. **Call Parker**. Have one of our application engineers study your application.
3. **Have Parker engineers design and build a prototype** harness for your approval.
4. **Approve the prototype** as our basis to engineer your production model harness.
5. **Implement the harness** into your Purchasing and Production systems – one harness, one part number instead of multiple part numbers you once had for each air brake line.

Features

- Preformed, pre-bundled tubing or hose custom designed to reduce installation time and improve throughput
- Your production line will run faster and be virtually free from tubing scrap
- Individual tubes are pre-cut and assembled into a single unit

Certifications

- Designed and engineered to meet the exacting requirements of each bus or truck manufacturer for each vehicle
- The air brake tubing used in a Parflex Harness conforms to SAE J844 type 3A and 3B (all sizes) and also D.O.T. FMVSS 106 (Except sizes 2A, 3A and 5A)
- Parflex Division is third party certified for ISO 14001 and TS 16949
- 6mm Nylon, 5.5mm EPDM, and 4mm EPDM are IP6X, IPX8, and IPX9K Certified

Tubing

Construction

Tube: Nylon Air Brake Tubing

Operating Parameters

Temperature Range: -40˚F (-40˚C) to +200˚F (93˚C)

Working Pressure: 150 psi (10.3 bar)

Options


Each tube can be color-coded and/or numbered

Each harness may contain any number of tube sizes ranging from 1/8" O.D. to 3/4" O.D.

The harness can be supplied with special clamps, brackets and fittings to meet any need required by the customer


Hose

Contact Parflex Customer Service for custom formed hoses and hose assemblies




Cut Tubes

Any tube offered by Parflex can be cut-to-length, with options for additional marking




Straight Harnesses

Combine multiple cut tubes into a harness built specifically for your application




Formed Tubes

Tubes can be formed into shapes for ease of installation



Formed Harnesses

Combine multiple formed tubes to create a repeatable tubing routing solution



Jacketed Bundles

Two or more tubes can be bundled together with an extruded thermo-plastic jacket



Formed Assemblies

Most Parflex thermoplastic hoses can be formed into application specific shapes

SCR Hose Assemblies for Tier IV Compliance



Features

- Thermoplastic and EPDM core tubes reinforced for strength and flexibility
- Stainless steel heating wire
- Extruded thermoplastic jacket
- Heated fittings
- Optional heat/abrasion shield
- 100% electrically tested, pressure tested, and cleaned before shipped

Certifications

- TS 16949
- ISO 14001
- IP6X, IPX8, and IPX9K Certified (4mm EPDM, 5.5mm EPDM, and 6mm Nylon)

Applications/Markets



With Parflex Electrically Heated SCR Hose Assemblies, a cleaner exhaust system means a cleaner environment.

Designed for heating and conveying DEF (Diesel Exhaust Fluid) throughout the SCR system on commercial vehicles. Parflex hoses are made to handle both on-road and off-road applications while helping you stay Tier IV and EPA 10 compliant. Combine these hoses with other high value Parflex fluid conveyance products (pilot lines, grease lines, hydraulic hoses, etc.) and customers can enjoy best in class durability and performance.

Unlike the competition's electrically heated hose, Parflex SCR hoses lock-in the heating elements with an extruded sheath for added protection and long-lasting uniform heating.



U.S. Patent No. 8,819,922

Check www.scrhose.com for product updates



For detailed ordering information, please consult price list or contact Parflex Division.



- Protective Overmolding
  -Protection against water ingression and damage of electrical components
  -Bolters fitting sgtrength and impact resistance
- Thermoplastic and EPDM core tubes reinforced for strength and flexibility
- Stainless steel heating wire
- Extruded thermoplastic jacket
- Heated fittings
- Optional heat/abrasion shield
- 100% electrically tested, pressure tested, and cleaned before shipped

Core Tube Material	I.D.	O.D.	with heat/ abrasion shield (optional)	Maximum Operating Pressure		Minimum Burst Pressure		Vacuum Resistance		Bend Radius
	mm	mm	mm	psi	bar	psi	bar	inch	Hg/bar	mm
EPDM	4	14.5	21	174	12	435	30	14.8	500	30
	5.5	14.5	21	174	12	435	30	14.8	500	40
Nylon	6	14	21	150	10	600	40	8.9	300	40

Operating Parameters

EPDM Temperature Range: -40°F (-40°C) to +248°F (+120°C) with spikes to +266°F (+130°C)
EPDM 5.5 mm Pressure Range: 174 psi. (12 bar) with spikes to 232 psi (16 bar)
Nylon Pressure Line Temperature Range: -40°F (-40°C) to +248°F (+120°C) with spikes to +284°F(+140°C)
Nylon Suction/Throttle Line Temperature Range: -40°F (-40°C) to +158°F (+70°C) with spikes to +221°F(+105°C)
Available in 12VDC, 24VDC, and unheated

Certifications

TS 16949
ISO 14001
IP6X, IPX8, and IPX9K Certified (4mm EPDM, 5.5mm EPDM, and 6mm Nylon)

Notes

EPDM 7.5 mm and 12.3 mm core tubes are available on request in custom configurations.
Standard lengths available in 500 mm increments, ranging from 500 mm (0.5 m) O.A.L. through 6000 mm (6.0 m) in most configurations.



Custom Options Available

SCR options include, but are not limited to:

- different electrical connectors, including options for heat and abrasion shield over lead wires;
- 1/4, 5/16, and 3/8 fittings; wide variety of lengths;
- 12V or 24V

Parflex also has designs for other sizes and core tubes for SCR hoses. These designs ensure that Parflex hoses can be utilized on SCR systems from multiple suppliers.

Notes

Permanent/Crimp

Field Attachable



Table of Contents

Intro

Hose Fitting Nomenclature E-3
Fitting Configurations by Connection and End Code E-4

Permanent/Crimp

54 Series E-7
56 Series E-10
91N Series E-31
92 Series E-40
93N Series E-41
94/95 Series E-44
PAGE Fittings E-45
CG Series E-53
CY Series E-59
SF Series E-64
MS Series E-62
SQ Series E-65

Field Attachable/Reuseable

51 Series E-5
90 Series E-26
BU Series E-52
MS Series E-63

Parflex Fittings

What's New?

In order to reduce the complexity for our customers, Parflex has converted 55, 58, 58H Series fittings to a new, CG Series fitting. The CG fittings will help customers reduce inventory and simplify ordering. Some of the CG Series fittings do require new crimp dies. For more details, contact Customer Service for a CG Conversion Bulletin.

We've continued the simplicity by converting the 57 Series into a 56 Series. This is a name change only. No new dies are required and there are no changes to the fitting dimensions.



Parker Legacy Fitting Nomenclature

Example: 10356-8-6

This example describes a permanent crimp 1/2" Male JIC 37° with a 3/8" I.D. hose size. This fitting is constructed of steel since the designated material is blank.

10356-8-6 – **Fitting Type** (1 = Permanent/Crimp)
(2 = Field Attachable Fitting)
1**03**56-8-6 – **End Configuration Code** (Male JIC 37°)
103**56**-8-6 – **Fitting Series** (Series 56)
10356-**8**-6 – **End Size** (1/2")
10356-8-**6** – **Hose I.D.** (3/8")
10356-8-6**C** – **Alternate Material**

Fitting part numbers that start with a "2" are field attachable fittings

Legacy Fitting Material Selection
- Blank = Steel (unless otherwise noted)
- C = Stainless Steel
- S = All Carbon Steel – Used only with PTFE Fittings

PAGE Fitting Nomenclature

Example: 08-16SAN-S

This example describes a permanent sanitary flange step down, 1/2" I.D. hose with a 1" sanitary flange. This fitting is constructed of stainless steel since the designated material is -S.

As demonstrated below, the nomenclature associated with the PAGE fitting is not consistent with the traditional Parker products, as the end size and hose I.D. are reversed and located at the front of the part construction.

08-16SAN-S – **Hose I.D.** (1/2")
08-**16**SAN-S – **End Size** (1")
08-16**SAN**-S – **End Configuration Code (Sanitary Flange)**
08-16SAN-**S** – **Alternate Material**

PAGE Fitting Material Selection
- C = Carbon Steel
- S = Stainless Steel






NOTE: *The PAGE fittings, which are designed for use with traditional PAGE fluoropolymer hoses only, are a two piece crimp connection and need to be combined with the corresponding crimp collars located on page E-46.*

Standard Fitting Configurations
by Connection and End Code


	Description	End Code
Pipe	Male NPTF Pipe - Rigid - Straight	01
	Male NPTF Pipe - Swivel - Straight	13
	Male NPTF Pipe - Swivel - 90° Elbow	1L
	Female NPTF Pipe - Rigid - Straight	02
	Female NPSM Pipe - Swivel - Straight (60° Cone)	07
SAE Str. Trd.	Male SAE Straight Thread with O-ring - Rigid - Straight	05
	Male SAE Straight Thread with O-ring - Swivel - Straight	0G
	Male SAE Straight Thread with O-ring - Swivel - 90° Elbow	0L
	Male SAE Straight Thread with O-ring - Adjustable - 90° Elbow	35
Flare	Male JIC 37° - Rigid - Straight	03
	Male JIC 37° - Bulkhead without Locknut - Straight	LB
	Female JIC 37° - Swivel - Straight	06
	Female JIC 37° - Swivel - 45° Elbow - Short Drop	37
	Female JIC 37° - Swivel - 45° Elbow - Medium Drop	L7
	Female JIC 37° - Swivel - 90° Elbow - Short Drop	39
	Female JIC 37° - Swivel - 90° Elbow - Medium Drop	L9
	Female JIC 37° - Swivel - 90° Elbow - Long Drop	41
	Male SAE 45° - Rigid - Straight	04
	Female SAE 45° - Swivel - Straight	08
	Female SAE 45 / Swivel - 45° Elbow	77
	Female SAE 45 / Swivel - 90° Elbow	79
	Female SAE 45 / Swivel - 90° Elbow - Long Drop	81
	Female JIC 37°/SAE 45° Dual Flare - Swivel - Straight	06
Inverted Flare	Male Inverted SAE 45° - Swivel - Straight	28
	Male Inverted SAE 45° - Swivel - 45° Elbow	67
	Male Inverted SAE 45° - Swivel - 90° Elbow	69
	Female Inverted SAE 45° - Rigid - Straight	29
Seal-Lok	Male Seal-Lok - Rigid - Straight (with O-ring)	J0
	Male Seal-Lok - Bulkhead without Locknut-Straight (with O-ring)	JB
	Female Seal-Lok - Swivel - Straight - Long	JS
	Female Seal-Lok - Swivel - Straight - Short	JC
	Female Seal-Lok - Swivel - 30° Elbow	J2
	Female Seal-Lok - Swivel - 22 1/2° Elbow	J6
	Female Seal-Lok - Swivel - 45° Elbow	J7
	Female Seal-Lok - Swivel - 90° Elbow - Short Drop	J9
	Female Seal-Lok - Swivel - 90° Elbow - Medium Drop	J5
	Female Seal-Lok - Swivel - 90° Elbow - Long Drop	J1
JIS	Female Metric Swivel - Straight (30° Flare)	MU
	Female BSP Parallel Pipe - Swivel - Straight (30° Flare)	FU
	Male BSP Taper Pipe - Rigid - Straight (60° Cone)	UT
	Female BSP Parallel Pipe - Swivel - Straight (60° Cone)	GU
	Female BSP Parallel Pipe - Swivel - 45° Elbow (60° Cone)	G1
	Female BSP Parallel Pipe - Swivel - 90° Elbow (60° Cone)	G2
Metric	Male Metric L - Rigid - Straight (24° Cone)	D0
	Male Standpipe Metric L - Rigid - Straight	1D

	Description	End Code
Metric	Female Metric L - Swivel - Straight (Ball Nose)	C3
	Female Metric L - Swivel - 45° Elbow (Ball Nose)	C4
	Female Metric L - Swivel - 90° Elbow (Ball Nose)	C5
	Female Metric L - Swivel - Straight (24° Cone with O-ring)	CA
	Female Metric L - Swivel - 45° Elbow (24° Cone with O-ring)	CE
	Female Metric L - Swivel - 90° Elbow (24° Cone with O-ring) -	CF
	Male Metric S - Rigid - Straight (24° Cone)	D2
	Male Standpipe Metric S - Rigid - Straight	3D
	Female Metric S - Swivel - Straight (Ball Nose)	C6
	Female Metric S - Swivel - 45° Elbow (Ball Nose)	C7
	Female Metric S - Swivel - 90° Elbow (Ball Nose)	C8
	Female Metric S - Swivel - Straight (24° Cone with O-ring)	C9
	Female Metric S - Swivel - 45° Elbow (24° Cone with O-ring)	0C
	Female Metric S - Swivel - 90° Elbow (24° Cone with O-ring)	1C
BSP	Male BSP Taper Pipe - Rigid - Straight	91
	Female BSP Parallel Pipe - Swivel - Straight (60° Cone)	92
	Male BSP Parallel Pipe - Rigid - Straight (60° Cone)	D9
	Female BSP Parallel Pipe - Swivel - 45° Elbow (60° Cone)	B1
	Female BSP Parallel Pipe - Swivel - 90° Elbow (60° Cone)	B2
	Female BSP Parallel Pipe - Swivel - 90° Elbow Block Type (60° Cone)	B4
	Female BSP Parallel Pipe - Swivel - Straight (Flat Seat)	B5
	Male BSP Taper Pipe - Rigid - 45° Elbow	BV
	Male BSP Taper Pipe - Rigid - 90° Elbow or Side Outlet	BZ
Fr. Gaz	Male French Gaz Series - Rigid - Straight (24° Cone)	FG
	Female French Gaz Series - Swivel - Straight (Ball Nose)	F4
Specialty	Male Ferulok Flareless Rigid-Straight (24° Cone with Nut & Ferrule)	11
	Female Ferulok Flareless - Swivel - Straight (24° Cone)	12
	DIN Metric Banjo - Straight	49
	ANSI B16.5 Flange	4K
	Female A-Lok® Compression	AL
	Female Cam & Groove	FC
	Sanitary Flange & Step Downs	FN
	Mini Sanitary Flange	FV
	Bulkhead w/Zerk Port Integrated	GK
	Male I-Line® Sanitary	H1
	Female I-Line® Sanitary	H2
	Male Sanitary Bevel Seat	H4
	Female Sanitary Bevel Seat	H5
	Male Standpipe - Rigid - Straight (Inch Size Tube O.D.)	34
	Male Standpipe - Rigid - Straight with V-Notch	TW
	Universal Tube Stub	TU
	Male Rapid Assembly, Straight	WU
	Male Rapid Assembly, 45° Elbow	WW
	Male Rapid Assembly, 90° Elbow	WY

51 Series Visual Index

51 Series FIELD ATTACHABLE	201 Male Taper Pipe Rigid	203 Male (JIC) 37°	206 SAE (JIC) 37° Swivel	208 SAE 45° Swivel	239 (JIC) 37° Swivel 90° Elbow Short
					
	E-5	E-5	E-6	E-6	E-6


20151 Male Taper Pipe Rigid



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	W Hex
#									
		inch	mm	inch	mm	inch	mm	inch	inch
20151-2-3	1/8-27	3/16	5	1.71	43	1	25	7/16	5/8
20151-4-3	1/4-18	3/16	5	1.90	48	1-1/8	29	9/16	5/8
20151-2-4	1/8-27	1/4	6	1.90	48	1	25	1/2	5/8
20151-4-4	1/4-18	1/4	6	2.08	53	1-3/16	30	9/16	5/8
20151-4-5	1/4-18	5/16	8	2.17	55	1-7/16	37	9/16	3/4
20151-6-5	3/8-18	5/16	8	2.17	55	1-7/16	37	3/4	3/4
20151-4-6	1/4-18	3/8	10	2.61	66	1-7/16	37	3/4	7/8
20151-6-6	3/8-18	3/8	10	2.61	66	1-7/16	37	3/4	7/8
20151-8-6	1/2-14	3/8	10	2.80	71	1-9/16	40	7/8	7/8
20151-6-8	3/8-18	1/2	13	2.99	76	1-1/2	38	7/8	1-1/16
20151-8-8	1/2-14	1/2	13	3.17	81	1-11/16	43	7/8	1-1/16
20151-12-12	3/4-14	3/4	19	3.42	87	1-3/4	44	1-1/8	1-3/8
20151-16-16	1-11-1/2	1	25	3.74	95	2-1/4	57	1-3/8	1-9/16

20351 Male (JIC) 37° Rigid




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	W Hex
#									
		inch	mm	inch	mm	inch	mm	inch	inch
20351-4-3	7/16-20	3/16	5	1.88	48	1-1/8	29	1/2	5/8
20351-5-4	1/2-20	1/4	6	2.06	52	1-1/8	29	9/16	5/8
20351-6-5	9/16-18	5/16	8	2.16	55	1-5/16	33	5/8	3/4
20351-6-6	9/16-18	3/8	10	2.61	66	1-7/16	37	3/4	7/8
20351-8-6	3/4-16	3/8	10	2.71	69	1-7/16	37	13/16	7/8
20351-8-8	3/4-16	1/2	13	3.08	78	1-5/8	41	7/8	1-1/16

51 series field attachable couplings are not intended for use on hose that has previously been in service.

20651 SAE (JIC) 37° Swivel




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex	W Hex
#										
		inch	mm	inch	mm	inch	mm	inch	inch	inch
20651-4-3	7/16-20	3/16	5	1.99	51	1-1/4	32	9/16	9/16	5/8
20651-4-4	7/16-20	1/4	6	2.18	55	1-1/4	32	9/16	9/16	5/8
20651-5-4	1/2-20	1/4	6	2.24	57	1-7/16	37	5/8	5/8	5/8
20651-6-4	9/16-18	1/4	6	2.34	59	1-7/16	37	11/16	11/16	5/8
20651-6-5	9/16-18	5/16	8	2.37	60	1-1/2	38	11/16	11/16	3/4
20651-6-6	9/16-18	3/8	10	2.74	70	1-7/16	37	11/16	11/16	7/8
20651-8-6	3/4-16	3/8	10	2.88	73	1-5/8	41	7/8	7/8	7/8
20651-8-8	3/4-16	1/2	13	3.25	83	1-3/4	44	7/8	7/8	1-1/16
20651-10-8	7/8-14	1/2	13	3.37	86	1-7/8	48	1	1	1-1/16
20651-12-12	1-1/16-12	3/4	19	3.75	95	2-1/8	54	1-1/4	1-1/4	1-3/8
20651-16-16	1/5/16-12	1	25	3.93	100	2-7/16	62	1-1/2	1-1/2	1-9/16

NOTE: Sizes -4, -5,-8 and -10 incorporate a dual seat.


20851 SAE 45° Swivel



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex	W Hex
#										
		inch	mm	inch	mm	inch	mm	inch	inch	inch
20851-6-6	5/8-18	3/8	10	2.82	72	1-9/16	40	3/4	3/4	7/8

23951 JIC 37° Swivel 90° Elbow Short Drop








Construction: Steel. Add "C" for Stainless Steel.





Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		H Hex	J Hex	W Hex
#												
		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch	inch
23951-4-3	7/16-20	3/16	5	1.77	45	1	25	0.83	21	3/8	9/16	5/8
23951-6-6	9/16-18	3/8	10	2.70	69	1-7/16	37	0.85	22	9/16	11/16	7/8
23951-8-6	3/4-16	3/8	10	2.90	74	1-5/8	41	1.09	28	11/16	7/8	7/8

51 series field attachable couplings are not intended for use on hose that has previously been in service.


54 Series Visual Index

54 Series
PERMANENT


106 Female SAE (JIC) 37° Swivel	137 Female (JIC) 37° Swl, 45° Elbow	139 Female (JIC) 37° Swl, 90° Elbow	1J7 Female Seal-Lok™ 45° Elbow	1J9 Female Seal-Lok™ 90° Elbow Short
 E-8	 E-8	 E-8	 E-7	 E-8

1JC Female Seal-Lok™ Str. Short O-ring	1WW Male Rapid Assembly, 45° Elb.	1WY Male Rapid Assembly, 90° Elb.	1WU Male Rapid Assembly, Straight
 E-7	 E-9	 E-9	 E-9

54 Series Adapter
PERMANENT

685RA Female Rapid Assy. Adapter Male SAE
 E-9


1JC54 Female Seal-Lok™ Straight Short O-ring Face Seal
ISO 12151-1 SWSA



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		C		H Hex
#										
		inch	mm	inch	mm	inch	mm	inch	mm	inch
1JC54-4-4	9/16-18	1/4	6	1.38	35	5/8	16	.32	8	11/16
1JC54-6-6	11/16-16	3/8	10	1.58	40	9/16	14	.32	8	13/16


1J754 Female Seal-Lok™ 45° Elbow O-ring Face Seal
ISO 12151-1 SWE45



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		inch	mm	inch	mm	inch	mm	inch	mm	inch
1J754-4-4	9/16-18	1/4	6	2.16	55	1-3/8	35	0.41	10	11/16


1J954 Female Seal-Lok™ 90° Elbow O-ring Face Seal Short Drop
ISO 12151-1 SWES90



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		inch	mm	inch	mm	inch	mm	inch	mm	inch
1J954-4-4	9/16-18	1/4	6	2.14	54	1-3/8	35	0.83	21	11/16
1J954-6-6	11/16-16	3/8	10	2.32	59	1-3/8	35	0.90	23	13/16

10654 Female SAE (JIC) 37° Swivel




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
#									
		inch	mm	inch	mm	inch	mm	inch	inch
10654-4-4	7/16-20	1/4	6	1.75	45	1	25	9/16	9/16
10654-6-6	9/16-18	3/8	10	2.13	54	1-3/16	30	11/16	11/16

NOTE: Sizs -4 incorporates a dual seat.


13754 Female JIC 37° Swivel 45° Elbow Short Drop



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		inch	mm	inch	mm	inch	mm	inch	mm	inch
13754-4-4	7/16-20	1/4	6	2.08	53	1-1/4	32	.33	8	9/16


13954 Female JIC 37° Swivel 90° Elbow Short Drop



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		inch	mm	inch	mm	inch	mm	inch	mm	inch
13954-4-4	7/16-20	1/4	6	1.97	50	1-3/16	30	.68	17	9/16
13954-6-6	9/16-18	3/8	10	2.30	59	1-5/8	41	.85	22	11/16

1WW54 Male Rapid Assembly 45º Elbow




Construction: Steel, Nitrile O-ring.
Add "C" for Stainless Steel.

Part Number	Stem O.D.		Hose I.D.		A		Cutoff Allow. B		E	
#										
	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
1WW54-4-4	1/4	6	1/4	6	1.97	50	1-3/16	30	.67	17
1WW54-6-6	3/8	10	3/8	10	2.19	56	1-3/16	30	.69	18

NOTE: Use with mating adapter PN 685RA.

1WY54 Male Rapid Assembly 90º Elbow




Construction: Steel, Nitrile O-ring.
Add "C" for Stainless Steel.

Part Number	Stem O.D.		Hose I.D.		A		Cutoff Allow. B		E	
#										
	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
1WY54-4-4	1/4	6	1/4	6	1.27	32	1/2	13	.90	23
1WY54-6-6	3/8	10	3/8	10	1.49	38	1/2	13	1.00	25

NOTE: Use with mating adapter PN 685RA.

1WU54 Male Rapid Assembly Straight




Construction: Steel, Nitrile O-ring.
Add "C" for Stainless Steel.

Part Number	Stem O.D.		Hose I.D.		A		Cutoff Allow. B	
#								
	inch	mm	inch	mm	inch	mm	inch	mm
1WU54-4-4	1/4	6	1/4	6	1.85	47	1-1/16	27
1WU54-6-6	3/8	10	3/8	10	2.13	54	1-1/8	29

NOTE: Use with mating adapter PN 685RA.

685RA Adapter Female Rapid Assembly - Male SAE Straight Thread ORB






































Construction: Steel, Nitrile O-ring.
Add "C" for Stainless Steel.

Part Number	Stem O.D.		Thread Size	A		H Hex
#						
	inch	mm		inch	mm	inch
685RA-4-4	1/4	6	7/16-20	1.05	27	11/16
685RA-6-4	3/8	10	7/16-20	1.15	29	3/4
685RA-4-6	1/4	6	9/16-18	1.12	28	3/4
685RA-6-6	3/8	10	9/16-18	1.15	29	3/4






NOTE: Use with mating fittings 1WU54, 1WW54, 1WY54.



56 Series Visual Index

56 Series
PERMANENT


101 Male Taper Pipe Rigid	**102** Female Taper Pipe Rigid	**103** Male (JIC) 37° Rigid	**104** Male SAE 45° Rigid	**105** Male Str. Thread O-ring
 E-11	 E-11	 E-12	 E-12	 E-12
106 SAE (JIC) 37° Swivel	**107** Female Pipe Swivel	**108** Female SAE 45° Swivel	**10C** M FM Swivel 24° O-ring 45° Elb. Lt.	**11C** M FM Swivel 24° O-ring 90° Elb. Lt.
 E-13	 E-13	 E-14	**METRIC**  E-20	**METRIC**  E-20
113 Male Pipe Swivel	**13E** Male (JIC) 37° Long	**137** FM JIC 37° Swivel 45° Elbow	**139** FM JIC 37° Swivel 90° Elbow	**141** Female JIC 37° Swivel 90° Elbow-Lg
 E-14	 E-14	 E-15	 E-15	 E-16
149 Banjo Union	**192** FM BSP Parallel Pipe Swivel Str.	**1AL** A-Lok Compression	**1B1** Female BSP Pipe Swivel 45° Elb. (60° Cone)	**1B2** Female BSP Pipe Swivel 90° Elb. (60° Cone)
 E-16	**METRIC**  E-20	 E-21	 E-21	 E-21
1B4 FM BSP Swivel 90° Elb. Block Type (60° Cone)	**1C3** M FM Swivel Nut Light	**1C4** M FM Swivel 45° Elbow Lt.	**1C5** M FM Swivel 90° Elbow Lt.	**1C6** M FM Swivel DIN 20078 HW w/o O-ring
 E-21	**METRIC**  E-22	**METRIC**  E-22	**METRIC**  E-22	**METRIC**  E-23
1C9 M FM Swivel DIN 20078 HW O-ring	**1CA** M FM Swivel 24° Lt. O-ring	**1CE** M FM Swivel 24° O-ring 45° Elb.	**1CF** M FM Swivel 24° Oring 90° Elb.	**1D0** M Male Stud DIN 20078 Lt.
METRIC  E-23	**METRIC**  E-23	**METRIC**  E-24	**METRIC**  E-24	**METRIC**  E-25
1D2 M Male Stud 24° Heavy	**1D9** Male BSPP - Str. (60° Cone)	**1J0** Male Seal-Lok™ Rigid Str. w/O-ring	**1J1** Female Seal-Lok™ 90° Elbow Long	**1J2** Female Seal-Lok™ 30° Elbow
METRIC  E-25	 E-25	 E-17	 E-17	 E-18

56 Series
PERMANENT

1J5 Female Seal-Lok™ Swivel 90° Elb.Med.	1J7 Female Seal-Lok™ Swivel 45° Elbow	1J9 Female Seal-Lok™ Swivel 90° Elb.Short	1JC Female Seal-Lok™ Str. Swivel Short	1JS Female Seal-Lok™ Straight
 E-18	 E-19	 E-19	 E-17	 E-18

1L9 Female JIC 37° Swivel 90° Elb. Med.	1TU Universal Inch Tube Stub End
 E-16	 E-19

10156 Male Taper Pipe Rigid




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#								
		inch	mm	inch	mm	inch	mm	inch
10156-2-2	1/8-27	1/8	3	1.35	34	3/4	19	1/2
10156-2-3	1/8-27	3/16	5	1.60	41	7/8	22	9/16
10156-4-2	1/4-18	1/8	3	1.56	40	15/16	24	5/8
10156-4-3	1/4-18	3/16	5	1.82	46	1-1/8	28	9/16
10156-4-4	1/4-18	1/4	6	2.09	53	1-1/8	28	9/16
10156-4-6	1/4-18	3/8	10	2.16	55	1-3/16	30	11/16
10156-6-6	3/8-18	3/8	10	2.16	55	1-3/16	30	3/4
10156-8-8	1/2-14	1/2	13	2.55	65	1-7/16	37	7/8
10156-12-10	3/4-14	5/8	16	2.88	73	1-9/16	40	1-1/8
10156-12-12	3/4-14	3/4	19	2.97	75	1-5/8	41	1-1/16
10156-16-16	1-11-1/2	1	25	3.76	96	1-7/8	48	1-3/8

NOTE: Metric hex parts are available upon request.


10256 Female Taper Pipe Rigid



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#								
		inch	mm	inch	mm	inch	mm	inch
10256-4-4	1/4-18	1/4	6	1.99	51	1	25	11/16

10356 Male (JIC) 37° Rigid




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#								
		inch	mm	inch	mm	inch	mm	inch
10356-4-3	7/16-20	3/16	5	1.83	46	1-1/8	28	9/16
10356-4-4	7/16-20	1/4	6	2.10	53	1-1/8	28	9/16
10356-5-4	1/2-20	1/4	6	2.10	53	1-1/8	28	9/16
10356-6-4	9/16-18	1/4	6	2.14	54	1-3/16	30	11/16
10356-6-5	9/16-18	5/16	8	2.22	56	1-3/16	30	11/16
10356-5-6	1/2-20	3/8	10	2.14	54	1-1/8	28	5/8
10356-6-6	9/16-18	3/8	10	2.15	55	1-3/16	30	5/8
10356-8-6	3/4-16	3/8	10	2.25	57	1-1/4	32	13/16
10356-8-8	3/4-16	1/2	13	2.40	61	1-5/16	33	7/8
10356-10-8	7/8-14	1/2	13	2.60	66	1-1/2	38	15/16
10356-12-10	1-1/16-12	5/8	16	2.97	75	1-5/8	42	1-1/8
10356-12-12	1-1/16-12	3/4	19	3.07	78	1-3/4	44	1-1/8
10356-16-16	1-5/16-12	1	25	3.66	93	1-3/4	44	1-3/8

NOTE: Metric hex parts are available upon request.

10456 Male SAE 45° Rigid




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#								
		inch	mm	inch	mm	inch	mm	inch
10456-4-3	7/16-20	3/16	5	1.71	43	1	25	9/16
10456-5-4	1/2-20	1/4	6	2.11	54	1-1/8	28	9/16
10456-6-5	5/8-18	5/16	8	2.18	55	1-3/16	30	11/16
10456-6-6	5/8-18	1/2	13	2.16	55	1-3/16	30	11/16
10456-6-8	5/8-18	1/2	13	2.37	60	1-1/4	32	3/4
10456-8-8	3/4-16	1/2	13	0.25	64	1-3/8	35	7/8
10456-12-12	1-1/16-14	3/4	19	3.11	79	1-3/4	44	1-1/8

10556 Male Straight Thread O-ring

(Nitrile O-ring included)




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#								
		inch	mm	inch	mm	inch	mm	inch
10556-4-3	7/16-20	3/16	4	1.61	41	15/16	24	9/16
10556-6-3	9/16-18	3/16	4	1.64	42	15/16	24	11/16
10556-4-4	7/16-20	1/4	6	1.84	47	7/8	22	9/16
10556-5-4	1/2-20	1/4	6	1.84	47	7/8	22	5/8
10556-6-4	9/16-18	1/4	6	1.91	49	15/16	24	11/16
10556-4-5	7/16-20	5/16	8	1.91	49	7/8	22	5/8
10556-5-5	1/2-20	5/16	8	1.91	49	7/8	22	5/8
10556-6-6	9/16-18	3/8	10	1.95	50	15/16	24	11/16
10556-8-6	3/4-16	3/8	10	1.98	50	1	25	7/8
10556-8-8	3/4-16	1/2	12	2.21	56	1-1/8	28	7/8
10556-10-8	7/8-14	1/2	12	2.28	58	1-3/16	30	1

NOTE: Metric hex parts are available upon request.

10656 SAE (JIC) 37° Swivel




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
#									
		inch	mm	inch	mm	inch	mm	inch	inch
10656-2-2	5/16-24	1/8	3	1.63	41	1	25	1/2	1/2
10656-3-2	3/8-24	1/8	3	1.60	41	1	25	1/2	9/16
10656-4-2	7/16-20	1/8	3	1.68	43	1	25	1/2	5/8
10656-3-3	3/8-24	3/16	5	1.91	49	1-3/16	30	1/2	1/2
10656-4-3	7/16-20	3/16	5	1.78	45	1-1/16	27	9/16	9/16
10656-5-3	1/2-20	3/16	5	1.84	47	1-1/8	28	9/16	5/8
10656-2-4	3/8-24	1/4	6	1.98	50	1	25	1/2	7/16
10656-4-4	7/16-20	1/4	6	2.05	52	1-1/16	27	9/16	9/16
10656-5-4	1/2-20	1/4	6	2.12	54	1-1/8	28	9/16	5/8
10656-6-4	9/16-18	1/4	6	2.14	54	1-3/16	30	11/16	9/16
10656-4-5	7/16-20	5/16	8	2.10	53	1-1/16	27	9/16	9/16
10656-5-5	1/2-20	5/16	8	2.21	56	1-3/16	30	5/8	5/8
10656-6-5	9/16-18	5/16	8	2.23	57	1-3/16	30	5/8	11/16
10656-4-6	7/16-20	3/8	10	2.09	53	1-1/8	28	9/16	9/16
10656-5-6	1/2-20	3/8	10	2.23	57	1-1/4	32	5/8	5/8
10656-6-6	9/16-18	3/8	10	2.22	56	1-1/4	32	11/16	11/16
10656-8-6	3/4-16	3/8	10	2.37	60	1-3/8	35	11/16	7/8
10656-6-8	9/16-18	1/2	13	2.42	61	1-5/16	33	3/4	11/16
10656-8-8	3/4-16	1/2	13	2.54	64	1-7/16	36	13/16	7/8
10656-10-8	7/8-14	1/2	13	2.64	67	1-1/2	38	7/8	1
10656-8-10	3/4-16	5/8	16	2.73	69	1-7/16	36	15/16	7/8
10656-10-10	7/8-14	5/8	16	2.99	76	1-11/16	43	15/16	1
10656-12-10	1-1/16-12	5/8	16	3.06	78	1-3/4	44	1-1/16	1-1/4
10656-10-12	7/8-14	3/4	19	2.88	73	1-1/2	38	1-1/16	1
10656-12-12	1-1/16-12	3/4	19	3.06	78	1-3/4	44	1-1/16	1-1/4
10656-16-12	1-5/16-12	3/4	19	3.27	83	1-15/16	49	1-1/4	1-1/2
10656-16-16	1-5/16-12	1	25	3.81	97	1-15/16	49	1-3/8	1-1/2
10656-20-16	1-5/8-12	1	25	3.96	101	2-1/16	52	1-5/8	2

NOTE: Metric hex parts are available upon request. Sizes -4, -5, -8 and -10 incorporate a dual seat.


10756 Female Pipe Swivel



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
#									
		inch	mm	inch	mm	inch	mm	inch	inch
10756-4-4	1/4-18	1/4	6	2.03	52	1-1/16	27	9/16	11/16
10756-4-5	1/4-18	5/16	8	2.09	53	1-1/16	27	9/16	11/16
10756-6-6	3/8-18	3/8	10	2.13	54	1-1/8	28	11/16	7/8
10756-8-8	1/2-14	1/2	13	2.40	61	1-5/16	33	7/8	1
10756-12-12	3/4-14	3/4	19	2.98	76	1-5/8	41	1-1/16	1-1/4
10756-16-16	1-11-1/2	1	25	3.74	95	1-7/8	48	1-3/8	1-1/2


10856 Female SAE 45° Swivel



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
#									
		inch	mm	inch	mm	inch	mm	inch	inch
10856-6-4	5/8-18	1/4	6	2.19	56	1-1/4	32	11/16	3/4
10856-6-5	5/8-18	5/16	8	2.28	58	1-1/4	32	11/16	3/4
10856-6-6	5/8-18	3/8	10	2.36	60	1-3/8	35	11/16	3/4
10856-12-12	1-1/16-14	3/4	19	3.06	78	1-3/4	44	1-1/16	1-1/4

11356 Male Pipe Swivel




Construction: Steel. Add "C" for Stainless Steel.
WARNING: Fittings allow minor movement to relieve stress on hose but are not recommended for continued or extensive swiveling. Not recommended for use in CNG applications

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		J Hex
#								
		inch	mm	inch	mm	inch	mm	inch
11356-2-2	1/8-27	3/16	5	2.85	73	2-1/8	54	5/8
11356-2-3	1/8-27	3/16	5	2.85	73	2-1/8	54	5/8
11356-4-3	1/4-18	3/16	5	2.59	66	1-7/8	48	5/8
11356-4-4	1/4-18	1/4	6	2.95	75	2	50	5/8
11356-4-5	1/4-18	5/16	8	2.95	75	1-15/16	49	5/8
11356-6-6	3/8-18	3/8	10	3.06	78	2-1/16	52	3/4
11356-8-6	1/2-14	3/8	10	3.24	82	2-1/4	57	7/8
11356-8-8	1/2-14	1/2	13	3.37	86	2-1/4	57	7/8
11356-12-12	3/4-14	3/4	19	3.71	94	2-3/8	60	1-1/4
11356-16-16	1-11-1/2	1	25	4.64	118	2-3/4	70	1-1/2

NOTE: Nitrile O-ring. See O-ring Material Selection section, pg. G-50.

13E56 Male (JIC) 37° Long




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#								
		inch	mm	inch	mm	inch	mm	inch
13E56-4-4	7/16-20	1/4	6	2.80	71	1-13/16	46	5/8
13E56-6-5	9/16-18	5/16	8	2.97	75	1-15/16	49	3/4
13E56-6-6	9/16-18	3/8	10	2.97	75	2	50	7/8
13E56-8-8	3/4-16	1/2	13	3.24	82	2-1/8	54	7/8

NOTE: Bulkhead Locknut sold separately. WLN Locknuts are manufactured by the Tube Fittings Division. Refer to Catalog 4300 for additional information.

13756 Female JIC 37° Swivel 45° Elbow




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		inch	mm	inch	mm	inch	mm	inch	mm	inch
13756-4-2	7/16-20	1/8	3	1.98	50	1-5/16	33	.33	8	9/16
13756-4-3	7/16-20	3/16	5	1.93	49	1-1/4	32	.39	10	9/16
13756-4-4	7/16-20	1/4	6	2.19	56	1-1/4	32	.39	10	9/16
13756-5-4	1/2-20	1/4	6	2.46	62	1-1/2	38	.39	10	5/8
13756-6-4	9/16-18	1/4	6	2.24	57	1-1/4	32	.43	11	11/16
13756-6-5	9/16-18	5/16	8	2.53	64	1-1/2	38	.43	11	11/16
13756-6-6	9/16-18	3/8	10	2.57	65	1-9/16	40	.43	11	11/16
13756-8-6	3/4-16	3/8	10	2.76	70	1-3/4	44	.59	15	7/8
13756-8-8	3/4-16	1/2	13	2.72	69	1-5/8	41	.59	15	7/8
13756-10-8	7/8-14	1/2	13	2.87	73	1-3/4	45	.63	16	1
13756-10-10	7/8-14	5/8	16	3.23	83	2	50	.63	16	1
13756-12-10	1-1/16-12	5/8	16	3.74	95	2.40	61	.83	21	1-1/4
13756-12-12	1-1/16-12	3/4	19	4.03	102	2-11/16	68	.83	21	1-1/4
13756-16-16	1-5/16-12	1	25	4.53	115	2.63	67	.94	24	1-1/2

NOTE: Metric hex parts are available upon request.

13956 Female JIC 37° Swivel 90° Elbow




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		inch	mm	inch	mm	inch	mm	inch	mm	inch
13956-4-2	7/16-20	1/8	3	1.83	46	1-1/4	32	.68	17	9/16
13956-4-3	7/16-20	3/16	5	1.75	44	1-1/16	27	.83	21	9/16
13956-4-4	7/16-20	1/4	6	2.01	51	1-1/16	27	.83	21	9/16
13956-5-4	1/2-20	1/4	6	2.01	51	1-1/16	27	.83	21	5/8
13956-6-4	9/16-18	1/4	6	2.01	51	1-1/16	27	.91	23	11/16
13956-6-5	9/16-18	5/16	8	2.14	54	1-1/8	28	.91	23	11/16
13956-6-6	9/16-18	3/8	10	2.22	56	1-1/4	32	.91	23	11/16
13956-8-6	3/4-16	3/8	10	2.55	65	1-9/16	40	1.14	29	7/8
13956-8-8	3/4-16	1/2	13	2.48	63	1-3/8	35	1.14	29	7/8
13956-10-8	7/8-14	1/2	13	2.60	66	1-1/2	38	1.26	32	1
13956-10-10	7/8-14	5/8	16	3.08	78	1-3/4	45	1.26	32	1
13956-12-10	1-1/16-12	5/8	19	3.39	86	2-1/16	52	1.89	48	1-1/4
13956-12-12	1-1/16-12	3/4	19	3.89	99	2-9/16	65	1.89	48	1-1/4
13956-16-16	1-5/16-12	1	25	4.50	114	2.60	66	2.20	56	1-1/2

NOTE: Metric hex parts are available upon request.


14156 Female JIC 37° Swivel 90° Elbow Long Drop



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		inch	mm	inch	mm	inch	mm	inch	mm	inch
14156-4-3	7/16-20	3/16	5	2.00	51	1-5/16	33	1.81	46	9/16
14156-4-4	7/16-20	1/4	6	2.31	59	1-3/8	35	1.81	46	9/16
14156-5-4	1/2-20	1/4	6	2.34	60	1-3/8	35	1.81	46	5/8
14156-6-4	9/16-18	1/4	6	2.39	61	1-7/16	36	2.13	54	11/16
14156-6-5	9/16-18	5/16	8	2.36	60	1-5/16	33	2.13	54	11/16
14156-6-6	9/16-18	3/8	10	2.39	61	1-3/8	35	2.13	54	11/16
14156-8-6	3/4-16	3/8	10	2.49	63	1-1/2	38	2.52	64	7/8
14156-8-8	3/4-16	1/2	13	2.61	66	1-1/2	38	2.52	64	7/8
14156-10-8	7/8-14	1/2	13	2.48	63	1-3/8	35	2.76	70	1
14156-12-12	1-1/16-12	3/4	19	3.59	91	2-1/4	57	3.78	96	1-1/4
14156-16-16	1-5/16-12	1	25	4.36	111	2-1/2	63	4.49	114	1-1/2


1L956 Female JIC 37° Swivel 90° Elbow Medium Drop



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		inch	mm	inch	mm	inch	mm	inch	mm	inch
1L956-4-3	7/16-20	3/16	5	1.97	50	1-1/4	32	1.26	32	9/16
1L956-4-4	7/16-20	1/4	6	2.29	58	1-5/16	34	1.26	32	9/16
1L956-5-4	1/2-20	1/4	6	2.31	59	1-3/8	35	1.26	32	5/8
1L956-6-5	9/16-18	5/16	8	2.33	59	1-5/16	34	1.50	38	11/16
1L956-6-6	9/16-18	3/8	10	2.36	60	1-1/4	31	1.50	38	11/16
1L956-8-6	3/4-16	3/8	10	2.44	62	1-7/16	37	1.61	41	7/8
1L956-8-8	3/4-16	1/2	13	2.57	65	1-7/16	37	1.61	41	7/8
1L956-10-8	7/8-14	1/2	13	2.48	63	1-3/8	35	1.85	47	1
1L956-12-12	1-1/16-12	3/4	19	3.89	99	2-9/16	65	2.28	58	1-1/4
1L956-16-16	1-5/16-12	1	25	4.36	111	2-1/2	63	2.80	71	1-1/2


14956 – Banjo Union
DIN7642



Construction: Steel.

Part Number	Diameter R	Hose I.D.		A		Cutoff Allow. B	
#	∅						
	mm	mm	inch	mm	inch	mm	inch
14956-14-3	14	5	3/16	49	1.93	31	1.22
14956-12-4	12	6	1/4	50	1.97	25	1.50
14956-14-4	14	6	1/4	56	2.20	32	1.26
14956-12-5	12	8	5/16	54	2.13	29	1.14
14956-14-5	14	8	5/16	53	2.09	27	1.06
14956-16-6	16	10	3/8	58	2.28	33	1.30
14956-17-6	17	10	3/8	55	2.17	29	1.14

1J056 Male Seal-Lok™ Rigid Straight w/O-ring
ISO 12151-1-S




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#								
		inch	mm	inch	mm	inch	mm	inch
1J056-4-4	9/16-18	1/4	6	1.93	49	15/16	24	5/8
1J056-6-4	11/16-16	1/4	6	2.01	51	1-1/16	27	3/4
1J056-6-6	11/16-16	3/8	10	1.98	50	1	25	3/4
1J056-8-6	13/16-16	1/2	13	2.16	55	1-3/16	30	7/8
1J056-8-8	13/16-16	1/2	13	2.18	55	1-1/16	27	7/8

NOTE: Metric hex parts are available upon request.

1J156 Female Seal-Lok™ Swivel 90° Elbow Long Drop
ISO 12151-1-SWEL90




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		inch	mm	inch	mm	inch	mm	inch	mm	inch
1J156-4-3	9/16-18	3/16	5	2.05	52	1-3/8	35	1.81	46	11/16
1J156-4-4	9/16-18	1/4	6	2.37	60	1-3/8	35	1.81	46	11/16
1J156-6-4	11/16-16	1/4	6	2.45	62	1-1/2	38	2.13	54	13/16
1J156-6-6	11/16-16	3/8	10	2.45	62	1-7/16	37	2.13	54	13/16
1J156-8-6	13/16-16	3/8	10	2.53	64	1-7/16	37	2.52	64	15/16
1J156-8-8	13/16-16	1/2	13	2.67	68	1-9/16	40	2.52	64	15/16
1J156-12-12	1-3/16-12	3/4	19	3.59	91	2-1/4	57	3.78	96	1-3/8
1J156-16-16	1-7/16-12	1	25	4.36	111	2-1/2	63	4.49	114	1-5/8

NOTE: Metric hex parts are available upon request.

1JC56 Female Seal-Lok™ Straight Swivel Short
ISO 12151-1-SWSA




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		C		H Hex	J Hex
#											
		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
1JC56-4-2	9/16-18	1/8	3	1.34	34	3/4	19	0.32	8	5/8	11/16
1JC56-4-3	9/16-18	3/16	5	1.58	40	7/8	22	.32	8	9/16	11/16
1JC56-4-4	9/16-18	1/4	6	1.86	47	7/8	22	.32	8	9/16	11/16
1JC56-6-4	11/16-16	1/4	6	1.90	48	15/16	24	.34	9	11/16	13/16
1JC56-4-5	9/16-18	5/16	8	1.81	46	13/16	21	.32	8	11/16	11/16
1JC56-6-5	11/16-16	5/16	8	1.95	49	15/16	24	.34	9	11/16	13/16
1JC56-4-6	9/16-18	3/8	10	1.91	48	15/16	24	.32	8	5/8	11/16
1JC56-6-6	11/16-16	3/8	19	1.89	48	7/8	22	.34	9	11/16	13/16
1JC56-8-6	13/16-16	3/8	10	2.00	51	1	25	.43	11	13/16	15/16
1JC56-8-8	13/16-16	1/2	13	2.13	54	1	25	.43	11	13/16	15/16
1JC56-10-8	1-14	1/2	13	2.30	58	1-3/16	30	.48	12	15/16	1-1/8
1JC56-10-10	1-14	5/8	16	2.48	63	1-3/16	30	.48	12	15/16	1-1/8
1JC56-12-10	1-3/16-12	5/8	16	2.61	66	1-5/16	33	.55	14	1-1/8	1-3/8
1JC56-10-12	1-14	3/4	19	2.50	64	1-3/16	30	.48	12	1-1/8	1-1/8
1JC56-12-12	1-3/16-12	3/4	19	2.54	65	1-3/16	30	.55	14	1-1/8	1-3/8
1JC56-16-16	1-7/16-12	1	25	3.21	82	1-5/16	33	.56	14	1-3/8	1-5/8

NOTE: Metric hex parts are available upon request.

1JS56 Female Seal-Lok™ Straight
ISO 12151-1-SWSB




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
#									
		inch	mm	inch	mm	inch	mm	inch	inch
1JS56-4-3	9/16-18	3/16	5	1.89	48	1-3/16	30	9/16	11/16
1JS56-4-4	9/16-18	1/4	6	2.17	51	1-3/16	30	9/16	11/16
1JS56-6-4	11/16-16	1/4	6	2.24	57	1-1/4	32	11/16	13/16
1JS56-6-5	11/16-16	5/16	8	2.29	58	1-1/4	32	11/16	13/16
1JS56-6-6	11/16-16	3/8	10	2.28	58	1-5/16	33	11/16	13/16
1JS56-8-6	13/16-16	3/8	10	2.40	61	1-7/16	36	13/16	15/16
1JS56-6-8	11/16-16	1/2	13	2.40	61	1-5/16	33	3/4	13/16
1JS56-8-8	13/16-16	1/2	13	2.52	64	1-3/8	35	13/16	15/16
1JS56-10-8	1-14	1/2	13	2.68	68	1-9/16	40	15/16	1-1/8
1JS56-10-10	1-14	5/8	16	2.92	74	1-5/8	41	15/16	1-1/8
1JS56-12-12	1-3/16-12	3/4	19	3.17	81	1-13/16	46	1-1/8	1-3/8
1JS56-16-16	1-7/16-12	1	25	3.76	96	1-7/8	48	1-3/8	1-5/8

NOTE: Metric hex parts are available upon request.


1J256 Female Seal-Lok™ Swivel 30° Elbow



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		inch	mm	inch	mm	inch	mm	inch	mm	inch
1J256-8-8	13/16-16	1/2	13	2.84	72	1-11/16	43	.43	11	15/16

1J556 Female Seal-Lok™ Swivel 90° Elbow Medium Drop
ISO 12151-1-SWEM90




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		inch	mm	inch	mm	inch	mm	inch	mm	inch
1J556-4-3	9/16-18	3/16	5	1.89	48	1-3/16	30	1.26	32	11/16
1J556-4-4	9/16-18	1/4	6	2.14	53	1-1/8	28	1.26	32	11/16
1J556-6-4	11/16-16	1/4	6	2.14	55	1-3/16	30	1.50	38	13/16
1J556-6-5	11/16-16	5/16	8	2.28	58	1-1/4	32	1.50	38	13/16
1J556-6-6	11/16-16	3/8	10	2.42	61	1-7/16	36	1.50	38	13/16
1J556-8-6	13/16-16	3/8	10	2.22	56	1-1/4	32	1.61	41	15/16
1J556-8-8	13/16-16	1/2	13	2.48	63	1-3/8	35	1.61	41	15/16
1J556-10-8	1-14	1/2	13	2.48	63	1-3/8	35	1.85	47	1-1/8
1J556-10-10	1-14	5/8	16	2.83	72	1-1/2	38	1.85	47	1-1/8
1J556-12-12	1-3/16-12	3/4	19	3.59	91	2-1/4	57	2.28	58	1-3/8
1J556-16-16	1-7/16-12	1	25	4.36	111	2-1/2	63	2.80	71	1-5/8

NOTE: Metric hex parts are available upon request.

1J756 Female Seal-Lok™ Swivel 45° Elbow
ISO 12151-1-SWE45




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		inch	mm	inch	mm	inch	mm	inch	mm	inch
1J756-4-2	9/16-18	1/8	3	2.07	53	1-7/16	36	0.39	10	11/16
1J756-4-3	9/16-18	3/16	5	2.00	51	1-5/16	33	.39	10	11/16
1J756-4-4	9/16-18	1/4	6	2.25	57	1-1/4	32	.39	10	11/16
1J756-6-4	11/16-16	1/4	6	2.27	58	1-5/16	33	.43	11	13/16
1J756-6-5	11/16-16	5/16	8	2.32	59	1-3/8	35	.43	11	13/16
1J756-4-6	9/16-18	3/8	10	2.25	57	1-1/4	32	.39	10	11/16
1J756-6-6	11/16-16	3/8	10	2.35	60	1-3/8	35	.43	11	13/16
1J756-8-6	13/16-16	3/8	10	2.54	65	1-9/16	40	.59	15	15/16
1J756-8-8	13/16-16	1/2	13	2.72	69	1-5/8	41	.59	15	15/16
1J756-10-10	1-14	5/8	16	3.27	83	2	50	.63	16	1-1/8
1J756-12-12	1-3/16-12	3/4	19	4.03	102	2-11/16	68	.83	21	1-3/8
1J756-16-16	1-7/16-12	1	25	4.53	115	2.63	67	.94	24	1-5/8

NOTE: Metric hex parts are available upon request.

1J956 Female Seal-Lok™ Swivel 90° Elbow Short Drop
ISO 12151-1-SWE90




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		inch	mm	inch	mm	inch	mm	inch	mm	inch
1J956-4-2	9/16-18	1/8	3	2.04	52	1-7/16	36	0.83	21	11/16
1J956-4-3	9/16-18	3/16	5	1.89	48	1-3/16	30	.83	21	11/16
1J956-4-4	9/16-18	1/4	6	2.14	53	1-1/8	28	.83	21	11/16
1J956-6-4	11/16-16	1/4	6	2.14	55	1-3/16	30	.91	23	13/16
1J956-6-5	11/16-16	5/16	8	2.28	58	1-1/4	32	.91	23	13/16
1J956-6-6	11/16-16	3/8	10	2.22	56	1-1/4	32	.91	23	13/16
1J956-8-6	13/16-16	3/8	10	2.22	56	1-1/4	32	1.14	29	15/16
1J956-8-8	13/16-16	1/2	13	2.48	63	1-3/8	35	1.14	29	15/16
1J956-10-8	1-14	1/2	13	2.48	63	1-3/8	35	1.26	32	1-1/8
1J956-10-10	1-14	5/8	16	3.08	78	1-3/4	45	1.26	32	1-1/8
1J956-12-12	1-3/16-12	3/4	19	3.89	99	2-9/16	65	1.89	48	1-3/8
1J956-16-16	1-7/16-12	1	25	4.50	114	2.60	66	2.20	56	1-5/8

NOTE: Metric hex parts are available upon request.

1TU56 Universal Inch Tube Stub End




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Diameter R	Hose I.D.		A		Cutoff Allow. B		C		H Hex
#	∅									
	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch
1TU56-4-4	1/4	1/4	6	2.35	60	1-3/8	35	.72	18	5/8
1TU56-6-4	3/8	1/4	6	2.41	61	1-7/16	36	.78	20	11/16
1TU56-6-6	3/8	3/8	10	2.46	62	1-7/16	36	.78	20	3/4
1TU56-8-8	1/2	1/2	13	2.68	68	1-9/16	40	1.03	26	3/4
1TU56-12-12	3/4	3/4	19	2.88	73	1-9/16	40	1.03	26	1
1TU56-16-16	1	1	25	4.03	102	1-7/8	48	1.03	26	1-1/4

NOTE: Use with A-Lok & CPI nuts, sleeves and adapters. These components are manufactured by Parker's Instrumentation Connectors Division. Refer to catalogs 4230 & 4233 for additional information.


10C56 – Metric Female Swivel 24° With O-ring 45° Elbow
Heavy Series, ISO 12151-2



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		mm	inch	mm	inch	mm	inch	mm	inch	mm
10C56-6-3	M14x1.5	5.0	3/16	58	2.28	40	1.57	16	0.63	17
10C56-8-3	M16x1.5	5	3/16	59	2.32	41	1.61	18	0.71	19
10C56-10-4	M18x1.5	6	1/4	64	2.52	40	1.57	17	0.67	22
10C56-12-5	M20x1.5	8	5/16	69	2.72	43	1.69	17	0.67	24
10C56-12-6	M20x1.5	10	3/8	75	2.95	49	1.93	20	0.79	24
10C56-16-8	M24x1.5	13	1/2	80	3.15	51	2.01	23	0.91	30


11C56 – Metric Female Swivel 24° With O-ring 90° Elbow
Heavy Series, ISO 12151-2



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		mm	inch	mm	inch	mm	inch	mm	inch	mm
11C56-8-3	M16x1.5	5	3/16	48	1.89	30	1.18	29	1.14	19
11C56-10-4	M18x1.5	6	1/4	53	2.09	29	1.14	32	1.26	22
11C56-12-5	M20x1.5	8	5/16	65	2.56	39	1.54	34	1.34	24
11C56-12-6	M20x1.5	10	3/8	63	2.48	38	1.50	37	1.46	24
11C56-16-8	M24x1.5	13	1/2	68	2.68	40	1.57	45	1.77	30


19256 Female BSP Parallel Pipe Swivel Straight (60° Cone)



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		J Hex
#								
		mm	inch	mm	inch	mm	inch	mm
19256-4-3	G 1/4	5	3/16	35	1.38	17	0.67	19
19256-2-4	G 1/8	6	1/4	43	1.69	18	0.71	14
19256-4-4	G 1/4	6	1/4	42	1.65	17	0.67	19
19256-6-4	G 3/8	6	1/4	45	1.77	20	0.79	22
19256-4-5	G 1/4	8	5/16	47	1.85	21	0.83	19
19256-6-5	G 3/8	8	5/16	46	1.81	20	0.79	22
19256-6-6	G 3/8	10	3/8	46	1.81	21	0.83	22
19256-8-6	G 1/2	10	3/8	48	1.77	23	0.91	27
19256-6-8	G 3/8	13	1/2	53	2.09	25	0.98	22
19256-8-8	G 1/2	13	1/2	51	2.01	23	0.91	27
19256-10-8	G 5/8	13	1/2	49	1.93	22	0.87	30
19256-12-12	G 3/4	19	3/4	60	2.36	26	1.02	32
19256-16-16	G 1	25	1	74	2.91	26	1.02	41

1AL56 A-LOK® Compression (With Nut and Ferrule)




Construction: 316 Stainless nipple and shell.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
#									
		inch	mm	inch	mm	inch	mm	inch	inch
1AL56-4-4	7/16-20	1/4	6	1/4	6	1.91	49	9/16	9/16
1AL56-6-6	9/16-20	3/8	10	3/8	10	2.09	53	11/16	11/16
1AL56-8-8	3/4-20	1/2	13	3/8	10	2.21	56	7/8	7/8

NOTE: Nut part No. is XNUX or XNUX-316 for stainless steel.
Front ferrule part No. is XFFX or XFFX-316 for stainless steel.
Back ferrule part No. is XBFX or XBFX-316 for stainless steel.
X denotes dash size.


1B156 – Female BSP Parallel Pipe Swivel 45° Elbow (60° Cone) ISO 228-1



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		mm	inch	mm	inch	mm	inch	mm	inch	mm
1B156-4-3	G 1/4	5	3/16	57	2.24	15	0.59	39	1.542	19
1B156-4-4	G 1/4	6	1/4	62	2.44	15	0.59	38	1.50	19
1B156-6-5	G 3/8	8	5/16	65	2.56	17	0.67	39	1.54	22
1B156-6-6	G 3/8	10	3/8	67	2.64	17	0.67	42	1.65	22
1B156-8-8	G 1/2	13	1/2	77	3.03	20	0.79	48	1.89	27
1B156-12-12	G 3/4	19	3/4	99	3.90	25	1.00	65	2.56	32
1B156-16-16	G 1	25	1	127	5.00	31	1.22	79	3.11	41


1B256 – Female BSP Parallel Pipe Swivel 90° Elbow (60° Cone) ISO 228-1



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		mm	inch	mm	inch	mm	inch	mm	inch	mm
1B256-4-3	G 1/4	5	3/16	48	1.89	28	1.10	30	1.18	19
1B256-4-4	G 1/4	6	1/4	53	2.09	28	1.10	29	1.14	19
1B256-4-5	G 1/4	8	5/16	56	2.20	34	1.34	30	1.18	19
1B256-6-5	G 3/8	8	5/16	55	2.16	30	1.18	30	1.18	22
1B256-6-6	G 3/8	10	3/8	60	2.36	33	1.30	31	1.22	22
1B256-8-8	G 1/2	13	1/2	70	2.76	40	1.57	42	1.65	27
1B256-12-12	G 3/4	19	3/4	92	3.62	52	2.05	58	2.28	32
1B256-16-16	G 1	25	1	125	4.92	68	2.68	77	3.03	41


1B456 – Female BSP Parallel Swivel 90° Elbow Block Type (60° Cone) ISO 228-1



Construction: Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		mm	inch	mm	inch	mm	inch	mm	inch	mm
1B456-4-4	G 1/4	6	1/4	47	1.85	22	0.87	22	0.87	19
1B456-6-6	G 3/8	10	3/8	52	2.05	27	1.06	25	0.98	22
1B456-8-8	G 1/2	13	1/2	58	2.28	29	1.14	29	1.14	27


1C356 – Metric Female Swivel Nut
Light Series, 24°/60°



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		J Hex
#								
		mm	inch	mm	inch	mm	inch	mm
1C356-6-3	M12x1.5	5	3/16	37	1.46	20	0.79	14
1C356-8-4	M14x1.5	6	1/4	44	1.73	20	0.79	17
1C356-10-4	M16x1.5	6	1/4	45	1.77	21	0.83	19
1C356-10-5	M16x1.5	8	5/16	46	1.81	20	0.79	19
1C356-12-5	M18x1.5	8	5/16	47	1.85	21	0.83	22
1C356-10-6	M16x1.5	10	3/8	46	1.81	21	0.83	19
1C356-12-6	M18x1.5	10	3/8	47	1.85	21	0.83	22
1C356-15-6	M22x1.5	10	3/8	46	1.81	21	0.83	27
1C356-15-8	M22x1.5	13	1/2	50	1.97	21	0.83	27
1C356-18-10	M26x1.5	16	5/8	57	2.24	25	0.98	32
1C356-18-12	M26x1.5	19	3/4	58	2.28	24	0.94	32
1C356-22-12	M30x2	19	3/4	60	2.36	27	1.06	36


1C456 – Metric Female Swivel 45° Elbow
Light Series, 24°/60°



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		mm	inch	mm	inch	mm	inch	mm	inch	mm
1C456-6-3	M12x1.5	5	3/16	57	2.24	40	1.57	16	0.63	14
1C456-8-4	M14x1.5	6	1/4	60	2.36	36	1.42	14	0.55	17
1C456-10-5	M16x1.5	8	5/16	62	2.44	37	1.46	15	0.59	19
1C456-10-6	M16x1.5	10	3/8	67	2.64	41	1.61	17	0.67	19
1C456-12-6	M18x1.5	10	3/8	72	2.83	47	1.85	18	0.71	22
1C456-15-8	M22x1.5	13	1/2	76	2.99	48	1.89	19	0.75	27


1C556 – Metric Female Swivel 90° Elbow
Light Series, 24°/60°



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		mm	inch	mm	inch	mm	inch	mm	inch	mm
1C556-6-3	M12x1.5	5	3/16	48	1.89	30	1.18	30	1.18	14
1C556-8-4	M14x1.5	6	1/4	53	2.09	28	1.10	26	1.02	17
1C556-10-4	M16x1.5	6	1/4	53	2.09	28	1.10	27	1.06	19
1C556-12-5	M18x1.5	8	5/16	58	2.28	33	1.30	34	1.34	22
1C556-10-6	M16x1.5	10	3/8	63	2.48	38	1.50	33	1.30	19
1C556-12-6	M18x1.5	10	3/8	63	2.48	38	1.50	34	1.34	22
1C556-15-8	M22x1.5	13	1/2	72	2.83	44	1.73	39	1.54	27
1C556-18-12	M26x1.5	19	3/4	87	3.43	53	2.09	52	2.05	32


1C656 – Female Metric Swivel DIN 20078
Heavy Series (Without O-ring) ISO 8434-1



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		J Hex
#								
		mm	inch	mm	inch	mm	inch	mm
1C656-8-3	M16x1.5	5	3/16	38	1.50	20	0.79	19
1C656-10-4	M18x1.5	6	1/4	47	1.85	22	0.87	22
1C656-12-5	M20x1.5	8	5/16	50	1.97	24	0.94	24
1C656-12-6	M20x1.5	10	3/8	49	1.93	24	0.94	24
1C656-14-6	M22x1.5	10	3/8	49	1.93	23	0.89	27
1C656-16-8	M24x1.5	10	1/2	53	2.09	25	0.98	30
1C656-20-12	M30x2	13	3/4	61	2.40	27	1.06	36


1C956 – Female Metric Swivel DIN 20078
Heavy Series (With O-ring) ISO 12151-2-SWS



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		J Hex
#								
		mm	inch	mm	inch	mm	inch	mm
1C956-8-3	M16x1.5	5	3/16	41	1.61	23	0.91	19
1C956-8-4	M16x1.5	6	1/4	48	1.89	23	0.91	19
1C956-10-4	M18x1.5	6	1/4	48	1.89	23	0.91	22
1C956-12-4	M20x1.5	6	1/4	48	1.89	24	0.94	24
1C956-10-5	M18x1.5	8	5/16	49	1.93	23	0.91	22
1C956-12-5	M20x1.5	8	5/16	50	1.97	24	0.94	24
1C956-12-6	M20x1.5	10	3/8	49	1.93	24	0.94	24
1C956-14-6	M22x1.5	10	3/8	49	1.93	24	0.94	27
1C956-16-8	M24x1.5	13	1/2	56	2.17	27	1.06	30
1C956-20-12	M30x2	19	3/4	65	2.56	31	1.22	36
1C956-25-12	M36x2	19	3/4	66	2.60	32	1.30	46


1CA56 – Metric Female Swivel 24° With O-ring
Light Series, ISO 12151-2-SWS



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		J Hex
#								
		mm	inch	mm	inch	mm	inch	mm
1CA56-6-3	M12x1.5	5	3/16	40	1.57	22	0.87	14
1CA56-6-4	M12x1.5	6	1/4	48	1.89	24	0.94	14
1CA56-8-4	M14x1.5	6	1/4	47	1.85	23	0.91	17
1CA56-10-4	M16x1.5	6	1/4	47	1.85	22	0.87	19
1CA56-12-4	M18x1.5	6	1/4	47	1.85	22	0.87	22
1CA56-10-5	M16x1.5	8	5/16	48	1.89	22	0.87	19
1CA56-12-5	M18x1.5	8	5/16	48	1.89	22	0.87	22
1CA56-10-6	M16x1.5	10	3/8	48	1.89	22	0.87	19
1CA56-12-6	M18x1.5	10	3/8	48	1.89	22	0.87	22
1CA56-15-6	M22x1.5	10	3/8	50	1.97	25	0.98	27
1CA56-12-8	M18x1.5	13	1/2	53	2.09	27	1.06	22
1CA56-15-8	M22x1.5	13	1/2	53	2.09	25	0.98	27
1CA56-18-8	M26x1.5	13	1/2	53	2.09	25	0.98	32
1CA56-18-10	M26x1.5	16	5/8	60	2.36	26	1.02	32
1CA56-18-12	M26x1.5	19	3/4	60	2.36	26	1.02	32
1CA56-22-12	M30x2	19	3/4	62	2.44	28	1.10	36
1CA56-28-16	M36x2	25	1	77	3.03	28	1.10	41


1CE56 – Metric Female Swivel 24° With O-ring 45° Elbow
Light Series, ISO 12151-2-SWE45



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		mm	inch	mm	inch	mm	inch	mm	inch	mm
1CE56-6-3	M12x1.5	5	3/16	58	2.28	40	1.57	17	0.67	14
1CE56-8-4	M14x1.5	6	1/4	65	2.56	40	1.57	18	0.71	17
1CE56-10-4	M16x1.5	6	1/4	62	2.44	38	1.50	16	0.63	19
1CE56-10-5	M16x1.5	8	5/16	72	2.83	46	1.81	18	0.71	19
1CE56-10-6	M16x1.5	10	3/8	75	2.95	50	1.97	19	0.75	19
1CE56-12-6	M18x1.5	10	3/8	73	2.87	48	1.89	19	0.75	22
1CE56-15-8	M22x1.5	13	1/2	78	3.07	50	1.97	22	0.87	27
1CE56-18-10	M26x1.5	16	5.8	89	3.50	56	2.20	24	0.94	32
1CE56-18-12	M26x1.5	19	3/4	101	3.74	67	2.64	27	1.06	32
1CE56-22-12	M30x2	19	3/4	100	3.94	66	2.60	26	1.02	36
1CE56-28-16	M36x2	25	1	133	5.27	85	3.35	33	1.30	41


1CF56 – Metric Female Swivel 24° With O-ring 90° Elbow
Light Series, ISO 12151-2-SWE90



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		mm	inch	mm	inch	mm	inch	mm	inch	mm
1CF56-6-3	M12x1.5	5	3/16	48	1.89	30	1.18	30	1.18	14
1CF56-6-4	M12x1.5	6	1/6	53	2.09	29	1.14	33	1.30	14
1CF56-8-4	M14x1.5	6	1/6	55	2.17	30	1.18	29	1.14	17
1CF56-10-4	M16x1.5	6	1/6	55	2.17	31	1.22	29	1.14	17
1CF56-10-5	M16x1.5	8	5/16	66	2.60	40	1.57	29	1.14	19
1CF56-12-5	M18x1.5	8	5/16	65	2.56	40	1.57	30	1.18	22
1CF56-10-6	M16x1.5	10	3/8	64	2.52	39	1.54	37	1.46	19
1CF56-12-6	M18x1.5	10	3/8	63	2.48	38	1.50	35	1.38	22
1CF56-15-8	M22x1.5	13	1/2	68	2.68	40	1.57	43	1.69	27
1CF56-18-10	M26x1.5	16	5/8	79	3.11	45	1.77	52	2.05	32
1CF56-22-12	M30x2	19	3/4	91	3.58	57	2.24	55	2.17	36
1CF56-28-16	M36x2	25	1	122	50	74	2.91	71	2.80	41


1D056 - Male Stud DIN 20078
Light Series, ISO 8434-1



Construction: Steel. Add “C” for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#								
		mm	inch	mm	inch	mm	inch	mm
1D056-6-3	M12x1.5	5	3/16	41	1.61	23	0.91	12
1D056-6-4	M12x1.5	6	1/4	48	1.89	23	0.91	12
1D056-8-4	M14x1.5	6	1/4	47	1.85	23	0.91	14
1D056-10-5	M16x1.5	8	5/16	50	1.97	24	0.94	17
1D056-12-5	M18x1.5	8	5/16	52	2.05	26	1.02	19
1D056-10-6	M16x1.5	10	3/8	50	1.97	24	0.94	17
1D056-12-6	M18x1.5	10	3/8	50	1.97	24	0.94	19
1D056-15-6	M22x1.5	10	3/8	52	2.05	27	1.06	22
1D056-15-8	M22x1.5	13	1/2	55	2.16	27	1.06	22
1D056-18-10	M26x1.5	16	5/8	64	2.52	30	1.18	27
1D056-22-12	M30x2	19	3/4	68	2.68	34	1.34	30
1D056-28-16	M36x2	25	1	82	3.23	34	1.34	36


1D256 - Metric Male Stud 24°
Heavy Series, ISO 12151-2



Construction: Steel. Add “C” for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#								
		mm	inch	mm	inch	mm	inch	mm
1D256-8-3	M16x1.5	5	3/16	42	1.65	25	0.98	12
1D256-10-4	M18x1.5	6	1/4	52	2.05	27	1.06	12
1D256-10-5	M18x1.5	8	5/16	53	2.09	27	1.06	14
1D256-12-5	M20x1.5	8	5/16	53	2.09	27	1.06	17
1D256-12-6	M20x1.5	10	3/8	53	2.09	27	1.06	19
1D256-14-6	M22x1.5	10	3/8	57	2.24	31	1.22	17
1D256-16-6	M24x1.5	10	3/8	57	2.24	31	1.22	19
1D256-16-8	M24x1.5	13	1/2	60	2.36	31	1.22	22
1D256-20-12	M30x2	19	3/4	72	2.83	38	1.50	22

1D956 Male BSPP - Straight
(60° Cone) ISO 228-1













Construction: Steel. Add “C” for Stainless Steel.



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#								
		mm	inch	mm	inch	mm	inch	mm
1D956-4-3	G 1/4	5	3/16	44	1.73	27	1.06	19
1D956-4-4	G 1/4	6	1/4	52	2.05	27	1.06	19
1D956-6-5	G 3/8	8	5/16	53	2.09	27	1.06	22
1D956-6-6	G 3/8	10	3/8	53	2.09	28	1.10	22
1D956-8-8	G 1/2	13	1/2	60	2.36	32	1.26	27
1D956-12-12	G 3/4	19	3/4	75	2.95	41	1.61	32
1D956-16-16	G 1	25	1	91	3.58	42	1.65	41

90 Series Visual Index





90 Series
FIELD ATTACHABLE

201 Male Taper Pipe Rigid	206 SAE (JIC) 37° Swivel	208 SAE 45° Swivel	228 SAE Male Inverted Swivel Straight	234 Straight Tube
 E-26	 E-27	 E-27	 E-27	 E-28


237 JIC 37° Swivel 45° Elbow	239 JIC 37° Swivel 90° Elbow Short	261 SAE Compression Air Brake	267 SAE Male Inverted Swivel 45° Elbow	269 SAE Male Inverted Swivel 90° Elbow
 E-28	 E-28	 E-28	 E-29	 E-29

277 SAE 45° Swivel 45° Elbow	279 SAE 45° Swivel 90° Elbow
 E-29	 E-29

90 Series
REPLACEMENT COMPONENTS

200 Replacement Socket	090 Replacement Ferrule	60HAB SAE Compression Airbrake Sleeve	61HAB SAE Compression Airbrake Nut
 E-30	 E-30	 E-30	 E-30

20190 Male Taper Pipe Rigid




Construction: Brass nipple and ferrule, steel socket. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex
#							
			inch	mm	inch	mm	inch
20190-2-4	1/8-27	-4	1.33	34	7/8	22	9/16
20190-4-4	1/4-18	-4	1.58	40	1-1/16	27	9/16
20190-4-5	1/4-18	-5	1.66	42	1-1/8	29	5/8
20190-4-6	1/4-18	-6	1.66	42	1-1/8	29	11/16
20190-6-6	3/8-18	-6	1.66	42	1-1/8	29	11/16
20190-6-8	3/8-18	-8	1.77	45	1-3/16	30	7/8
20190-8-8	1/2-14	-8	1.97	50	1-7/16	37	7/8
20190-8-10	1/2-14	-10	2.13	54	1-7/16	37	1
20190-12-12	3/4-14	-12	2.26	57	1-9/16	40	1-1/8
20190-12-16	3/4-14	-16	2.29	58	1-5/8	41	1-3/8
20190-16-16	1-11-1/2	-16	2.46	62	1-7/8	48	1-3/8
20190-20-20	1-1/4-11-1/2	-20	2.69	68	2-1/16	52	2

For detailed ordering information, please consult price list or contact Parflex Division.

20690 SAE (JIC) 37° Swivel




Construction: Brass nipple and ferrule, steel nut and socket.
Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex	J Hex
#								
			inch	mm	inch	mm	inch	inch
20690-4-4	7/16-20	-4	1.58	40	1-1/8	29	9/16	9/16
20690-5-5	1/2-20	-5	1.66	42	1-1/8	29	5/8	5/8
20690-6-6	9/16-18	-6	1.74	44	1-3/16	35	11/16	11/16
20690-8-6	3/4-16	-6	1.85	47	1-5/16	33	7/8	7/8
20690-8-8	3/4-16	-8	1.98	50	1-3/8	35	7/8	7/8
20690-8-10	3/4-16	-10	2.07	53	1-7/16	37	1	7/8
20690-10-10	7/8-14	-10	2.22	56	1-1/2	38	1	1
20690-12-12	1-1/16-12	-12	2.33	59	1-5/8	41	1-1/4	1-1/4
20690-16-16	1-5/16-12	-16	2.52	64	1-15/16	49	1-3/8	1-1/2
20690-20-20	1-5/8-12	-20	2.99	76	2-5/16	59	2	2

NOTE: Sizes -4, -5,-8 and -10 incorporate a dual seat.


20890 SAE 45° Swivel



Construction: Brass nipple and ferrule, steel nut and socket.
Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex	J Hex
#								
			inch	mm	inch	mm	inch	inch
20890-6-6	5/8-18	-6	1.77	45	1-1/4	32	11/16	3/4
20890-12-12	1-1/16-14	-12	2.34	59	1-11/16	43	1-1/8	1-1/4


22890 SAE Male Inverted Swivel Straight



Construction: Steel nipple, nut and socket, brass ferrule.
Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex	J Hex
#								
			inch	mm	inch	mm	inch	inch
22890-4-4	7/16-24	-4	2.15	55	1-11/16	43	9/16	7/16
22890-5-5	1/2-20	-5	2.21	56	1-11/16	43	5/8	1/2
22890-5-6	1/2-20	-6	2.20	56	1-11/16	43	11/16	1/2
22890-6-6	5/8-18	-6	2.22	56	1-11/16	43	11/16	5/8
22890-8-8	3/4-18	-8	2.34	59	1-13/16	46	13/16	3/4
22890-10-10	7/8-18	-10	2.53	64	1-7/8	48	15/16	7/8
22890-12-12	1-1/16-16	-12	3.01	76	2-3/8	60	1-1/8	1-1/16


23490 Straight Tube



Construction: Brass nipple and ferrule, steel socket.
NOTE: 26T90 fitting includes 23490 with the 60HAB sleeve & 61HAB nut.

Part Number	Hose Size	Tube Size		A		Cutoff Allow. B		H Hex
#								
		inch	mm	inch	mm	inch	mm	inch
23490-8-8	-8	1/2	6	3.06	78	2-1/2	64	13/16
23490-8-10	-10	1/2	8	3.15	80	2-1/2	64	1
23490-10-8	-8	5/8	8	3.26	83	2-5/8	67	13/16
23490-10-10	-10	5/8	10	3.28	83	2-5/8	67	1
23490-12-12	-12	3/4	13	3.28	83	2-11/16	68	1-1/8


23790 JIC 37° Swivel 45° Elbow



Construction: Brass ferrule, steel tube, nut and socket. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		H Hex	J Hex
#										
			inch	mm	inch	mm	inch	mm	inch	inch
23790-4-4	7/16-20	-4	1.79	45	1-3/8	35	0.33	8	9/16	9/16
23790-5-5	1/2-20	-5	1.86	47	1-3/8	35	0.36	9	5/8	5/8
23790-6-6	9/16-18	-6	1.96	50	1-7/16	37	0.39	10	11/16	11/16
23790-8-6	3/4-16	-6	2.11	54	1-11/16	43	0.55	14	11/16	7/8
23790-8-8	3/4-16	-8	2.40	61	1-3/4	44	0.55	14	13/16	7/8
23790-10-10	7/8-14	-10	2.45	62	1-7/8	48	0.63	16	15/16	1
23790-12-12	1-1/16-12	-12	3.04	77	2-7/16	62	0.78	20	1-1/8	1-1/4
23790-16-16	1-5/16-12	-16	3.28	83	2-11/16	68	0.90	23	1-3/8	1-1/2
23790-20-20	1-5/8-12	-20	3.70	94	3-1/16	78	1.18	30	1-3/4	2


23990 JIC 37° Swivel 90° Elbow Short Drop



Construction: Brass ferrule, steel tube, nut and socket. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		H Hex	J Hex
#										
			inch	mm	inch	mm	inch	mm	inch	inch
23990-4-4	7/16-20	-4	1.67	41	1-1/4	32	0.68	17	9/16	9/16
23990-5-5	1/2-20	-5	1.75	44	1-1/4	32	0.77	20	5/8	5/8
23990-6-6	9/16-18	-6	1.86	47	1-3/8	35	0.85	22	11/16	11/16
23990-8-6	3/4-16	-6	1.95	50	1-7/16	37	1.09	28	11/16	7/8
23990-8-8	3/4-16	-8	2.15	55	1-1/2	38	1.09	28	13/16	7/8
23990-10-10	7/8-14	-10	2.38	60	1-3/4	44	1.23	31	15/16	1
23990-12-12	1-1/16-12	-12	2.95	75	2-5/16	59	1.82	46	1-1/8	1-1/4
23990-16-16	1-5/16-12	-16	3.13	80	2-1/2	64	2.14	54	1-3/8	1-1/2
23990-20-20	1-5/8-12	-20	3.54	90	2-7/8	73	2.57	65	1-3/4	2


26190 SAE Compression Air Brake



Construction: Brass nipple and ferrule, steel socket.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex
#							
			inch	mm	inch	mm	inch
26190-8-8	11/16-20	-8	1.69	43	1-1/16	27	13/16
26190-8-10	11/16-20	-10	1.86	47	1-3/16	30	1
26190-10-10	13/16-18	-10	1.92	49	1-1/4	32	1
26190-12-10	1-18	-10	2.09	53	1-7/16	37	1
26190-12-12	1-18	-12	2.09	53	1-7/16	37	1-1/8


26790 SAE Male Inverted Swivel 45° Elbow



Construction: Brass ferrule, steel tube, nut and socket. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		H Hex	J Hex
#										
			inch	mm	inch	mm	inch	mm	inch	inch
26790-4-4	7/16-24	-4	2.11	54	1-11/16	43	0.63	16	9/16	7/16
26790-5-5	1/2-20	-5	2.51	64	2	51	0.94	24	5/8	1/2
26790-5-6	1/2-20	-6	2.55	65	2-1/16	52	0.94	24	11/16	1/2
26790-6-6	5/8-18	-6	2.61	66	2-1/8	54	0.94	24	11/16	5/8
26790-8-8	3/4-18	-8	2.97	75	2-3/8	60	0.94	24	13/16	3/4
26790-8-10	3/4-18	-10	3.05	77	2-7/16	62	0.94	24	15/16	3/4
26790-10-10	7/8-18	-10	3.43	87	2-11/16	68	1.02	26	15/16	7/8
26790-12-12	1-1/16-16	-12	3.83	97	3-3/16	81	1.15	29	1-1/8	1-1/16


26990 SAE Male Inverted Swivel 90° Elbow



Construction: Brass ferrule, steel tube, nut and socket. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		H Hex	J Hex
#										
			inch	mm	inch	mm	inch	mm	inch	inch
26990-4-4	7/16-24	-4	1.79	45	1-5/16	33	1.19	30	9/16	7/16
26990-5-5	1/2-20	-5	2.01	51	1-1/2	38	1.65	42	5/8	1/2
26990-5-6	1/2-20	-6	2.05	52	1-9/16	40	1.65	42	11/16	1/2
26990-6-6	5/8-18	-6	2.03	52	1-1/2	38	1.70	43	11/16	5/8
26990-8-8	3/4-18	-8	2.30	58	1-11/16	43	1.78	45	13/16	3/4
26990-8-10	3/4-18	-10	2.39	61	1-3/4	44	1.78	45	15/16	3/4
26990-10-10	7/8-18	-10	3.16	80	2-1/2	64	2.18	55	15/16	7/8
26990-12-12	1-1/16-16	-12	3.56	90	2-15/16	75	2.51	64	1-1/8	1-1/16


27790 SAE 45° Swivel 45° Elbow



Construction: Brass ferrule, steel tube, nut and socket. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		H Hex	J Hex
#										
			inch	mm	inch	mm	inch	mm	inch	inch
27790-6-6	5/8-18	-6	1.72	44	1-3/16	30	0.39	10	11/16	3/4
27790-12-12	1-1/16-14	-12	3.03	77	2-3/8	60	0.78	20	1-1/8	1-1/4


27990 SAE 45° Swivel 90° Elbow



Construction: Brass ferrule, steel tube, nut and socket. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		H Hex	J Hex
#										
			inch	mm	inch	mm	inch	mm	inch	inch
27990-6-6	5/8-18	-6	1.86	47	1-3/8	35	.85	22	11/16	3/4
27990-8-8	3/4-16	-8	2.09	53	1-1/2	38	1.09	28	13/16	7/8
27990-12-12	1-1/16-14	-12	2.95	75	2-5/16	39	1.82	46	1-1/8	1-1/4


20090 Replacement Socket for Field Attachable Fittings



Part Number #	H Hex ⬡
	inch
20090-4	9/16
20090-5	5/8
20090-6	11/16
20090- 8	7/8
20090-10	1
20090-12	1-1/8
20090-16	1-3/8
20090-20	1-3/4

Construction: Steel or Stainless Steel.
Add "C" for Stainless Steel.


60 HAB SAE Compression Airbrake Sleeve



Part Number #	Tube Size ◎		L
	inch	mm	inch
60HAB-4	1/4	6	.250
60HAB-6	3/8	10	.313
60HAB-8	1/2	13	.375
60HAB-10	5/8	16	.438
60HAB-12	3/4	19	.500

Construction: Brass.
NOTE: To be used with 13491N & 23490.


090 Replacement Ferrule for 90 Series Field Attachable Fittings



Part Number #	Hose Size
090-4B	-4
090-5B	-5
090-6B	-6
090- 8B	-8
090-10B	-10
090-12B	-12
090-16B	-16
090-20B	-20

Construction: Brass.
Replace "B" with "C" for Stainless Steel.

61 HAB SAE Compression Airbrake Nut































Part Number #	Thread Size ≈	Tube Size ◎		L		W Hex ⬡
		inch	mm	inch	mm	inch
61HAB-4	7/16-24	1/4	6	0.75	19	9/16
61HAB-6	7/32-24	3/8	10	1.13	29	5/8
61HAB- 8	11/16-20	1/2	13	1.25	32	13/16
61HAB-10	13/16-18	5/8	16	1.38	35	15/16
61HAB-12	1-18	3/4	19	1.56	40	1-1/8



Construction: Brass.
NOTE: To be used with 13491N & 23490 Fittings.

91N Series Visual Index

91N Series
PERMANENT


101 Male Taper Pipe Rigid	103 Male JIC 37°	106 JIC 37° Female Swivel	106 RD JIC 37° Female Swivel w/o Nip. Hex	107 Female Pipe Swivel
 E-32	 E-32	 E-32	 E-33	 E-33
108 Female SAE 45° Swivel	**128** Male Inverted Swivel Straight	**134** Straight Tube	**137** Female JIC 37° Swivel 45° Elbow	**139** Female JIC 37° Swivel 90° Elbow Sht.
 E-33	 E-33	 E-34	 E-34	 E-34
141 Female JIC 37° Swivel 90° Elb Long	**161** Compression Air Brake	**167** SAE Male Inverted 45° Elbow	**169** SAE Male Inverted 90° Elbow	**177** SAE 45° Swivel 90° 45° Elbow
 E-35	 E-35	 E-35	 E-35	 E-36
179 SAE 45° Swivel 90° Elbow	**192** Female BSP Pipe Swivel - Str. (60° Cone)	**1AL** A-Lok® Compression	**1B2** Female BSP Pipe Swivel 90° Elb. (37° Cone)	**1FN** Sanitary Flange
 E-36	 E-39	 E-36	 E-39	 E-37
1GK Bulkhead w/Zerk Port Integrated	**1J1** Female Seal-Lok™ 90° Elbow Long	**1J7** Female Seal-Lok™ 45° Elbow	**1J9** Female Seal-Lok™ 90° Elbow	**1J9** Female Seal-Lok™ Swivel Straight
 E-39	 E-37	 E-37	 E-37	 E-38
1P6 CPI® Compression w/nut and ferrule	**1Q1** Ultra Seal	**1TU** Universal Tube Stub		
 E-36	 E-38	 E-38		

1GK91N OPTIONS

Nut 2GK-Nut	Zerk NA-6520
 E-39	 E-39

For detailed ordering information, please consult price list or contact Parflex Division.


10191N Male Taper Pipe Rigid



Construction: Brass nipple, steel shell. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex
#							
		inch	inch	mm	inch	mm	inch
10191N-2-4	1/8-27	-4	1.27	32	3/4	19	7/16
10191N-4-4	1/4-18	-4	1.50	38	15/16	24	9/16
10191N-4-5	1/4-18	-5	1.55	39	15/16	24	9/16
10191N-4-6	1/4-18	-6	1.60	41	15/16	24	9/16
10191N-6-6	3/8-18	-6	1.65	58	1	25	11/16
10191N-6-8	3/8-18	-8	1.71	43	1	25	11/16
10191N-8-8	1/2-14	-8	1.94	49	1-1/4	32	7/8
10191N-8-10	1/2-14	-10	1.96	50	1-1/4	32	7/8
10191N-8-12	1/2-14	-12	2.42	61	1-1/4	32	1
10191N-12-12	3/4-14	-12	2.19	56	1-3/8	35	1-1/8
10191N-16-16	1-11-1/2	-16	2.46	62	1-1/2	38	1-3/8
10191-20-20	1-1/4-11-1/2	-20	3.05	77	2-1/16	52	1-3/4


10391N Male (JIC) 37°



Construction: Brass nipple, steel shell. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex
#							
			inch	mm	inch	mm	inch
10391N-4-4	7/16-20	-4	1.37	35	13/16	21	1/2
10391N-6-6	9/16-18	-6	1.64	42	1	25	11/16
10391N-8-8	3/4-16	-8	1.79	35	1-1/8	29	7/8
10391N-8-6	3/4-16	-6	1.73	44	1-1/16	27	7/8
10391N-10-10	7/8-14	-10	2.07	53	1-3/8	35	1
10391N-12-12	1-1/16-12	-12	2.10	53	1-5/16	33	1-1/8
10391N-16-16	1-5/16-12	-16	2.43	62	1-1/2	38	1-3/8

10691N Female SAE (JIC) 37° Swivel




Construction: Brass nipple, steel nut and shell. Add "S" for Steel nipple, nut and shell. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex	J Hex
#								
			inch	mm	inch	mm	inch	inch
10691N-4-4	7/16-20	-4	1.43	36	7/8	22	3/8	9/16
10691N-5-5	1/2-20	-5	1.56	40	15/16	24	7/16	5/8
10691N-6-6	9/16-18	-6	1.63	41	1	25	1/2	11/16
10691N-6-8	9/16-18	-8	1.69	43	1	25	9/16	11/16
10691N-8-8	3/4-16	-8	1.89	48	1-3/16	30	11/16	7/8
10691N-8-10	3/4-16	-10	1.86	58	1-1/8	29	3/4	7/8
10691N-10-10	7/8-14	-10	2.03	52	1-5/16	33	13/16	1
10691N-12-12	1-1/16-12	-12	2.18	55	1-3/8	35	1	1-1/4
10691N-16-16	1-5/16-12	-16	2.45	62	1-9/16	40	1-1/4	1-1/2
10691-20-20	1-5/8-12	-20	2.98	76	1-13/16	46	1-11/16	2

NOTE: Sizes -4, -5,-8 and -10 Incorporate a dual seat.

10691NRD SAE (JIC) 37° Swivel




Construction: Brass nipple, steel nut and shell. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		J Hex
#							
			inch	mm	inch	mm	inch
10691N-4-4-RD	7/16-20	-4	1.34	34	13/16	21	9/16
10691N-5-5-RD	1/2-20	-5	1.51	38	7/8	22	5/8
10691N-6-6-RD	9/16-18	-6	1.60	41	15/16	24	11/16
10691N-8-8-RD	3/4-16	-8	1.79	45	1-1/16	27	7/8
10691N-10-10-RD	7/8-14	-10	1.91	49	1-3/16	30	1
10691N-12-12-RD	1-1/16-12	-12	2.09	52	1-5/16	33	1-1/4
10691N-16-16-RD	1-5/16-12	-16	2.27	58	1-5/16	33	1-1/2

NOTE: Sizes -4, -5,-8 and -10 Incorporate a dual seat..


10791N Female Pipe Swivel



Construction: Brass nipple, steel nut and shell. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex	J Hex
#								
			inch	mm	inch	mm	inch	inch
10791N-4-4	1/4-18	-4	1.50	38	15/16	24	9/16	11/16
10791N-6-6	3/8-18	-6	1.67	42	1	25	5/8	7/8
10791N-8-8	1/2-14	-8	1.83	46	1-1/8	29	3/4	1
10791N-12-12	3/4-14	-12	2.09	53	1-5/16	33	1	1-1/4
10791N-16-16	1-11-1/2	-16	2.26	57	1-5/16	33	1-3/16	1-3/8


10891N SAE 45° Swivel



Construction: Brass nipple, steel nut and shell. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex	J Hex
#								
			inch	mm	inch	mm	inch	inch
10891N-6-6	5/8-18	-6	1.69	43	1-1/16	27	5/8	3/4
10891N-12-12	1-1/16-14	-12	2.18	55	1-3/8	35	1	1-1/4


12891N Male Inverted Swivel–Straight



Construction: Steel nipple, tube, nut and shell. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		J Hex
#							
			inch	mm	inch	mm	inch
12891N-4-4	7/16-24	-4	2.09	53	1-1/2	38	7/16
12891N-5-5	1/2-20	-5	2.15	55	1-9/16	40	1/2
12891N-5-6	1/2-20	-6	2.23	57	1-9/16	40	1/2
12891N-6-6	5/8-18	-6	2.23	57	1-9/16	40	5/8
12891N-8-8	3/4-18	-8	2.31	59	1-5/8	41	3/4
12891N-10-10	7/8-18	-10	2.43	58	1-3/4	44	7/8
12891N-12-12	1-1/16-16	-12	2.50	64	1-11/16	43	1-1/16

13491N Straight Tube




Construction: Brass nipple, steel shell.

Part Number #	Hose Size	Diameter R	A		Cutoff Allow. B	
		inch	inch	mm	inch	mm
13491N-8-8	-8	1/2	2.80	71	2-1/8	54
13491N-8-10	-10	1/2	2.81	71	2-1/8	54
13491N-10-10	-10	5/8	2.96	75	2-1/4	58
13491N-12-12	-12	3/4	3.37	86	2-9/16	65

NOTE: The 16T91N fitting includes 13491N with the 60HAB sleeve and 61HAB nut.


13791N JIC 37° Swivel 45° Elbow



Construction: Steel nipple, tube, nut and shell. Add "C" for Stainless Steel.

Part Number #	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
			inch	mm	inch	mm	inch	mm	inch
13791N-4-4	7/16-20	-4	1.74	44	1-3/16	30	0.33	8	9/16
13791N-5-5	1/2-20	-5	1.87	47	1-1/4	32	0.36	9	5/8
13791N-6-6	9/16-18	-6	1.94	49	1-5/16	33	0.43	11	11/16
13791N-8-8	3/4-16	-8	2.28	58	1-9/16	37	0.55	14	7/8
13791N-10-10	7/8-14	-10	2.42	61	1-11/16	43	0.64	43	1
13791N-12-12	1-1/16-12	-12	2.83	58	2-1/16	52	0.78	20	1-1/4
13791N-16-16	1-5/16-12	-16	3.18	81	2-1/4	57	0.89	23	1-1/2
13791-20-20	1-5/8-12	-20	3.67	93	2-9/16	65	1.10	28	2


13991N JIC 37° Swivel 90° Elbow Short Drop



Construction: Steel nipple, tube, nut and shell. Add "C" for Stainless Steel.

Part Number #	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
			inch	mm	inch	mm	inch	mm	inch
13991N-4-4	7/16-20	-4	1.62	41	1-1/16	37	0.68	17	9/16
13991N-5-5	1/2-20	-5	1.73	44	1-1/8	29	0.77	20	5/8
13991N-6-6	9/16-18	-6	1.91	49	1-1/4	32	0.91	23	11/16
13991N-8-8	3/4-16	-8	2.03	52	1-5/16	33	1.09	28	7/8
13991N-10-10	7/8-14	-10	2.27	58	1-9/16	37	1.23	43	1
13991N-12-12	1-1/16-12	-12	2.75	58	1-15/16	49	1.82	46	1-1/2
13991N-16-16	1-5/16-12	-16	3.15	80	2-3/16	56	2.14	52	1-1/2
13991-20-20	1-5/8-12	-20	3.53	90	2-7/16	62	1.18	30	2


14191N JIC 37° Swivel 90° Elbow Long Drop



Construction: Steel nipple, tube, nut and shell. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
#									
			inch	mm	inch	mm	inch	mm	inch
14191N-4-4	7/16-20	-4	1.66	42	1-1/8	29	1.80	46	9/16
14191N-5-5	1/2-20	-5	1.72	44	1-1/8	29	1.77	45	5/8
14191N-6-6	9/16-18	-6	1.93	49	1-5/16	33	2.13	54	11/16
14191N-8-8	3/4-16	-8	2.11	54	1-3/8	35	2.52	64	7/8
14191N-10-10	7/8-14	-10	2.34	59	1-5/8	41	2.57	65	1
14191N-12-12	1-1/16-12	-12	2.63	67	1-7/8	48	3.73	95	1-1/4
14191N-16-16	1-5/16-12	-16	3.15	80	2-3/16	56	4.33	110	1-1/2
14191-20-20	1-5/8-12	-20	4.00	102	2-15/16	75	5.28	134	2


16191N Compression Air Brake



Construction: Brass nipple, steel shell.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex
#							
			inch	mm	inch	mm	inch
16191N-8-8	11/16-20	-8	1.61	41	15/16	24	3/4
16191N-8-10	11/16-20	-10	1.61	41	15/16	24	7/8
16191N-10-10	13/16-18	-10	1.82	46	1-1/8	29	15/16
16191N-12-12	1-18	-12	1.93	49	1-1/8	29	1-1/4


16791N Male Inverted Swivel 45° Elbow



Construction: Steel nipple, tube, nut and shell. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
#									
			inch	mm	inch	mm	inch	mm	inch
16791N-4-4	7/16-24	-4	2.05	52	1-1/2	38	0.63	16	7/16
16791N-5-5	1/2-20	-5	2.48	63	1-7/8	48	0.71	18	1/2
16791N-6-6	5/8-18	-6	2.60	66	1-15/16	49	0.96	24	5/8
16791N-8-8	3/4-18	-8	2.85	72	2-1/8	54	0.90	23	3/4
16791N-10-10	7/8-18	-10	3.30	84	2-5/8	67	1.02	43	7/8
16791N-12-12	1-1/16-16	-12	3.64	58	2-13/16	71	1.15	29	1-1/16


16991N Male Inverted Swivel 90° Elbow



Construction: Steel nipple, tube, nut and shell. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
#									
			inch	mm	inch	mm	inch	mm	inch
16991N-4-4	7/16-24	-4	1.72	44	1-3/16	30	1.19	30	7/16
16991N-5-5	1/2-20	-5	1.98	50	1-3/8	35	1.65	42	1/2
16991N-5-6	1/2-20	-6	2.03	52	1-7/16	37	1.65	42	1/2
16991N-6-6	5/8-18	-6	2.08	53	1-7/16	37	1.70	43	5/8
16991N-8-8	3/4-18	-8	2.18	55	1-1/2	38	1.87	43	3/4
16991N-10-10	7/8-18	-10	3.02	58	2-5/16	59	2.18	55	7/8
16991N-12-12	1-1/16-16	-12	3.36	85	2-9/16	64	2.51	64	1-1/16


17791N SAE 45° Swivel 45° Elbow



Construction: Steel nipple, tube, nut and shell. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
#									
			inch	mm	inch	mm	inch	mm	inch
17791N-6-6	5/8-18	3/8	2.06	52	1-5/16	33	0.39	10	3/4
17791N-12-12	1-1/16-14	3/4	3.07	78	2-7/16	62	0.78	20	1-1/4


17991N SAE 45° Swivel 90° Elbow



Construction: Steel nipple, tube, nut and shell. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
#									
			inch	mm	inch	mm	inch	mm	inch
17991N-6-6	5/8-18	3/8	2.06	52	1-5/16	49	1.19	30	3/4
17991N-12-12	1-1/16-14	3/4	2.92	74	2-1/8	54	1.82	46	1-1/4

1AL91N A-LOK® Compression




Construction: Stainless steel nipple and shell.

Part Number		Thread Size	Hose Size	A		Cutoff Allow. B		H Hex	J Hex
#									
w/nut & ferrule	w/o nut & ferrules			inch	mm	inch	mm	inch	inch
1AL91N-4-4C	1AL91N-4-4NC		-4	1.30	33	7/16	11	1/2	9/16
1AL91N-4-5C	1AL91N-4-5NC		-5	1.35	34	7/16	11	1/2	9/16
1AL91N-6-6C	1AL91N-6-6NC		-6	1.53	39	1/2	13	5/8	11/16
1AL91N-8-8C	1AL91N-8-8NC		-8	1.61	41	7/16	11	13/16	7/8
1AL91N-12-12C	1AL91N-12-12NC		-12	1.86	47	1/2	13	1-1/8	1-1/8
1AL91N-16-16C	1AL91N-16-16NC		-16	2.11	58	7/16	11	1-3/8	1-1/2

NOTE: Nuts and Ferrules are Manufactured by the Instrumentation Products Division. Refer to Catalog 4230/4233 for information.
Nut part No. is XNUX-316. Front ferrule part No. is XFFX-316.
Back ferrule part No. is XBFX-316. X denotes dash size.

1P691N CPI® Compression (With Nut and Ferrule)




Construction: Stainless steel nipple and shell.

Part Number	Hose Size	A		Cutoff Allow. B		H Hex	J Hex
#							
w/nut & ferrules		inch	mm	inch	mm	inch	inch
1P691N-4-4C	-4	1.30	33	7/16	11	1/2	9/16
1P691N-6-6C	-6	1.53	39	1/2	13	5/8	11/16
1P691N-8-8C	-8	1.61	41	7/16	11	13/16	7/8

NOTE: Nuts and Ferrules are Manufactured by the Instrumentation Products Division. Refer to Catalog 4230/4233 for information.
Nut part No. is **XBZ-SS**. Ferrule part No. is **XTZ-SS**.
X denotes dash size


1FN91N Sanitary Flange



Part Number	Hose Size	A		Cutoff Allow. B		C		Flange Size D	
#									
		inch	mm	inch	mm	inch	mm	inch	mm
1FN91N-16-16C	-16	1.96	50	1-1/16	27	0.87	22	1.98	50

Construction: Stainless steel nipple and shell.


1J191N Female Seal-Lok™ Swivel 90° Elbow Long Drop



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
#									
			inch	mm	inch	mm	inch	mm	inch
1J191N-4-4	9/16-18	-4	1.66	42	1-1/16	27	1.80	46	11/16
1J191N-4-5	9/16-18	-5	1.78	45	1-1/16	27	1.80	46	11/16
1J191N-6-5	11/16-16	-5	1.92	49	1-3/16	30	2.13	54	13/16
1J191N-6-6	11/16-16	-6	1.92	49	1-3/16	30	2.13	54	13/16
1J191N-8-6	13/16-16	-6	2.00	51	1-9/16	40	2.51	43	15/16
1J191N-8-8	13/16-16	-8	2.15	58	1-7/16	37	2.51	64	15/16
1J191N-10-10	1-14	-10	1.25	32	1-9/16	40	2.76	70	1-1/8
1J191N-12-12	1-3/16-12	-12	2.65	67	1-13/16	46	3.78	96	1-3/8
1J191N-16-16	1-7/16-12	-16	3.15	80	2-1/4	57	4.50	114	1-1/2

Construction: Steel nipple, tube, nut and shell. Add "C" for Stainless Steel.


1J791N Female Seal-Lok™ Swivel 45° Elbow



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
#									
			inch	mm	inch	mm	inch	mm	inch
1J791N-4-4	9/16-18	-4	1.73	44	1-1/4	32	0.41	10	11/16
1J791N-4-6	9/16-18	-6	1.91	49	1-5/16	33	0.41	10	11/16
1J791N-6-6	11/16-16	-6	2.02	51	1-3/8	35	0.43	11	13/16
1J791N-8-8	13/16-16	-8	2.18	55	1-1/2	38	0.59	15	15/16
1J791N-8-10	13/16-16	-8	2.39	61	1-11/16	43	0.59	15	15/16
1J791N-10-10	1-14	-10	2.47	63	1-3/4	44	0.59	43	1-1/8
1J791N-12-12	1-3/16-12	-12	2.74	58	1-15/16	49	0.81	21	1-3/8
1J791N-16-16	1-7/16-12	-16	3.50	89	2-1/2	64	0.94	24	1-5/8

Construction: Steel nipple, tube, nut and shell. Add "C" for Stainless Steel.


1J991N Female Seal-Lok™ Swivel 90° Elbow Short Drop



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
#									
			inch	mm	inch	mm	inch	mm	inch
1J991N-4-4	9/16-18	-4	1.73	44	1-1/4	32	0.82	21	11/16
1J991N-6-6	11/16-16	-6	1.91	49	1-5/16	33	0.91	23	13/16
1J991N-8-8	13/16-16	-6	2.02	51	1-3/8	35	1.15	29	15/16
1J991N-10-10	1-14	-10	2.18	55	1-1/2	38	1.27	32	1-1/8
1J991N-12-12	1-3/16-12	-12	2.39	61	1-11/16	43	1.85	43	1-3/8
1J991N-16-16	1-7/16-12	-16	2.47	63	1-3/4	44	2.21	56	1-5/8

Construction: Steel nipple, tube, nut and shell. Add "C" for Stainless Steel.


1JC91N Female Seal-Lok™ Swivel Straight



Construction: Steel nipple, steel nut and shell. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		C		H Hex	J Hex
#										
			inch	mm	inch	mm	inch	mm	inch	inch
1JC91N-4-4	9/16-18	-4	1.46	37	5/8	16	.32	8	9/16	11/16
1JC91N-6-6	11/16-16	-6	1.62	41	11/16	17	.32	8	5/8	13/16
1JC91N-8-8	13/16-16	-8	1.93	49	13/16	21	.43	11	3/4	15/16
1JC91N-10-10	1-14	-10	2.05	52	7/8	22	.53	13	15/16	1-1/8
1JC91N-12-10	1-3/16-12	-10	2.05	52	1-1/4	32	.57	14	15/16	1-3/8
1JC91N-12-12	1-3/16-12	-12	2.05	58	1-1/4	32	.57	14	15/16	1-3/8
1JC91N-16-16	1-7/16-12	-16	2.56	65	1-1/16	27	.58	15	1-3/8	1-5/8
1JC91N-20-16	1-11/16-12	-16	2.30	58	1-3/8	35	.59	15	1-5/8	1-7/8
1JC91-20-20	1-11/16-12	-20	2.68	68	1-11/16	43	.59	15	1-11/16	1-7/8


1Q191N Ultra Seal



Construction: Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		J Hex
#							
			inch	mm	inch	mm	inch
1Q191N-8-8C	7/8-20	-8	1.62	41	15/16	24	1

1TU91N Universal Tube Stub




Construction: Stainless Steel.

Part Number	Thread Size	Hose Size	Diameter R	A		Cutoff Allow. B	
#			∅				
		inch	inch	inch	mm	inch	mm
1TU91-2-3C	-3	1/8	1/8	1.33	34	7/8	22
1TU91-3-3C	-3	3/16	3/16	1.33	34	7/8	22
1TU91N-4-4C	-4	1/4	1/4	1.63	41	1-1/16	27
1TU91N-4-5C	-5	1/4	1/4	1.70	43	1-1/16	27
1TU91N-6-6C	-6	3/8	3/8	1.81	46	1-3/16	30
1TU91N-8-8C	-8	1/2	1/2	2.72	58	1-7/16	37
1TU91N-8-10C	-10	1/2	1/2	2.14	54	1-7/16	37
1TU91N-10-10C	-10	5/8	5/8	2.14	54	1-7/16	37
1TU91N-12-12C	-12	3/4	3/4	2.24	57	1-7/16	37
1TU91N-16-16C	-16	1	1	2.73	69	1-3/4	44

NOTE: Use with A-Lok & CPI nuts, sleeves and adapters. These components are manufactured by Parker's Instrumentation Connectors Division. Refer to catalogs 4230 & 4233 for information.


19291N Female BSP Parallel Pipe Swivel Straight (60° Cone)



Construction: Steel nipple, nut and shell. Add “C” for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex	J Hex
#								
			inch	mm	inch	mm	inch	inch
19291N-8-8	PF-1/2-14	-8	1.99	51	1-5/16	33	27	27
19291N-12-12	PF-3/4-14	-12	2.35	60	1-9/16	40	36	36


1B291N Female BSP Parallel Pipe Swivel - 90° Elbow (60° Cone)



Construction: Steel nipple, nut and shell. Add “C” for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
#									
			inch	mm	inch	mm	inch	mm	inch
1B291N-8-8	PF-1/2-14	-8	2.04	52	1-3/8	35	1.57	40	27
1B291N-12-12	PF-3/4-14	-12	2.93	74	2-1/8	54	2.54	65	36


1GK91N Bulkhead with Integrated Zerk Port -Bulkhead Nut and Grease Zerk




Construction: Steel nipple, nut and shell. Add “C” for Stainless Steel.

Part Number	Thread Size	Hose Size		A		Cutoff Allow. B		H Hex
#								
		inch	mm	inch	mm	inch	mm	inch
1GK91N-2-4*	1/8-27 NPSM Male with 1/4-28 UNF Female	3/16	5	1.46	37	15/16	24	1/2

NOTE: *Long bulkhead for use with plates under 3/4" thick. Uses 2GK-NUT, sold separately.







2GK-Nut




NA-6520

Part Number	Description	Thread Size	A		C		H Hex
2GK-Nut	Bulkhead Nut	1/8-27 NPSM	0.188	4.8	na	na	11/16
NA-6520	Grease Zerk Fitting	1/4-28 UNF	0.540	13.7	0.18	4.6	5/16
CY02-652317	HLB02 Spring Guard	-	-	-	-	-	-
3PSG-4	HLB03 Spring Guard	-	-	-	-	-	-

92 Series Visual Index

92 Series PERMANENT	111 Ferrule Fix	128 SAE Male Inverted Swivel Straight	167 SAE Male Inverted 45° Elbow	169 SAE Male Inverted 90° Elbow
	 E-40	 E-40	 E-40	 E-40

11192 Ferrule-Fix (Nut and Sleeve Included)




Construction: Steel.
Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size		A		Cutoff Allow. B		H Hex	J Hex
#									
		inch	mm	inch	mm	inch	mm	inch	inch
11192-3-3	3/8-24	3/16	5	1.37	35	15/16	24	5/8	7/16

NOTE: Nuts and Ferrules are Manufactured by the Instrumentation Products Division. Refer to Catalog 4230/4233 for information. "Ferrul-Fix" affords salvaging of bent tube section of combination tube-hose assemblies and quick, easy repair on the job. See page G-41 for Ferrule-Fix installation instructions.

Nut Part Number is 111-size. Sleeve Part Number is 110-size.


12892 SAE Male Inverted Swivel Straight



Construction: Stainless Steel.

Part Number	Thread Size	Hose Size		A		Cutoff Allow. B		C		J Hex
#										
		inch	mm	inch	mm	inch	mm	inch	mm	inch
12892-3-3C	3/8-24	3/16	5	2.01	55	1-1/2	38	1.25	32	7/16


16792 SAE Male Inverted Swivel 45° Elbow



Construction: Stainless Steel.

Part Number	Thread Size	Hose Size		A		Cutoff Allow. B		E		J Hex
#										
		inch	mm	inch	mm	inch	mm	inch	mm	inch
16792-3-3C	3/8-24	3/16	5	2.36	60	1-15/16	50	0.62	16	3/8

16992 SAE Male Inverted Swivel 90° Elbow











Construction: Stainless Steel.

Part Number	Thread Size	Hose Size		A		Cutoff Allow. B		E		J Hex
#										
		inch	mm	inch	mm	inch	mm	inch	mm	inch
16992-3-3C	3/8-24	3/16	5	1.45	37	1	25	1.25	32	3/8


93N Series Visual Index

93N Series
PERMANENT

101 Male Taper Pipe Rigid	106 Female JIC 37° Swivel	137 Female JIC 37° Swivel 45° Elbow	139 Female JIC 37° Swivel 90° Elbow Sht.	14K ANSI B16.5 Flange
 E-41	 E-41	 E-42	 E-42	 E-42

1J7 Female Seal-Lok™ 45° Elbow	1J9 Female Seal-Lok™ 90° Elbow Short	1JC Female Seal-Lok™ Swivel Straight Short
 E-43	 E-43	 E-43


10193N Male Taper Pipe Rigid



Construction: Steel nipple, nut and shell. Add "C" for Stainless Steel.

Part Number #	Thread Size	Hose Size		A		Cutoff Allow. B		H Hex
		inch	mm	inch	mm	inch	mm	inch
10193N-8-8	1/2-14	1/2	13	2.09	53	1-1/2	38	7/8
10193N-12-12	3/4-14	3/4	19	2.70	69	1-5/8	41	1-1/8
10193N-16-16	1-11-1/2	1	25	3.03	77	1-13/16	46	1-3/8
10193N-20-20	1-1/4-11-1/2	1-1/4	32	3.20	58	1-7/8	48	1-11/16
10193N-24-24	1-1/2-11-1/2	1-1/2	38	3.76	96	2-1/16	52	2
10193N-32-32	2-11-1/2	2	51	3.97	101	2-5/16	59	2-1/2


10693N (JIC) 37° Female Swivel



Construction: Steel nipple, nut and shell. Add "C" for Stainless Steel.

Part Number #	Thread Size	Hose Size		A		Cutoff Allow. B		H Hex	J Hex
		inch	mm	inch	mm	inch	mm	inch	inch
10693N-6-6	9/16-18	3/8	10	1.69	43	1-3/32	28	3/4	11/16
10693N-8-8	3/4-16	1/2	13	2.02	51	1-3/8	35	7/8	7/8
10693N-10-10	7/8-14	5/8	16	2.51	64	1-11/16	43	1	1
10693N-12-12	1-1/16-12	3/4	19	2.86	73	1-3/4	44	1-1/8	1-1/4
10693N-16-16	1-5/16-12	1	25	3.11	79	1-13/16	46	1-3/8	1-1/2
10693N-20-20	1-5/8-12	1-1/4	32	3.28	83	2	51	1-3/4	2
10693N-24-24	1-7/8-12	1-1/2	38	3.92	58	2-1/4	57	2	2-1/4
10693N-32-32	2-1/2-12	2	51	4.12	105	2-7/16	62	2-1/2	2-7/8


13793N JIC 37° Swivel 45° Elbow



Construction: Steel nipple, nut and shell.
Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
#									
			inch	mm	inch	mm	inch	mm	inch
13793N-12-12	1-1/16-12	-12	3.37	86	2-1/4	57	.78	20	1-1/4
13793N-16-16	1-5/16-12	-16	3.71	94	2-5/8	67	.90	23	1-1/2
13793N-20-20	1-5/8-12	-20	4.06	103	2-3/4	70	1.18	43	2
13793N-24-24	1-7/8-12	-24	5.76	146	4-1/4	108	1.47	37	2-1/4


13993N JIC 37° Swivel 90° Elbow Short Drop



Construction: Steel nipple, nut and shell. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
#									
			inch	mm	inch	mm	inch	mm	inch
13993N-8-8	3/4-16	-8	2.20	56	1-9/16	40	1.09	28	7/8
13993N-10-10	7/8-14	-10	2.41	61	1-11/16	43	1.23	31	1
13993N-12-12	1-1/16-12	-12	3.28	83	2-3/16	56	1.82	46	1-1/4
13993N-16-16	1-5/16-12	-16	3.71	94	2-1/2	64	2.14	54	1-1/2
13993N-20-20	1-5/8-12	-20	3.89	99	2-9/16	65	2.57	43	2
13993N-24-24	1-7/8-12	-24	5.72	58	4-1/4	108	3.17	81	2-1/4

14K93N ANSI B16.5 Flange




Construction: Steel nipple and shell, stainless steel flange.

Part Number	Hose Size		Flange Diameter		A		Cutoff Allow. B		Bolt Spacing E	
#			∅							
	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
14K93N-8-8	1/2	13	3-1/2	89	2.03	52	1-3/8	35	2-3/8	60
14K93N-12-12	3/4	19	3-7/8	98	2.70	69	1-3/4	44	2-3/4	70
14K93N-16-16	1	25	4-1/4	108	2.84	72	1-5/8	41	3-1/8	79
14K93N-20-20	1-1/4	32	4-5/8	117	2.98	76	1-5/8	41	3-1/2	89
14K93N-24-24	1-1/2	38	5	127	3.45	88	1-3/4	44	3-7/8	98
14K93N-32-32	2	51	6	152	3.62	58	2	51	4-3/4	121

NOTE: Also available in PAGE Fittings.


1JC93N Seal-Lok™ Swivel Straight Short



Construction: Steel nipple, nut and shell. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size		A		Cutoff Allow. B		C		H Hex	J Hex
#											
		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
1JC93N-12-12	1-3/16-12	3/4	19	2.30	58	1-3/8	35	.57	14	1-3/8	1-3/8
1JC93N-16-16	1-7/16-12	1	25	2.61	66	1-3/8	35	.58	15	1-3/8	1-5/8
1JC93N-20-20	1-11/16-12	1-1/4	32	2.65	67	1-5/16	33	.59	15	1-7/8	1-7/8

1J793N Seal-Lok™ 45° Elbow




Construction: Steel nipple, nut and shell. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size		A		Cutoff Allow. B		E		J Hex
#										
		inch	mm	inch	mm	inch	mm	inch	mm	inch
1J793N-20-20	1-11/16-12	1-1/4	32	4.25	108	2-15/16	75	1.00	25	1-7/8

NOTE: Also available in PAGE Fittings.

1J993N Seal-Lok™ 90° Elbow Short Drop





Construction: Steel nipple, nut and shell. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size		A		Cutoff Allow. B		E		J Hex
#										
		inch	mm	inch	mm	inch	mm	inch	mm	inch
1J993N-20-20	1-11/16-12	1-1/4	32	4.36	111	3-1/16	78	2.51	64	1-7/8


NOTE: Also available in PAGE Fittings.

94/95 Series Visual Index






10694 SAE (JIC) 37° Female Swivel



Construction: Steel nipple, nut and shell. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		J Hex
#							
			inch	mm	inch	mm	inch
10694-6-6	9/16-18	-6	1.76	45	15/16	24	11/16
10694-8-8	3/4-16	-8	2.09	53	1-3/16	30	7/8
10694-10-10	7/8-14	-10	2.30	58	1-5/16	33	1
10694-12-12	1-1/16-12	-12	2.45	62	1-5/16	33	1-1/4
10694-16-16	1-5/16-12	-16	2.72	69	1-7/16	37	1-1/2

10695 SAE (JIC) 37° Female Swivel



















Construction: Steel nipple, nut and shell. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		J Hex
#							
			inch	mm	inch	mm	inch
10695-4-4	7/16-20	-4	1.76	45	15/16	24	11/16
10695-6-6	9/16-18	-6	2.09	53	1-3/16	30	7/8
10695-8-8	3/4-16	-8	2.30	58	1-5/16	33	1
10695-12-12	1-1/16-12	-12	2.45	62	1-5/16	33	1-1/4
10695-16-16	1-5/16-12	-16	2.72	69	1-7/16	37	1-1/2

PAGE Fittings Visual Index

PAGE Series

PERMANENT

CL	Female Cam & Groove	E	Male Cam & Groove	FBS	Female Sanitary Bevel Seat	FIL	Female I-Line® Sanitary	FJX	Female JIC 37° Swivel
 E-47		 E-47		 E-47		 E-48		 E-49	
FORFS	Female Seal-Lok™ Swivel Short	**FP**	Female NPTF Pipe Rigid	**MBS**	Male Sanitary Bevel Seat	**MIL**	Male I-Line® Sanitary	**MP**	Male NPTF Pipe Rigid
 E-49		 E-48		 E-47		 E-48		 E-49	
MSAN	Mini Sanitary Flange	**PF**	ANSI Flange	**PLCF**	Female A-Lok® Compression	**SAN**	Sanitary Flange & Step Downs	**SFR**	Flange Retainer
 E-51		 E-50		 E-50		 E-51		 E-51	
TUBE	A-Lok® Male Stand pipe Rigid "V" Notch								
 E-50									

PAGE fittings require a PAGE collar. See pg. E-46.

NOTE:
The PAGE fitting call-out does not follow traditional Parker fitting nomenclature. The end size and hose size are reversed.

Length calculations for PAGE hose assemblies are typically made sealing surface to sealing surface per the NAHAD Fluoropolymer Hose Assembly Specification Guidelines unless otherwise requested by customer at time of order.

PAGE Fitting Collars - Size & Style

PAGE COLLARS

By Size

Hose	Collar # Size	04	06	08	12	16	20	24	32	40	48	64
STW STB	ST300	ST300	ST300	ST300	ST300	ST300	ST300	ST300				
SCW SCB	SC300	SC300	SC300	SC300	SC300	SC300	SC300	SC300	SC300			
PCW PCB	PC300	PC300	PC300	PC300	PC300	PC300	PC300	PC300	PC300			
SCWV SCBV	SC300			SC300	SC300	SC300	SC300	SC300	SC300	SC300	SC300	SC300
PCWV PCBV	PC300			PC300	PC300	PC300	PC300	PC300	PC300	PC300	PC300	PC300
SBFW SBFB	SBF300		SBF300	SBF300	SBF300	SBF300		SBF300				
RCTW RCTB	RC300			RC300	RC300	RC300	RC300	RC300	RC300	RC300	RC300	RC300

Inserts & Collars Sold Separately

Examples:
If you need a Female JIC Swivel Fitting for a 08-SCW Hose (1/2" Convoluted), place an order for (1) 08-08 FJX-S and (1) 08-SC300.

If you need a Male Pipe Fitting for a 12-RCTW Hose, place an order for (1) 12-12 MP-S and (1) 12-RC300.


By Style

Size	ST300	SC300	PC300	SBF300	RC300
	For use with STW/STB	For use with SCW/SCB, SCWV/SCBV	For use with PCW/PCB, PCWV/PCBV	For use with SBFW/SBFB	For use with RCTW/RCTB
1/4"	04-ST300	04-SC300	04-PC300	—	—
3/8"	06-ST300	06-SC300	06-PC300	06-SBF300	—
1/2"	08-ST300	08-SC300	08-PC300	08-SBF300	08-RC300
3/4"	12-ST300	12-SC300	12-PC300	12-SBF300	12-RC300
1"	16-ST300	16-SC300	16-PC300	16-SBF300	16-RC300
1-1/4"	20Z-ST300	20-SC300	20-PC300	—	20-RC300
1-1/2"	24Z-ST300	24-SC300	24-PC300	24-SBF300	24-RC300
2"	—	32-SC300	32-PC300	—	32-RC300
3"	—	48-SC300	48-PC300	—	48-RC300
4"	—	64-SC300	64-PC300	—	64-RC300

Construction: Stainless Steel.
NOTE: also available in carbon steel “CS”.

NOTE: The PAGE fitting call-out does not follow traditional Parker fitting nomenclature. The end size and hose size are reversed. Length calculations for PAGE hose assemblies are typically made sealing surface to sealing surface per the NAHAD Fluoropolymer Hose Assembly Specification Guidelines unless otherwise requested by customer at time of order.

CL Female Cam & Groove




Construction: Stainless Steel.

Part Number	Hose I.D.		A		E	
#	○					
	inch	mm	inch	mm	inch	mm
16-16CL	1	25	4.2	107	1.44	37
24-24CL	1-1/2	38	5.2	132	2.10	53
32-32CL	2	51	6.0	152	2.48	63
48-48CL	3	76	7.2	183	3.60	91
64-64CL	4	102	7.8	198	4.70	119

NOTE: Also available as encapsulated female cam under part number TEC and TECL.


E Male Cam & Groove



Construction: Stainless Steel.

Part Number	Hose I.D.		A		E	
#	○					
	inch	mm	inch	mm	inch	mm
12-12E	3/4	19	2.60	66	1.26	32
16-16E	1	25	2.91	74	1.44	37
20-20E	1-1/4	32	3.64	93	1.78	45
24-24E	1-1/2	38	4.03	102	2.10	53
32-32E	2	51	4.75	121	2.48	63
48-48E	3	76	5.75	146	3.60	91
64-64E	4	102	5.88	149	4.70	119


FBS Female Sanitary Bevel Seat



Construction: Stainless Steel.

Part Number	Acme Thread	Hose Size		A	
#		○			
	inch	inch	mm	inch	mm
16-16FBS	1-1/2-8	1	25	2.74	70
24-24FBS	2-8	1-1/2	38	3.41	87
32-32FBS	2-1/2-8	2	51	3.94	100
40-40FBS	3-8	2-1/2	64	4.37	110
48-48FBS	3-1/2-8	3	76	4.85	123
64-64FBS	4-5/8-6	4	102	5.24	133

MBS Male Sanitary Bevel Seat




Construction: Stainless Steel.

Part Number	Acme Thread	Hose Size		A	
#		○			
	inch	inch	mm	inch	mm
16-16MBS	1-1/2-8	1	25	2.74	70
24-24MBS	2-8	1-1/2	38	3.41	87
32-32MBS	2-1/2-8	2	51	3.94	100
40-40MBS	3-8	2-1/2	64	4.37	110
48-48MBS	3-1/2-8	3	76	4.85	123
64-64MBS	4-5/8-6	4	102	5.24	133

NOTE: The PAGE fitting call-out does not follow traditional Parker fitting nomenclature. The end size and hose size are reversed. Length calculations for PAGE hose assemblies are typically made sealing surface to sealing surface per the NAHAD Fluoropolymer Hose Assembly Specification Guidelines unless otherwise requested by customer at time of order.


FIL Female I-Line® Sanitary



Construction: Stainless Steel.

Part Number #	Hose I.D.		A		Flange Size C		D	
	inch	mm	Inch	mm	Inch	mm	Inch	mm
16-16FIL	1	25	2.60	66	1.25	32	2.00	51
24-24FIL	1-1/2	38	3.43	87	1.76	45	2.00	51
32-32FIL	2	51	4.23	107	2.26	57	2.64	67
40-40FIL	2-1/2	64	4.42	112	2.76	70	3.31	84
48-48FIL	3	76	4.84	123	3.31	84	3.87	98


MIL Male I-Line® Sanitary



Construction: Stainless Steel.

Part Number #	Hose I.D.		A		Flange Size C		D	
	inch	mm	Inch	mm	Inch	mm	Inch	mm
16-16MIL	1	25	2.60	66	1.25	32	2.00	51
24-24MIL	1-1/2	38	3.43	87	1.76	45	2.00	51
32-32MIL	2	51	4.23	107	2.26	57	2.64	67
40-40MIL	2-1/2	64	4.42	112	2.76	70	3.31	84
48-48MIL	3	76	4.84	123	3.31	84	3.87	98

FP Female NPTF Pipe Rigid




Construction: Stainless Steel.

Part Number #	Thread Size	Hose I.D.		A		H Hex
		inch	mm	Inch	mm	Inch
04-04FP	1/4-18	1/4	6	1.63	41	3/4
06-06FP	3/8-18	3/8	10	1.73	44	7/8
08-08FP	1/2-14	1/2	13	2.25	57	1-1/16
12-12FP	3/4-14	3/4	19	2.60	66	1-5/16
16-16FP	1-11 1/2	1	25	2.85	72	1-5/8
20-20FP	1 1/4-11 1/2	1-1/4	32	3.50	89	2
24-24FP	1 1/2-11 1/2	1-1/2	38	3.63	92	2-3/8
32-32FP	2-11 1/2	2	51	4.25	108	2-7/8

NOTE: The PAGE fitting call-out does not follow traditional Parker fitting nomenclature. The end size and hose size are reversed. Length calculations for PAGE hose assemblies are typically made sealing surface to sealing surface per the NAHAD Fluoropolymer Hose Assembly Specification Guidelines unless otherwise requested by customer at time of order.


MP Male NPTF Pipe Rigid



Construction: Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		H Hex
#						
		inch	mm	inch	mm	inch
04-04MP	1/4-18	1/4	6	1.63	41	9/16
06-06MP	3/8-18	3/8	10	1.76	45	11/16
08-08MP	1/2-14	1/2	13	2.34	59	7/8
12-12MP	3/4-14	3/4	19	2.59	66	1-1/8
16-16MP	1-11 1/2	1	25	3.00	76	1/3/8
20-20MP	1 1/4-11 1/2	1-1/4	32	3.39	86	1-3/4
24-24MP	1 1/2-11 1/2	1-1/2	38	3.89	99	2
32-32MP	2-11 1/2	2	51	4.58	116	2-1/2
40-40MP	2-1/2 8	2-1/2	64	5.28	134	3
48-48MP	3-8	3	76	5.93	151	3-3/4
64-64MP	4-8	4	102	6.82	173	4-5/8


FJX Female JIC 37° Swivel



Construction: Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		H Hex
#						
		inch	mm	inch	mm	inch
04-04FJX	7/16-20	1/4	6	1.44	37	9/16
06-06FJX	9/16-18	3/8	10	1.65	42	11/16
08-08FJX	3/4-16	1/2	13	2.13	54	7/8
12-12FJX	1-1/16-12	3/4	19	2.54	65	1-1/4
16-16FJX	1-5/16-12	1	25	2.76	70	1-1/2
20-20FJX	1-5/8-12	1-1/4	32	3.25	83	2
24-24FJX	1-7/8-12	1-1/2	38	3.73	95	2-1/4
32-32FJX	2-1/2-12	2	51	4.55	116	2-7/8
40-40FJX	3-12	2-1/2	64	4.76	121	3-3/8

FORFS Female Seal-Lok® Swivel Short




Construction: Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		C		H Hex	J Hex
#									
		inch	mm	inch	mm	inch	mm	inch	inch
04-04FORFS	9/16-18	1/4	6	1.50	38	.32	8	9/16	11/16
06-06FORFS	11/16-16	3/8	10	1.85	47	.32	8	11/16	13/16
08-08FORFS	13/16-16	1/2	13	2.00	51	.43	11	13/16	15/16
12-12FORFS	1-3/16-12	3/4	19	2.30	58	.57	14	1-1/8	1-3/8
16-16FORFS	1-7/16-12	1	25	2.50	64	.58	15	1-3/8	1-5/8
24-24FORFS	2-12	1-1/2	38	3.98	101	.59	15	2	2-1/4

NOTE: The PAGE fitting call-out does not follow traditional Parker fitting nomenclature. The end size and hose size are reversed. Length calculations for PAGE hose assemblies are typically made sealing surface to sealing surface per the NAHAD Fluoropolymer Hose Assembly Specification Guidelines unless otherwise requested by customer at time of order.


PLCF Female A-LOK® Compression (With Nut & Ferrules)



Construction: Stainless Steel.

Part Number	Thread Size	Hose Size		A		H Hex	J Hex
#							
		inch	mm	inch	mm	inch	inch
04-04PLCF	7/16-20	1/4	6	1.52	39	9/16	9/16
06-06PLCF	9/16-20	3/8	10	1.63	41	11/16	11/16
08-08PLCF	3/4-20	1/2	13	2.05	52	7/8	7/8
12-12PLCF	1-20	3/4	19	2.30	58	1-1/8	1-1/8
16-16PLCF	1-5/16-20	1	25	2.57	65	1-3/8	1-1/2


TUBE A-LOK® Male Standpipe Rigid with "V" Notch



Construction: Stainless Steel.

Part Number	Diameter R	Hose Size		A		C		D		H Hex
#	∅									
	inch	inch	mm	inch	mm	inch	mm	inch	mm	inch
04-04TUBE	1/4	1/4	6	1.75	45	.18	5	.66	17	7/16
06-06TUBE	3/8	3/8	10	2.06	52	.25	6	.85	2	5/8
08-08TUBE	1/2	1/2	13	2.56	65	.34	9	.97	25	3/4
12-12TUBE	3/4	3/4	19	2.86	73	.40	10	1.02	26	1-1/8
16-16TUBE	1	1	25	3.34	85	.52	13	1.30	33	1-3/8
20-20TUBE	1-1/4	1-1/4	32	4.05	10	.50	13	1.75	45	1-3/4

PF ANSI B16.5 Flange




Carbon Steel (Epoxy Coated)	316 Stainless Steel	304 Stainless Steel	Flange Diameter A		Hose Size		Bolt Spacing B	
#	#	#	∅					
Flange	Flange	Flange	inch	mm	inch	mm	inch	mm
08-PF150	08-PF156	08-PF154	3-1/2	89	1/2	13	2-3/8	60
12-PF150	12-PF156	12-PF154	3-7/8	98	3/4	19	2-3/4	70
16-PF150	16-PF156	16-PF154	4-1/4	108	1	25	3-1/8	79
20-PF150	20-PF156	20-PF154	4-5/8	117	1-1/4	32	3-1/2	89
24-PF150	24-PF156	24-PF154	5	127	1-1/2	38	3-7/8	98
32-PF150	32-PF156	32-PF154	6	152	2	51	4-3/4	120
40-PF150	40-PF156	40-PF154	7	178	2-1/2	64	5-1/2	140
48-PF150	48-PF156	48-PF154	7-1/2	191	3	76	6	152
64-PF150	64-PF156	64-PF154	9	229	4	102	7-1/2	191

NOTE: Also available in 300 lb. flange and other materials. Contact Customer Service for options.

NOTE: The PAGE fitting call-out does not follow traditional Parker fitting nomenclature. The end size and hose size are reversed. Length calculations for PAGE hose assemblies are typically made sealing surface to sealing surface per the NAHAD Fluoropolymer Hose Assembly Specification Guidelines unless otherwise requested by customer at time of order.


SFR Flange Retainer



Construction: Stainless Steel.

Part Number #	Flange Diameter ∅		Hose Size ○		A		Bolt Spacing E	
	inch	mm	inch	mm	inch	mm	inch	mm
08-08SFR	3-1/2	89	1/2	13	2.30	58	2-3/8	60
12-12SFR	3-7/8	98	3/4	19	2.60	66	2-3/4	70
16-16SFR	4-1/4	108	1	25	3.00	76	3-1/8	79
20-20SFR	4-5/8	117	1-1/4	32	3.25	83	3-1/2	89
24-24SFR	5	127	1-1/2	38	3.65	93	3-7/8	98
32-32SFR	6	152	2	51	4.25	108	4-3/4	120
40-40SFR	7	178	2-1/2	64	5.00	127	5-1/2	140
48-48SFR	7-1/2	191	3	76	5.50	140	6	152
64-64SFR	9	229	4	102	7.00	178	7-1/2	191


MSAN Mini Sanitary Flange



Construction: Stainless Steel.
Compliant ASME-BPE

Part Number #	Hose Size ○		A		Flange Size D	
	inch	mm	inch	mm	inch	mm
04-04MSAN	1/4	6	1.47	37	.98	25
04-08MSAN	1/4	6	1.50	38	.98	25
06-06MSAN	3/8	10	1.53	39	.98	25
06-08MSAN	3/8	10	1.53	39	.98	25
06-12MSAN	3/8	10	1.66	42	.98	25
08-08MSAN	1/2	13	1.90	48	.98	25
08-12MSAN	1/2	13	1.94	49	.98	25
12-12MSAN	3/4	19	2.16	55	.98	25
16-16MSAN	1	25	2.27	58	1.34	34

SAN Sanitary Flange & Step-Downs






Construction: Stainless Steel.
Compliant ASME-BPE

Part Number #	Hose Size ○		A		Flange Size D	
	inch	mm	inch	mm	inch	mm
08-08SAN	1/2	13	2.11	54	1.98	50
08-16SAN	1/2	13	2.11	54	1.98	50
08-24SAN	1/2	13	2.34	59	1.98	50
12-12SAN	3/4	19	2.32	59	1.98	50
16-16SAN	1	25	2.45	62	1.98	50
12-24SAN	3/4	19	2.34	59	1.98	50
16-24SAN	1	25	2.32	59	1.98	50
24-24SAN	1-1/2	38	3.10	79	1.98	50
24-32SAN	1-1/2	38	3.12	79	2.52	64
32-32SAN	2	51	3.67	93	2.52	64
40-40SAN	2-1/2	64	4.00	102	3.05	77
48-48SAN	3	76	4.50	114	3.58	91
64-64SAN	4	102	4.75	121	4.68	119


NOTE: The PAGE fitting call-out does not follow traditional Parker fitting nomenclature. The end size and hose size are reversed. Length calculations for PAGE hose assemblies are typically made sealing surface to sealing surface per the NAHAD Fluoropolymer Hose Assembly Specification Guidelines unless otherwise requested by customer at time of order.

BU Series Visual Index

BU Series
PERMANENT

201 Male Taper Pipe Rigid	206 Female SAE (JIC) 37° Swivel	213 Male Taper Pipe Swivel
		
E-52	E-52	E-52


201BU Male Taper Pipe Rigid



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	W Hex
#									
		inch	mm	inch	mm	inch	mm	inch	inch
201BU-2-2	1/8-27	1/8	3	1.50	38	1	25	7/16	7/16

Construction: Steel.

206BU Female SAE (JIC) 37° Swivel




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex	W Hex
#										
		inch	mm	inch	mm	inch	mm	inch	inch	inch
206BU-3-2	3/8-24	1/8	3	1.72	44	1-3/16	30	1/2	9/16	7/16
206BU-4-2	7/16-20	1/8	3	1.77	45	1-3/16	30	9/16	9/16	7/16
206BU-4-3	7/16-20	3/16	5	1.89	48	1-1/16	27	9/16	9/16	7/16

NOTE: Size -4 incorporates a dual seat.

Construction: Steel.

213BU Male Taper Pipe Swivel





















Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex	W Hex
#										
		inch	mm	inch	mm	inch	mm	inch	inch	inch
213BU-2-2	1/8-27	1/8	3	2.07	53	1-1/2	38	1/2	1/2	7/16

WARNING: Fittings allow minor movement to relieve stress on hose but are not recommended for continued or extensive swiveling. Not recommended for use in CNG applications.


Construction: Steel.

CG Series Visual Index

CG Series
PERMANENT

101 Male Taper Pipe Rigid	102 Female Taper Pipe Rigid	103 Male (JIC) 37° Rigid	105 Male Str. Thread O-ring	106 SAE (JIC) 37° Swivel
 E-53	 E-54	 E-54	 E-54	 E-55
107 Female Pipe Swivel	**111** Ferrul-Fix	**137** FM JIC 37° Swivel 45° Elbow	**139** FM JIC 37° Swivel 90° Elbow	**1AL** A-Lok® Compression
 E-55	 E-55	 E-56	 E-56	 E-56
1FU (JIS)/BSP 30° Flare Female Swivel	**1J0** Male Seal-Lok™ Rigid Str. w/O-ring	**1J7** Female Seal-Lok™ 45° Elbow	**1J9** Female Seal-Lok™ 90° Elbow Short	**1JC** Female Seal-Lok™ Str. Swivel Short
 E-57	 E-57	 E-57	 E-57	 E-58
1JS Female Seal-Lok™ Straight	**1L9** FM JIC 37° Swivel 90° Elbow, SPL Drop	**1TU** Universal Tube Stub End		
 E-58	 E-58	 E-58		


101CG Male Taper Pipe Rigid



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#								
		inch	mm	inch	mm	inch	mm	inch
101CG-2-3	1/8-27	3/16	5	1.94	49	1	25	9/16
101CG-2-4	1/8-27	1/4	6	2.13	54	1	25	5/8
101CG-4-3	1/4-18	3/16	5	2.12	54	1-3/16	30	11/16
101CG-4-4	1/4-18	1/4	6	2.31	59	1-3/16	30	11/16
101CG-4-6	1/4-18	3/8	10	2.66	68	1-5/16	33	3/4
101CG-6-4	3/8-18	1/4	6	2.41	61	1-5/16	33	3/4
101CG-6-6	3/8-18	3/8	10	2.66	68	1-5/16	33	3/4
101CG-6-8	3/8-18	1/2	13	2.85	72	1-5/16	33	7/8
101CG-8-6	1/2-14	3/8	10	2.91	74	1-9/16	40	15/16
101CG-8-8	1/2-14	1/2	13	3.09	78	1-9/16	40	15/16
101CG-12-12	3/4-14	3/4	19	3.91	99	1-11/16	43	1-1/4
101CG-16-16	1-11-1/2	1	25	4.76	121	2	51	1-3/4


102CG Female Taper Pipe Rigid



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#								
		inch	mm	inch	mm	inch	mm	inch
102CG-4-4	1/4-18	1/4	6	2.39	61	1-1/4	32	3/4
102CG-6-4	3/8-18	1/4	6	2.60	66	1-1/2	38	7/8
102CG-8-8	1/2-14	1/2	13	2.87	73	1-3/8	35	1-1/16


103CG Male (JIC) 37° Rigid



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#								
		inch	mm	inch	mm	inch	mm	inch
103CG-4-4	7/16-20	1/4	6	2.31	58	1-3/16	30	5/8
103CG-5-4	1/2-20	1/4	6	2.30	58	1-3/16	30	5/8
103CG-6-4	9/16-18	1/4	6	2.30	58	1-3/16	30	11/16
103CG-6-6	9/16-18	3/8	10	2.65	67	1-1/4	32	3/4


105CG Male Straight Thread O-ring (Nitrile O-ring included)



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#								
		inch	mm	inch	mm	inch	mm	inch
105CG-4-3	7/16-20	3/16	4	1.98	50	1-1/8	29	9/16
105CG-4-4	7/16-20	1/4	6	2.11	54	1	25	5/8
105CG-6-4	9/16-18	1/4	6	2.14	54	1	25	11/16
105CG-6-6	9/16-18	3/8	10	2.42	61	1-1/8	29	3/4
105CG-8-8	3/4-16	1/2	13	2.65	67	1-3/16	30	7/8
105CG-10-8	7/8-14	1/2	13	2.77	70	1-5/16	33	1

106CG SAE (JIC) 37° Swivel




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
#									
		inch	mm	inch	mm	inch	mm	inch	inch
106CG-3-3	3/8-24	3/16	5	2.23	57	1-5/16	33	9/16	9/16
106CG-4-3	7/16-20	3/16	5	2.23	57	1-1/4	32	9/16	9/16
106CG-4-4	7/16-20	1/4	6	2.36	60	1-3/16	30	5/8	9/16
106CG-5-4	1/2-20	1/4	6	2.43	62	1-1/4	32	5/8	5/8
106CG-6-4	9/16-18	1/4	6	2.45	62	1-5/16	33	5/8	11/16
106CG-6-6	9/16-18	3/8	10	2.70	69	1-5/16	33	11/16	11/16
106CG-8-6	3/4-16	3/8	10	2.89	73	1-1/2	38	11/16	7/8
106CG-8-8	3/4-16	1/2	13	3.08	78	1-1/2	38	7/8	7/8
106CG-10-8	7/8-14	1/2	13	3.12	79	1-5/8	41	7/8	1-1/16
106CG-12-8	1-1/16-12	1/2	13	3.35	85	1-13/16	46	1	1-1/4
106CG-12-12	1-1/16-12	3/4	19	4.17	106	1-13/16	46	1-1/4	1-5/16
106CG-16-12	1-5/16-12	3/4	19	4.27	108	2	51	1-1/2	1-5/8
106CG-16-16	1-5/16-12	1	25	4.93	125	2-3/16	56	1-3/4	1-5/8

NOTE: Sizes -4, -5,-8 and -10 incorporate a dual seat.


107CG Female Pipe Swivel



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
#									
		inch	mm	inch	mm	inch	mm	inch	inch
107CG-6-6	3/8-18	3/8	10	2.61	66	1-3/16	30	11/16	7/8

111CG Ferrul-Fix (Nut and Sleeve included)




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Tube O.D.		Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
#											
		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
111CG-6-4	9/16-18	3/8	10	1/4	6	2.34	59	1-1/8	32	11/16	11/16

NOTE: Nut Part Number is 111-size. Sleeve Part Number is 110-size. Nut and Sleeve are Manufactured by the Tube Fittings Division. Refer to Catalog 4300 for additional information.

"Ferrul-Fix" affords salvaging of bent tube section of combination tube-hose assemblies and quick, easy repair on the job. See page G-41 for Ferrule-Fix installation instructions.


137CG Female JIC 37° Swivel 45° Elbow



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		H Hex	J Hex
#											
		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
137CG-4-4	7/16-20	1/4	6	2.49	63	1-1/2	38	0.33	8	5/8	9/16
137CG-6-6	9/16-18	3/8	10	2.91	74	1-9/16	40	0.39	10	3/4	11/16
137CG-8-8	3/4-16	1/2	13	3.37	86	1-13/16	46	0.55	14	7/8	7/8


139CG Female JIC 37° Swivel 90° Elbow



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		H Hex	J Hex
#											
		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
139CG-4-4	7/16-20	1/4	6	2.49	63	1-3/8	35	0.68	17	5/8	9/16
139CG-6-4	9/16-18	1/4	6	2.57	65	1-9/16	36	0.85	22	5/8	11/16
139CG-6-6	9/16-18	3/8	10	2.88	73	1-1/2	38	0.91	23	3/4	11/16
139CG-8-6	3/4-16	3/8	10	2.92	74	1-9/16	40	1.09	28	3/4	7/8
139CG-8-8	3/4-16	1/2	13	3.11	79	1-5/8	41	1.09	28	7/8	7/8
139CG-12-12	1-1/16-12	3/4	19	4.55	116	2-1/4	57	1.82	46	1-1/8	1-1/4

1ALCG A-LOK® Compression (With Nut and Ferrule)




Construction: Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
#									
		inch	mm	inch	mm	inch	mm	inch	inch
1ALCG-6-6C	9/16-20	3/8	3/8	2.56	65	13/16	21	3/4	11/16

NOTE: Nut part No. is **XNUX** or **XNUX-316** for stainless steel.
Front ferrule part No. is **XFFX** or **XFFX-316** for stainless steel.
Back ferrule part No. is **XBFX** or **XBFX-316** for stainless steel.
X denotes dash size.

Nuts and Ferrules are Manufactured by the Instrumentation Products Division.
Refer to Catalog 4300 for additional information


1FUCG (JIS)/BSP 30° Flare Female Swivel
ISO 228-1



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
#									
		inch	mm	inch	mm	inch	mm	inch	inch
1FUCG-4-4	PF 1/4-19	1/4	6	2.48	63	1-9/16	40	19	19


1J0CG Male Seal-Lok™ Rigid Straight (with Nitrile O-ring)
ISO 12151-1-S



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#								
		inch	mm	inch	mm	inch	mm	inch
1J0CG-4-4	9/16-18	1/4	6	2.20	56	1-1/16	27	5/8


1J7CG Female Seal-Lok™ Swivel 45° Elbow
ISO 12151-1-SWE45



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		H Hex	J Hex
#											
		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
1J7CG-4-4	9/16-18	1/4	6	2.66	68	1-1/2	38	0.41	10	5/8	11/16
1J7CG-8-8	13/16-16	1/2	13	3.43	87	1-15/16	49	0.59	15	7/8	15/16
1J7CG-12-12	1-3/16-12	3/4	19	4.51	115	2-3/16	56	0.81	21	1-1/8	1-3/8


1J9CG Female Seal-Lok™ Swivel 90° Elbow Short Drop
ISO 12151-1-SWE90



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		H Hex	J Hex
#											
		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
1J9CG-4-4	9/16-18	1/4	6	2.49	63	1-3/8	35	0.82	21	5/8	11/16
1J9CG-6-6	11/16-16	3/8	10	2.85	72	1-1/2	38	0.91	23	3/4	13/16
1J9CG-12-12	1-3/16-12	3/4	19	4.42	112	2-1/8	54	1.89	48	1-1/8	1-3/8
1J9CG-16-16	1-7/16-12	1	25	5.78	147	3	76	2.28	58	1-3/4	1-5/8


1JCCG Female Seal-Lok™ Straight Swivel Short
ISO 12151-1-SWSA



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		C		H Hex	J Hex
#											
		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
1JCCG-4-3	9/16-18	3/16	5	1.88	48	15/16	24	.32	8	9/16	11/16
1JCCG-4-4	9/16-18	1/4	6	2.16	55	1-1/16	25	.32	8	5/8	11/16
1JCCG-6-4	11/16-16	1/4	6	2.22	56	1-1/16	27	.32	8	11/16	13/16
1JCCG-6-6	11/16-16	3/8	10	2.47	63	1-1/16	27	.32	8	11/16	13/16
1JCCG-8-6	13/16-16	3/8	10	2.56	65	1-3/16	30	.43	11	7/8	15/16
1JCCG-8-8	13/16-16	1/2	13	2.75	70	1-3/16	30	.43	11	7/8	15/16
1JCCG-10-8	1-14	1/2	13	2.95	75	1-3/8	35	.53	13	1-1/8	1-1/8
1JCCG-12-12	1-3/16-12	3/4	19	3.86	98	1-1/2	38	.55	14	1-1/4	1-3/8
1JCCG-16-16	1-7/16-12	1	25	4.66	118	1-7/8	48	.56	14	1-3/4	1-5/8


1JSCG Female Seal-Lok™ Straight



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
#									
		inch	mm	inch	mm	inch	mm	inch	inch
1JSCG-4-4	9/16-18	1/4	6	2.42	61	1-1/4	32	5/8	11/16
1JSCG-6-6	11/16-16	3/8	10	2.73	69	1-5/16	33	11/16	13/16
1JSCG-8-6	13/16-16	3/8	10	3.00	76	1-5/8	41	7/8	15/16
1JSCG-12-12	1-3/16-12	3/4	19	4.29	109	2	51	1-1/4	1-3/8
1JSCG-16-16	1-7/16-12	1	25	4.99	127	2-3/16	56	1-3/4	1-5/8


1L9CG Female JIC 37° Swivel 90° Elbow Special Drop



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		H Hex	J Hex
#											
		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
1L9CG-4-4	7/16-20	1/4	6	2.47	63	1-3/8	35	0.88	22	5/8	9/16
1L9CG-6-6	9/16-18	3/8	10	2.88	73	1-7/16	36	1.12	28	3/4	11/16

1TUCG Universal Inch Tube Stub End








Construction: Stainless Steel.






Part Number	Diameter R	Hose I.D.		A		Cutoff Allow. B		C		H Hex
#	∅									
		inch	mm	inch	mm	inch	mm	inch	mm	inch
1TUCG-4-4C	1/4	1/4	6	2.60	66	1-1/2	38	0.72	18	5/8
1TUCG-6-6C	3/8	3/8	10	2.91	74	1-1/2	38	0.78	20	3/4
1TUCG-8-8C	1/2	1/2	13	3.35	85	1-13/16	46	1.03	26	7/8
1TUCG-12-12C	3/4	3/4	19	4.18	106	1-7/8	48	1.03	26	1-1/4
1TUCG-16-16C	1	1	25	5.14	131	2-3/8	60	1.36	35	1-3/4

NOTE: Use with A-Lok & CPI nuts, sleeves and adapters. These components are manufactured by Parker's Instrumentation Connectors Division. Refer to catalogs 4230 & 4233 for additional information.



CY Series Visual Index

CY Series
PERMANENT


101 Male Taper Pipe Rigid	102 Female Pipe Thread	106 Female SAE JIC 37° Swivel	113 Male Pipe Swivel	139 Female JIC 37° Swivel 90° Elbow Sht.
 E-59	 E-59	 E-60	 E-60	 E-60

1GK Bulkhead w/Zerk Port Integrated	1J9 Female Seal-Lok™ 90° Elbow Sht.	1JC Female Seal-Lok™ Swivel Straight Short	1LM Male Grease	1PD Integrated Bulkhead Diagnostic Nipple
 E-61	 E-61	 E-60	 E-61	 E-61

1GKCY
OPTIONS

Nut 2GK-Nut	Zerk NA-6520
 E-61	 E-61


101CY Male Taper Pipe Rigid



Construction: Steel. Add “C” for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#								
		inch	mm	inch	mm	inch	mm	inch
101CY-2-2	1/8-27	1/8	3	1.31	33	13/16	21	7/16
101CY-2-3	1/8-27	3/16	5	1.74	44	7/8	22	1/2
101CY-4-2	1/4-18	1/8	3	1.51	38	1	25	9/16
101CY-4-3	1/4-18	3/16	5	1.97	50	1-1/8	28	9/16


102CY Female Pipe Thread



Construction: Steel. Add “C” for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#								
		inch	mm	inch	mm	inch	mm	inch
102CY-2-3	1/8-27	3/16	5	1.97	50	1-1/16	27	1/2

106CY Female SAE (JIC) 37° Swivel




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
#									
		inch	mm	inch	mm	inch	mm	inch	inch
106CY-2-2	5/16-24	1/8	3	1.52	39	15/16	24	7/16	7/16
106CY-3-2	3/8-24	1/8	3	1.55	39	1	25	1/2	1/2
106CY-4-2	7/16-20	1/8	3	1.58	40	1	25	7/16	9/16
106CY-4-3	7/16-20	3/16	5	1.98	50	1-1/16	27	9/16	9/16

NOTE: Size -4 incorporates a dual seat.

113CY Male Pipe Swivel*




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
#									
		inch	mm	inch	mm	inch	mm	inch	inch
113CY-2-2	1/8-27	1/8	3	1.89	48	1-5/16	33	1/2	1/2
113CY-2-3	1/8-27	3/16	3	2.29	58	1-7/16	36	1/2	1/2

*NOTE: Nitrile O-ring. See O-ring Material Selection section, pg. G-48.
WARNING: Fittings allow minor movement to relieve stress on hose but are not recommended for continued or extensive swiveling. Not recommended for use in CNG applications.


139CY Female JIC 37° Swivel 90° Elbow Short Drop



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		inch	mm	inch	mm	inch	mm	inch	mm	inch
139CY-4-2	7/16-20	1/8	3	1.61	41	1-1/8	29	0.83	21	9/16
139CY-4-3	7/16-20	3/16	5	1.90	48	1	25	0.83	21	9/16

1JCCY Female Seal-Lok™ Swivel Straight Short




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		C		H Hex	J Hex
#											
		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
1JCCY-4-2	9/16-18	1/8	3	1.29	33	3/4	19	.32	8	9/16	11/16

NOTE: When measuring overall length to the end of the nut, B+C dimensions must be used to calculate cut-off allowance.


1GKCY Bulkhead with Integrated Zerk Port Bulkhead Nut and Grease Zerk




Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#								
		inch	mm	inch	mm	inch	mm	inch
1GKCY-2-2*	1/8-27 NPSM Male with 1/4-28 UNF Female	1/8	3	1.45	37	7/8	22	1/2
1GKCY-2-3*	1/8-27 NPSM Male with 1/4-28 UNF Female	3/16	5	1.86	47	1	25	1/2
1GKCY-2-2-L77**	1/8-27 NPSM Male with 1/4-28 UNF Female	1/8	3	1.71	43	1-1/4	32	1/2

NOTE: *Standard bulkhead for use with plates up to 1/4" thick. Uses 2GK-NUT, sold separately.
**Long bulkhead for use with plates under 3/4" thick. Uses 2GK-NUT, sold separately.




2GK-Nut



NA-6520

Part Number	Description	Thread Size	A		C		H Hex
2GK-Nut	Bulkhead Nut	1/8-27 NPSM	0.188	4.8	na	na	11/16
NA-6520	Grease Zerk Fitting	1/4-28 UNF	0.540	13.7	0.18	4.6	5/16
CY02-652317	HLB02 Spring Guard	-	-	-	-	-	-
3PSG-4	HLB03 Spring Guard	-	-	-	-	-	-


1J9CY Female Seal-Lok™ 90° Elbow Short Drop



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
#										
		inch	mm	inch	mm	inch	mm	inch	mm	inch
1J9CY-4-2	9/16-18	1/8	3	1.81	46	1-1/4	32	.83	21	11/16


1LMCY Male Grease



Construction: Steel. Add "C" for Stainless Steel.

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#								
		inch	mm	inch	mm	inch	mm	inch
1LMCY-2-2	1/4-28	1/8	3	1.26	32	11/16	17	3/8

1PDCY Integrated Bulkhead Diagnostic Nipple






Construction: Steel. Add "C" for Stainless Steel.


Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#								
		inch	mm	inch	mm	inch	mm	inch
1PDCY-2-2	3/4"-16 UNF	1/8	3	2.40	61	1.875	48	1

NOTE: Bulkhead nut sold with fitting.

MS Series Visual Index

MS Series PERMANENT	108 SAE 45° Swivel	134 Straight Tube	1TF Marine Tube Connector
			
	E-62	E-62	E-62


108MS Permanent SAE 45° Swivel (Brass)



Construction: Brass

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
#									
		inch	mm	inch	mm	inch	mm	inch	inch
108MS-6-5B	5/8-18	5/16	8	1.75	45	1-1/8	29	5/8	13/16
108MS-6-6B	5/8-18	3/8	10	1.82	46	1-1/16	27	3/4	13/16


134MS Permanent Straight Tube (Brass)



Construction: Brass

Part Number	Diameter R		Hose I.D.		A		Cutoff Allow. B		H Hex
#	∅								
	inch	mm	inch	mm	inch	mm	inch	mm	inch
134MS-6-5B	3/8	10	5/16	8	2.00	51	1-3/8	35	5/8
134MS-6-6B	3/8	10	3/8	10	2.08	53	1-3/8	35	3/4

1TFMS Permanent Marine Tube Connector (Brass)




Construction: Steel nipple, nut and shell.


Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		J Hex	H Hex
#									
		inch	mm	inch	mm	inch	mm	inch	inch
1TFMS-6-5B	9/16-24	5/16	8	1.70	43	1 1/16	27	3/4	5/8

NOTE: Connector Mates are Manufactured by the Fluid Systems Connection Division. Refer to Catalog 3501E for Ordering, Installation Instructions and Replacement Components.

MS Series
FIELD ATTACHABLE

208 SAE 45° Swivel	2TF Marine Tube Connector
	
E-63	E-63


208MS Field-Attachable SAE 45° Swivel (Brass)



Construction: Brass

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		J Hex	H Hex	W Hex
#										
		inch	mm	inch	mm	inch	mm	inch	inch	inch
208MS-6-5B	5/8-18	5/16	8	2.06	52	1 5/16	33	13/16	5/8	5/8
208MS-6-6B	5/8-18	3/8	10	2.37	60	1 7/16	37	13/16	5/8	5/8

2TFMS Field-Attachable Marine Tube Connector (Brass)







Construction: Brass

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		J Hex	H Hex	W Hex
#										
		inch	mm	inch	mm	inch	mm	inch	inch	inch
2TFMS-6-5B	9/16-24	5/16	8	2.02	51	1 5/16	33	3/4	5/8	5/8


NOTE: Connector Mates are Manufactured by the Fluid Systems Connection Division. Refer to Catalog 3501E for more information.

SF Series Visual Index

SF Series
PERMANENT

101 Male Taper Pipe Rigid	106 JIC 37° Swivel	1JS Female Seal-Lok™ Swivel Long	1JB Male Seal-Lok™ Bulkhead w/O-ring
			
E-64	E-64	E-64	E-64


101SF Male Taper Pipe Rigid



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#								
		inch	mm	inch	mm	inch	mm	inch
101SF-2-1	1/8-27	.090	2.3	1.13	29	3/4	19	7/16

Construction: Steel.


106SF JIC 37° Swivel



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
#									
		inch	mm	inch	mm	inch	mm	inch	inch
106SF-2-1	5/16-24	.090	2.3	1.37	35	15/16	24	7/16	1/2

Construction: Steel.


1JSSF Female Seal-Lok™ Swivel Long



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#								
		inch	mm	inch	mm	inch	mm	inch
1JSSF-4-1	9/16-18	.090	2.3	1.18	29.8	3/4	19	11/16

Construction: Steel.

1JBSF Male Seal-Lok™ Bulkhead with O-ring





Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#								
		inch	mm	inch	mm	inch	mm	inch
1JBSF-4-1	9/16-18	.090	2.3	2.06	52	1-11/16	43	5/8

Construction: Steel.


NOTE: Bulkhead Locknut sold separately.
WLNL Locknuts are manufactured by the Tube Fittings Division. Refer to Catalog 4300 for information.

For detailed ordering information, please consult price list or contact Parflex Division.

SQ Series Visual Index

SQ Series PERMANENT	101 Male Taper Pipe Rigid	1HU SQ Mender
		
	E-65	E-65

101SQ Male Taper Pipe Rigid




Construction: Steel.

Part Number		Hose I.D.		A		Cutoff Allow. B	
	#		○				
Hose		inch	mm	inch	mm	inch	mm
S612	101SQ-12-12	3/4	19	3.08	78	1-1/2	38
S616	101SQ-16-16	1	25	3.42	87	1-13/16	46
S912	101SQ-12-12	3/4	19	3.08	78	1-1/2	38
S916	101SQ-16-16	1	25	3.42	87	1-13/16	46

NOTE: See pg. G-35 for swage die selection.

1HUSQ Mender



Construction: Steel.

Part Number		Hose I.D.		A		Cutoff Allow. B	
	#		○				
Hose		inch	mm	inch	mm	inch	mm
S612	1HUSQ-12-12	3/4	19	3.70	94	9/16	14
S616	1HUSQ-16-16	1	25	3.99	101	9/16	14
S912	1HUSQ-12-12	3/4	19	3.70	94	9/16	14
S916	1HUSQ-16-16	1	25	3.99	101	9/16	14

NOTE: See pg. G-35 for swage die selection.

Notes

Equipment & Accessories

MiniKrimp™

Karrykrimp

Karrykrimp 2

Parkrimp2

Pumps

Accessories



Table of Contents

Crimpers

Karrykrimp F-10
Karrykrimp 2 ..... F-11
MiniKrimp™ F-5
Parkrimp 2 ..... F-12

Pumps

Air Over Hydraulic Pumps F-13
Electric Pumps F-14
Hand Pumps ..... F-13 : F-14

Conversion Kits

Hydraulic Press, Gates, Weatherhead F-16

Sewer Hose Swager & Swage Tooling

SQ-101-SW Swager/Mender F-13

Accessories

Cut-off Tools F-17
Dies (Parkrimp 2) F-15
Die Racks F-15
Hose Guards/Sleeves ..... F-18 : F-22
Hose Insertion Depth Blocks F-14
SplashShield Protective Cover F-22
Vise Blocks F-14

Technical

MiniKrimp Assembly Detail ..... F-8 : F-9
Spring/Armor/PVC Guard Selection Tables ..... F-19 : F-20

For detailed ordering information, please consult price list or contact Parflex Division.

Tooling, Equipment & Accessories Visual Index

MiniKrimp™

94C-001-PFD	94C-002-PFD	Hose Stand 94C-MKS
		
F-5	F-5	F-7

Karrykrimp

Karrykrimp 82C-061L-PFD	Karrykrimp Bench Mount 82C-KKB-PFD	Karrykrimp2 85C-061L-PFD	Karrykrimp 2 Bench Mount 85C-KKB-PFD
			
F-10	F-10	F-11	F-11

Parkrimp 2

Parkrimp 2 83C-081-PFD

F-12

Swagers, Swager Tooling

Swager Mender SQ-101-SW

F-13

Pumps

Hand Pump 015301	Hand Pump 82C-0HP-PFD	Hand Pump 85C-0HP-PFD	Air/Hydraulic Pump 025399	Air/Hydraulic Pump 82C-0AP
				
F-13	F-14	F-14	F-13	F-13

Electric Pump 82C-0EP-PFD	Electric Pump 85C-0EP-PFD
	
F-14	F-14

Parkrimp Dies

Dies	Die Storage Racks
	
F-15	F-15

For detailed ordering information, please consult price list or contact Parflex Division.

Tooling, Equipment & Accessories Visual Index

Conversion Kits

Hydraulic Press Kit	Weatherhead Kit	Gates Kit
		
F-16	F-16	F-16

Vise Blocks

Vise Blocks VBS & VBL

F-14

Hose Insertion Depth Blocks

TH-9-1-xxx TH-8-1-xxx

F-14

Cutoff Tools

Hose Cutoff Machine 332T-115V	Push-Lok Cut-Off 885140	Hose Cutter HTC	Hose Cutter TH11-1	Plastic Tube Cutter PTC
				
F-17	F-17	F-17	F-17	F-17

Hose Guards & Sleeves

AG Flat Steel Armor	AS Partek Sleeve	CNG CNGG Guard Kit	FS Fire Sleeve	HBR Bend Restrictor
				
F-19	F-20*	F-18	F-20*	F-18
PSG and SSG Pre-Made Spring	**PSG Parker Spiral Guard**	**PV Clear Vinyl**	**SG Steel Spring Guard**	**SplashShield Protective Cover**
				
F-19	F-21	F-18	F-19	F-22
2613 Internal FlatSpring	**2625 External Round Spring**	**2740 External Flat Spring**	**2799 Internal Round Spring**	
				
F-20*	F-20*	F-20*	F-20*	

* Items on page F-20 are for PTFE hose.

For detailed ordering information, please consult price list or contact Parflex Division.

Crimping Machines

MiniKrimp™ Hand Pump Model

Part No. 94C-001-PFD

The Parker Hannifin MiniKrimp is the best portable crimper on the market. By utilizing a one-piece, high-strength cast aluminum frame, the MiniKrimp is light, robust and highly corrosion resistant.

For use with 54, 56, 91, 91N, 92, 93N, CG, CY, MS, SF and HY Series fittings



Features

- Lightweight, portable, compact all-in-one unit
- Unit with pump weighs only 42 pounds
- 10,000 psi and 30+ tons of force
- No gauges to set - exclusive Parkalign™ feature positions the fitting correctly every time
- Removable pusher design for easy die change
- Hand pump easily removed for use with jumper hose for bench-mounted units (Part No.– 015309)
- No additional power source required for operation
- Capable of crimping a majority of thermoplastic, rubber, PTFE and specialty hoses up to 3/4" I.D.

Specifications

- Dimensions: 6" Deep, 13" Wide, 15" High
- Weight: 42 lbs with hand pump
- Rating: 30 tons force @ 10,000 psi maximum
- Full Cycle Time: Approximately 30 seconds

Standard Equipment

Part Number			Individual
94C-001-PFD	94C-002 -PFD	Description	Part Number
●	●	Base unit	94C-080-PFD
●		Hand pump	015301
	●	Air over hydraulic pump kit with tubing and adapters	025399
●	●	Silver die ring	82C-R01-PFD

MiniKrimp™ Air Over Hydraulic Model

Part No. 94C-002-PFD

The Parker Hannifin MiniKrimp is the best portable crimper on the market. By utilizing a one-piece, high-strength cast aluminum frame, the MiniKrimp is light, robust and highly corrosion resistant.

For use with 54, 56, 91, 91N, 92, 93N, CG, CY, MS, SF and HY Series fittings



Features

- Lightweight, portable, compact all-in-one unit
- Unit with pump weighs only 45 pounds
- 10,000 psi and 30+ tons of force
- No gauges to set - exclusive Parkalign™ feature positions the fitting correctly every time
- Removable pusher design for easy die change
- Air pump utilizes a rugged activation and release lever for greater durability
- Can operate with as little as 60 psi air pressure (60-100 psi, 9 CFM recommended)
- Capable of crimping a majority of thermoplastic, rubber, PTFE and specialty hoses up to 3/4" I.D.

Specifications

- Dimensions: 6" Deep, 12" Wide, 15" High
- Weight: 45 lbs with air/hydraulic pump
- Rating: 30 tons force @ 10,000 psi maximum
- Full Cycle Time: Approximately 30 seconds

Operating Parameters

Reference Crimpsource™ online or appropriate catalog (4660 or 4400) of the Parker division that supplies the hose for detailed crimp specifications as exceptions do occur based on the particular hose type, size, and fitting material.
www.parker.com/crimpsource

MiniKrimp™ Crimping Machine Accessories



Upright Vise Mount
Part No. 015307

- Material - High Strength Steel
- Mount connects to the bottom of the MiniKrimp using (4) 3/8-16 18-8 SS SHCS 2.5" long bolts (not included)
- Once connected, the Minikrimp can be clamped into a vise for operation




Side Vise Mount
Part No. 015736

- Manufactured from high strength steel
- Mount connects to the side of the MiniKrimp using four 1/4"-20 18-8 SS SHCS , 1" long bolts (not included)
- Once connected, MiniKrimp can be clamped into a vise for operation



Table Mount
Part No. 015306

- Material - High Strength Steel
- Mount connects to the bottom of the MiniKrimp using (4) 3/8-16 18-8 SS SHCS 2.5" long bolts (not included)
- Once connected, the Minikrimp can be mounted to a table using the (4) 3/8" clearance holes on the opposite side of the plate (bolts not included)



High Pressure Hose Assembly
Part No. 015309

- Parker 10,000 psi, 1/4" I.D. hose with 3/8" female JIC connections on both ends (PN HP0606060604-72")
- Hose is used when a flexible connection is required between the MiniKrimp and a hydraulic pressure source



Replacement Connector
Part No. 015308

- Replacement stainless-steel bent tube rigid connector
- For use with 94C-001-PFD (MiniKrimp Hand Pump Model)



Replacement Connector
Part No. 025349

- Replacement stainless-steel bent tube rigid connector
- For use with 94C-002-PFD (MiniKrimp Air Over Hydraulic Model)

Note: The hydraulic connectors shown on this page are designed exclusively for use with the MiniKrimp. No other connectors are approved for use with the MiniKrimp without expressed written consent from Parker Parflex Division's technical support. Any worn connectors should be replaced immediately.



High Pressure Hose Assembly
Part No. 045234

- Parker 10,000 psi, 1/4" ID hose assembly with 3000 series quick disconnects (PN - HP0101060404-36" with 3050-2/3010-2 coupler and nipple)
- Hose is designed to be used when mounting a hand pump (015301) to the MiniKrimp stand (94C-MKS) base



Folding Stand
Part No. 94C-MKS

(See pictures below for configuration examples)

- Lightweight folding stand designed exclusively for the MiniKrimp portable crimper
- Fold up design is easy to store
- Mounting hardware and safety instructions are included
- Patented design



Hand Pump MiniKrimp™



Hand Pump MiniKrimp™




Air Over Hydraulic MiniKrimp™




Air Over Hydraulic MiniKrimp™ and Folding Stand

MiniKrimp™ Assembly Detail & Parts List
Hand Pump Model

Part No.	Description	Qty.
015301	2 Speed Light Weight Hand Pump	1
015302	Hardened Steel Sleeve	1
015303	Custom Cylinder	1
015304	Aluminum Frame	1
015305	Cup Pusher	1
015306	Bent Tube Assembly	1
015310	3/8" x 3/8" Shoulder Bolt	1
015415	Spring Plunger	1
6 CTX-S	3/8" 37° to 1/4" NPT Elbow	1
6-6 CTX-S	3/8" 37° to 3/8" NPT Elbow	1
822011	Die Separator	1
822012	Spring	1
822031	Retention Ring	1
82C-R01-PFD	Silver Die Ring	1
015411	3/8-16 18-8 SS SHCS 2.5" Long	2
015413	1/4-20 18-8 SS Lock Washer	2
015414	1/4-20 18-8 SS Flat Washer	2
015412	1/4-20 18-8 SS SHCS .75" Long	4




MiniKrimp™ Serial Number




For detailed ordering information, please consult price list or contact Parflex Division.

Air Over Hydraulic Model



Part No.	Description	Qty.
015302	Hardened Steel Sleeve	1
015303	Custom Cylinder	1
015304	Aluminum Frame	1
015305	Cup Pusher	1
015310	3/8" x 3/8" Shoulder Bolt	1
015415	Spring Plunger	1
6-2 CTX-S	3/8" 37° to 1/8" NPT Elbow	1
6-6 CTX-S	3/8" 37° to 3/8" NPT Elbow	1
822011	Die Separator	1
822012	Spring	1
822031	Retention Ring	1
82C-R01-PFD	Silver Die Ring	1
015411	3/8-16 18-8 SS SHCS 2.5" Long	2
015413	1/4-20 18-8 SS Lock Washer	2
015414	1/4-20 18-8 SS Flat Washer	2
015412	1/4-20 18-8 SS SHCS .75" Long	2
025349	Bent Tube Assembly	1
025399	Air Powered Pump	1



MiniKrimp™ Serial Number

Karrykrimp
Part No. 82C-061L-PFD



The Karrykrimp is now available in a modular design with all the familiar Parkrimp System advantages.

The same unit now offers portability and bench mountability.

Capability

- Crimps most hoses up to 1-1/4 I.D. (check crimpsource for details)

Features

- Portable, compact rugged design
- Numerous portable power unit options available
- Pivoting pusher design for easy die change out
- Increased height enables longer bent tube fittings to be crimped
- For use with 54, 56, 91, 91N, 92, 93N, CG, CY, MS, SF and HY Series fittings

Specifications

- Dimensions: 15" wide, 12" deep, 30" high
- Weight: 60 lbs (without power unit)
- Rating: 30 ton force @ 10,000 psi maximum
- Full Cycle Time: 30 seconds

Standard Equipment

Part Number				Individual
82C-CHD-PFD	82C-061L-PFD	82C-KKB-PFD	Description	Part Number
●	●	●	Crimp Head	82C-CHD-PFD
		●	Bench Power Unit Assembly	85C-1PH-PFD
●	●	●	Silver die ring	82C-R01-PFD
●	●	●	Black die ring	82C-R02-PFD
	●		Hose Assembly	85C-00L-PFD
	●		Stand Assembly	85C-STD-PFD

Karrykrimp Bench Mount
Part No. 82C-KKB-PFD



View Video Tutorial

Capability

- Crimps most hoses up to 1-1/4 I.D. (check crimpsource for details)

Features

- Faster cycle times on bench mounted units
- Pivoting pusher design for easy die change out
- Compact bench mount design
- Increased height enables longer bent tube fittings to be crimped
- For use with 54, 56, 91, 91N, 92, 93N, CG, CY, MS, SF and HY Series fittings

Specifications

- Dimensions: 17" wide, 23" deep, 27-1/2" high
- Weight: 146 lbs
- Rating: 30 ton force @ 10,000 psi maximum
- Full Cycle Time: 11 seconds
- Hydraulic Fluid: AW32 oil

This unit is designed to make about 400 crimps per day and is not designed to be a production crimper. Exceeding these suggested production amounts will significantly reduce the life expectancy of the crimper components.

Note:

Motor is dual voltage, 50/60hz suitable for 208-230/115v, 1ph, 60hz and 220-230/110v, ph, 50hz. Motor can be rewired by a qualified electrician to operate at alternate voltage.

For detailed ordering information, please consult price list or contact Parflex Division.

Karrykrimp 2
Part No. 85C-061L-PFD



The Karrykrimp 2 is now available in a modular design with all the familiar Parkrimp System advantages.

The same unit now offers portability and bench mountability.

Capability

- Crimps most hoses up to 1-1/4 I.D. (check crimpsource for detail

Features

- Portable, compact rugged design
- Numerous portable power unit options available
- Pivoting pusher design for easy die change out
- For use with 54, 56, 91, 91N, 92, 93N, CG, CY, MS, SF and HY Series fittings

Specifications

- Dimensions: 14" wide, 14" deep, 31-1/2" high
- Weight: 120 lbs (without power unit)
- Rating: 60 ton force @ 10,000 psi maximum
- Full Cycle Time: 20 seconds

Standard Equipment

Part Number				Individual
85C-CHD-PFD	85C-061L-PFD	85C-KKB-PFD	Description	Part Number
●	●	●	Crimp Head	85C-CHD-PFD
		●	Bench Power Unit Assembly	85C-1PH-PFD
●	●	●	Silver die ring	85C-R01-PFD
●	●	●	Black die ring	85C-R02-PFD
	●		Hose Assembly	85C-00L-PFD
	●		Stand Assembly	85C-STD-PFD

Karrykrimp 2 Bench Mount
Part No. 85C-KKB-PFD



View Video Tutorial

Capability

- Crimps most hoses up to 1-1/4 I.D. (check crimpsource for detail

Features

- Faster cycle times on bench mounted units
- Pivoting pusher design for easy die change out
- Compact bench mount design
- For use with 54, 56, 91, 91N, 92, 93N, CG, CY, MS, SF and HY Series fittings

Specifications

- Dimensions: 17" wide, 23" deep, 28" high
- Weight: 208 lbs
- Rating: 60 ton force @ 10,000 psi maximum
- Full Cycle Time: 17 seconds
- Hydraulic Fluid: AW32 oil

This unit is designed to make about 400 crimps per day and is not designed to be a production crimper. Exceeding these suggested production amounts will significantly reduce the life expectancy of the crimper components.

Note:

Motor is dual voltage, 50/60hz suitable for 208-230/115v, 1ph, 60hz and 220-230/110v, ph, 50hz. Motor can be rewired by a qualified electrician to operate at alternate voltage.

Parkrimp 2
Part No. 83C-081-PFD



View video tutorial

Capability

- Crimps hoses up to 2" I.D.
  (reference crimp source for details)

Features

- Easy to use vertical design
- Crimps full range of Parker hoses from 1/8" through 2" I.D.
- For use with 54, 56, 91, 91N, 92, 93N, CG, CY, MS, SF and HY Series fittings

Specifications


- Dimensions: 31" wide, 24" deep, 77" high
- Weight: 842 lbs (Head is 558 lbs and base is 284 lbs)
- Rating: 125 ton force @ 5,000 psi maximum
- Full Cycle Time: 30 seconds without adapter bowl
  20 seconds with adapter bowl
- Hydraulic oil: Enerpac oil only

Standard Equipment

Part Number					Individual
83C-001-PFD	83C-081-PFD	83C-002-PFD	83C-082-PFD	Description	Part Number
●	●	●	●	Parkrimp 2 crimper head assembly	83C-080-PFD
●	●			Parkrimp 2 stand assembly with 230/460 volt, 3 phase, 50/60 Hz power unit (wired for 230 volt)	83C-S40-PFD
		●	●	Parkrimp 2 stand assembly with 230 volt, 1 phase, 50/60 Hz power unit	83C-S20-PFD
●	●	●	●	Adapter bowl	83C-0CB-PFD
●	●	●	●	Spacer ring	83C-R02-PFD
●	●	●	●	Spacer Plate	83C-R02H-PFD

Crimper Pumps

Air/Hydraulic Pump
Part No. 82C-0AP-PFD



(for use with the MiniKrimp, Karrykrimp and Karrykrimp 2)

Lightweight pump operates with 80-110 psi shop air pressure and delivers 10,000 psi

- Length: 15"
- Width: 6"
- Height: 6"
- Intake Port Size: 1/4" NPTF
- Output Port Size: 3/8" NPTF
- Weight: 14 lbs
- Hydraulic Fluid: Enerpac oil only

Air/Hydraulic Pump
Part No. 025399



(for use with the MiniKrimp)

Lightweight pump operates with 80-110 psi shop air pressure and delivers 10,000 psi

- Length: 13"
- Width: 4-1/2"
- Height: 5"
- Intake Port Size: 1/4" NPTF
- Output Port Size: 1/8" NPTF
- Weight: 12 lbs.
- Hydraulic Fluid: Enerpac oil only

Hand Pump
Part No. 015301




(for use with the MiniKrimp)

Ease of operation hand pump delivers 10,000 psi

- Length: 13-3/8"
- Width: 3-1/4"
- Height: 3-5/8"
- Port Size: 1/4" NPTF
- Weight: 4.7 lbs.
- Hydraulic Fluid: Enerpac oil only

Swagers



SQ-101-SW Swager/Mender

- Used for field assembly or repair on Predator S6 and S9 hoses

Hand Pump
Part No. 82C-0HP-PFD



(for use with the MiniKrimp, Karrykrimp and Karrykrimp 2)
Ease of operation hand pump delivers 10,000 psi

- Length: 13-3/8"
- Width: 3-1/4"
- Height: 3-5/8"
- Port Size: 1/4" NPTF
- Weight: 4.7 lbs.
- Hydraulic Fluid: Enerpac oil only

Hand Pump
Part No. 85C-0HP-PFD



(for use with the MiniKrimp, Karrykrimp and Karrykrimp 2)
Ease of operation hand pump delivers 10,000 psi

- Length: 29"
- Width: 13"
- Height: 11"
- Port Size: 3/8" NPTF
- Weight: 61 lbs
- Hydraulic Fluid: Enerpac oil only

Electric Pump
Part No. 82C-0EP-PFD



(for use with the MiniKrimp, Karrykrimp and Karrykrimp 2)
Ease of operation electric pump delivers 10,000 psi

- Length: 13"
- Width: 13"
- Height: 15"
- Port Size: 3/8" NPTF
- Weight: 31 lbs
- Hydraulic Fluid: Enerpac oil only
- 115 volt, 1 phase, 50/60 Hz, 9 amp

Electric Pump
Part No. 85C-0EP-PFD



(for use with the MiniKrimp, Karrykrimp and Karrykrimp 2)
Heavy duty electric pump delivers 10,000 psi at a faster cycle time

- Length: 19"
- Width: 11"
- Height: 17"
- Port Size: 3/8" NPTF
- Weight: 59 lbs
- Hydraulic Fluid: Enerpac oil only
- 115 volt, 1 phase, 50/60 Hz, 20 amp

Vise Blocks
For Parflex Hose Sizes



Part Number	Hose Size	
VBS	-3	3/16
	-4	1/4
	-5	5/16
	-6	3/8
	-8	1/2
VBL	-12	3/4
	-16	1

Hose Insertion Depth Blocks
Part No. TH9-1-xxx
Part No. TH8-1-xxx



Part Number	Description
TH9-1-CG	CG Series. All sizes.
TH9-1-56	56 Series. All sizes.
TH9-1-54A	54 Series All sizes.
TH9-1-91N	91N Series. All sizes.
TH9-1-93N_20_32	93N Series. Sizes: -20, -24, -32
TH9-1-93N_6_16	93N Series. Sizes: -6, -12, -16
TH9-1-94_95	94 & 95 Series. All sizes.
TH9-1-CY_SF	CY & SF Series. All sizes.
TH9-1-MS	MS Series. All sizes.
TH9-1-HY	HY Series. All sizes.

Parflex Parkrimp Dies



Parkrimp dies, specifically engineered for thermoplastic and fluoropolymer hose:

- Linked die segments
- Pre-matched and assembled
- Fitting size color coded

Color Code	
Size	Color
-1.5	GR
-2	BR
-3	GR
-4	R
-5	P

Color Code	
Size	Color
-6	Y
-8	BL
-10	O
-12	G
-16	B

Color Code	
Size	Color
-20	W
-24	R
-32	G

Parkrimp Approved Silver Die Rings	
Machine	Approved Die
Parkrimp 2	NA*
Karrykrimp and MiniKrimp	82C-R01-PFD
Karrykrimp 2	85C-R01-PFD

*No additional silver die rings required.

Note: 1) Parflex dies have been designed for use with the silver die ring. Silver die rings are to be used with all Parflex hoses unless otherwise specified.

2) For most Parker products, Crimp Die information and selection charts can be found online at www.parker.com/crimpsource. Access instructions are on pg. G-13.

Die Racks



Die Storage Rack

Part No. 80C-0DR-PFD/83C-0DR-PFD

- Holds small and large Parkimp dies
- Can be bolted together to a work bench

Description	Part No.
Storage 3 small dies	80C-0DR-PFD
Storage 2 large dies	83C-0DR-PFD



Swivel Die Rack

Part No. 80C-SDR-XXXX-PFD

- Holds up to 30 Parkimp dies
- Powder coated, heavy duty steel construction
- Consist of base unit and up to 5 circular holders
- Floor or bench mounted

Description	Part No.
Swivel Die Rack and Small Die Holder	80C-SDR-SM-PFD
Swivel Die Rack and Large Die Holder	80C-SDR-LG-PFD
Swivel Die Rack Base	80C-SDR-BASE-PFD

Conversion Kits



Hydraulic Press Kit

Specifications

- Required Height from Press Base to Press Ram: 10 inches
- Required Width of Bowl Diameter: 5 inches
- Bowl Rating: 30 tons force maximum
- Minimum Required Press Capacity: Hose Size 1/4" to 1/2" needs a 20 ton press
  Hose size 5/8" to 1-1/4" needs a 30 ton press

Standard Equipment

Each component must be ordered separately	Individual
Description	**Part Number**
Bowl Assembly	8PC-030-PFD
Pusher	8PC-00P-PFD
Silver Die Ring	81C-R01-PFD
Black Die Ring	81C-R02-PFD



Weatherhead Conversion Kit

Weatherhead T-400 crimper to utilize Parker Parkrimp No-Skive fittings.

Standard Equipment

Each component must be ordered separately	Individual
Description	**Part Number**
Bowl Assembly	8PC-030-PFD
Pusher	8WC-00P-PFD
Silver Die Ring	81C-R01-PFD
Black Die Ring	81C-R02-PFD



Gates Conversion Kit

Convert Gates 701, 703 and 707 bottom loading crimpers to utilize Parker Parkrimp No-Skive fittings.

Standard Equipment

Each component must be ordered separately	Individual
Description	**Part Number**
Bowl Assembly	8PC-030-PFD
Silver Die Ring	81C-R01-PFD
Black Die Ring	81C-R02-PFD

Cutting Tools



Hose Cut-Off Machine
Part No. 332T-115V-PFD

Features

- For quick, easy cutting of reinforced hose up to 1-1/4" I.D.
- Moving parts shielded by guards

Specifications

- Dimensions: 13" wide x 26" long x 22" high
- Shipping Weight: 71 lbs.

Standard Equipment

Part Number		Individual
332T-115V-PFD	Description	Part Number
●	Hose Cut-Off Machine with 1-1/2 HP, 3450 RPM, 115/230V single phase electic motor wired for 115V	
●	Scallop Cutting Blade (8" with 5/8" arbor size)	24398-PFD

Optional Equipment

Smooth Cutting Blade (580661-PFD)



Push-Lok Cut-Off & Assembly Tool
Part No. 881540-PFD

- Combines hose cutter and toggle action press
- Cuts and assembles Parker 83FR in sizes 1/4" through 3/4" I.D.



Hose & Tubing Cutter
Part No. HTC

- Special V-block design with easy adjustable blade ensures a straight, clean cut
- Minimal flattening of hose/tubing during cutting - Straight, square cut enhances fitting retention
- Cuts up to 1" O.D. hose or tubing (Non-wire reinforced thermoplastic hose and tubing and rubber hose and tubing)
- Replacement blades: HTC-RB



Hose Cut-Off Tool
Part No. TH11-1-PFD

- Designed for quick, easy cutting of textile reinforced hose
- Squarely cuts fiber reinforced hoses in sizes 1/4" through 3/4" I.D.



Plastic Tube Cutter
Part No. PTC


- Razor-edged tube cutter
- Closes automatically, assuring clean and square cuts
- May be used with most plastic tubing up to 5/8" I.D.

Description	Part Number
Replacement Blades	PTC-001-RB

Hose Guards

Parker hose guards prolong the life of hoses that are exposed to rugged operating conditions. In addition to protecting the hose from abrasion and cutting, they limit the bending radius which prevents kinking.


PV - Clear Vinyl Hose Guard



Part Number	Guard I.D.		Standard Length	
#	◎			
	inch	mm	feet	mtr.
PV97-1	0.44	11	100	30.5
PV139-1	0.56	14	100	30.5
PV1611-1	0.68	17	100	30.5
PV2014-1	0.87	22	50	15.2
PV2420-1	1.25	32	50	15.2
PV3224-1	1.50	38	50	15.2

HBR - Hose Bend Restrictor (Black Elastomer)






Part Number	Hose Size		L		D1		D2	
#	◎							
	inch	mm	inch	mm	inch	mm	inch	mm
HBR-4	1/4	6	5	127	.600	15	.500	13
HBR-6	3/8	10	6	152	.640	16	.625	16

Parker reserves the right to change dimensions and performance parameters without notice.

5CNG/CNGLT - Black Vinyl CNG Hose Guard



Hose Part Number	Hose Guard Part Number
#	#
5CNG-3	CNGG5-3
5CNG-4	CNGG5-4
5CNG-6	HBR-6
5CNG-8	CNGG5-8
5CNG/CNGLT-12	CNGG5-12
5CNG/CNGLT-16	CNGG5-16


- Use with Parflex CNG hose
- Contact Parflex Division for information on Hose Guard Kits.

For detailed ordering information, please consult price list or contact Parflex Division.

Metallic Spring Guards

Use Spring Guards for protection from abrasion and extreme physical abuse.


SSG & PSG - Pre-made Spring Guards



Plated, hard-drawn steel wire

Part Number	Hose O.D. (reference)		Standard Length	
#				
	inch	mm	inch	mm
55SSG-3	0.44	11	6	152
55SSG-4	0.55	14	6	152
55SSG-5	0.61	15	6	152
55SSG-6	0.68	17	6	152
55SSG-8	0.83	21	6	152
55SSG-12	1.09	28	7	178


Special configurations available upon request.
Contact factory.



For CNG Hose (Stainless Steel)


Part Number	Hose Max. O.D.		Standard Length	
#				
	inch	mm	inch	mm
3PSG-3	0.46	12	5.30	135
3PSG-4	0.54	14	6.25	159
5PSG-4	0.57	14	6.25	159
5PSG-6	0.68	17	6.50	165
5PSG-8	0.90	23	6.50	165

SG - Steel Spring Guards
(Plated, hard-drawn steel wire)



Part Number	Hose O.D. (reference)		Standard Length	
#				
	inch	mm	feet	mtr.
55SG-3	0.47	12	25	7.6
55SG-4	0.55	14	25	7.6
55SG-5	0.61	16	25	7.6
55SG-6	0.67	17	25	7.6
55SG-8	0.83	21	25	7.6
55SG-12	1.09	28	10	3
55SG-16	1.35	34	10	3
58SG-12	1.18	30	10	3
58SG-16	1.51	38	10	3

AG - Flat Steel Armor Guards



Part Number	Guard I.D.		Standard Length	
#				
	inch	mm	feet	mtr.
55AG-3	0.47	12	25	7.6
55AG-4	0.55	14	25	7.6
55AG-5	0.61	16	25	7.6
55AG-6	0.67	17	25	7.6
55AG-8	0.83	21	25	7.6
55AG-12	1.09	28	10	3
55AG-16	1.35	34	10	3
58AG-12	1.18	30	10	3
58AG-16	1.51	38	10	3


Guards for PTFE Hoses



AS



2625, 2799



2740, 2613



FS

Hose		Max. O.D.	Partek Sleeve	External Round Spring	Internal Round Spring	External Flat Spring	Internal Flat Spring	Fire Sleeve
919/929	-4	0.32	-	2625-11	-	2740-11	-	FS-F-5
	-5	0.40	-	2625-14	-	2740-14	-	FS-F-7
	-6	0.46	AS-Y-11/AS-B-11	2625-15	-	2740-16	-	FS-F-8
	-8	0.56	AS-Y-11/AS-B-11	2625-19	-	2740-19	2613-13CR	FS-F-10
	-10	0.66	AS-Y-13/AS-B-13	2625-22	-	2740-22	2613-16CR	FS-F-12
	-12	0.79	AS-Y-15/AS-B-15	2625-26	-	2740-26	2613-20CR	FS-F-14
	-16	1.05	AS-Y-17/AS-B-17	2625-34	-	2740-34	2613-28CR	FS-F-20
	-20	1.32	AS-Y-22/AS-B-22	2625-44	-	2740-44	2613-37CR	FS-F-24
939	-4	0.48	AS-Y-11/AS-B-11	2625-16	-	2740-18	-	FS-F-10
	-6	0.59	AS-Y-13/AS-B-13	2625-20	-	2740-20	-	FS-F-11
	-8	0.75	AS-Y-15/AS-B-15	2625-25	-	2740-25	-	FS-F-14
	-10	0.88	AS-Y-17/AS-B-17	2625-29	-	2740-30	-	FS-F-16
	-12	1.09	AS-Y-19/AS-B-19	2625-36	-	2740-36	-	FS-F-20
	-16	1.33	AS-Y-27/AS-B-27	2625-44	2799-16CR	2740-44	-	FS-F-24
	-20	1.75	AS-Y-35/AS-B-35	2625-58	2799-20CR	2740-58	-	FS-F-32
	-24	2.05	AS-Y-39/AS-B-39	2625-67	2799-24CR	2740-70	-	FS-F-38
	-32	2.56	AS-Y-47/AS-B-47	2625-83	2799-32CR	2740-83	-	FS-F-48
943	-6	0.49	AS-Y-11/AS-B-11	2625-17	-	2740-18	-	FS-F-10
	-8	0.62	AS-Y-13/AS-B-13	2625-21	-	2740-21	2613-13CR	FS-F-11
	-10	0.73	AS-Y-15/AS-B-15	2625-24	-	2740-23	2613-16CR	FS-F-14
	-12	0.99	AS-Y-17/AS-B-17	2625-33	-	2740-35	2613-20CR	FS-F-18
	-16	1.39	AS-Y-27/AS-B-27	2625-45	-	2740-46	2613-28CR	FS-F-24

NOTE:
Partek sleeves come in yellow and black.
All internal guards are fabricated from 300 series stainless steel.
All external guards are plated steel.

For detailed ordering information, please consult price list or contact Parflex Division.

PSG – Parker Spiral Guard



Features

- High-strength and resilient, Spiral Guard protects hose and cable with superior anti-crush performance
- Exceptionally smooth facing and rounded edges prevent Spiral Guard from getting caught on rough surfaces
- Easy installation and routing
- Low friction interior minimizes wear on hose
- For bundling, organizing and protecting hose and cable, Parflex Spiral Guard is the superior solution for mining operations - In fact, it delivers more advantages than cut pipe or sleeving at a competitive price or less
- Spiral Guard is available in:
  - An MSHA/FRAS approved version for underground mining
  - A standard version (with yellow stripe) for surface applications not requiring fire-resistant, anti-static properties
- Manufactured with high density polyethylene materials

Applications



- Mining
- Automotive
- Mobile Equipment

Part Number	Hose O.D. Range		Package Qty.		1-Wire Braid Size		2-Wire Braid Size		Multi-Spiral Size		Weight	
#	◎										lbs	kg
	mm	inch	mtr.	feet	inch	mm	inch	mm	inch	mm	lbs./ft.	kg./mtr.
PSG 12	10 – 13	.394-.512	20	65.6	-		-		-		.034	.015
PSG 16 FRAS or PSG 16	12 – 17	.472-.669	20	65.6	1/4	6	1/4	6	-		.040	.018
PSG 20 FRAS or PSG 20	16 – 22	.630-.866	20	65.6	3/8	10	1/4 3/8	6 10	3/8	10	.060	.027
PSG 25 FRAS or PSG 25	22 – 28	.866-1.10	20	65.6	1/2 5/8	13 16	1/2 5/8	13 16	1/2 5/8	13 16	.101	.046
PSG 32 FRAS or PSG 32	27 – 33	1.06-1.30	20	65.6	3/4	19	5/8 3/4	16 19	5/8 3/4	16 19	.151	.068
PSG 40 FRAS or PSG 40	33 – 42	1.30-1.65	20	65.6	1	25	1	25	1	25	.235	.107
PSG 50 FRAS or PSG 50	42 – 55	1.65-2.17	20	65.6	1-1/4 1-1/2	32 38	1-1/4	32	1-1/4	32	.268	.122
PSG 63 FRAS or PSG 63	52 – 65	2.05-2.56	20	65.6	2	51	1-1/2	38	1-1/2	38	.402	.182
PSG 75 FRAS or PSG 75	65 – 80	2.56-3.15	10	32.8	-		2	51	2	51	.637	.289
PSG 90 FRAS or PSG 90	80 – 150	3.15-5.91	10	32.8	-		-		-		.771	.350
PSG 110 FRAS or PSG 110	150 – above	5.91-above	10	32.8	-		-		-		1.00	.454

Temperature Range: -148°F to 212°F (-100°C to 100°C)

SplashShield™ Protective Cover

Double Your Protection



Features

- Exemplary abrasion resistance
- Protects hose from external hot hydraulic oil
- Easy to clean vs. other protective covers
- Does not slide down
- Multiple sleeves may be linked together to use on longer assemblies
- Lightweight
- Special colors available for color coding

SPLASH SHIELD™

Applications/Markets



- Agricultural Equipment
- Construction Equipment
- General Mobile Applications

Part Number #	Nominal I.D.		Nominal Wall		Nominal O.D.		Weight		Nominal Cut Length	
	inch	mm	inch	mm	inch	mm	lbs./ft.	kg./m.	feet	mtr.
900911-18	0.67	17.0	0.045	1.14	0.76	19.3	0.06	0.09	10	3.05
900911-20	0.72	18.4	0.045	1.14	0.81	20.7	0.06	0.09	10	3.05
900911-04	0.86	21.8	0.086	2.18	1.03	26.2	0.14	0.21	10	3.05
900911-21	0.86	21.8	0.045	1.14	0.95	24.1	0.07	0.11	12	3.66
900911-05	0.88	22.2	0.043	1.09	0.96	24.4	0.07	0.11	10	3.05
900911-06	1.02	25.8	0.043	1.09	1.1	28.0	0.13	0.19	10	3.05
900911-02	1.05	26.6	0.086	2.18	1.22	30.9	0.17	0.25	10	3.05
900911-22	1.13	28.8	0.045	1.14	1.22	31.1	0.09	0.13	12	3.66
900911-07	1.19	30.3	0.065	1.65	1.32	33.6	0.14	0.21	10.8	3.29
900911-23	1.24	31.6	0.045	1.14	1.33	33.9	0.1	0.15	10	3.05
900911-24	1.3	33.1	0.045	1.14	1.39	35.4	0.11	0.16	12	3.66
900911-25	1.52	38.7	0.045	1.14	1.61	41.0	0.12	0.18	12	3.66
900911-26	1.69	42.9	0.045	1.14	1.78	45.2	0.14	0.21	12	3.66
900911-19	2.13	54.0	0.06	1.52	2.25	57.0	0.23	0.34	12	3.66

How To Choose A Liner

1. Establish the maximum outside diameter of the hose or bundle.
2. Add 1/16" clearance over the established maximum O.D.

   i.e. Maximum O.D. = .696
   add 1/16th .062
   Total .758
3. Refer to the I.D. column on the SplashShield™ table. Find the next size larger than the established O.D.

   In this case, the correct part number would be 900911-04, with a nominal .860 I.D.

   Although 900911-20 clears the maximum O.D. of the hose, it doesn't allow enough space for clearance over the entire length of the hose.

Construction

Manufactured from a unique, high-durometer, proprietary blended material

Operating Parameters

Use in environments less than +250°F (+121°C)

Color

● Black

Note

-Special colors available upon request
-Multiple sleeves may be linked together to use on longer assemblies

For detailed ordering information, please consult price list or contact Parflex Division.

Hose Assembly Instructions

Hose Selection, Installation & Maintenance

Die Selection & Crimp Charts

Materials

Government Agency & Specifications




Table of Contents

Hose Selection, Installation & Maintenance

Intro G-4

Selection of Hose Diameter G-5
Calculation of Hose Length G-6
Hose Permeation Data (510/510A) G-7
Volumetric Expansion of Hose G-8
Pressure Rating of Hose End Connections G-10
Selection, Installation & Maintenance G-11

Hose Assembly & Crimping Instructions

How To Use Crimpsource G-14

Permanent Crimp, Series 56 ..... G-15
MiniKrimp™ Assembly, Series 56 ..... G-18

Permanent Crimp, Series 92, CY, CG, LV, MS, SF. G-21
MiniKrimp™ Assembly G-24

Field Attachable, Series 51, BU & MS. G-27

PTFE Permanent Crimp, Series 91, 91N & 93N. G-29

PTFE Permanent Crimp, Series PAGE. G-32

PTFE Field Attachable, Series 90. ..... G-34

Sewer Hose SQ-Swage Assembly Instructions. G-37

Twin/Multi-Line Separation..... G-40

Technical Data

Ferrul-Fix Installation Instructions..... G-42

Die Selection & Swage Specification Chart (Sewer Hose)..... G-43

Hose Fitting Insertion Values..... G-44
Hose Fitting Thread Guide..... G-45
Media to Fitting & Seal Compatibility Guide..... G-46
Metal Tube & Fitting Material Compatibility Guide..... G-48
O-Ring Material Selection Guide..... G-50

Metals Corrosion Scale..... G-51
Materials to Parflex Part Number..... G-52
Media to Hose Material Compatibility Guide..... G-53
Media to Plastic Tubing Material Compatibility Guide..... G-57
Metric Conversion Chart..... G-60

Other

Government Agency & Specifications..... G-61
Parker Safety Guide..... G-62
ENERPAC Warranty..... G-66
Offer of Sale..... G-67
Part Number Index..... i
Key Word Index..... iv

General Technical Introduction

Hose Assembly Tutorial

Crimping

Steps for crimping are clearly marked with sequences showing product distinctions between products lines.

- Crimping section, as well as universal preparations, for all hoses appear first. The global 56 series fitting assembly instructions are segmented on pages G:14-G:19. Instructions have also been added for the new CG series fittings pages G:20-G:25.
- Field Attachable assemblies appear next

Twin/Multi-Line Hose

Review **twin/multi-line hose separation,** pg. G-39 if applicable – this will give you information before proceeding to the assembly pages – Not following this procedure may cause permanent damage to hoses.

*The PARKRIMP crimping system is the same for all standard Parker portable or bench style crimpers.

Please note: You must become familiar with your own specific crimper to determine its operational features. Please review thoroughly and understand your operator's manual included with your machine. Never use a crimper beyond its recommended published capacities. Crimp specifications are found online by accessing Crimp Source. *www.parker.com/crimpsource*

Selection of Hose Diameter
Flow Capacities at Recommended Flow Velocities

The nomogram below is provided as an aid in determining the correct hose size.

How to use the nomogram: Determine the proper flow rate your system requires, then connect a straight edge from the selected flow rate to the recommended velocity range. The required hose I.D. will appear at the intersection of the straight edge and the center column. If the straight edge passes through the scale between sizes listed, use the next larger I.D. hose.


Example: Locate 16 gallons per minute in the left-hand column and 20 feet per second (fps) in the right-hand column (the maximum recommended velocity range for pressure lines). Lay a straight edge across these two points. The inside diameter required is shown in the center column at or above the straight edge. In this case, we need a hose I.D. of 0.625 (5/8") inch (or larger).

Use the same procedure for suction of return lines, except utilizing their respective maximum recommend velocities.

The nomogram is based on the following formula:

$$D = \sqrt{\frac{Q \times 0.4081}{V}}$$

Where: Q = Flow in Gallons per Minute (gpm)
V = Velocity in Feet per Second (ft/sec)
D = Hose Inside Diameter (inches)



For detailed ordering information, please consult price list or contact Parflex Division.

Calculation of Hose Length
For Over-the-Sheave Applications

The exact cutoff length for an optimum over-the-sheave assembly depends on the particular mechanical arrangement of the machine. A method for finding an approximate starting point is as follows:


1. Assemble hose with one coupling as shown in diagram.

2. Measure hose length from point 1 to point 2 with hose taut. LO = length

3. Calculation of insert allowance (x) may be found from the coupling dimension tabulations in the fittings section or from direct measurement on the coupling. A 1.5% stretch allowance is provided in the following formula.

4. Calculate hose cutoff hose cut length HCL:
   HCL = 0.985 LO +2X
   Where HCL includes coupling, insert allowance on both ends.

5. Couple the remaining hose end, check crimp, and assemble on the machine.



For detailed ordering information, please consult price list or contact Parflex Division.

Hose Permeation Data (510A)

Permeation Rate at 120°F
(Pound per Linear Hose Foot per Year)

Hose Size	R12	R22	R507	R404A	R502	R134A
-2	-	.28	-	-	.03	-
-3	-	.30	.08	.07	-	-
-4	-	.71	.15	.10	-	-
-6	-	1.11	-	-	.87	-

Permeation Rate at 212°F
(Pound per Linear Hose Foot per Year)

Hose Size	R12	R22	R507	R404A	R502	R134A
-2	-	-	-	-	-	-
-3	-	1.25	-	-	-	-
-4	.08	2.32	-	-	-	.07
-6	-	-	-	-	-	-

Notes:

1. Data is for comparison only. Actual results may vary due to differences in application temperature and pressure.
2. Data is collected in highly controlled tests per UL1963.
3. Parker Safety Guide for Selecting and Using Hose, Tubing,Fittings and Related Accessories, Section 2.6:

   Permeation: Permeation (that is, seepage through the Hose) will occur from inside the Hose to outside when Hose is used with gases, liquid and gas fuels, and refrigerants (including but not limited to such materials as helium, diesel fuel, gasoline, natural gas, or LPG). This permeation may result in high concentrations of vapors which are potentially flammable, explosive, or toxic, and in loss of fluid. Dangerous explosions, fires, and other hazards can result when using the wrong Hose for such applications.

   The system designer must take into account the fact that this permeation will take place and must not use Hose if this permeation could be hazardous. The system designer must take into account all legal, government, insurance, or any other special regulations which govern the use of fuels and refrigerants. Never use a Hose even though the fluid compatibility is acceptable without considering the potential hazardous effects that can result from permeation through the Hose Assembly.

   Permeation of moisture from outside the Hose to inside the Hose will also occur in Hose assemblies, regardless of internal pressure. If this moisture permeation would have detrimental effects (particularly, but not limited to refrigeration and air conditioning systems), incorporation of sufficient drying capacity in the system or other appropriate system safeguards should be selected and used.

Volumetric Expansion of Hose

Hydraulic hoses expand under pressure. On some applications, customers can use the differences in expansion between hoses to tune systems for better performance or even noise reduction. Parflex has tested a select list of hoses and determined the rate of expansion in cubic centimeters per foot of hose (cc/ft).

To calculate the volumetric expansion of a hose, substitute the desired pressure into the "X" values in the appropriate equation. For other hoses, please contact the division.

Hose Part Number	Volumetric Expansion at Maximum Working Pressure		Equation for Volumetric Expansion
	(psi)	(cc/ft)	Y=(cc/ft) X=(psi)
510C-3	3250	2.33	Y=0.0007X+0.0581
510C-4	3000	2.71	Y=0.0009X+0.0059
510C-5	2500	3.41	Y=0.0013X+0.1647
510C-6	2250	4.32	Y=0.0019X+0.0471
510C-8	2250	7.36	Y=0.0032X+0.1637
510C-12	1250	8.99	Y = 0.00745x - 0.29910
510C-16	1000	15.33	Y = 0.01573x - 0.44928
518C-3	3250	2.33	Y=0.0007X+0.0581
518C-4	3150	2.71	Y=0.0009X+0.0059
518C-5	3150	3.41	Y=0.0013X+0.1647
518C-6	3000	4.32	Y=0.0019X+0.0471
518C-8	3000	7.36	Y=0.0032X+0.1637
518C-12	1660	8.99	Y = 0.00745x - 0.29910
518C-16	1330	15.33	Y = 0.01573x - 0.44928
520N-3/528N-3	5000	1.13	Y = 0.0002x + 0.1621
520N-4/528N-4	5000	2.05	Y = 0.00031x + 0.47589
520N-5/528N-5	4500	2.63	Y = 0.00048x + 0.48415
520N-6/528N-6	4000	2.87	Y = 0.00053x + 0.75151
520N-8/528N-8	3500	3.64	Y = 0.00086x + 0.64994
520N-10/528N-10	2750	4.25	Y = 0.001x + 1.505
53DM-4/538DM-4	3000	1.90	Y = 0.00062x + 0.02373
53DM-6/538DM-6	3000	3.19	Y = 0.0010x + 0.0647
53DM-8/538DM-8	3000	4.68	Y = 0.0016x + 0.0384
53DM-10/538DM-10	3000	9.82	Y = 0.0033x - 0.2254
540N-2	3000	1.11	Y = 0.00036x + 0.04607
540N-3	3000	1.75	Y = 0.00057x + 0.03059
540N-4	2750	2.33	Y = 0.00079x + 0.14354
540N-5	2500	3.46	Y = 0.00124x + 0.31870
540N-6/548N-6	2250	4.06	Y = 0.00174x + 0.15045
540N-8	2000	6.05	Y = 0.0030x + 0.0928
540N-12/548N-12	1250	10.26	Y = 0.0081x - 0.2671

Hose Part Number	Volumetric Expansion at Maximum Working Pressure		Equation for Volumetric Expansion
	(psi)	(cc/ft)	Y=(cc/ft) X=(psi)
560TJ-3	3626	0.575	Y = 0.00017x + 0.00875
560TJ-4	3263	0.757	Y = 0.0002x + 0.1172
560TJ-5	3118	0.729	Y = 0.00021x + 0.09887
560TJ-6	2750	1.33	Y = 0.0004x + 0.1918
560TJ-8	2500	1.98	Y = 0.0007x + 0.2093
560TJ-10	2000	3.04	Y = 0.0012x + 0.5704
560TJ-12	1750	3.07	Y = 0.0015x + 0.4449
575X-3	5000	1.69	Y = 0.0003x + 0.2119
575X-4	5000	2.05	Y = 0.0003x + 0.5601
575X-6	5000	2.71	Y = 0.0004x + 0.8412
575XN-8	5000	4.59	Y = 0.00064x + 1.41795
575X-12	5000	12.52	Y = 0.00192x + 2.92038
575X-16	5000	16.81	Y = 0.0028x + 2.9560
590TJ-4	5000	0.888	Y = 0.00016x + 0.09821
590TJ-6	4000	1.87	Y = 0.00038x + 0.32317
590TJ-8	3500	2.17	Y = 0.00049x + 0.43765
590TJ-12	2500	4.20	Y = 0.0013x + 0.8216
590TJ-16	2000	6.21	Y = 0.0026x + 1.0558
D6R04 / D6RX04	3000	2.71	Y = 0.0009x + 0.0059
D6R05	3000	1.28	Y = 0.0003x + 0.3834
D6R06 / D6RX06	3000	1.28	Y = 0.0003x + 0.3834
D6R08 / D6RX08	3000	2.88	Y = 0.00057x + 1.20744
D6R10	3000	2.08	Y = 0.00061x + 0.23127
D6R12	3000	5.53	Y = 0.00142x + 1.21743
D6R16	3000	7.33	Y = 0.00205x + 1.24905
H604	3000	1.80	Y = 0.00044x + 0.51607
H605	3000	1.35	Y = 0.00036x + 0.26536
H606	3000	2.00	Y = 0.0006x + 0.2892
H608	3000	2.88	Y = 0.00057x + 1.20744
H610	3000	2.08	Y = 0.00061x + 0.23127
H612	3000	5.53	Y = 0.00142x + 1.21743

Example: Find the volumetric expansion of 560-8 hose at 2000 psi

-From the chart, the appropriate equation would be: Y=0.0007x + 0.2093

-Substituting: Y=0.0007* (2000) + 0.2093

-Therefore the volumetric expansion "Y" equals 1.60 cc/ft @ 2000 psi

The actual volumetric expansion achieved is influenced by multiple variables including fluid properties, hose routing and application temperature. The volumetric expansion calculation is only a general guideline and must be verified by actual testing in the end-use application. No performance warranty in design is expressed or implied by this calculation. Parker recommends that the user review and understand all the precautions listed in the Parker Safety Guide for Selecting and Using Hose, Fittings and Accessories, bulletin BUL. 4400-b.1.

Pressure Rating of Hose End Connections

The maximum dynamic working pressure of the hose assembly is the lesser of the rated working pressure of the hose and the end connections used.

PRESSURE RATINGS HOSE ASSEMBLIES - psi (MPa) — PRESSURE OF THE HOSE AND THE END CONNECTIONS USED

Hose End Connection Description	Part Number Codes	Inch Fittings													
		-2	-4	-5	-6	-8	-10	-12	-16	-20	-24	-32	-40	-48	-64
		psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)
Male Pipe (NPTF)	01	12,000 (82.7)	12,000 (82.7)		10,000 (68.9)	10,000 (68.9)		7,500 (51.7)	6,500 (44.8)	5,000 (34.5)	3,000 (20.7)	2,500 (17.2)			
Female Pipe (NPTF, NPSM)	02 & 07	7,500 (51.7)	7,000 (48.3)		6,000 (41.4)	5,000 (34.5)		4,000 (27.6)	3,000 (20.7)	2,500 (17.2)	2,000 13.8)	2,000 13.8)			
Male Pipe (BSP)	91 & D9	5,000 (34.5)	9,000 (62.1)		8,000 (55.2)	6,250 43.1)		5,000 (34.5)	4,000 (27.6)	3,500 (24.1)	3,000 (20.7)	3,000 (20.7)			
Female Pipe (BSP)	92, B1, B2 & B4	5,000 (34.5)	9,000 (62.1)		8,000 (55.2)	6,250 43.1)	5,500 (37.9)	5,000 (34.5)	4,000 (27.6)	3,500 (24.1)	3,000 (20.7)	3,000 (20.7)			
Female Pipe (JIS)	FU, GU, MU & UT		5,000 (34.5)		5,000 (34.5)	5,000 (34.5)		4,000 (27.6)	3,000 (20.7)	2,500 (17.2)	1,500 (10.3)	1,500 (10.3)			
O-Ring Swivel and 45° Flare	13, 1L, S2, 0G, 0L, 48, 08, 77 & 79		3,000 (20.7)	3,000 (20.7)	3,000 (20.7)	3,000 (20.7)	2,750 (19.0)	2,250 (15.5)	2,000 13.8)	1,625 (11.2)	1,250 (8.6)	1,125 (7.8)			
37° Flare and Straight Thread	03, 05, 06, 37, 39, 41, L7 & L9		6,000 (41.4)	6,000 (41.4)	5,000 (34.5)	5,000 (34.5)	5,000 (34.5)	5,000 (34.5)	4,000 (27.6)	3,000 (20.7)	2,500 (17.2)	2,500 (17.2)			
Flare	04														
SAE Flareless	11 & 12		6,000 (41.4)	6,000 (41.4)	5,600 (38.6)	5,600 (38.6)	4,200 (29.0)	4,200 (29.0)	3,500 (24.1)	3,500 (24.1)	3,000 (20.7)	3,000 (20.7)			
SAE Inverted Flare	28, 67 & 69		2,750 (19.0)	2,500 (17.2)	2,250 (15.5)	2,000 13.8)									
Seal-Lok® (O-Ring Face Seal)	JM, JC, JS, J0, J1, J5, J7 & J9		6,000 (41.4)		6,000 (41.4)	6,000 (41.4)	6,000 (41.4)	6,000 (41.4)	6,000 (41.4)	4,000 (27.6)	4,000 (27.6)				
A-Lok®	TU, AL		6,000 (41.4)	6,000 (41.4)	5,600 (38.6)	5,600 (38.6)	4,200 (29.0)	4,200 (29.0)	3,500 (24.1)	3,500 (24.1)	3,000 (20.7)	3,000 (20.7)			
Rapid Assembly	WU, WY, WW		2,000 (13.8)		1,500 (10.3)										


Hose End Connection Description	Part Number Codes	Metric Fittings														
		-6	-8	-10	-12	-14	-15	-16	-18	-20	-22	-25	-28	-30	-35	-38	-42
		psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)	psi (MPa)
DIN Light "L" without O-Ring	C3, C4, C5 & 1D	3,500 (24.1)	3,500 (24.1)	3,500 (24.1)	3,500 (24.1)		3,500 (24.1)		2,250 (15.5)		2,250 (15.5)		1,400 (9.7)		1,400 (9.7)		1,400 (9.7)
DIN Light "L" with O-Ring	D0, CA, CE & CF	4,500 (31.0)	4,500 (31.0)	4,500 (31.0)	4,500 (31.0)		4,500 (31.0)		2,250 (15.5)		2,250 (15.5)		2,250 (15.5)		2,250 (15.5)		2,250 (15.5)
DIN Heavy "S" without O-Ring	C6, C7, C8 & 3D		9,000 (62.1)	9,000 (62.1)	9,000 (62.1)	9,000 (62.1)		5,750 (39.6)		5,750 (39.6)		5,750 (39.6)		3,500 (24.1)		3,500 (24.1)	
DIN Heavy "S" with O-Ring	C9, 0C, 1C & D2		9,000 (62.1)	9,000 62.1)	9,000 62.1)	9,000 62.1)		6,000 (41.4)		6,000 (41.4)		6,000 (41.4)		6,000 (41.4)		4,500 (31.0)	

NOTE: All the above ratings are based on low carbon steel hose fittings.

PRESSURE RATING OF HOSE - psi (MPa)

THE MAXIMUM WORKING PRESSURES OF HOSES ARE LISTED ON PAGE A-10 : A-17 WITH EACH HOSE DESCRIPTION IN SECTION A.

wrong



The routing of the hose assembly and the environment in which the hose assembly operates directly influence the service life of the hose assembly. The following diagrams indicate the correct routing of hose assemblies that will maximize its service life and assure a safe working functionality.

When hose installation is straight, there must be enough slack in the hose to allow for changes in length that occur when pressure is applied. When pressurized, hose that is too short may pull loose from its hose fittings or stress the hose fitting connections, causing premature metallic or seal failures.

The hose length must be determined so that the hose assembly has enough slack to allow the system components to move or vibrate without creating tension in the hose.


However, do not allow too much slack and therefore introduce the risk of the hose snagging on other equipment or rubbing on other components.

Mechanical straining of the hoses needs to be avoided, so the hose must not be bent below its minimum bend radius or twisted during installation. The minimum bending radii for each hose is stated in the hose tables in the catalogue.

The plane of movement must also be considered and the hose routing selected accordingly.

Hose routing also plays an important role on the selection of the hose fittings, as the correct fittings can avoid straining the hoses, unnecessary hose length or multiple threaded joints.


right



Selection, Installation & Maintenance (cont.)

Recommended Practices for Hydraulic Hose Assemblies

wrong



Correct clamping (holding/supporting) of the hose should be exercised to securely route the hose or to avoid the hose contacting surfaces that will cause the hose damage. It is however, vital that the hose be allowed to keep its functionality as a "flexible-pipe" and not be restricted from changing in length when under pressure.

It should also be noted that hoses for high- and low-pressure lines shall not be crossed or clamped together, as the difference in changes in length could wear the hose covers.

Hose should not be bent in more than one plane. If hose follows a compound bend, it shall be coupled into separate segments or clamped into segments that each flex in only one plane.


Hoses should be kept away from hot parts as high ambient temperatures shorten hose life.

Protective insulation may need to be used in unusually high ambient temperature areas.


While the importance of the functionality is primary, the aesthetics and practicality of the installation should also be considered in the design.

Maintenance might be necessary at some point in the future, so prohibitive design routings should be avoided.

right




wrong



Abrasive influences

In general care should be taken so that the hose is not exposed to direct surface contact that will cause abrasive wearing of the outer cover (either hose to object or hose to hose contact). If however, the application is such that this cannot be avoided, either a hose with a higher abrasion resistant hose cover or a protective sleeve need to be used.

right



Hose Assembly and Crimping

How To Use Crimpsource


1 Data

The most **up-to-date** information for crimping is located at www.parker.com/crimpsource. Not only is it accurate, but it is easy.


NOTE: If the hose does not come up, then you cannot crimp that hose on the machine you selected.

If the fitting you choose doesn't come up, then that series is not available for that hose. Same with size.

2 Make your Selections




Choose the correct machine.




Choose the hose you are crimping.

Note If the hose does not come up, then the crimper chosen does not work with the selected hose.

3 Make your Selections



Choose the fitting style.



Choose the fittings size. Once you have selected values from each field, hit the search button.

Note If the chosen fitting/size doesn't come up, the series/size is not available for that hose.

4 Review The Results

Hose Style:	Coupling Style:	Crimper:	Hose Description
540N	**56**	**Minikrimp**	Meets or exceeds SAE 100R7

Size	Die		Die Ring	Crimp Diameter	Crimp Length	Hose Insertion	Drawing
Parker Parflex Crimp Dies							
-8	80C-P08		82C-R01	0.850	FULL	1-1/8	PKFull

Comments


PFD: Crimp diameter is measured four places, 45 degrees apart, at the top, then middle and bottom of the crimp.

PFD: Crimp diameter tolerance on all Parkrimp Crimpers is ± 0.010" (± 0.25mm) unless otherwise specified. Crimp length tolerance is ± 0.030" (± 0.76mm).

PFD: Align measurement caliper or micrometer on the center of crimp impressions avoiding the crimp ribs.

PFD: Crimp diameter tolerance on all Adjustable Crimpers is ± 0.005" (± 0.13mm). Crimp length tolerance is ± 0.030" (± 0.76mm).

PFD: Reference Parker Fluid Connector Group (FCG) Safety Bulletin 4400-B.1 (www.parker.com/safety)



For detailed ordering information, please consult price list or contact Parflex Division.

Hose Assembly and Crimping

Permanent Crimp Series 56

CAUTION: There are several different sections for Hose Assembly and Crimping. Be sure you are in the section that corresponds to the fitting series you are using. See Table of Contents for listing.

1 Inspection



Hose – Visually inspect both ends of hose for square cut. Remove any burrs, loose fibers or wires.



Fittings – Verify fitting series corresponds to the selected hose. Visually inspect fitting(s) for a through-hole, threads and damage.

2 Assembly Prep



Insertion Depth – Shown is a 56 series fitting. Using Parflex Depth Insertion Block (part# TH9-1-56), mark the hose with the proper insertion depth line. On some fittings such as 56 Series, this depth is represented by a dashed or knurled line on the crimp shell.



Lubrication (as required) – Using an SAE 20 weight lubricating oil, lightly lubricate inside of hose end.

Warning

Do not use lubricating oil when installing fittings on hose used in oxygen service. When installing fittings on hose used in oxygen service, lubricate with a non-oil based soap solution. Failure to do so may result in an explosion and personal injury when hose is used.

3 Assembly



Assemble hose – Push hose into fitting all the way to depth insertion mark. (If fitting does not readily slide onto hose, perform the next step.)



Using Parker VBS or VBL (vise blocks) and a rubber mallet, tap fitting onto hose until bottom of fitting shell is aligned with depth insertion mark.

Hose Assembly and Crimping

Permanent Crimp Series 56

4 Die Selection



Select proper Parkrimp die set. (Reference Crimp Die Selection on Crimpsource online at www.parker.com/crimpsource)

5 Lubricate Bowl




Grease frequently using a premium, quality, lithium-base grease. Apply a thin layer of grease on bowl of crimper base plate.

6 Die & Spacer Ring



Crimp Die – Place die set into bowl.




Die Ring – Place applicable die ring on top of die. Position ring so it is centered on die.

(Reference Crimp Die Selection on Crimpsource online at www.parker.com/crimpsource)

7 Crimp



Assemble hose – Insert hose and fitting from bottom of crimper and up through die set. Position fitting so bottom of fitting skirt rests on die step (PARKALIGN® feature).



While holding hose and fitting in position on die step, crimp fitting onto hose until die ring contacts base plate.

Warning

Keep fingers and hands away from die-pusher area. Failure to do so may result in personal injury.

Note

Pump on crimper must not exceed the rated pressure of the crimper being used. Parker Hannifin will not accept responsibility for the operation of or provide warranty coverage for a crimper that is operated by a power unit other than equipment supplied by Parker Hannifin for the express purpose of operating the crimper.

8

Measure & Inspect



Measure and verify hose assembly length.



Inspect insertion depth mark at fitting ends. Insertion mark must be visible but not exceed 1/8" from end of crimped fitting shell.



Measure crimp diameter of each fitting at top, middle and bottom of shell. Take measurements at a minimum of three places around shell circumference. Verify crimp diameter is within tolerances.

(Reference Crimp Die Selection on Crimpsource online at www.parker.com/crimpsource)

MiniKrimp™ Fitting Assembly Procedures

Permanent Crimp Series 56

CAUTION: There are several different sections for Hose Assembly and Crimping. Be sure you are in the section that corresponds to the fitting series you are using. See Table of Contents for listing.

1 Inspection




Hose – Visually inspect both ends of hose for square cut. Remove any burrs, loose fibers or wires.



Fittings – Verify fitting series corresponds to the selected hose. Visually inspect fitting(s) for a through-hole, threads and damage.

2 Assembly Prep



Insertion Depth – Shown is a 56 series fitting. Using Parflex Depth Insertion Block (part# TH9-1-56), mark the hose with the proper insertion depth line. On some fittings such as 56 Series, this depth is represented by a dashed or knurled line on the crimp shell.



Lubrication (as required) – Using an SAE 20 weight lubricating oil, lightly lubricate inside of hose end.

Warning

Do not use lubricating oil when installing fittings on hose used in oxygen service. When installing fittings on hose used in oxygen service lubricate with a non-oil based soap solution. Failure to do so may result in an explosion and personal injury when hose is used.

3 Assembly




Assemble hose – Push hose into fitting all the way to depth insertion mark. (If fitting does not readily slide onto hose, perform the next step.)



Using Parker VBS or VBL (vise blocks) and a rubber mallet, tap fitting onto hose until bottom of fitting shell is aligned with depth insertion mark.

For detailed ordering information, please consult price list or contact Parflex Division.

4
Die Selection



Select proper Parkrimp die set. (Reference Crimp Die Selection on Crimpsource online at www.parker.com/crimpsource)


5
Lubricate Bowl



Remove pusher from shoulder bolt.

Using a premium, quality, lithium-base grease, apply a thin layer of grease on bowl of crimper base plate.

6
Die & Spacer Ring



Crimp Die – Place die set into bowl.



Die Ring – Place applicable die ring on top of die. Position ring so it is centered on die.

(Reference Crimp Die Selection on Crimpsource online at www.parker.com/crimpsource)




Replace pusher onto shoulder bolt.

7
Crimp



Assemble hose – Insert hose and fitting from bottom of crimper and up through die set. Position fitting so bottom of fitting skirt rests on die step (PARKALIGN® feature).



While holding hose and fitting in position on die step, crimp fitting onto hose until die ring contacts base plate.

Warning

Keep fingers and hands away from die-pusher area. Failure to do so may result in personal injury.

Note

Parker Hannifin will not accept responsibility for the operation of or provide warranty coverage for a crimper that is operated by a power unit other than equipment supplied by Parker Hannifin for the express purpose of operating the crimper.

MiniKrimp™ Fitting Assembly Procedures (cont.)

Permanent Crimp Series 56

8

Measure & Inspect



Measure and verify hose assembly length.



Inspect insertion depth mark at fitting ends. Insertion mark must be visible but not exceed 1/8" from end of crimped fitting shell.



Measure crimp diameter of each fitting at top, middle and bottom of shell. Take measurements at a minimum of three places around shell circumference. Verify crimp diameter is within tolerances.

(Reference Crimp Die Selection on Crimpsource online at www.parker.com/crimpsource)

Hose Assembly and Crimping

Permanent Crimp

Series 54, CG, 92, CY, MS, SF

CAUTION: There are several different sections for Hose Assembly and Crimping. Be sure you are in the section that corresponds to the fitting series you are using. See Table of Contents for listing.

1 Inspection



Hose – Visually inspect both ends of hose for square cut. Remove any burrs, loose fibers or wires.



Fittings – Verify fitting series corresponds to the selected hose. Visually inspect fitting(s) for a through-hole, threads and damage.

2 Assembly Prep



Insertion Depth – Shown is a 56 Series fitting. See Hose Fitting Insertion Values, pg. G-43 for insertion depths of fitting series that do not incorporate an insertion depth. Mark hose end with proper insertion depth line.



Lubrication (as required) – Using an SAE 20 weight lubricating oil, lightly lubricate inside of hose end.

Warning

Do not use lubricating oil when installing fittings on hose used in oxygen service. When installing fittings on hose used in oxygen service, lubricate with a non-oil based soap solution. Failure to do so may result in an explosion and personal injury when hose is used.

3 Assembly



Assemble hose – Push hose into fitting all the way to depth insertion mark. (If fitting does not readily slide onto hose, perform the next step.)



Using Parker VBS or VBL (vise blocks) and a rubber mallet, tap fitting onto hose until bottom of fitting shell is aligned with depth insertion mark.

Hose Assembly and Crimping (cont.)

Permanent Crimp

Series 54, CG, 92, CY, MS, SF

4 Die Selection



Select proper Parkrimp die set. (Reference Crimp Die Selection on Crimpsource online at www.parker.com/crimpsource)

5 Lubricate Bowl



Grease frequently using a premium, quality, lithium-base grease. Apply a thin layer of grease on bowl of crimper base plate.

6 Die & Spacer Ring



Crimp Die – Place die set into bowl.




Die Ring – Place applicable die ring on top of die. Position ring so it is centered on die.

(Reference Crimp Die Selection on Crimpsource online at www.parker.com/crimpsource)

7 Crimp



Assemble hose – Insert hose and fitting from bottom of crimper and up through die set. Position fitting so bottom of fitting skirt rests on die step (PARKALIGN® feature).



While holding hose and fitting in position on die step, crimp fitting onto hose until die ring contacts base plate.

Warning

Keep fingers and hands away from die-pusher area. Failure to do so may result in personal injury.

Note

Pump on crimper must not exceed the rated pressure of the crimper being used. Parker Hannifin will not accept responsibility for the operation of or provide warranty coverage for a crimper that is operated by a power unit other than equipment supplied by Parker Hannifin for the express purpose of operating the crimper.

8

Measure & Inspect



Measure and verify hose assembly length.



Inspect insertion depth mark at fitting ends. Insertion mark must be visible but not exceed 1/8" from end of crimped fitting shell.



Measure crimp diameter of each fitting at top, middle and bottom of shell. Take measurements at a minimum of three places around shell circumference. Verify crimp diameter is within tolerances.

(Reference Crimp Die Selection on Crimpsource online at www.parker.com/crimpsource)

MiniKrimp™ Fitting Assembly Procedures

CAUTION: There are several different sections for Hose Assembly and Crimping. Be sure you are in the section that corresponds to the fitting series you are using. **See Table of Contents for listing.**

1 Inspection



Hose – Visually inspect both ends of hose for square cut. Remove any burrs, loose fibers or wires.



Fittings – Verify fitting series corresponds to the selected hose. Visually inspect fitting(s) for a through-hole, threads and damage.

2 Assembly Prep



Insertion Depth – Mark hose end with proper insertion depth line. See Hose Fitting Insertion Values, pg. G-43 for insertion depths of fitting series that do not incorporate an insertion depth.



Lubrication (as required) – Using an SAE 20 weight lubricating oil, lightly lubricate inside of hose end.


Warning

Do not use lubricating oil when installing fittings on hose used in oxygen service. When installing fittings on hose used in oxygen service lubricate with a non-oil based soap solution. Failure to do so may result in an explosion and personal injury when hose is used.

3 Assembly



Assemble hose – Push hose into fitting all the way to depth insertion mark. (If fitting does not readily slide onto hose, perform the next step.)




Using Parker VBS or VBL (vise blocks) and a rubber mallet, tap fitting onto hose until bottom of fitting shell is aligned with depth insertion mark.

MiniKrimp™ Fitting Assembly Procedures (cont.)

4

Die Selection



Select proper Parkrimp die set. (Reference Crimp Die Selection on Crimpsource online at www.parker.com/crimpsource)

5

Lubricate Bowl




Remove pusher from shoulder bolt.

Using a premium, quality, lithium-base grease, apply a thin layer of grease on bowl of crimper base plate.

6

Die & Spacer Ring



Crimp Die – Place die set into bowl.



Die Ring – Place applicable die ring on top of die. Position ring so it is centered on die.

(Reference Crimp Die Selection on Crimpsource online at www.parker.com/crimpsource)




Replace pusher onto shoulder bolt.

7

Crimp



Assemble hose – Insert hose and fitting from bottom of crimper and up through die set. Position fitting so bottom of fitting skirt rests on die step (PARKALIGN® feature).



While holding hose and fitting in position on die step, crimp fitting onto hose until die ring contacts base plate.

Warning

Keep fingers and hands away from die-pusher area. Failure to do so may result in personal injury.

Note

Parker Hannifin will not accept responsibility for the operation of or provide warranty coverage for a crimper that is operated by a power unit other than equipment supplied by Parker Hannifin for the express purpose of operating the crimper.

MiniKrimp™ Fitting Assembly Procedures (cont.)

8

Measure & Inspect



Measure and verify hose assembly length.



Inspect insertion depth mark at fitting ends. Insertion mark must be visible but not exceed 1/8" from end of crimped fitting shell.




Measure crimp diameter of each fitting at top, middle and bottom of shell. Take measurements at a minimum of three places around shell circumference. Verify crimp diameter is within tolerances.

(Reference Crimp Die Selection on Crimpsource online at www.parker.com/crimpsource)

Hose Assembly and Crimping
Field Attachable
Series 51, BU & MS (Do not use these fittings on oxygen service lines)

CAUTION: There are several different sections for Hose Assembly and Crimping. Be sure you are in the section that corresponds to the fitting series you are using. See Table of Contents for listing.

1
Inspection



Hose – Visually inspect both ends of hose for square cut. Remove any burrs, loose fibers or wires.




Fittings – Inspect socket for damaged or missing threads. Do not use if conditions exist.



Inspect nipple for a through-hole, damaged or missing threads and improperly crimped nut (if applicable). Do not use if these conditions exist.

2
Assembly



Using the Parker VBS or VBL vise block, place hose in proper hole of the vise block and then clamp in a bench vise. Ensure enough hose extends from the vise block to install socket.

Caution

Ensure hose is installed in correct size hole of vise block. Clamping hose in a smaller hole will crush hose.

3
Assembly



Using a wrench, screw socket onto hose counterclockwise until it bottoms. Ensure end of hose is against inside shoulder. Back off socket 1/4 turn clockwise.

Socket should be firm when tightened but not difficult to turn. If socket is difficult to install, apply lubricant that is compatible with the hose material.

Note

Do not use a lubricant with MS series.


Hose Assembly and Crimping (cont.)

Field Attachable

Series 51, BU & MS (Do not use these fittings on oxygen service lines)

4

Assembly



Place hex portion of socket into vise and tighten vise. Ensure socket extends past vise jaws enough to allow for installation of nipple.

Caution


When tightening socket in vise, do not over tighten vise jaws. Over tightening vise jaws will distort internal threads of socket and hamper installation of nipple.

5

Assembly



Using an SAE 20 weight lubricating oil, generously lubricate nipple and socket, threads and hose I.D.



Using a wrench on the nipple hex, screw nipple into socket clockwise until nipple bottoms against socket shoulder.

Caution

Nipple should be firm when tightened but not difficult to turn. If nipple is difficult to install, check hose for proper lubrication. Re-apply lubricating oil as necessary. Installation of nipple without proper lubrication will damage core tube.

6

Inspection



Measure and verify hose assembly length.

For detailed ordering information, please consult price list or contact Parflex Division.

Hose Assembly and Crimping

PTFE Permanent Crimp

Series 91, 91N & 93N

CAUTION: There are several different sections for Hose Assembly and Crimping. Be sure you are in the section that corresponds to the fitting series you are using. See Table of Contents for listing.

1

Cut



Using a power hose cutoff saw, cut hose squarely.

Note

PTFE Hose should be taped prior to cutting. Hose should be cut at center point of taped section.

2

Inspection




Hose – Visually inspect both ends of hose for square cut. Remove any burrs, loose fibers or wires.



Fittings – Verify fitting series corresponds to the selected hose. Visually inspect fitting(s) for a through-hole, threads and damage.

3

Assembly Prep



Insertion Depth – Mark hose end with proper insertion depth line. See Hose Fitting Insertion Values, pg. G-43 for insertion depths of fitting series that do not incorporate an insertion depth. For jacketed PTFE hoses, use a sharp knife and light pressure to cut back the cover at least the length of the insertion depth of the fitting.

Warning

Do not use lubricating oil when installing fittings on hose used in oxygen service. When installing fittings on hose used in oxygen service, lubricate with a non-oil based soap solution. Failure to do so may result in an explosion and personal injury when hose is used.



Assemble hose – Push fitting onto hose slightly and then remove tape. Continue pushing fitting onto hose until fitting reaches depth insertion mark.

Hose Assembly and Crimping (cont.)

PTFE Permanent Crimp

Series 91, 91N & 93N

4

Die Selection



Select proper Parkrimp die set. (Reference Crimp Die Selection on Crimpsource online at www.parker.com/crimpsource)

5

Lubricate Bowl



Using a premium, quality, lithium-base grease, apply a thin layer of grease on bowl of crimper base plate.

6

Die & Spacer Ring



Crimp Die – Place die set into bowl.



Die Ring – Place applicable die ring on top of die. Position ring so it is centered on die.


(Parflex hoses utilize silver die ring with the exception of HTB hose. Reference Crimp Die Selection on Crimpsource online at www.parker.com/crimpsource)

7

Crimp



Assemble hose – Insert hose and fitting from bottom of crimper and up through die set. Position fitting so bottom of fitting skirt rests on die step (PARKALIGN® feature).



While holding hose and fitting in position on die step, crimp fitting onto hose until die ring contacts base plate.

Warning

Keep fingers and hands away from die-pusher area. Failure to do so may result in personal injury.

Note

Pump on crimper must not exceed the rated pressure of the crimper being used. Parker Hannifin will not accept responsibility for the operation of or provide warranty coverage for a crimper that is operated by a power unit other than equipment supplied by Parker Hannifin for the express purpose of operating the crimper.

8

Measure & Inspect



Measure and verify hose assembly length.



Inspect insertion depth mark at fitting ends. Insertion mark must be visible but not exceed 1/8" from end of crimped fitting shell.



Measure crimp diameter of each fitting at top, middle and bottom of shell. Take measurements at a minimum of three places around shell circumference. Verify crimp diameter is within tolerances.

(Reference Crimp Die Selection on Crimpsource online at www.parker.com/crimpsource)

Hose Assembly and Crimping


PTFE Permanent Crimp

Series PAGE Fittings

CAUTION: There are several different sections for Hose Assembly and Crimping. Be sure you are in the section that corresponds to the fitting series you are using. See Table of Contents for listing.

1

Inspection/Marking




Obtain correct hose, fittings and collars per customer order. Inspect to make certain no defects are present on fittings, collars or hose.

Using 1" wide filament tape, apply 1 to 1½ wraps of tape tightly around hose at location to be cut. Mark tape in the middle where cut will be made. Tape will be left on during crimping so only ½" width of tape should remain.

Fittings – Inspect each component for possible damage. In addition, inspect socket and nipple for a through-hole and threads.

2

Cutting




Using a rotary power cutting saw with a smooth toothless blade, cut hose squarely to proper length. Fitting length being used in the assembly shall be taken into account when calculating hose length.



Blow ends of hose off / out to remove any debris left from cutting operation. Cut off wires or fabric extending past the end ofthe hose.

3

Assembly




PAGE series fittings are not one piece but two pieces (insert plus collar) and must be properly installed to assure leak free long life assemblies.

4

Assembly




a. Orient and place collar on hose end fully.



b. Using a taper punch, push punch into tube to enlarge bore of hose so insert just slides into hose.


c. Push insert into hose until lock groove of insert is just at end of collar.



d. Pull collar out towards end of insert until at correct crimp position on insert of collar.

5

Assembly



Crimp assembly only in Parker Approved adjustable crimper. Select correct die and crimp spec from Parker Crimp Source.

www.parker.com/crimpsource

a. Place assembly into crimp dies so full collar length crimp is obtained.

b. Check crimp dimensions in four places around the middle of the crimp circumference. Verify the average of those readings is within crimp specification tolerances. Adjust crimper up or down if needed to obtain proper dimension.

c. Crimp opposite end following the same procedures.

Warning

Keep fingers and hands away from die-pusher area. Failure to do so may result in personal injury.


6

Inspect



Inspect assembly, noting the length.

a. Test to correct test pressures to assure no leaks are observed using hydrostatic pressure unit (recommended). Air or nitrogen under water can be used with caution utilizing the proper pressure and procedures for that equipment.



Blow out all water from the assembly and recheck length.

**Note any movement of length and make compensations as needed on next assembly.

Package assembly appropriately for customer requirements.

Hose Assembly and Crimping

PTFE Field Attachable

Series 90

CAUTION: There are several different sections for Hose Assembly and Crimping. Be sure you are in the section that corresponds to the fitting series you are using. See Table of Contents for listing.

1

Inspection



Hose – Visually inspect both ends of hose for square cut. Remove any burrs, loose fibers or wires.








Fittings – Inspect each component for possible damage. In addition, inspect socket and nipple for a through-hole and threads.

2

Assembly






Slide two sockets over end of hose with bottom of sockets back to back. Position sockets at each end of hose.

Note

When installing sockets on hose, check hose ends to determine if wire braid "necks down" (bends inward). If one end "necks down" use this end to slide sockets onto hose.

3

Assembly



Mount nipple hex in vise. Ensure nipple end extends beyond vise jaws sufficiently to allow installation of hose.




Push hose bore onto nipple to size tube and to aid in separating braid before assembling ferrule onto hose.

Once completed, remove hose from nipple.

4

Assembly




By hand, push sleeve over end of PTFE core tube and under wire braid.




To complete positioning of sleeve, push hose end with sleeve against a solid flat surface.

5

Assembly



Verify tube butts against inside shoulder of ferrule.



Using a tapered punch, push punch into end of sleeve and tube to set sleeve barbs into tube.

6

Assembly



Using SAE 20 weight oil, lubricate nipple and socket threads. For stainless steel fittings use Parker ThreadMate® or a molybdenum type lubricant.

Warning

Do not use lubricating oil when installing fittings on hose used in oxygen service. When installing fittings on hose used in oxygen service lubricate with a non-oil based soap solution. Failure to do so may result in an explosion and personal injury when hose is used.



Assemble hose – Using a twisting motion, push hose over nipple until hose is seated against nipple chamfer.


Hose Assembly and Crimping (cont.)

PTFE Field Attachable

Series 90

7


Assembly



Push socket forward and hand-start threading of socket to nipple.

Caution


When tightening socket in vise, do not over tighten vise jaws. Over tightening vise jaws will distort internal threads of socket.




Remove assembly from vise and reposition with socket in vise jaws. Ensure socket extends beyond vise jaws far enough to allow nipple to be completely tightened.

8

Assembly



Wrench tighten nipple hex until clearance between hex and socket hex is 1/32" or less.



Tighten further to align corners of nipple and socket hexes if necessary.

9

Measure & Inspect




Measure and verify hose assembly length.

For detailed ordering information, please consult price list or contact Parflex Division.

SQ-Swage Instructions
Sewer Hose

CAUTION: There are several different sections for Hose Assembly and Crimping. Be sure you are in the section that corresponds to the fitting series you are using. **See Table of Contents for listing.**

1
Inspection




Hose – Visually inspect both ends of hose for square cut. Remove any burrs, loose fibers or wires.



Fittings – Visually inspect fitting for properly crimped shells, internal barbs, a through-hole and damage.

2
Assembly



Insertion Depth – Mark hose end with proper insertion depth line.




Lubricate – Using an SAE 20 weight oil, lightly lubricate inside of both hose ends.




Assemble hose – Push each hose end into fitting to the depth insertion mark.

3
Assembly



Remove both die securing bolts and nuts.




Place hose and fitting assembly into position on swager.


SQ-Swage Instructions (cont.)
Sewer Hose

4

Assembly




Insert both die halves around hose in each end of swager.




Install both die securing bolts with nuts positioned in opening of swager plates. Tighten die securing bolts 1/4 turn past finger tight.

5

Assembly



Lubricate - Using SAE 20 oil, generously lubricate the steel fitting surface and ID of the swage dies.



Assemble hose – Align swager plates in parallel and tighten nuts on swaging bolts uniformly until dies touch.


Caution

Ensure swager plates remain in parallel when tightening swager bolts. Failure to do so will result in an improperly swaged fitting.


Generously lubricate swaging bolts. Failure to do so may result in an improperly swaged fitting.

6


Assembly



Loosen swaging bolts to release pressure on dies.



Remove die securing bolts and nuts. Then remove dies.




Assemble hose – Remove completed hose assembly.


For detailed ordering information, please consult price list or contact Parflex Division.

7


Measure & Inspect



Measure and verify hose assembly length.



Inspect insertion depth mark at fitting ends. Insertion mark must be visible but not exceed 1/8" from end of crimped fitting shell.




Measure swage diameter of each fitting at top, middle and bottom of shell. Take measurements at a minimum of three places around shell circumference. Verify swage diameter is within tolerances.

(Reference Swage Specification & Tool Selection Chart on pg. G-42 for proper swage diameters.)

Twin/Multi-Line Separation


Factory-built assemblies are available using twin/multi-line hoses. When field-built assemblies are preferred, the following steps must be taken.

1



Set-Up – Position twinned or multi-line hose assembly so that it lies flat on work surface without tendency to twist or turn.

2



Measure hose to length – Measure and mark the length that the hoses are to be separated (commonly referred to as Splitback Length).


3



Lubricate – Lightly lubricate the web area between the hoses. Distribute the lubricant uniformly along the web of the assembly to be separated. Any lightweight oil will suffice (SAE 10 or 20). The function of the oil is to reduce the friction of the knife blade so that it naturally seeks the center of the valley formed by the hoses. This eliminates the need for the operator to steer the knife.

Twin/Multi-Line Separation (cont.)

4




Cut Hose to Length – Press the multi-line hose assembly firmly and flat against the work surface with your free hand so that it does not move. Using a sharp utility knife, carefully draw the knife toward you with constant light to moderate pressure, and a smooth stroke. Multiple strokes will be necessary to separate the hoses.

Note

It is important that the knife blade be perpendicular to the hose during this procedure so that the blade cuts only the center line of the web. Extreme care must be taken to avoid cutting through the cover of the hoses and thereby exposing the hose reinforcement. If this occurs, the hose assembly must be discarded (See Figure 1). If the separation length is greater than that which can be accomplished with one continuous, smooth stroke, then the procedure should be repeated over shorter distances always cutting toward the free end of the hoses.

5



Measure Separation – It is suggested that the separation length be sufficiently long so that the swaging or crimping operation can be accomplished without risk of kinking the hoses or tearing the web which could result in exposure of the hose reinforcement (See Figure 2).

6



Apply Tape – At the option of the assembler, as dictated by the installation, a nylon lashing strap or tape may be applied at the termination of the separated length to provide protection against tearing of the web or hose covers.

INCORRECT HANDLING



Figure 1 – Extreme care must be taken to avoid cutting through the cover of the hoses and thereby exposing the hose reinforcement. If this occurs, the hose assembly must be discarded.





Figure 2 – The separation length must allow for the swaging or crimping operation without damaging the hose.

Ferrul-Fix Installation Instructions

Fast, on-the-job repair for ruptured bent tube hose assemblies and power steering lines.



The life of the combination tube-hose assembly is often limited to the service life of the hose alone. A replacement assembly may not be available, some equipment dealers are unable to stock all of the many odd tube configurations.

Parker FERRUL-FIX, a field attachable, reusable hose end fitting, now makes it possible to salvage the bent tube section of the original assembly for replacement. Most important, it gets you back into operation FAST!


1. Gets you back in operation fast - No costly delays while replacement assemblies are rushed from the factory.
2. Lets you reuse expensive bent tube ends with Parker Hose fittings. You can replace the hose at a fraction of the cost of a complete assembly.
3. Eliminates the need for emergency brazing or welding in the field - Ferrul-Fix can be assembled without special tools or equipment when using Parker S5Reusable Hose fittings.

3-Piece Design - Body, nut and ferrule
Wedging action of ferrule, when drawn down by nut, forms seal between body and ferrule, while cutting edge of ferrule "bites" into tube wall forming another positive seal.

Visible Bite
Extent of bite at cutting edge of ferrule is completely visible when fitting is dis-assembled, an important safety feature. Self-centering action assures even bite around circumference of tube.

Parkerized Finish
Ferrul-Lok fittings have the Parkerized black finish, providing "built-in" lubrication which reduces wrench torque required.

Ferrul-Fix Installation Instructions



1. Cut the formed tube off squarely next to the permanent hose fitting. Lightly deburr the end of the tube internally and externally.
2. Disassemble the Ferrul-Fix fitting, and lubricate threads and both ends of the ferrule with Parker Ferulube.
3. Slide nut and ferrule onto tubing, with the long, straight end of the ferrule pointing toward the tube end.
4. Insert tube end into the Ferrul-Fix body until it bottoms against the shoulder. Slide ferrule inside body, and screw nut down finger tight.
5. Wrench nut down 1-3/4 turns to preset the ferrule.
6. Disconnect nut and inspect lead edge of ferrule to make certain that the biting edge has turned up a shoulder to a height of at least 50% of the ferrule and completely around the tube.
7. Assemble Ferrul-Fix fitting to hose. Refer to assembly instructions listed in appropriate fittings section. Do not assemble to hose before steps 1-6.
8. Reassemble tubing into Ferrul-Fix end and turn nut down easily until a sudden increase in force is evident. Turn bent tube to proper position if required. Using two wrenches, one on the fitting nipple hex and the other on the nut tighten nut an additional 1/6 turn (one wrench flat).

For detailed ordering information, please consult price list or contact Parflex Division.

Die Selection & Swage Specification Chart
Sewer Hose

Swage Data For Sewer Cleaning Hose
(SQ-101-SW SWAGE MACHINE ONLY)

Hose Type	Hose I.D.	Male Pipe			Mender/Splicer		Swage O.D. +/-.015	Swage Length
		Fitting P/N	Die P/N	Pusher P/N	Fitting P/N	Die P/N		
	inch						inch	inch
S508N	1/2	-	-	-	1HU55-8-8	SQ-101-08S5S	0.850	0.750
S612	3/4	101SQ-12-12	SQ-101-12S6/S9	SQ-101-12P	1HUSQ-12-12	SQ-101-12S6/S9	1.172	1.109
S616	1	101SQ-16-16	SQ-101-16S6	SQ-101-16P	1HUSQ-16-16	SQ-101-16S6	1.445	1.156
S912	3/4	101SQ-12-12	SQ-101-12S6/S9	SQ-101-12P	1HUSQ-12-12	SQ-101-12S6/S9	1.172	1.109
S916	1	101SQ-16-16	SQ-101-16S9	SQ-101-16P	1HUSQ-16-16	SQ-101-16S9	1.488	1.156

Comments:

1. Two dies required when swaging a mender/splicer fitting. A pusher is not required when swaging a mender/splicer fitting.
2. One die and one pusher required when swaging a male pipe fitting.
3. End fittings cannot be swaged on S5N series hose. Only mender/splicers can be swaged.
4. Fittings cannot be swaged on SLH series hose.

The information covered in the Swage Specification & Tool Selection Chart pertains to steel, stainless and brass hose fittings. Swage diameter roundness shall not vary by more than .010". Swage diameters are measured in the center to the crimp area. Parflex Division reserves the right to alter swage specifications.

Hose Fitting Insertion Values

Inch

Hose Dash Size	51	54	56	CG	91N	92	93N	BU	CY	LV/LH	MS Reusable	MS Permanent
-2			5/8					1/2	1/2			
-3	13/16	5/8	5/8	29/32	7/16	9/16		13/16	13/16	13/16		
-4	15/16	3/4	15/16	1-3/16	1/2							
-5	15/16	7/8	1		9/16						11/16	11/16
-6	1-5/16	15/16	1	1-5/16	5/8		7/16				15/16	3/4
-8	1-19/32	15/16	1-1/8	1-9/16	11/16		7/16			2-1/8		
-10			1-1/8		11/16		3/4			2-1/4		
-12	1-13/16		1-3/8	2-3/16	3/4		7/8			2-3/8		
-16	1-9/16		1-7/8	2-3/4	15/16		15/16			2-13/16		
-20					1		1					
-24							1-1/8					
-32							1-3/8					








Metric (mm)







Hose Dash Size	51	54	56	CG	91N	92	93N	BU	CY	LV/LH	MS Reusable	MS Permanent
-2			16					13	13			
-3	21	16	16	23	11	14		21	21	21		
-4	24	19	24	30	13							
-5	24	22	25		14						17	17
-6	33	24	25	33	16		11				24	19
-8	40	24	29	40	17		11			54		
-10			29		17		19			57		
-12	46		35	56	19		22			60		
-16	40		48	70	24		24			71		
-20					25		25					
-24							29					
-32							35					

For detailed ordering information, please consult price list or contact Parflex Division.

Hose Fitting Thread Guide

There are more than one hundred types of threads for fittings. Below are some of the most common thread styles offered by Parflex. The end code in a fitting part number is located directly after the first digit. i.e. 1**03**56-8-8

End Code ⇨	 01	 03	 04	 05	 28, 67, 69	 09	 11	 JM
Dash Size	**NPTF Pipe Thread Size**	**SAE (JIC) 37° Flare Thread Size**	**SAE 45° Flare Thread Size**	**"O" Ring Style Straight Thread Size**	**SAE Inverted Flare Thread Size**	**PTT 30° Flare Thread Size**	**SAE Flareless Thread Size**	**Seal-Lok™ Thread**
2	1/8 - 27	5/16 - 24	5/16 - 24	5/16 - 24	-	-	5/16 - 24	-
3	-	3/8 - 24	3/8 - 24	3/8 - 24	3/8 - 24	-	3/8 - 24	-
4	1/4 - 18	7/16 - 20	7/16 - 20	7/16 - 20	7/16 - 18	-	7/16 - 20	9/16 - 18
5	-	1/2 - 20	1/2 - 20	1/2 - 20	1/2 - 20	-	1/2 - 20	-
6	3/8 - 18	9/16 - 18	5/8 - 18	9/16 - 18	5/8 - 18	-	9/16 - 18	11/16 - 16
8	1/2 - 14	3/4 - 16	3/4 - 16	3/4 - 16	3/4 - 18	-	3/4 - 16	13/16 - 16
10	-	7/8 - 14	7/8 - 14	7/8 - 14	7/8 - 18	-	7/8 - 14	1 - 14
12	3/4 - 14	1 1/16 - 12	1 1/16 - 14	1 1/16 - 12	1 1/16 - 16	-	1 1/16 - 12	1 3/16 - 12
14	-	1 3/16 - 12	-	1 3/16 - 12	-	-	1 3/16 - 12	-
16	1 - 11 1/2	1 5/16 - 12	-	1 5/16 - 12	-	1 5/16 - 14	1 5/16 - 12	1 7/16 - 12
20	1 1/4 - 11 1/2	1 5/8 - 12	-	1 5/8 - 12	-	1 5/8 - 14	1 5/8 - 12	-
24	1 1/2 - 11 1/2	1 7/8 - 12	-	1 7/8 - 12	-	1 7/8 - 14	1 7/8 - 12	-
32	2 - 11 1/2	2 1/2 - 12	-	2 1/2 - 12	-	2 1/2 - 12	2 1/2 - 12	-

End Code ⇨	 C3	 C6	 D0	 D2	 D9	 92	 92	 F9	 FG
Dash Size	**Metric Swivel Female Thread Size**	**Metric Swivel Female Thread Size**	**Male Stud Thread Size**	**Male Stud Thread Size**	**Male BSPP Thread Size**	**BSP Swivel Female Thread Size**	**French Swivel Female Gas Series**	**French Swivel Female Metric Series**	**French Male Stud Gas Series**
4	-	-	-	-	1/4"	1/4"	-	-	-
6	M12 x 1,5	-	M12 x 1,5	-	3/8"	3/8"	-	M12 x 1	-
8	M14 x 1,5	M16 x 1,5	M14 x 1,5	M16 x 1,5	1/2"	1/2"	-	M14 x 1,5	-
10	M16 x 1,5	M18 x 1,5	M16 x 1,5	M18 x 1,5	-	5/8"	-	M16 x 1,5	-
12	M18 x 1,5	M20 x 1,5	M18 x 1,5	M20 x 1,5	3/4"	3/4"	-	M18 x 1,5	-
-	-	-	-	-	-	-	M20 x 1,5	-	M20 x 1,5
14	-	M22 x 1,5	-	M22 x 1,5	-	-	-	M20 x 1,5	-
15	M22 x 1,5	-	M22 x 1,5	-	-	-	-	M22 x 1,5	-
16	-	M24 x 1,5	-	M24 x 1,5	1"	1"	-	M24 x 1,5	-
-	-	-	-	-	-	-	M24 x 1,5	-	M24 x 1,5
18	M26 x 1,5	-	M26 x 1,5	-	-	-	-	M27 x 1,5	-
20	-	M30 x 2	-	M30 x 2	-	-	-	M27 x 1,5	-
-	-	-	-	-	-	-	M30 x 1,5	-	M30 x 1,5
22	M30 x 2	-	M30 x 2	-	-	-	-	M30 x 1,5	-
25	-	M36 x 2	-	M36 x 2	-	-	-	M33 x 1,5	-
-	-	-	-	-	-	-	M36 x 1,5	-	M36 x 1,5
28	M36 x 2	-	M36 x 2	-	-	-	-	-	-
30	-	M42 x 2	-	M42 x 2	-	-	-	M39 x 1,5	-
33	-	-	-	-	-	-	M45 x 1,5	-	M45 x 1,5

For detailed ordering information, please consult price list or contact Parflex Division.

Media to Fitting & Seal Compatibility

Media	Fitting Material			Seal Material			
	Brass	Steel	316 SS	BUNA-N	Ethylene Propylene	Fluorocar-bon	Neoprene
Acetylene	NR	F	S	S	S	S	F
Air (oil free) @ 190° F	S	F	S	S	S	S	S
Air (oil free) @ 300° F	S	F	S	F	F	S	F
Air (oil free) @ 400° F	S	F	S	NR	NR	S	NR
Alcohol, Ethyl	S	NR	NR	NR	S	NR	S
Animal Oils (Lard Oil)	F	F	F	S	F	S	F
Aromatic Fuel - 50%	ID	ID	ID	F	NR	S	NR
Aromatic Solvents	ID	ID	F	F	ID	S	NR
Asphalt	NR	NR	S	F	NR	S	F
ASTM Oil #1	S	S	S	S	NR	S	S
ASTM Oil #2	S	S	S	S	NR	S	F
ASTM Oil #3	S	S	S	S	NR	S	NR
ASTM Oil #4	S	S	S	F	NR	S	NR
ATF Oil	S	S	S	S	NR	S	F
Automotive Brake Fluid	ID	ID	ID	NR	S	NR	F
Benzene	NR	F	NR	NR	NR	S	NR
Brine (Sodium Chloride)	NR	NR	S	S	S	S	S
Butane	NR	S	S	S	NR	S	S
Carbon Dioxide	S	F	S	S	S	S	S
Carbon Monoxide	S	S	S	S	S	S	F
Chlorine (Dry)	F	F	NR	NR	ID	F	F
Compressed Air	S	F	S	S	S	S	S
Crude Oil	NR	F	S	F	NR	S	NR
Cutting Oil	ID	S	S	S	NR	S	F
Diesel Fuel	S	S	S	S	NR	S	NR
Ethanol	S	NR	NR	NR	S	NR	S
Ethers	S	S	S	NR	F	F	NR
Freon 11	S	ID	ID	F	NR	F	NR
Freon 12	S	S	NR	F	NR	S	S
Freon 22	S	NR	S	NR	NR	NR	S
Fuel Oil	NR	S	S	S	NR	S	F
Gasoline	S	F	S	S	NR	S	NR
Gas, Liquid Propane (LPG)	S	S	S	S	NR	S	F
Gas, Natural	F	S	S	S	NR	S	S
Helium	S	S	S	S	S	S	S
Hydraulic Oil, Petroleum Base	S	S	S	S	NR	S	S
Hydraulic Oil, Water Base	ID	S	S	F	S	NR	F
Hydrogen Gas	S	S	S	S	S	S	S
Jet Fuel	S	S	S	S	NR	S	NR
Kerosene	S	S	S	S	NR	S	F

Media to Fitting & Seal Compatibility

Media	Fitting Material			Seal Material			
	Brass	Steel	316 SS	BUNA-N	Ethylene Propylene	Fluorocar-bon	Neoprene
Lubricating Oil SAE 10, 20, 30, 40, 50	S	S	S	S	NR	S	F
Methanol	S	S	S	S	S	NR	S
MIL-F-8192 (JP-9)	S	S	S	NR	NR	S	NR
MIL-H-5606	S	S	S	S	NR	S	F
MIL-H-6083	S	S	S	S	NR	S	S
MIL-H-7083	S	S	S	S	S	F	F
MIL-H-8446 (MLO-8515)	F	S	S	F	NR	S	S
Mil-L-2104 & 2104B	S	S	S	S	NR	S	F
MIL-L-7808	NR	F	S	F	NR	S	NR
Mineral Oil	S	S	S	S	NR	S	F
Nitrogen	S	S	S	S	S	S	S
Petrolatum	S	S	S	S	NR	S	F
Petroleum Oil (<250° F)	S	S	S	S	NR	S	F
Propane	S	S	S	S	NR	S	F
R134A	S	S	S	NR	S	NR	NR
Sea Water	F	NR	S	S	S	S	F
Skydrol 500, Type 2	NR	S	S	NR	S	NR	NR
Skydrol 7000, Type 2	NR	S	S	NR	S	F	NR
Soap Solutions	NR	NR	S	S	S	S	F
Steam (<400° F)	F	S	S	NR	S	NR	NR
Stoddard Solvent	F	S	S	S	NR	S	F
Transmission Fluid (Type A)	S	S	S	S	NR	S	F
Trichloroethane	ID	F	S	NR	NR	S	NR
Water	S	F	S	S	S	F	F

Table U4 – Fluid Compatibility Chart

Codes:
S = Satisfactory
F = Fair
NR = Not recommended
ID = Insufficient data

Metal Tube & Fitting Material Compatibility

As a general rule, tube and fitting materials should be the same. If different materials must be considered, the following chart can be used as a general guide. Since operating conditions differ with applications, this chart should be used only as a guide and not a firm recommendation. Before making a final decision on material combination, it should be sufficiently tested under appropriate conditions to assure suitability for the intended application. For additional material combinations, contact the Tube Fittings Division.

Tube Material	Specification	Construction	Condition	Maximum Hardness	Temperature Range (7)	Application	Tube Material to Fitting & Material Compatibility											
							Seal-Lok™ ORFS (SAE J1453)			Triple-Lok® 37° Flare (SAE J514)				Ferulok® Flareless (SAE J514)			Intru-Lok® Flareless	EO/EO-2 Flareless (ISO 8434-1)
							S	SS	B	S	SS	B	M	S	SS	M	B	S SS B, M
Carbon Steel C-1010	SAE J524 (ASTM A179) (8)	Seamless	Fully Annealed	HRB 72	-65° to 500°F -55° to 260°C	High pressure hydraulics, air, & some specialty chemicals	E	NR	(6)	G	NR	(6)	NR	E	NR	NR	NR	NR
	SAE J525 (ASTM A178) (8)	Welded & Drawn					E	NR	(6)	E	NR	(6)	NR	E	NR	NR	NR	NR
	SAE J356	Welded & Flash Controlled					G	NR	(6)	NR	NR	(6)	NR	G	NR	NR	NR	NR
Carbon Steel C-1021	SAE J2467	Welded & Flash Controlled	Fully Annealed	HRB 75	-65° to 500°F -55° to 260°C	High pressure hydraulics	E	NR	(6)	NR	NR	(6)	NR	E	NR	NR	NR	NR
	SAE J2435	Welded & Drawn					E	NR	(6)	E	NR	(6)	NR	E	NR	NR	NR	NR
Carbon Steel High Strength Low Alloy (HSLA)	SAE 2613	Welded & Flash Controlled	Sub-critically annealed	HRB 90	-65° to 500°F -55° to 260°C	High pressure hydraulics	E (10)	NR	(6)	NR	NR	NR	NR	NR	NR	NR	NR	NR
	SAE J2614	Welded & Drawn					E	NR	(6)	NR	NR	NR	NR	NR	NR	NR	NR	NR
Alloy Steel 4130	ASTM A519	Seamless			-65° to 500°F -55° to 260°C	High pressure hydraulics	E (4)	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR
St 37.4 (Carbon Steel)	DIN 2391 Part 2 (Metric)	Seamless	Fully Annealed	HRB 72	-65° to 500°F -55° to 260°C	High pressure hydraulics, air, & some specialty chemicals	E	NR	NR	G	NR	NR	NR	NR	NR	NR	NR	E
Stainless Steel 304 & 316	ASTM A213 ASTM A269	Seamless	Fully Annealed	HRB 90	-425° to 1200°F -255° to 650°C (3)	High pressure, high temp, or generally corrosive media (1)	(6)	E	(6)	(6)	G	(6)	NR	(6)	E	NR	NR	NR
	ASTM A249 ASTM A269	Welded & Drawn					(6)	E	(6)	(6)	E	(6)	NR	(6)	E	NR	NR	NR
1.4571 1.4541 Stainless Steel	DIN 17458 Tab 8 (Metric)	Seamless	Fully Annealed	HRB 90	-425° to 120°F -255° to 650°C (3)	High pressure, high temp, or generally corrosive media (1)	(6)	E	NR	(6)	G	NR	NR	NR	E	NR	NR	E
Copper	SAE J528 (ASTM B-75) (8)	Seamless	Soft Annealed Temper 0	60 Max. Rockwell 15T	-325° to 400°F -200° to 205°C	Low pressure, low temp, water, oil & air	E	(6)	E	G	(6)	E	NR	G (2)	NR	NR	E	E
Aluminum 6061	ASTM-B210	Seamless	T6 Temper	HRB 56	-325° to 400°F -200° to 205°C	Low pressure,low temp, water, oil, air & some specialty chemicals	NR	NR	NR	G	NR	NR	NR	E (2)	NR	NR	(6)	NR
			0 & T4 Temper	HRB 30			E (5)	NR	NR	G	NR	NR	NR	E (2)	NR	NR	(6)	NR
Monel 400	ASTM-B165	Seamless	Fully Annealed	HRB 70	-400° to 800°F -240° to 425°C	Sour gas, marine & gen chemical processing media	NR	(6)	NR	NR	(6)	NR	E	NR	(6)	E	NR	NR

(Cont.)

Metal Tube & Fitting Material Compatibility

Tube Material	Specification	Construction	Condition	Maximum Hardness	Temperature Range (7)	Application	Tube Material to Fitting & Material Compatibility											
							Seal-Lok™ ORFS (SAE J1453)			Triple-Lok® 37° Flare (SAE J514)				Ferulok® Flareless (SAE J514)			Intru-Lok® Flareless	EO/EO-2 Flareless (ISO 8434-1)
							S	SS	B	S	SS	B	M	S	SS	M	B	S SS B, M
Nylon		Extruded	Flexible & Semi-Rigid		-60° to 200°F -50° to 95°C	Lube lines, chemical process controls & air	NR	NR	NR	NR	NR	NR	NR	G (2)	G (2)	G (2)	E	G (2), (9)
Polyethylene	ASTM D-1248	Extruded	Instrument Grade		-80° to 150°F -60° to 65°C	Instrumentation lines	NR	NR	NR	NR	NR	NR	NR	G (2)	G (2)	G (2)	E	G (2), (9)
PVC		Extruded	Instrument & Laboratory Grade		0° to 140°F -20° to 60°C	General purpose laboratory use	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR	G	NR
PTFE		Extruded & Sintered			-65° to 400°F -55° to 205°C	Very high temp, fuel, lube, chemical, pharma, food	NR	NR	NR	NR	NR	NR	NR	G (2)	G (2)	G (2)	G	G (2), (9)

Table U7 – Tube and Fitting Material Compatibility

Ratings Key:
NR = Not Recommended
F = Fair
G = Good
E = Excellent

Fittings Materials Code:
S = Steel
SS = Stainless Steel
B = Brass
M = Monel

Notes:
1. For highly corrosive media or service environment, contact the Tube Fittings Division.
2. Requires different assembly procedure. Contact the Tube Fittings Division.
3. Low temperature limit for stainless steel Ferulok® fittings is -20°F (-30°C).
4. For brazing only. Grade 4130 not recommended with Parflange process.
5. For use with Parflange process only. Not recommended with brazing.
6. Use depends on specific application. Contact the Tube Fittings Division.
7. Applies to tube material.
8. Comparable specifications to SAE.
9. With metric version of tubing.
10. Not tested with Parflange. Contact the Tube Fittings Division.

O-Ring Material Selection

Standard O-rings supplied with Parker tube fittings and adapters are 90 durometer hard nitrile (Buna-N) Parker compound #N0552. These O-rings are well suited for most industrial hydraulic and pneumatic systems. They have high extrusion resistance making them suitable for very high pressure static applications. Optional high temperature fluorocarbon, Parker compound #V0894, is also available for higher temperature specifications.

O-rings for other than normal hydraulic media or higher temperature applications can be selected from the following chart. The chart should be used only as a general guide. Before making final selection for a given application, it is recommended that appropriate tests be conducted to assure compatibility with the fluid, temperature, pressure and other environmental conditions.

For fluids not shown in the chart, please contact the Tube Fittings Division.

Polymer	Abbreviated Name	Parker Compound No.	Color	SAE J515 Type	Hardness Shore "A"[7]	Temperature Range	Recommended For	Not Recommended For
Nitrile-Butadiene	NBR	N0552	● B	CH[2]	90[6]	-30° to 250°F	Petroleum base oils and fluids, mineral oils, ethylene glycol base fluids, silicone and di-ester base lubricants, air, water under 150°F, and natural gas. Hydrogen fuel cells. Meets FDA requirements for food products. CNG Applications.	Phosphate ester base hydraulic fluids, automotive brake fluids, strong acids, ozone, freons, ketones, halogenated hydrocarbons, and methanol.
		N0674		-	70	-30° to 250°F		
		N0103		-	70	-65° to 225°F		
Nitrile-Butadiene (Low compression set – N1059)		N1059		CH[2]	90	-30° to 275°F		
Nitrile-Butadiene		N0507		-	90	-65° to 180°F		
		N0304		-	75	-65° to 225°F		
		N0508		-	75	-35° to 250°F		
		N0756		-	75[6]	-65° to 275°F		
Ethylene-Propylene	EPDM	E0540	● B	CA[3]	80	-65° to 275° F	Phosphate ester base hydraulic fluids, hot water, steam to 400°F, silicone oils and greases, dilute acids and alkalis, ketones, alcohols and automotive brake fluids. CO_2 climate control systems.	Petroleum base oils and di-ester base lubricants.
		E0893	● P[1]	CA[3]	80			
		E0962	● B	-	90			
Neoprene	CR	C0873	● B	-	70	-45° to 250° F	Refrigerants (freons, ammonia), high aniline point petroleum oils, mild acids and silicate ester lubricants.	Phosphate ester fluids and ketones.
		C0944	● R[1]	-	70			
Fluorocarbon	FKM[5] or FPM	V0747	● B	-	75	-15° to 400° F	Petroleum base oils and fluids, some phosphate ester base fluids, silicone and silicate ester base lubricants, di-ester base lubricants, acids and halogenated hydrocarbons.	Ketones, skydrol fluids, amines (VDMH), anhydrous ammonia, low molecular weight esters and ethers, and hot hydrofluoric or chlorosulfonic acids.
		V0884	● BR[1]	-	75			
		V0894	● BR[1]	HK[4]	90[6]			
Silicone	Si	S0604	● RU[1]	-	70	-65° to 450° F	Dry heat (air to 400°F) and high aniline point oils.	Most petroleum fluids, ketones, water and steam.

Table U-6 – O-Ring Selection

*Color Code: B – Black, P – Purple, R – Red, BR – Brown, RU – Rust

Notes:

1. These Parker "Chromassure" color assurance O-rings are available from the Parker Hannifin O-Ring Division. They help eliminate assembly errors, reduce warranty costs and liability risks, and assure safety in aftermarket business.
2. Formerly SAE Type I.
3. Formerly SAE Type II.
4. Formerly SAE Type III.
5. "FKM" is the ASTM designation for fluorocarbon. Its ISO designation is "FPM".
6. Standard compounds available from stock.
7. Use 90 durometer hard O-rings for applications with 1500 psi or higher pressures.

Metals Corrosion Scale

Corrosion of Base Metals in Contact

The susceptibility of different base metals to corrosion while in contact depends upon the difference between the contact potentials or the electromotive voltages of the metals involved. The greater the potential difference is, the greater is the tendency for corrosion. The metal with the higher potential forms the anode and is corroded. The larger the separation distance in the electromotive chart between the two metals in contact, the higher the contact potential and chances for corrosion. For example, zinc and aluminum are very short distance apart in the chart; therefore potential for corrosion when these two metals are in contact is very low. On the other hand, aluminum and passivated 316 stainless steel are far apart; hence, when in contact, the potential for corrosion is very high. Aluminum, being more anodic metal, will corrode in this combination.

As a general guideline, if the metals are half the length of the chart or more apart, the combination should be avoided. Also, it is not a good idea to combine an anodic metal part with thin cross section, such as thin wall tubing, with a cathodic or less anodic metal part of a heavy cross section, such as a fitting.

Example: A thin wall brass tube with steel fitting is a better, although not ideal, combination than a thin wall steel tube with brass fitting.

Electromotive or Galvanic Series for Metals

+ Anodic (least noble) corroded

Electric current flows from plus to minus

Direction of attack

- Cathodic (most noble) protected

Magnesium
Magnesium alloys
Zinc **(Parker steel fittings are zinc plated)**
Berillium
Aluminum 5052, 3004, 3003, 1100, 6053
Cadmium
Aluminum 2117, 2017, 2024
Mild steel (1018), wrought iron, **free machining steel (12L14)**
Low alloy high strength steel, cast iron
Chrome iron (active)
430 Stainless (active)
302, 303, 321, 347, 410, 416, stainless steel (active)
Ni-resist
316, 317 stainless steel (active)
Carpenter 20Cb-3 stainless (active)
Aluminum bronze (CA 687)
Hastelloy C (active) Inconel 625 (active) Titanium (active)
Lead/Tin solder
Lead
Tin
Inconel 600 (active)
Nickel (active)
60 Ni-15 Cr (active)
80 Ni-20 Cr (active)
Hastelloy B (active)
Naval brass (CA 464), Yellow brass (CA 268), **Brass (CA360)**
Red brass (CA 230), Admiralty brass (CA 443)
Copper (CA 102)
Maganese bronze (CA 675), Tin bronze (CA 903, 905)
410, 416 Stainless (passive) Phosphor bronze (CA 521, 524)
Silicon bronze (CA 651, 655)
Nickel silver (CA 732, 735, 745, 752, 754, 757, 764, 770, 794)
Cupro Ni 90-10
Cupro Ni 80-20
430 Stainless steel (passive)
Cupro Ni 70-30
Nickel aluminum bronze (CA 630, 632)
Monel 400, K500
Silver solder
Nickel (passive)
60 Ni 15 Cr (passive)
Inconel 600 (passive)
80 Ni 20 Cr (passive)
Chrome iron (passive)
302, 303, 304, 321, 347 stainless steel (passive)
316, 317 stainless steel (passive) **(Parker stainless steel fittings are passivated)**
Carpenter 20 Cb-3 stainless (passive), Incoloy 825
Silver
Titanium (passive), Hastelloy C & C276 (passive), Inconel 625 (passive)
Graphic
Zirconium
Gold
Platinum

Table U5 – Electromotive or Galvanic Series for Metals

Materials to Parflex Part Number Guide

Ratings Code:

G – Good to excellent. Little or no swelling, tensile or surface changes. Preferred choice.

L – Marginal or conditional. Noticeable effects but not necessarily indicating lack of serviceability. Further testing suggested for specific application. Very long-term effects such as stiffening or potential for crazing should be evaluated.

P – Poor or unsatisfactory. Not recommended without extensive and realistic testing.

— – Indicates that this was not tested.

– For fluoropolymer. Indicates good chemical resistance but potential for excessive permeation.

Material Code for Hose Core Tubes		Hose
H	Copolyester	D6R, H6, R6, HFSR, HFS2R, M8, HTB, HJK, 560TJ, 563TJ, 590TJ, 594TJ, 510C, 518C, 515H, 53DM/538DM, 55LT, HLB, S6, S9, SLH
N	Nylon	518D, 520N, 526BA, 527BA, 528N, 540N, 548N, 56DH/568DH, 575X, 575XN, 580N, H580N, 588N, 1035HT, 5CNG, MSH, MSXL, PTH, S5N, 1035HT, CNGRP
NC	Proprietary Nylon Blend	510A
O	Polyethylene	540P
TFE/PFA	Fluoropolymer PTFE/PFA	919/919B, 919J, 919U, 929/929B, 929BJ, 939/939B, 943B, 944B, 950B, 955B, STW/STWB, SCW/SCB, PCW/PCB, NCW/NCB, SBFB/SBFW, SCWV/SCBV, PCWV/PCBV, SCWV-FS/SCBV-FS, PCWV-FS/PCBV-FS
U	Polyurethane	83FR, B9
Material Code for Hose Covers		**Hose**
EPDM	Rubber	RCTW (Contact Engineering for chemical resistance questions)
HF	Low Temperature Copolyester	55LT, 53DM/538DM
PFX	Proprietary Blend (PFX)	510C, 518C, 518D
M	Silicone	919J, 929BJ
U	Polyurethane	560TJ, 563TJ, 590TJ, 594TJ, 510A, 515H, 520N, 528N, 526BA, 527BA, 540N, 540P, 56DH, 569, 575X, 580N, 588N, 83FR, 1035HT, B9, 5CNG, HLB, MSH, PTH, S5N, S6, S9
N	Flexible Nylon	575XN
Material Code for Thermoplastic Tubing		**Tubing**
HDPE	High Density Polyethylene	HDPE
N	Flexible Nylon	N
NR	Unplasticized Nylon (semi-rigid)	NR
PE	Linear Low Density Polyethylene	E
PEFR	Flame Resistant Polyethylene	PEFR
PP	Polypropylene	PP
PV	Flexible Polyvinyl Chloride (PVC)	PV
U	Polyurethane	U, HU
Material Code for Fluoropolymer Tubing		**Tubing**
FEP	Fluorinated Ethylene Propylene	103, 203, HS1.3FEP, HS1.6FEP, CV03, CR03, 81914/3, 81914/4
PFA	Perfluoroalkoxy	104, 204, 105, 205, CV04, CR04, 704, 705
TFE	Polytetrafluoroethylene	TFL, TFS, TFT, TFH, 101, 201, TFB, HS2TFS, HS2TFT, HS2TFL, HS2TFI, HS4TFI, CV01, CVL, CVH, 81914/1, 81914/2
PVDF	Polyvinylidene Fluoride	110,111

Media to Hose Material Compatibility Guide

Media	H	N	U/HF UFR	PV	NC	O	PFX	HFR	FEP	PTFE/ PFA
Acetaldehyde	G	L	L	P	-	L	L	G	G	G
Acetic Acid Glacial	L	L	L	G	P	G	L	L	L	G
Acetone	L	G	P	P	G	P	P	L	G	G
Acetylene	2	2	2	2	2	2	2	2	2	2
Air (4)	G	G	G	G	G	G	G	G	G	G
Ammonium Chloride	G	P	G	G	P	G	G	G	L	G
Ammonium Hydroxide	L	G	P	L	-	G	P	L	G	G
Anhydrous Ammonia	P	P	P	P	P	P	P	P	8	8
Aniline	P	P	P	P	P	L	P	P	G	G
Animal Oils (6)	G	G	G	G	G	P	G	G	-	G
Aromatic Hydrocarbons	L	G	L	P	G	P	L	L	-	G
Asphalt	G	G	G	G	G	L	G	G	L	G
Baygon (Insecticide)	L	G	P	-	-	-	P	L	-	G
Beer	G	G	G	G	-	G	G	G	G	G
Benzene	L	G	L	P	L	P	L	L	G	G
Brake Fluid (DOT #3)	-	G	P	P	-	P	P	-	-	G
Butane (2) (4)	G	G	L	L	P	L	L	G	#	#
Butter (6)	G	G	G	G	-	G	G	G	-	G
Calcium Chloride	G	3	G	L	3	G	G	G	G	G
Carbon Dioxide (4)	G	G	G	G	G	G	G	G	#	#
Carbon Monoxide (4)	G	3	G	G	3	L	G	G	#	#
Carbon Tetrachloride	L	G	P	L	G	P	P	L	G	G
Castor Oil	G	L	L	G	L	P	L	G	-	G
Chlorinated Hydrocarbon Base Fluids	L	G	L	P	-	-	L	L	-	G
Chlorinated Petroleum Oil	G	G	L	-	L	-	L	G	-	-
Chlorinated Solvents	P	3	P	L	3	L	P	P	-	G
Chlorine, Gaseous, Dry	P	P	P	G	P	L	P	P	#	#
Chlordane (Insecticide)	L	G	P	-	-	-	P	L	-	-
Chloroform	P	P	P	P	P	P	P	P	G	G
Chromic Acid	P	3	P	G	P	3	P	P	L	G
Citric Acid Solutions	G	G	L	G	G	G	L	G	G	G
Crude Petroleum Oil	G	G	G	G	G	P	G	G	-	G
Cyclohexane (2)	G	G	G	-	-	P	G	G	G	G
Cygon (Insecticide)	L	G	P	-	-	-	P	L	-	-
Diazion (Insecticide)	L	-	P	L	-	-				
Diesel Fuel (2)	G	G	G	L	G	P	G	G	-	G
Diester Oils	L	G	P	P	-	P	P	L	-	G
Enamels	G	G	G	L	-	L	G	G	-	G
Ethanol (6)	G	G	L	L	L	G	L	G	-	G
Ethers	L	G	P	L	G	L	P	L	G	G
Ethylene Glycol	L	G	L	G	G	G	L	G	G	G
Ethylene Oxide	G	G	L	P	-	L	L	G	#	#
Fatty Acids	G	G	3	G	G	L	3	G	G	G
Formaldehyde	L	L	P	L	L	G	P	L	G	G
Formic Acid	P	P	P	G	P	G	P	P	G	G

(Cont.)

Media to Hose Material Compatibility Guide (cont.)

Media	H	N	U/HF UFR	PV	NC	O	PFX	HFR	FEP	PTFE/ PFA
Freon 12 (5)	P	G	L	G	G	L	L	P	#	#
Freon 22 (5)	P	G	L	G	G	L	L	P	#	#
Fruit Juices	G	G	G	G	-	G	G	G	-	G
Fuel Oil (2)	G	G	L	L	G	P	L	G	G	G
Gas (Oil) (2)	G	G	G	G	G	P	G	G	-	G
Gas (Natural) (4)	2	2	2	2	2	2	2	2	2	2
Gasoline (2)	G	G	3	P	G	P	3	G	G	G
Glue	3	3	3	3	3	3	3	3	3	3
Glycerin	G	G	L	G	G	G	L	G	G	G
Glycols (to 135°F)	L	G	L	G	G	-	L	G	G	G
Grease (Petroleum base)	G	G	G	G	G	L	G	G	-	G
Heptachlor (Insecticide)	L	G	P	L	-	P	P	L	-	G
Hexane (2)	G	G	G	L	G	P	G	G	G	G
Houghto Safe-600 Series (Hydraulic fluid)	G	G	L	G	G	G	L	G	-	G
Houghto Safe-1000 Series (Phosphate esters)	L	G	P	G	G	P	P	L	-	G
Hydraulic Fluid (Petroleum base)	G	G	G	G	G	L	G	G	L	G
Hydraulic Fluid (Phosphate ester base)	L	G	L	L	G	P	P	L	-	G
Hydraulic Fluid (Water glycol base)	G	G	G	L	G	-	G	G	-	G
Hydraulic Oil (Petroleum base)	G	G	G	G	G	L	G	G	L	G
Hydrochloric Acid	P	L	P	L	P	L	P	P	G	G
Hydrofluoric Acid	P	P	P	L	P	L	P	P	G	G
Hydrogen, Gaseous (2) (4) (5)	G	G	G	G	G	G	G	#	#	
Hydrolube (Hydraulic fluid/water glycol base)	G	G	L	G	G	G	L	G	-	G
IRUS 902 (Hydraulic fluid/water-oil emulsion)	G	G	G	G	G	L	G	G	-	G
Isocyanates (2)	L	L	L	P	-	L	L	L	-	G
IsoOctane (2)	G	G	G	L	G	L	L	G	G	G
Isopropyl Alcohol	G	G	L	L	G	G	L	G	G	G
Kerosene (2)	G	G	L	L	G	L	P	G	G	G
Ketones	L	G	P	P	G	G	P	L	G	G
Lacquer Solvents	L	G	P	P	3	L	P	L	L	G
Lactic Acid	P	G	P	G	G	G	P	P	G	G
Lime (Calcium oxide)	G	G	G	G	-	G	G	G	G	G
Lindol (Hydraulic fluid/phosphate esters)	L	G	P	-	-	-	P	L	-	G
Linseed Oil	G	G	G	L	G	L	G	G	G	G
LP - Gas	2	2	2	2	2	2	2	2	2	2
Lubricating Oils (Diester base)	L	G	P	-	G	-	P	L	-	G
Lubricating Oils (Petroleum base)	G	G	G	G	G	L	G	G	G	G
Malathion (Insecticide)	L	G	P	-	-	-	P	L	-	G
Magnesium Hydroxide	L	G	L	G	-	G	L	L	G	G
Magnesium Salts	-	G	G	G	-	G	G	-	-	G
Mercury	G	G	G	G	G	G	G	G	G	G
Meropa Oil (Sulphur base)	G	G	-	-	-	-	-	-	-	G
Methane	2	2	2	2	2	2	2	2	2	2
Methanol	G	G	P	P	G	L	P	G	-	G
Methoxychlor (Insecticide)	L	G	P	-	-	-	P	L	-	G

(Cont.)

Media to Hose Material Compatibility Guide (cont.)

Media	H	N	U/HF UFR	PV	NC	O	PFX	HFR	FEP	PTFE/ PFA
Methyl Alcohol (6)	G	G	P	P	G	L	P	G	G	G
Methylene Chloride	P	L	P	L	P	L	P	P	G	G
Methyl Ethyl Ketone (MEK)	L	G	P	P	G	G	P	L	G	G
Methyl Ethyl Ketone Peroxide (MEKP)	-	L	P	-	-	-	P	-	-	G
Methyl Isobutyl Ketone (MIBK)	L	G	P	P	G	L	P	L	G	G
Milk (6)	G	G	G	G	-	G	G	G	G	G
Mineral Oil	G	G	G	G	G	L	G	G	G	G
Mineral Spirits	P	-	L	P	-	-	L	P	-	G
Motor Oils	G	G	G	G	G	-	G	G	G	G
Naphtha	L	G	P	P	G	P	P	L	G	G
Natural Gas (4)	2	2	2	2	2	2	2	2	2	2
Nitric Acid	P	P	P	L	P	P	P	P	L	G
Nitrobenzene	P	G	P	P	G	P	P	P	G	G
Nitrogen, Gaseous (4) (5)	G	G	G	G	G	G	G	G	G	G
Nitrous Oxide	-	L	-	G	-	L	G	-	#	#
Oil (SAE)	G	G	G	G	G	L	G	G	-	G
Oil of Turpentine	G	G	P	G	G	P	P	G	-	G
Oleic Acid	G	G	G	L	G	L	G	G	G	G
OS 45 Type 3 Hydraulic Fluid (Silicate esters)	L	G	L	P	-	P	L	L	-	-
Oxygen, Gaseous (4) (5) (6)	G	G	G	G	G	G	G	G	G	G
Ozone	L	P	L	G	P	L	P	L	G	G
Paint Solvents (Oil base)	L	G	L	P	-	P	L	L	-	G
Paint (Oil Base) (7)	G	G	G	P	-	L	G	G	-	G
Pentane (2)	G	G	L	L	-	P	L	G	G	G
Perchloric Acid	P	P	P	L	P	P	P	P	L	G
Perchloroethylene	P	P	P	L	P	P	P	P	-	G
Petroleum Ether	-	2	2	P	2	P	2	-	2	2
Petroleum Oils	G	G	G	G	G	L	G	G	-	G
Phenols	P	P	P	L	P	P	P	P	-	G
Phosphate Esters (above 135°F)	P	G	P	P	-	P	P	L	-	G
Phosphate Esters (to 135°F)	G	G	P	P	G	P	P	G	-	G
Polyol Esters	L	G	P	P	-	-	P	L	-	G
Potassium Hydroxide, 50%	P	P	P	L	-	L	P	P	G	G
Propane (4) (5)	2	2	2	2	2	2	2	2	2	2
Propylene Glycol	-	-	G	G	-	G	-	-	G	G
Pydraul F-9, 150, 160 (to 135°F)	G	G	P	P	G	P	P	G	-	G
Pydraul 312C, 625 (to 135°F)	P	G	P	P	G	P	P	G	-	G
Quintolubric 822 Fluid	-	G	G	-	-	-	-	-	-	G
Salt Water	3	3	3	3	3	3	3	3	G	G
Sevin (Insecticides in water)	G	G	G	-	-	-	G	G	-	G
Silicone Greases	G	G	G	G	G	-	G	G	-	G
Silicone Oils	G	G	G	G	G	-	G	G	-	G
Skydrol 500 & 7000	L	G	P	P	G	P	P	L	G	G
Soap Solutions	G	G	G	G	G	G	G	G	G	G

(Cont.)

Media to Hose Material Compatibility Guide (cont.)

Media	H	N	U/HF UFR	PV	NC	O	PFX	HFR	FEP	PTFE/ PFA
Soda Water	G	G	G	G	G	3	G	G	-	G
Sodium Borate	G	G	G	G	G	G	G	G	G	G
Sodium Carbonate	3	3	3	3	3	3	3	3	3	3
Sodium Chloride Solutions	G	G	G	G	3	G	G	G	G	G
Sodium Hydroxide, 50%	L	P	P	L	P	L	P	L	G	G
Sodium Hypochlorite	L	P	P	L	-	3	P	L	G	G
Steam	P	P	P	P	P	P	P	P	G	G
Stoddard Solvent	P	G	P	L	G	P	P	P	G	G
Straight Synthetic Oils (Phosphate esters)	L	G	P	P	G	-	P	L	-	G
Sulfur	G	G	G	G	-	L	G	G	G	G
Sulfur Dioxide	P	L	L	L	-	P	L	P	G	G
Sulfur Hexafluoride Gas (4) (5)	G	G	G	G	-	G	G	G	-	G
Sulphuric Acid	P	P	P	3	P	P	P	P	-	G
Toluene	L	G	L	P	G	P	P	L	G	G
Toloul	L	G	L	P	G	P	P	L	-	G
Transmission Fluid	G	G	G	P	G	-	G	G	-	G
Trichloroethylene	P	L	P	L	G	P	P	P	G	G
Trisodium Phosphate Solutions	L	G	P	G	G	G	P	L	G	G
Turpentine	G	G	L	L	G	P	P	G	G	G
Ucon (Hydraulic fluid-water glycol base)	G	G	L	G	G	-	L	G	-	G
Varnish	G	G	G	P	G	G	G	G	-	G
Vinegar (6)	L	G	L	G	G	G	L	L	G	G
Water (to 135°F) (6)	G	G	G	G	G	G	L	G	G	G
Water (above 135°F) (6)	P	G	P	L	-	P	P	P	L	G
Water Glycols (to 135°F)	L	G	L	G	G	L	L	G	-	G
Water Glycols (above 135°F)	P	G	P	L	-	P	P	P	-	G
Water in oil Emulsions (to 135°F)	G	G	L	G	G	-	L	G	-	G
Water in oil Emulsions (above 135°F)	P	G	P	L	-	-	P	P	-	G
Whiskey, Wines (6)	G	G	L	G	G	G	G	G	G	G
Wood Oils	G	G	L	G	G	-	G	G	-	G
Xylene	L	G	P	P	G	P	P	L	G	G
Zinc Chloride	G	G	G	G	P	G	G	G	G	G

Notes:

1. The Fluid Compatibility Guides are simplified rating tabulations based on immersion tests at 75°F. Higher temperatures tend to reduce ratings. Since final selection depends on pressure, fluid and ambient temperature and other factors not known to Parker Hannifin Co., no performance guarantee is expressed or implied. Ratings do not imply compliance with specialized codes such as FDA, NSF, AGA or UL and do not cover possible fluid discoloration, taste or odor effects. For conveying foodstuffs, use FDA sanctioned materials and for potable water, use NSF listed materials. For chemicals not listed, or for advice on particular applications, please consult Product Engineering, Parflex Div., Ravenna, Ohio.
2. Hose applications for these fluids must take into account legal and insurance regulations. This does not imply AGA or UL compliance.
3. Satisfactory at some concentrations and temperatures, unsatisfactory in others.
4. For high pressure gases, the cover should be pinpricked and the pressure must not be released quickly. Chain or restrain the hose to prevent personal injury in the event of damage or failure.
5. Chemical compatibility does not imply low permeation rates. Consult the Parker factory for a suggestion for your specific requirement.
6. Does not imply NSF or FDA compliance.
7. Chemical compatibility does not imply acceptability for use in airless paint spray applications. These applications require a special conductive hose.
8. Fluoropolymers are chemically compatible with Anhydrous Ammonia. However,extreme caution must be used in dealing with Anhydrous Ammonia since it can cause severe injuries such as blindness and/or chemical burns.

Media to Plastic Tubing Material Compatibility Guide

Media	PE	HDPE	PP	N	NR	PV	U	PEFR	FEP	PFA	PTFE
Acetone	P	L	G	G	G	P	P	L	G	G	G
Acetyl Bromide	L	L	L	P	P	P	-	-	-	-	-
Acetyl Chloride	L	L	L	P	P	P	-	-	G	G	G
Air	G	G	G	G	G	G	G	G	G	G	G
Alcohols	G	G	G	G	G	L	L	G	G	G	G
Aluminum Salts	G	G	G	G	G	G	G	G	-	-	-
Ammonia	G	G	G	G	G	G	G	L	-	-	-
Amyl Acetate	G	G	G	G	G	P	L	-	G	G	G
Aniline	L	G	L	P	P	P	P	-	G	G	G
Animal Oils (6)	P	L	L	G	G	G	G	-	-	-	G
Arsenic Salts	G	G	G	G	G	G	G	G	-	-	-
Aromatic Hydrocarbons	P	L	L	G	G	P	L	P	-	-	G
Barium Salts	G	G	G	G	G	G	G	G	-	-	-
Benzaldehyde	P	L	L	L	L	P	L	P	G	G	G
Benzene	P	L	L	G	G	P	L	P	G	G	G
Benzyl Alcohol	P	G	L	L	L	G	L	P	G	G	G
Bleaching Liquors	G	L	G	L	L	L	L	-	-	-	-
Boric Acid Solutions	G	G	G	G	G	G	G	G	G	G	G
Bromine	L	L	P	P	P	P	P	-	G	L	G
Butane (2)	L	G	G	G	G	L	P	-	#	#	#
Butanol	G	G	G	G	G	G	G	G	-	-	-
Butyl Acetate	G	G	L	G	G	P	L	G	G	G	G
Calcium Hypochlorite	L	L	P	P	L	L	P	L	G	G	G
Calcium Salts	G	G	G	G	G	G	G	G	-	-	-
Carbon Dioxide	G	G	G	G	G	G	G	G	#	#	#
Carbon Disulfide	L	L	L	L	L	P	L	-	#	#	#
Carbon Tetrachloride	P	P	L	L	L	L	P	P	G	G	G
Caustic Potash	G	G	G	G	G	L	G	-	G	G	G
Caustic Soda	G	G	G	G	G	L	G	-	G	L	G
Chloracetic Acid	L	G	L	L	L	P	P	-	G	L	G
Chlorine (Dry)	L	L	L	P	P	G	P	-	#	#	#
Chlorine (Wet)	L	L	L	P	P	G	L	-	G	G	G
Chlorobenzene	P	L	L	L	L	P	L	P	G	G	G
Chloroform	P	L	P	P	P	P	P	P	G	G	G
Chromic Acid	L	L	L	P	P	G	P	-	L	G	G
Copper Salts	G	G	G	G	G	G	G	G	-	-	-
Cresol	P	L	L	P	P	L	P	P	G	G	G
Cyclohexanone	L	L	L	L	L	P	P	-	G	G	G
Ethers	L	L	P	G	G	L	P	-	G	G	G
Ethyl Acetate	G	G	G	G	G	P	L	-	G	G	G
Ethyl Alcohol	G	G	G	L	L	L	G	G	-	-	-
Ethylamine	L	G	L	L	L	P	L	-	-	-	-
Ethyl Bromide	P	L	L	L	L	P	-	P	-	-	-
Ethyl Chloride	P	L	P	L	L	P	-	P	G	G	G
Fatty Acids	L	L	L	G	G	L	L	P	G	G	G

(Cont.)

Media to Plastic Tubing Material Compatibility Guide (cont.)

Media	PE	HDPE	PP	N	NR	PV	U	PEFR	FEP	PFA	PTFE
Ferric Salts	G	G	G	G	G	G	G	-	-	-	-
Formaldehyde	G	G	G	L	L	L	P	-	G	G	G
Formic Acid	G	G	G	P	P	G	P	G	G	G	G
Freon	L	L	L	G	G	P	L	-	#	#	#
Gasoline (2)	P	G	L	G	G	P	L	P	G	G	G
Glucose	G	G	G	G	G	G	G	G	G	G	G
Glycerin	G	G	G	G	G	G	L	G	G	G	G
Hydriodic Acid	L	G	G	P	P	G	-	-	-	-	-
Hydrochloric Acid. (Conc.)	L	G	G	L	L	L	P	-	G	L	G
Hydrochloric Acid. (Med. Conc.)	L	G	G	L	L	L	P	-	G	L	G
Hydrofluoric Acid	L	L	G	P	P	L	P	-	G	-	G
Hydrogen Peroxide (Conc.)	L	G	L	L	L	L	G	-	-	-	-
Hydrogen Peroxide (Dil.)	L	G	L	G	G	G	G	-	-	-	-
Hydrogen Sulfide	G	G	G	G	G	G	P	-	G	G	G
Iodine	L	G	G	G	G	L	L	-	G	G	G
Kerosene (2)	L	L	L	G	G	L	L	-	G	G	G
Ketones	G	G	G	G	G	P	P	-	G	G	G
Lacquer Solvents	L	L	L	G	G	P	-	-	L	G	G
Lactic Acid	G	G	G	G	G	G	G	-	G	G	G
Lead Acetate	G	G	G	G	G	G	G	-	G	G	G
Linseed Oil	L	G	G	G	G	L	G	-	G	G	G
Magnesium Salts	G	G	G	G	G	G	G	-	-	-	G
Naphtha	L	L	L	G	G	P	L	G	G	G	G
Natural Gas	L	L	L	G	G	G	G	-	2	2	2
Nickel Salts	G	G	G	G	G	G	G	-	-	-	-
Nitric Acid (Conc.)	P	L	P	P	P	L	P	G	L	L	G
Nitric Acid (Dil.)	P	G	L	L	L	G	P	P	L	L	G
Nitrobenzene	P	L	G	L	L	P	P	P	G	G	G
Nitrogen Oxides	L	L	G	L	L	G	-	-	-	-	-
Nitrous Acid	L	L	G	L	L	G	L	-	G	G	G
Oils (Animal and Mineral)	L	L	L	G	G	L	G	-	G	G	G
Oils (Vegetable)	L	L	L	G	G	L	G	-	G	G	G
Oxygen (5) (6)	G	G	G	G	G	G	G	G	G	G	G
Perchloric Acid	P	G	L	P	P	L	P	P	L	G	G
Phenols	P	G	G	P	P	L	P	P	-	-	G
Potassium Salts	G	G	G	G	G	G	G	G	-	-	-
Pyridine	L	L	L	L	L	P	P	-	G	G	G
Silver Nitrate	G	G	G	G	G	G	G	G	G	G	G
Soap Solutions	G	G	G	G	G	G	G	G	G	G	G
Sodium Salts	G	G	G	G	G	G	G	G	-	-	-
Stearic Acid	L	L	L	G	G	P	L	-	G	G	G
Sulfur Chloride	L	L	P	L	L	L	-	-	G	G	G
Sulfuris Acid (Conc.)	P	G	G	P	P	L	P	P	-	-	-
Sulfuris Acid (Dil.)	P	G	G	L	L	G	L	P	-	-	-
Sulfurous Acid	P	G	L	L	L	G	L	P	G	G	G

(Cont.)

For detailed ordering information, please consult price list or contact Parflex Division.

Media to Plastic Tubing Material Compatibility Guide (cont.)

Media	PE	HDPE	PP	N	NR	PV	U	PEFR	FEP	PFA	PTFE
Tannic Acid	G	G	G	G	G	G	P	-	G	G	G
Tanning Extracts	G	G	G	G	G	G	P	-	-	-	-
Titanium Salts	G	G	G	G	G	G	G	G	-	-	-
Toluene	P	L	P	G	G	P	L	P	G	G	G
Trichloroacetic Acid	L	L	L	P	P	P	P	-	-	-	-
Trichloroethylene	P	L	P	L	L	P	P	P	G	G	G
Turpentine	P	P	L	G	G	L	L	-	G	G	G
Urea	G	G	G	G	G	G	G	-	G	L	G
Uric Acid	G	G	G	G	G	G	G	-	G	G	G
Water (6)	G	G	G	G	G	G	G	G	G	G	G
Xylene	P	L	P	G	G	P	P	P	G	G	G
Zinc Chloride	G	G	G	G	G	G	G	-	G	L	G

Notes:

1. The Fluid Compatibility Guides are simplified rating tabulations based on immersion tests at 75°F. Higher temperatures tend to reduce ratings. Since final selection depends on pressure, fluid and ambient temperature and other factors not known to Parker Hannifin Co., no performance guarantee is expressed or implied. Ratings do not imply compliance with specialized codes such as FDA, NSF, AGA or UL and do not cover possible fluid discoloration, taste or odor effects. For conveying foodstuffs use FDA sanctioned materials, and for potable water use NSF listed materials. For chemicals not listed, or for advice on particular applications, please consult Product Engineering, Parflex Div., Ravenna, Ohio.
2. Hose applications for these fluids must take into account legal and insurance regulations. This does not imply AGA or UL compliance.
3. Satisfactory at some concentrations and temperatures, unsatisfactory in others.
4. For high pressure gases, the cover should be pinpricked and the pressure must not be released quickly. Chain or restrain the hose to prevent personal injury in the event of damage or failure.
5. Chemical compatibility does not imply low permeation rates. Consult the Parker factory for a suggestion for your specific requirement.
6. Does not imply NSF or FDA compliance.
7. Chemical compatibility does not imply acceptability for use in airless paint spray applications. These applications require a special conductive hose.
8. Fluoropolymers are chemically compatible with Anhydrous Ammonia. However, extreme caution must be used in dealing with Anhydrous Ammonia since it can cause severe injuries such as blindness and/or chemical burns.

Metric Conversion Chart

English to Metric			
	To Convert From	To	Multiply By
Area	Sq. in. (in^2)	Sq. mm (mm^2)	645.16
	Sq. in. (in^2)	Sq. cm (cm^2)	6.4516
	Sq. ft. (ft^2)	Sq. meters (m^2)	0.0929
Density	Pounds/Cubic foot ($lb.ft^2$)	Kilograms/Cubic meter (kg/m^2)	16.02
Energy	British thermal units (Btu) (1 J=Ws=0.2388 cal)	Joules (J)	1055
Force	Pounds – force (lbf) (1N=0.102 kgf)	Newtons (N)	4.448
Length	Inches (in)	Milimeters (mm)	25.4
	Feet (ft)	Meters (m)	0.3048
	Miles (mi)	Kilometers (km)	1.609
Mass (Weight)	Ounces (oz.)	Grams (g)	28.35
	Pounds – mass (lb)	Kilograms (kg)	0.4536
	Short tons (2000 lb) (tn)	Metric tons (100 kg) (t)	0.9072
Power	Horsepower (550 ft lb/s) (hp)	Kilowatts (kW)	0.7457
Pressure	Pounds/square inch (psi)	Kilograms (f)/square cm ($kg(f)/cm^2$)	0.7457
		Kilopascals (kPa)	0.0703
		Bars (100 kPa)	6.8948
Stress	Pounds/square inch (psi) ($1N/mm^2$=1MPa)	megapascals (MPa)	0.006895
Tempera-ture	Degrees Fahrenheit (°F)	Degrees Celsius (°C)	5/9 (after sub-tracting 32)
Torque or Bending Moment	Pounds-force-foot (lb-ft)	Newtons-meter (Nm)	1.3567
	Pounds-force-inch (lb-in)		0.113
Velocity	Feet/second (ft/s)	Meters/second (m/s)	0.3048
Viscosity	Dynamic (centipoise)	Pascal-second (Pas)	.001
	Denematic – $foot^2$/sec (ft^2/s)	$Meter^2$/sec (m^2/s)	0.0929
Volume	Cubic inch (in^3)	Cubic centimeter (cm^3) (mililiter)	16.3871
	Quarts (qt)	Liters (1000 cm^3)	0.9464
	Gallons (gal)	Liters	3.7854

Metric to English		
To Convert From	To	Multiply By
Sq. mm (mm^2)	Sq. in. (in^2)	0.00155
Kilograms/Cubic meter (kg/m^2)	Pounds/Cubic foot (lb/ft^2)	0.0624
Joules (J)	British Thermal Units (Btu)	0.000947
Newtons (N)	Pounds - force (lbf)	0.2248
Milimeters (mm)	Inches (in)	0.03937
Meters (m)	Feet (ft)	3.281
Kilometers (km)	Miles (mi)	0.621
Grams (g)	Ounces (oz.)	0.035
Kilograms (kg)	Pounds - mass (lb)	2.205
Metric tons (100 kg) (t)	Short tons (2000 lb) (tn)	1.102
Kilowatts (kW)	Horsepower (550 ft lb/s) (hp)	1.341
Kilograms (f)/square cm ($kg(f)/cm^2$)	Pounds/square inch (psi)	14.22
Kilopascals (kPa)		0.145
Bars (100 kPa)		14.503
megapascals (MPa)	Pounds/square inch (psi) ($1N/mm^2$=1MPa)	145.039
Degrees Celsius (°C)	Degrees Fahrenheit (°F)	9/5 (then add 32)
Newtons-meter (Nm)	Pounds-force-foot (lb-ft)	0.737
	Pounds-force-inch (lb-in)	8.85
Meters/second (m/s)	Feet/second (ft/s)	3.2808
Pascal-second (Pas)	Dynamic (centipoise)	1000
$Meter^2$/sec (m^2/s)	Denematic - $foot^2$/sec (ft^2/s)	10.7643
Cubic centimeter (cm^3) (mililiter)	Cubic inch (in^3)	0.061
Liters (1000 cm^3)	Quarts (qt)	1.057
Liters	Gallons (gal)	0.2642

For detailed ordering information, please consult price list or contact Parflex Division.

Government & Agency Specifications

Agency and Specifications	Parflex Products
Flame Resistance:	
MSHA	83FR, D6R, HFS2R, HTB, M8, 560TJ, 563TJ, 594TJ, 590TJ, 510A (except -4, -5, -6), 510C (except -4), 515H, 520N, 540N, 56DH-2, 575X, 580N, HLB, HJK
UL94V-2	PEFR, HUFR
UL94HB	83FR NN, NB, NNR, NBR (wall thickness above 0.033", contact Parflex for availability)
VW1, UL-83	All PFA, FEP & PTFE tubing products
Food Contact:	
FDA, CFR21 Part 177	E, F64, PP, PV, 540P, 919, 919J, 919U, 929, 939, S30, S40, STW, SBFW, SCW, PCW, SCWV, PCWV, PCWV-FS, SCWV-FS, RCTW, All natural and black PFA, FEP, PTFE & PVDF tubing products
NSF Standard 51*	E, EA, F64, PP, NTNA - Tubing
Potable Water:	
NSF Standard 61*	E - Tubing
Natural Gas Service: For Vehicles and Dispensing Systems	
ANSI CSA NGV 4.2; NFPA 52; CSA 12.52 Class A, Class D	5CNG
ANSI CSA NGV 3.1; NFPA 52; CSA 12.3, Class C	CNGRP
ECE-R110	5CNG factory built assemblies
Hydraulic Service:	
SAE 100R1AT	HFSR, 560TJ
SAE 100R2	590TJ
SAE 100R7	540N, 540P, 548N, 510A (less-2), 518C, 518D, 55LT, 510C (less-2), 943B
SAE 100R8	520N, 528N, 580N, 588N, H580N
SAE 100R14A	919, 919J, 919U, 929
SAE 100R14B	919B, 929B, 929BJ
SAE 100R17	D6R, H6, R6, 563TJ, 943B
SAE 100R18	53DM, 538DM
SAE 100R19	594TJ, M8
WASTEC WRP05:	
Waste Equipment Technology Association	S5N, S6, S9, SLH
Transportation Standards:	
SAE J844, FMVSS106 (49CFR571.106)	PFT, 1120A, 1120B, BRAKCOIL®, Dollycoil™, Duo-Coil™, SliderCoil™
Electrical, Non-Conductivity:	
SAE J517	518C, 518D, 548N, 528N, 588N, 538DM
DNV (with approved fittings only)	
Det Norski (Norwegian) Veritas Marine Steel Ships, Mobile Offshore & Fixed Offshore Drilling Units	510C, 518C, 518D, 520N, 528N, 540N, 575X, 575XN, 580N, 588N, H580N, 560TJ, 590TJ,
Breathing Air Applications:	
CGA (Compressed Gas Association)-G7.1-1 Grade E Breathing Air	526BA, 527BA
NFPA 1901	526BA, 527BA

*Indicates that products shown have been tested and certified by NSF International to the requirements of NSF Standards 51 and 61. NSF does not express or imply an approval on any product.

Agency and Specifications	Parflex Products
Aerospace Material Specifications:	
AMS 3584A	HS2TFI
AMS 3585	HS2TFT
AMS 3586	HS2TFS
AMS 3653E	101, 201, TFS, TFL, TFH, TFT, HS2TFS, HS2TFT, HS2TFL, HS2TFI, TSWTF, CV (PTFE), CVL, CVH, 81914/1, 81914/2
AMS 3654C	TFL
AMS 3655B	TFT
MIL-DTL-27267C	PTFE Conductive Tubing
AMS-DTL-23053/11A CLASS 1	HS1.3FEP
AMS-DTL-23053/11A CLASS 2	HS1.6FEP
AMS-DTL-23053/12A CLASS 1	HS2TFH
AMS-DTL-23053/12A CLASS 2	HS2TFS
AMS-DTL-23053/12A CLASS 3	HS2TFT
AMS-DTL-23053/12A CLASS 4	HS2TFL
AMS-DTL-23053/12A CLASS 5	HS2TFI
SAE AS81914/1	81914/1
SAE AS81914/2	81914/2
SAE AS81914/3	81914/3
SAE AS81914/4	81914/4
American Society for Testing and Materials:	
ASTM D1710, TYPE 1, GRADE 1, CLASS B	TFB
ASTM D2116-07	103, 203
ASTM D2902 TYPE 1	HS2TFS, HS2TFT, HS2TFL, HS2TFI, HS2TFH
ASTM D2902 TYPE II	HS1.3FEP, HS1.6FEP, HS1.25FEP
ASTM D3222	110, 111
ASTM D3295	TFB, TSWTF
ASTM D3295, Class 1	TFL
ASTM D3295, Class 2	TFT
ASTM D3295, Class 3	TFS
ASTM D3295, Class 4	TFH
ASTM D3296-03	HS1.3FEP, HS1.6FEP, CV (FEP), 81914/3, 81914/4, CR (FEP), 703
ASTM D3307-10	104, 204, 105, 205, CR (PFA), 704, 705
Canadian Standards Association:	
CSA 9032-01 300V	TFT (awg)
CSA 9032-01 600V	TFS (awg)
Military Standard - US Department of Defense:	
MIL-I-22129C	TFS
A-A-59602	TSWTF
Underwriters Laboratories:	
UL-224 150V 200°C	TFL (awg)
UL-224 300V 200°C	TFT (awg)
UL-224 600V 200°C	TFS (awg)
United States Pharmacopoeia:	
USP Class VI	101, 201, TFS, TFL, TFH, TFT, TFB, HS2TFS, HS2TFT, HS2TFL, HS2TFI, HS2TFH, CV, CVL, CVH, 103, 203, HS1.3FEP, HS1.6FEP, CR, 104, 204, 105, 205, RCTW, SBFW

Parker Safety Guide

Parker Safety Guide for Selecting and Using Hose, Tubing, Fittings, Connectors, Conductors, Valves and Related Accessories

⚠ Parker Safety Guide for Selecting and Using Hose, Tubing, Fittings and Related Accessories
Publication No. 4400-B.1
Revised: September 2015

WARNING: Failure or improper selection or improper use of hose, tubing, fittings, assemblies, valves, connectors, conductors or related accessories ("Products") can cause death, personal injury and property damage. Possible consequences of failue or improper selection or improper use of these Products include, but are not limited to:

- Fittings thrown off at high speed.
- High velocity fluid discharge.
- Explosion or burning of the conveyed fluid.
- Electrocution from high voltage electric powerlines.
- Contact with suddenly moving or falling objects that are controlled by the conveyed fluid.
- Injections by high-pressure fluid discharge.
- Dangerously whipping Hose.
- Tube or pipe burst.
- Weld joint fracture.
- Contact with conveyed fluids that may be hot, cold, toxic or otherwise injurious.
- Sparking or explosion caused by static electricity buildup or other sources of electricity.
- Sparking or explosion while spraying paint or flammable liquids.
- Injuries resulting from inhalation, ingestion or exposure to fluids.

Before selecting or using any of these Products, it is important that you read and follow the instructions below. No product from any division in Fluid Connector Group is approved for in-flight aerospace applications. For hoses and fittings used in in-flight aerospace applications, please contact Parker Aerospace Group.

1.0 GENERAL INSTRUCTIONS

1.0 Scope: This safety guide provides instructions for selecting and using (including assembling, installing, and maintaining) these Products. For convenience, all rubber and/or thermoplastic products commonly called "hose" or "tubing" are called "Hose" in this safety guide. Metallic tube or pipe are called "tube". All assemblies made with Hose are called "Hose Assemblies". All assemblies made with Tube are called "Tube Assemblies". All products commonly called "fittings", "couplings" or "adapters" are called "Fittings". Valves are fluid system components that control the passage of fluid. Related accessories are ancillary devices that enhance or monitor performance including crimping, flaring, flanging, presetting, bending, cutting, deburring, swaging machines, sensors, tags, lockout handles, spring guards and associated tooling. This safety guide is a supplement to and is to be used with the specific Parker publications for the specific Hose, Fittings and Related Accessories that are being considered for use. Parker publications are available at www.parker.com. SAE J1273 (www.sae.org) and ISO 17165-2 (www.ansi.org) also provide recommended practices for hydraulic Hose Assemblies, and should be followed.

1.1 Fail-Safe: Hose, Hose Assemblies, Tube, Tube Assemblies and Fittings can and do fail without warning for many reasons. Design all systems and equipment in a fail-safe mode, so that failure of the Hose, Hose Assembly, Tube, Tube Assembly or Fitting will not endanger persons or property.

1.2 Distribution: Provide a copy of this safety guide to each person responsible for selecting or using Hose, Tube and Fitting products. Do not select or use Parker Hose, Tube or Fittings without thoroughly reading and understanding this safety guide as well as the specific Parker publications for the Products.

1.3 User Responsibility: Due to the wide variety of operating conditions and applications for Hose, Tube and Fittings. Parker does not represent or warrant that any particular Hose, Tube or Fitting is suitable for any specific end use system. This safety guide does not analyze all technical parameters that must be considered in selecting a product. The user, through its own analysis and testing, is solely responsible for:

- Making the final selection of the Products.
- Assuring that the user's requirements are met and that the application presents no health or safety hazards.
- Following the safety guide for Related Accessories and being trained to operate Related Accessories.
- Providing all appropriate health and safety warnings on the equipment on which the Products are used.
- Assuring compliance with all applicable government and industry standards.

1.4 Additional Questions: Call the appropriate Parker technical service department if you have any questions or require any additional information. See the Parker publication for the Products being considered or used, or call 1-800-CPARKER, or go to www.parker.com, for telephone numbers of the appropriate technical service department.

2.0 HOSE, TUBE & FITTINGS SELECTION INSTRUCTIONS

2.1 Electrical Conductivity: Certain applications require that the Hose be nonconductive to prevent electrical current flow. Other applications require the Hose and the Fittings and the Hose/Fitting interface to be sufficiently conductive to drain off static electricity. Extreme care must be exercised when selecting Hose, Tube and Fittings for these or any other applications in which electrical conductivity or nonconductivity is a factor. The electrical conductivity or nonconductivity of Hose, Tube and Fittings is dependent upon many factors and may be susceptible to change. These factors include but are not limited to the various materials used to make the Hose and the Fittings, Fitting finish (some Fitting finishes are electrically conductive while others are nonconductive), manufacturing methods (including moisture control), how the Fittings contact the Hose, age and amount of deterioration or damage or other changes, moisture content of the Hose at any particular time, and other factors. The following are considerations for electrically nonconductive and conductive Hose. For other applications consult the individual catalog pages and the appropriate industry or regulatory standards for proper selection.

2.1.1 Electrically Nonconductive Hose: Certain applications require that the Hose be nonconductive to prevent electrical current flow or to maintain electrical isolation. For applications that require Hose to be electrically nonconductive, including but not limited to applications near high voltage electric lines, only special nonconductive Hose can be used. The manufacturer of the equipment in which the nonconductive Hose is to be used must be consulted to be certain that the Hose, Tube and Fittings that are selected are proper for the application. Do not use any Parker Hose or Fittings for any such application requiring nonconductive Hose, including but not limited to applications near high voltage electric lines or dense magnetic fields, unless (i) the application is expressly approved in the Parker technical publication for the product, (ii) the Hose is marked "nonconductive", and (iii) the manufacturer of the equipment on which the Hose is to be used specifically approves the particular Parker Hose, Tube and Fittings for such use.

2.1.2 Electrically Conductive Hose: Parker manufactures special Hose for certain applications that require electrically conductive Hose.

Parker manufactures special Hose for conveying paint in airless paint spraying applications. This Hose is labeled "Electrically Conductive Airless Paint Spray Hose" on its layline and packaging. This Hose must be properly connected to the appropriate Parker Fittings and properly grounded in order to dissipate dangerous static charge buildup, which occurs in all airless paint spraying applications. Do not use any other Hose for airless paint spraying, even if electrically conductive. Use of any other Hose or failure to properly connect the Hose can cause a fire or an explosion resulting in death, personal injury, and property damage. All hoses that convey fuels must be grounded.

Parker manufactures a special Hose for certain compressed natural gas ("CNG") applications where static electricity buildup may occur. Parker CNG Hose assemblies comply with the requirements of ANSI/IAS NGV 4.2; CSA 12.52, "Hoses for Natural Gas Vehicles and Dispensing Systems" (www.ansi.org). This Hose is labeled "Electrically Conductive for CNG Use" on its layline and packaging. This Hose must be properly connected to the appropriate Parker Fittings and properly grounded in order to dissipate

dangerous static charge buildup, which occurs in, for example, high velocity CNG dispensing or transfer. Do not use any other Hose for CNG applications where static charge buildup may occur, even if electrically conductive. Use of other Hoses in CNG applications or failure to properly connect or ground this Hose can cause a fire or an explosion resulting in death, personal injury, and property damage. Care must also be taken to protect against CNG permeation through the Hose wall. See section 2.6, Permeation, for more information. Parker CNG Hose is intended for dispenser and vehicle use within the specified temperature range. Parker CNG Hose should not be used in confined spaces or unventilated areas or areas exceeding the specified temperature range. Final assemblies must be tested for leaks. CNG Hose Assemblies should be tested on a monthly basis for conductivity per ANSI/IAS NGV 4.2; CSA 12.52.

Parker manufactures special Hose for aerospace in-flight applications. Aerospace in-flight applications employing Hose to transmit fuel, lubricating fluids and hydraulic fluids require a special Hose with a conductive inner tube. This Hose for in-flight applications is available only from Parker's Stratoflex Products Division. Do not use any other Parker Hose for in-flight applications, even if electrically conductive. Use of other Hoses for in-flight applications or failure to properly connect or ground this Hose can cause a fire or an explosion resulting in death, personal injury and property damage. These Hose assemblies for in-flight applications must meet all applicable aerospace industry, aircraft engine and aircraft requirements.

2.2 Pressure: Hose, Tube and Fitting selection must be made so that the published maximum working pressure of the Hose, Tube and Fittings are equal to or greater than the maximum system pressure. The maximum working pressure of a Hose, or Tube Assembly is the lower of the respective published maximum working pressures of the Hose, Tube and the Fittings used. Surge pressures or peak transient pressures in the system must be below the published maximum working pressure for the Hose, Tube and Fitting. Surge pressures and peak pressures can usually only be determined by sensitive electrical instrumentation that measures and indicates pressures at millisecond intervals. Mechanical pressure gauges indicate only average pressures and cannot be used to determine surge pressures or peak transient pressures. Published burst pressure ratings for Hose is for manufacturing test purposes only and is no indication that the Product can be used in applications at the burst pressure or otherwise above the published maximum recommended working pressure.

2.3 Suction: Hoses used for suction applications must be selected to insure that the Hose will withstand the vacuum and pressure of the system. Improperly selected Hose may collapse in suction application.

2.4 Temperature: Be certain that fluid and ambient temperatures, both steady and transient, do not exceed the limitations of the Hose, Tube, Fitting and Seals. Temperatures below and above the recommended limit can degrade Hose, Tube, Fittings and Seals to a point where a failure may occur and release fluid. Tube and Fittings performances are normally degraded at elevated temperature. Material compatibility can also change at temperatures outside of the rated range. Properly insulate and protect the Hose Assembly when routing near hot objects (e.g. manifolds). Do not use any Hose in any application where failure of the Hose could result in the conveyed fluids (or vapors or mist from the conveyed fluids) contacting any open flame, molten metal, or other potential fire ignition source that could cause burning or explosion of the conveyed fluids or vapors.

2.5 Fluid Compatibility: Hose, and Tube Assembly selection must assure compatibility of the Hose tube, cover, reinforcement, Tube, Plating and Seals with the fluid media used. See the fluid compatibility chart in the Parker publication for the product being considered or used. This information is offered only as a guide. Actual service life can only be determined by the end user by testing under all extreme conditions and other analysis. Hose, and Tube that is chemically compatible with a particular fluid must be assembled using Fittings and adapters containing likewise compatible seals. Flange or flare processes can change Tube material properties that may not be compatible with certain requirements such as NACE.

2.6 Permeation: Permeation (that is, seepage through the Hose or Seal) will occur from inside the Hose or Fitting to outside when Hose or Fitting is used with gases, liquid and gas fuels, and refrigerants (including but not limited to such materials as helium, diesel fuel, gasoline, natural gas, or LPG). This permeation may result in high concentrations of vapors which are potentially flammable, explosive, or toxic, and in loss of fluid. Dangerous explosions, fires, and other hazards can result when using the wrong Hose for such applications. The system designer must take into account the fact that this permeation will take place and must not use Hose or Fitting if this permeation could be hazardous. The system designer must take into account all legal, government, insurance, or any other special regulations which govern the use of fuels and refrigerants. Never use a Hose or Fitting even though the fluid compatibility is acceptable without considering the potential hazardous effects that can result from permeation through the Hose or Tube Assembly. Permeation of moisture from outside the Hose or Fitting to inside the Hose or Fitting will also occur in Hose or Tube assemblies, regardless of internal pressure. If this moisture permeation would have detrimental effects (particularly, but not limited to refrigeration and air conditioning systems), incorporation of sufficient drying capacity in the system or other appropriate system safeguards should be selected and used. The sudden pressure release of highly pressurized gas could also result in Explosive Decompression failure of permeated Seals and Hoses.

2.7 Size: Transmission of power by means of pressurized fluid varies with pressure and rate of flow. The size of the components must be adequate to keep pressure losses to a minimum and avoid damage due to heat generation or excessive fluid velocity.

2.8 Routing: Attention must be given to optimum routing to minimize inherent problems (kinking or flow restriction due to Hose collapse, twisting of the Hose, proximity to hot objects or heat sources). For additional routing recommendations see SAE J1273 and ISO 17165-2. Hose Assemblies have a finite life and should be installed in a manner that allows for ease of inspection and future replacement. Hose because of its relative short life,should not be used in residential and commercial buildings inside of inaccessible walls or floors, unless specifically allowed in the product literature. Always review all product literature for proper installation and routing instructions.

2.9 Environment: Care must be taken to insure that the Hose, Tube and Fittings are either compatible with or protected from the environment (that is,surrounding conditions) to which they are exposed. Environmental conditions including but not limited to ultraviolet radiation, sunlight, heat, ozone, moisture, water, salt water, chemicals and air pollutants can cause degradation and premature failure.

2.10 Mechanical Loads: External forces can significantly reduce Hose, Tube and Fitting life or cause failure. Mechanical loads which must be considered include excessive flexing, twist, kinking, tensile or side loads, bend radius, and vibration. Use of swivel type Fittings or adapters may be required to insure no twist is put into the Hose. Use of proper Hose or Tube clamps may also be required to reduce external mechanical loads. Unusual applications may require special testing prior to Hose selection.

2.11 Physical Damage: Care must be taken to protect Hose from wear, snagging, kinking, bending smaller that minimum bend radius and cutting, any of which can cause premature Hose failure. Any Hose that has been kinked or bent to a radius smaller than the minimum bend radius, and any Hose that has been cut or is cracked or is otherwise damaged should be removed and discarded. Fittings with damages such as scratches on sealing surfaces and deformation should be replaced.

2.12 Proper End Fitting: See instructions 3.2 through 3.5. These recommendations may be substantiated by testing to industry standards such as SAE J517 for hydraulic applications, or MIL-A-5070, AS1339, or AS3517 for Hoses from Parker's Stratoflex Products Division for aerospace applications.

2.13 Length: When determining the proper Hose or Tube length of an assembly take into consideration. The Hose length change due to pressure. The Tube length change due to thermal expansion or contraction, and the Hose or Tube machine tolerances and movements. When routing short hose assemblies, it is recommended that the minimum free hose length is always used. Consult the hose manufacturer for their minimum free hose length recommendations. Hose assemblies should be installed in such a way that any motion or flexing occurs within the same plane.

2.14 Specifications and Standards: When selecting Hose, Tube and Fittings, government, industry, and Parker specifications and recommendations must be reviewed and followed as applicable.

2.15 Hose Cleanliness: Hose and Tube components may vary in cleanliness levels. Care must be taken to ensure that the Hose and Tube Assembly selected has an adequate level of cleanliness for the application.

2.16 Fire Resistant Fluids: Some fire resistant fluids that are to be conveyed by Hose or Tube require use of the same type of Hose or Tube as used with petroleum base fluids. Some such fluids require a special Hose, Tube, Fitting and Seal, while a few fluids will not work with any Hose at all. See instructions 2.5 and 1.5. The wrong Hose, Tube, Fitting or Seal may fail after a very short service. In addition, all liquids but pure water may burn fiercely under certain conditions, and even pure water leakage may be hazardous.

2.17 Radiant Heat: Hose and Seals can be heated to destruction without contact by such nearby items as hot manifolds or molten metal. The same heat source may then initiate a fire. This can occur despite the presence of cool air around the Hose or Seal. Performance of Tube and Fitting subjected to the heat could be degraded.

2.18 Welding or Brazing: When using a torch or arc welder in close

proximity to hydraulic lines, the hydraulic lines should be removed or shielded with appropriate fire resistant materials. Flame or weld spatter could burn through the Hose or Seal and possibly ignite escaping fluid resulting in a catastrophic failure. Heating of plated parts, including Hose Fittings and adapters, above 450°F (232°C) such as during welding, brazing or soldering may emit deadly gases. Any elastomer seal on fittings shall be removed prior to welding or brazing, any metallic surfaces shall be protected after brazing or welding when necessary. Welding and brazing filler material shall be compatible with the Tube and Fitting that are joined.

2.19 Atomic Radiation: Atomic radiation affects all materials used in Hose and Tube assemblies. Since the long-term effects may be unknown, do not expose Hose or Tube assemblies to atomic radiation. Nuclear applications may require special Tube and Fittings.

2.20 Aerospace Applications: The only Hose, Tube and Fittings that may be used for in-flight aerospace applications are those available from Parker's Stratoflex Products Division. Do not use any other Hose or Fittings for in-flight applications. Do not use any Hose or Fittings from Parker's Stratoflex Products division with any other Hose or Fittings, unless expressly approved in writing by the engineering manager or chief engineer of Stratoflex Products Division with any other Hose or Fittings, unless expressly approved in writing by the engineering manager or chief engineer of Stratoflex Products Division and verified by the user's own testing and inspection to aerospace industry standards.

2.21 Unlocking Couplings: Ball locking couplings or other Fittings with quick disconnect ability can unintentionally disconnect if they are dragged over obstructions, or if the sleeve or other disconnect member, is bumped or moved enough to cause disconnect. Threaded Fittings should be considered where there is a potential for accidental uncoupling.

3.0 HOSE AND FITTINGS ASSEMBLY AND INSTALLATION INSTRUCTIONS

3.1 Component Inspection: Prior to assembly, a careful examination of the Hose and Fittings must be performed. All components must be checked for correct style, size, catalog number, and length. The Hose must be examined for cleanliness, obstructions, blisters, cover looseness, kinks, cracks,cuts or any other visible defects. Inspect the Fitting and sealing surfaces for burrs, nicks, corrosion or other imperfections. Do NOT use any component that displays any signs of nonconformance.

3.2 Hose and Fitting Assembly: Do not assemble a Parker Fitting on a Parker Hose that is not specifically listed by Parker for that Fitting, unless authorized in writing by the engineering manager or chief engineer of the appropriate Parker division. Do not assemble a Parker Fitting on another manufacturer's Hose or a Parker Hose on another manufacturer's Fitting unless (i) the engineering manager or chief engineer of the appropriate Parker division approves the Assembly in writing or that combination is expressly approved in the appropriate Parker literature for the specific Parker product, and (ii) the user verifies the Assembly and the application through analysis and testing. For Parker Hose that does not specify a Parker Fitting, the user is solely responsible for the selection of the proper Fitting and Hose Assembly procedures. See instruction 1.4.

To prevent the possibility of problems such as leakage at the Fitting or system contamination, it is important to completely remove all debris from the cutting operation before installation of the Fittings. The Parker published instructions must be followed for assembling the Fittings on the Hose. These instructions are provided in the Parker Fitting catalog for the specific Parker Fitting being used, or by calling 1-800-CPARKER, or at www.parker.com.

3.3 Related Accessories: Do not crimp or swage any Parker Hose or Fitting with anything but the listed swage or crimp machine and dies in accordance with Parker published instructions. Do not crimp or swage another manufacturer's Fitting with a Parker crimp or swage die unless authorized in writing by the engineering manager or chief engineer of the appropriate Parker division.

3.4 Parts: Do not use any Parker Fitting part (including but not limited to socket, shell, nipple, or insert) except with the correct Parker mating parts, in accordance with Parker published instructions, unless authorized in writing by the engineering manager or chief engineer of the appropriate Parker division.

3.5 Field Attachable/Permanent: Do not reuse any Field Attachable Hose Fitting that has blown or pulled off a Hose. Do not reuse a Parker permanent Hose Fitting (crimped or swaged) or any part thereof. Complete Hose Assemblies may only be reused after proper inspection under section 4.0. Do not assemble Fittings to any previously used hydraulic Hose that was in service, for use in a fluid power application.

3.6 Pre-Installation Inspection: Prior to installation, a careful examination of the Hose Assembly must be performed. Inspect the Hose Assembly for any damage or defects. DO NOT use any Hose Assembly that displays any signs of nonconformance.

3.7 Minimum Bend Radius: Installation of a Hose at less than the minimum listed bend radius may significantly reduce the Hose life. Particular attention must be given to preclude sharp bending at the Hose to Fitting juncture. Any bending during installation at less than the minimum bend radius must be avoided. If any Hose is kinked during installation, the Hose must be discarded.

3.8 Twist Angle and Orientation: Hose Assembly installation must be such that relative motion of machine components does not produce twisting.

3.9 Securement: In many applications, it may be necessary to restrain, protect, or guide the Hose to protect it from damage by unnecessary flexing, pressure surges, and contact with other mechanical components. Care must be taken to insure such restraints do not introduce additional stress or wear points.

3.10 Proper Connection of Ports: Proper physical installation of the Hose Assembly requires a correctly installed port connection insuring that no twist or torque is transferred to the Hose when the Fittings are being tightened or otherwise during use.

3.11 External Damage: Proper installation is not complete without insuring that tensile loads, side loads, kinking, flattening, potential abrasion, thread damage or damage to sealing surfaces are corrected or eliminated. See instruction 2.10.

3.12 System Checkout: All air entrapment must be eliminated and the system pressurized to the maximum system pressure (at or below the Hose maximum working pressure) and checked for proper function and freedom from leaks. Personnel must stay out of potential hazardous areas while testing and using.

3.13 Routing: The Hose Assembly should be routed in such a manner so if a failure does occur, the escaping media will not cause personal injury or property damage. In addition, if fluid media comes in contact with hot surfaces, open flame or sparks, a fire or explosion may occur. See section 2.4.

3.14 Ground Fault Equipment Protection Devices (GFEPDs): **WARNING!** Fire and Shock Hazard. To minimize the danger of fire if the heating cable of a Multitube bundle is damaged or improperly installed, use a Ground Fault Equipment Protection Device. Electrical fault currents may be insufficient to trip a conventional circuit breaker. For ground fault protection, the IEEE 515: (www.ansi.org) standard for heating cables recommends the use of GFEPDs with a nominal 30 milliampere trip level for "piping systems in classified areas, those areas requiring a high degree of maintenance, or which may be exposed to physical abuse or corrosive atmospheres".

4.0 TUBE AND FITTINGS ASSEMBLY AND INSTALLATION INSTRUCTIONS

4.1 Component Inspection: Prior to assembly, a careful examination of the Tube and Fittings must be performed. All components must be checked for correct style, size, material, seal, and length. Inspect the Fitting and sealing surfaces for burrs, nicks, corrosion, missing seal or other imperfections. Do NOT use any component that displays any signs of nonconformance.

4.2 Tube and Fitting Assembly: Do not assemble a Parker Fitting with a Tube that is not specifically listed by Parker for that Fitting, unless authorized in writing by the engineering manager or chief engineer of the appropriate Parker division. The Tube must meet the requirements specified to the Fitting.

The Parker published instructions must be followed for assembling the Fittings to a Tube. These instructions are provided in the Parker Fitting catalog for the specific Parker Fitting being used, or by calling 1-800-CPARKER, or at www.parker.com.

4.3 Related Accessories: Do not preset or flange Parker Fitting components using another manufacturer's equipment or procedures unless authorized in writing by the engineering manager or chief engineer of the appropriate Parker division. Tube, Fitting component and tooling must be check for correct style, size and material. Operation and maintenance of Related Accessories must be in accordance with the operation manual for the designated Accessory.

4.4 Securement: In many applications, it may be necessary to restrain, protect, or guide the Tube to protect it from damage by unnecessary flexing,pressure surges, vibration, and contact with other mechanical components. Care must be taken to insure such restraints do not introduce additional stress or wear points.

4.5 Proper Connection of Ports: Proper physical installation of the Tube Assembly requires a correctly installed port connection insuring that no torque is transferred to the Tube when the Fittings are being tightened or otherwise during use.

4.6 External Damage: Proper installation is not complete without

insuring that tensile loads, side loads, flattening, potential abrasion, thread damage or damage to sealing surfaces are corrected or eliminated. See instruction 2.10.

4.7 System Checkout: All air entrapment must be eliminated and the system pressurized to the maximum system pressure (at or below the Tube Assembly maximum working pressure) and checked for proper function and freedom from leaks. Personnel must stay out of potential hazardous areas while testing and using.

4.8 Routing: The Tube Assembly should be routed in such a manner so if a failure does occur, the escaping media will not cause personal injury or property damage. In addition, if fluid media comes in contact with hot surfaces, open flame or sparks, a fire or explosion may occur. See section 2.4.

5.0 HOSE AND FITTING MAINTENANCE AND REPLACEMENT INSTRUCTIONS

5.1 Even with proper selection and installation, Hose life may be significantly reduced without a continuing maintenance program. The severity of the application, risk potential from a possible Hose failure, and experience with any Hose failures in the application or in similar applications should determine the frequency of the inspection and the replacement for the Products so that Products are replaced before any failure occurs. Certain products require maintenance and inspection per industry requirements. Failure to adhere to these requirements may lead to premature failure. A maintenance program must be established and followed by the user and, at minimum, must include instructions 5.2 through 5.7

5.2 Visual Inspection Hose/Fitting: Any of the following conditions require immediate shut down and replacement of the Hose Assembly:

- Fitting slippage on Hose;
- Damaged, cracked, cut or abraded cover (any reinforcement exposed);
- Hard, stiff, heat cracked, or charred Hose;
- Cracked, damaged, or badly corroded Fittings;
- Leaks at Fitting or in Hose;
- Kinked, crushed, flattened or twisted Hose; and
- Blistered, soft, degraded, or loose cover.

5.3 Visual Inspection All Other: The following items must be tightened, repaired, corrected or replaced as required:

- Leaking port conditions;
- Excess dirt buildup;
- Worn clamps, guards or shields; and
- System fluid level, fluid type, and any air entrapment.

5.4 Functional Test: Operate the system at maximum operating pressure and check for possible malfunctions and leaks. Personnel must avoid potential hazardous areas while testing and using the system. See section 2.2.

5.5 Replacement Intervals: Hose assemblies and elastomeric seals used on Hose Fittings and adapters will eventually age, harden, wear and deteriorate under thermal cycling and compression set. Hose Assemblies and elastomeric seals should be inspected and replaced at specific replacement intervals, based on previous service life, government or industry recommendations, or when failures could result in unacceptable downtime, damage, or injury risk. See section 1.2. Hose and Fittings may be subjected to internal mechanical and/or chemical wear from the conveying fluid and may fail without warning. The user must determine the product life under such circumstances by testing. Also see section 2.5.

5.6 Hose Inspection and Failure: Hydraulic power is accomplished by utilizing high pressure fluids to transfer energy and do work. Hoses, Fittings and Hose Assemblies all contribute to this by transmitting fluids at high pressures. Fluids under pressure can be dangerous and potentially lethal and, therefore, extreme caution must be exercised when working with fluids under pressure and handling the Hoses transporting the fluids. From time to time, Hose Assemblies will fail if they are not replaced at proper time intervals. Usually these failures are the result of some form of misapplication, abuse, wear or failure to perform proper maintenance. When Hoses fail, generally the high pressure fluids inside escape in a stream which may or may not be visible to the user. Under no circumstances should the user attempt to locate the leak by "feeling" with their hands or any other part of their body. High pressure fluids can and will penetrate the skin and cause severe tissue damage and possibly loss of limb. Even seemingly minor hydraulic fluid injection injuries must be treated immediately by a physician with knowledge of the tissue damaging properties of hydraulic fluid.

If a Hose failure occurs, immediately shut down the equipment and leave the area until pressure has been completely released from the Hose Assembly. Simply shutting down the hydraulic pump may or may not eliminate the pressure in the Hose Assembly. Many times check valves, etc., are employed in a system and can cause pressure to remain in a Hose Assembly even when pumps or equipment are not operating. Tiny holes in the Hose, commonly known as pinholes, can eject small, dangerously powerful but hard to see streams of hydraulic fluid. It may take several minutes or even hours for the pressure to be relieved so that the Hose Assembly may be examined safely. Once the pressure has been reduced to zero, the Hose Assembly may be taken off the equipment and examined. It must always be replaced if a failure has occurred. Never attempt to patch or repair a Hose Assembly that has failed. Consult the nearest Parker distributor or the appropriate Parker division for Hose Assembly replacement information. Never touch or examine a failed Hose Assembly unless it is obvious that the Hose no longer contains fluid under pressure. The high pressure fluid is extremely dangerous and can cause serious and potentially fatal injury.

5.7 Elastomeric seals: Elastomeric seals will eventually age, harden, wear and deteriorate under thermal cycling and compression set. Elastomeric seals should be inspected and replaced.

5.8 Refrigerant gases: Special care should be taken when working with refrigeration systems. Sudden escape of refrigerant gases can cause blindness if the escaping gases contact the eye and can cause freezing or other severe injuries if it contacts any other portion of the body.

5.9 Compressed natural gas (CNG): Parker CNG Hose Assemblies should be tested after installation and before use, and at least on a monthly basis per instructions provided on the Hose Assembly tag. The recommended procedure is to pressurize the Hose and check for leaks and to visually inspect the Hose for damage and to perform an electrical resistance test. Caution: Matches, candles, open flame or other sources of ignition shall not be used for Hose inspection. Leak check solutions should be rinsed off after use.

6.0 HOSE STORAGE

6.1 Age Control: Hose and Hose Assemblies must be stored in a manner that facilitates age control and first-in and first-out usage based on manufacturing date of the Hose and Hose Assemblies. Unless otherwise specified by the manufacturer or defined by local laws and regulations:

6.1.1 The shelf life of rubber hose in bulk form or hose made from two or more materials is 28 quarters (7 years) from the date of manufacture, with an extension of 12 quarters (3 years), if stored in accordance with ISO 2230.

6.1.2 The shelf life of thermoplastic and polytetrafluoroethylene hose is considered to be unlimited;

6.1.3 Hose assemblies that pass visual inspection and proof test shall not be stored for longer than 2 years.

6.1.4 Storage: Stored Hose and Hose Assemblies must not be subjected to damage that could reduce their expected service life and must be placed in a cool, dark and dry area with the ends capped. Stored Hose and Hose Assemblies must not be exposed to temperature extremes, ozone,oils, corrosive liquids or fumes, solvents, high humidity, rodents, insects, ultraviolet light, electromagnetic fields or radioactive materials.

ENERPAC Warranty Policy

For those ENERPAC items sold as part of the Parker Parflex Division product offering, the following warranty applies.

ENERPAC products are warranted to be free of defects in materials and workmanship under normal use for as long as they are owned by the original purchaser, subject to the exclusions and limitations described below. This warranty does not cover ordinary wear and tear, overloading, alterations, (including repairs or attempted repairs by parties other than ENERPAC or its authorized service representatives), improper fluid, use in a manner for which they are not intended or use which is contrary to instructions for the products.

THIS WARRANTY IS LIMITED TO NEW PRODUCTS SOLD THROUGH ENERPAC AUTHORIZED DISTRIBUTORS, ORIGINAL EQUIPMENT MANUFACTURERS OR OTHER DESIGNATED CHANNELS OF DISTRIBUTION. NO AGENT, EMPLOYEE, OR OTHER REPRESENTATIVE OF ENERPAC HAS THE AUTHORITY TO IN ANY WAY CHANGE OR AMEND THIS WARRANTY.

Electronic products and components are warranted against defects in material and workmanship for a period of two years from the date of purchase.

The following items supplied with ENERPAC products are excluded from this warranty:

Components not manufactured by ENERPAC, including air motors, electric motors, gasoline engines, and diesel engines. Such items are warranted to the extent of the warranty provided by the manufacturers of such items.

If the customer believes a product is defective, the product must be delivered, or shipped freight prepaid, to the nearest ENERPAC Authorized Service Center. The customer should contact ENERPAC to locate and Authorized Service Center in the customer's area.

Products that do not conform to this warranty will be returned by ground transportation, freight prepaid.

THE FOREGOING WARRANT IS EXCLUSIVE AND IS IN LIEU OF ALL OTHER EXPRESS AND IMPLIED WARRANTIES, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

The remedy of repair, replacement or refund is customer's exclusive remedy in the event of breach of this warranty.

SELLER SHALL NOT BE SUBJECT TO AND DISCLAIMS:

(a) ANY OTHER OBLIGATIONS OR LIABILITIES ARISING OUT OF BREACH OF CONTRACT OR OF WARRANTY,

(b) ANY OBLIGATIONS WHATSOEVER ARISING FROM TORT CLAIMS (INCLUDING NEGLIGENCE AND STRICT LIABILITY) OR ARISING UNDER THEORIES OR LAW WITH RESPECT TO PRODUCTS SOLD OR SERVICES RENDERED BY SELLER OR ANY UNDERTAKINGS, ACTS OR OMISSIONS RELATING THERETO, AND

(c) ALL CONSEQUENTIAL, INCIDENTAL AND CONTINGENT DAMAGES WHATSOEVER.

ENERPAC's liability in all cases is limited to, and shall not exceed, the purchase price paid.

For the nearest authorized ENERPAC SERVICE CENTER, please call ENERPAC at 1-800-558-0530 or visit the ENERPAC web site at www.Enerpac.com.

Offer of Sale

The items described in this document and other documents or descriptions provided by Parker Hannifin Corporation, as subsidiaries and its authorized distributors are hereby offered for sale at prices to be established by Parker Hannifin Corporation, its subsidiaries and its authorized distributors. This offer and its acceptance by any customer ("Buyer") shall be governed by all of the following Terms and Conditions. Buyer's order for any such item, when communicated to Parker Hannifin Corporation, its subsidiary or an authorized distributor ("Seller") verbally or in writing, shall constitute acceptance of this offer.

1. Terms and Conditions of Sale: All descriptions, quotations, proposals, offers, acknowledgments, acceptances and sales of Seller's products are subject to and shall be governed exclusively by the terms and conditions stated herein. Buyer's acceptance of any offer to sell is limited to these terms and conditions. Any terms or conditions in addition to, or inconsistent with those stated herein, proposed by Buyer in any acceptance of an offer by Seller, are hereby objected to. No such additional, different or inconsistent terms and conditions shall become part of the contract between Buyer and Seller unless expressly accepted in writing by Seller. Seller's acceptance of any offer to purchase by Buyer is expressly conditional upon Buyer's assent to all the terms and conditions stated herein, including any terms in addition to, or inconsistent with those contained in Buyer's offer. Acceptance of Seller's products shall in all events constitute such assent.

2. Payment: Payment shall be made by Buyer net 30 days from the date of delivery of the items purchased hereunder. Any claims by Buyer for omissions or shortages in a shipment shall be waived unless Seller receives notice thereof within 30 days after Buyer's receipt of the shipment.

3. Delivery: Unless otherwise provided on the face hereof, delivery shall be made F.O.B. Seller's plant. Regardless of the method of delivery, however, risk of loss shall pass to Buyer upon Seller's delivery to a carrier. Any delivery dates shown are approximate only and Seller shall have no liability for any delays in delivery.

4. Warranty: Seller warrants that the items sold thereunder shall be free from defects in material or workmanship for a period of 365 days from the date of shipment to Buyer, or 2,000 hours of use, whichever expires first. THIS WARRANTY COMPRISES THE SOLE AND ENTIRE WARRANTY PERTAINING TO ITEMS PROVIDED HEREUNDER. SELLER MAKES NO OTHER WARRANTY, GAURANTEE, OR REPRESENTATION OF ANY KIND WHATSOEVER. ALL OTHER WARRANTIES, INCLUDING BUT NOT LIMITED TO, MERCHANTIBILITY AND FITNESS FOR PURPOSE, WHETHER EXPRESS, IMPLIED, OR ARISING BY OPERATION OF LAW, TRADE USAGE, OR COURSE OF DEALING ARE HEREBY DISCLAIMED. NOTWITHSTANDING THE FOREGOING, THERE ARE NO WARRANTIES WHATSOEVER ON ITEMS BUILT OR ACQUIRED WHOLELY OR PARTIALLY, TO BUYER'S DESIGNS OR SPECIFICATIONS.

5. Limitation Of Remedy: SELLER'S LIABILITY ARISING FROM OR IN ANY WAY CONNECTED WITH THE ITEMS SOLD OR THIS CONTRACT SHALL BE LIMITED EXCLUSIVELY TO REPAIR OR REPLACEMENT OF THE ITEMS SOLD OR REFUND OF THE PURCHASE PRICE PAID BY BUYER, AT SELLER'S SOLE OPTION. IN NO EVENT SHALL SELLER BE LIABLE FOR ANY INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES OF ANY KIND OR NATURE WHATSOEVER, INCLUDING BUT NOT LIMITED TO LOST PROFITS ARISING FROM OR IN ANY WAY CONNECTED WITH THIS AGREEMENT OR ITEMS SOLD HEREUNDER, WHETHER ALLEGED TO ARISE FROM BREACH OF CONTRACT, EXPRESS OR IMPLIED WARRANTY, OR IN TORT, INCLUDING WITHOUT LIMITATION, NEGLIGENCE, FAILURE TO WARN OR STRICT LIABILITY.

6. Changes, Reschedules and Cancellations: Buyer may request to modify the designs or specifications for the items sold herunder as well as the quantities and delivery dates thereof, or may request to cancel all or part of this order, however, no such requested modification or cancellation shall become part of the contract between Buyer and Seller unless accepted by Seller in a written amendment to this Agreement. Acceptance of any such requested modification or cancellation shall be at Seller's discretion, and shall be upon such terms and conditions as Seller may require.

7. Special Tooling: A tooling charge may be imposed for any special tooling, including without limitation, dies, fixtures, molds and patterns, acquired to manufacture items sold pursuant to this contract. Such special tooling shall be and remain Seller's property notwithstanding payment of any charges by Buyer. In no event will Buyer acquire any interest in apparatus belonging to Seller which is utilized in the manufacture of the items sold hereunder, even if such apparatus has been specially converted or adapted for such manufacture and notwithstanding any charges paid by Buyer. Unless otherwise agreed, Seller shall have the right to alter, discard or otherwise dispose of any special tooling or other property in its sole discretion at any time.

8. Buyer's Property: Any designs, tools, patterns, materials, drawings, confidential information or equipment furnished by Buyer or any other items which become Buyer's property, may be considered obsolete and may be destroyed by Seller after two (2) consecutive years have elapsed without Buyer placing an order for the items which are manufactured using such property. Seller shall not be responsible for any loss or damage to such property while it is in Seller's possession or control.

9. Taxes: Unless otherwise indicated on the face hereof, all prices and charges are exclusive of excise, sales, use, property, occupational or like taxes which may be imposed by any taxing authority upon the manufacture, sale or delivery of the items sold hereunder. If any such taxes must be paid by Seller of if Seller is liable for the collection of such tax, the amount thereof shall be in additon to the amounts for the items sold. Buyer agrees to pay all such taxes or to reimburse Seller therefore upon receipt of its invoice. If Buyer claims exemption from any sales, use or other tax imposed by any taxing authority, Buyer shall save Seller harmless from and against any such tax, together with any interest or penalties thereon which may be assessed if the items are held to be taxable.

10. Indemnity For Infringement of Intellectual Property Rights: Seller shall have no liability for infringement of any patents, trademarks, copyrights, trade dress, trade secrets or similar rights except as provided in this Part 10. Seller will defend and indemnify Buyer against allegations of infringement of U.S. patents, U.S. trademarks, copyrights, trade dress and trade secrets (hereinafter "Intellectual Property Rights"). Seller will defend at its expense and will pay the cost of any settlement or damages awarded in an action brought against Buyer based on an allegation that an item sold pursuant to this contract infringes in the Intellectual Property Rights of a third party. Seller's obligation to defend and indemnify Buyer is contingent on Buyer notifying Seller within ten (10) days after Buyer becomes aware of such allegations of infringement, and Seller having sole control over the defense of any allegations or actions including all negotiations for settlement or compromise. If an item sold hereunder is subject to a claim that it infringes the Intellectual Property Rights of a third party, Seller may, at its sole expense and options, procure for Buyer the right to continue using said item, replace or modify said item so as to make it noninfringing, or offer to accept return of said item and return the purchase price less a reasonable allowance for depreciation. Notwithstanding the foregoing, Seller shall have no liability for claims of infringement based on information provided by Buyer, or directed to items delivered hereunder for which the designs are specified in whole or part by Buyer, or infringements resulting from the modification, combination or use in a system of any item sold hereunder. The foregoing provisions of this Part 10 shall constitute Seller's sole and exclusive liability and Buyer's sole and exclusive remedy for infringement of Intellectual Property Rights.
If a claim is based on information provided by Buyer or if the design for an item delivered hereunder is specified in whole or in part by Buyer, Buyer shall defend and indemnify Seller for all costs, expenses or judgments resulting from any claim that such item infriges any patent, trademark, copyright, trade dress, trade secret or any similiar right.

11. Force Majeure: Seller does not assume the risk of and shall not be liable for delay or failure to perform any of Seller's obligations by reason of circumstances beyond the reasonable control of Seller (hereinafter "Events of Force Majeure"). Events of Force Majeure shall include without limitation, accidents, acts of God, strikes or labor disputes, acts, laws, rules or regulations of any government or government agency, fires, floods, delays or failures in delivery of carriers or suppliers, shortages of materials and any other cause beyond Seller's control.

12. Entire Agreement/Governing Law: The terms and conditions set forth herein, together with any amendments, modifications and any different terms or conditions expressly accepted by Seller in writing, shall constitute the entire Agreement concerning the items sold, and there are no oral or other representations or agreements which pertain thereto. This Agreement shall be governed in all respects by the law of the State of Ohio. No actions arising out of the sale of the items sold hereunder or this Agreement may be brought by either party more than two (2) years after the cause of action accrues.

5/14

Part Number Index

Part Number	Page
015301	F-5, F-8, F13
015302	F-8, F-9
015303	F-8, F-9
015304	F-8, F-9
015305	F-8, F-9
015306	F-6, F-8
015307	F-6
015308	F-6
015309	F-5, F-6
015310	F-8, F-9
015411	F-8, F-9
015412	F-8, F-9
015413	F-8, F-9
015414	F-8, F-9
015415	F-8, F-9
015736	F-6
025349	F-6, F-9
025399	F-5, F-9, F13
045234	F-7
062	C-20
072	C-20
090	E-30
101-(PTFE)	B-58 : B-60
10156	E-11
10191N	E-32
10193N	E-41
101CG	E-53
101CY	E-59
101SF	E-64
101SQ	E-65
10256	E-11
102CG	E-54
102CY	E-59
103-(FEP)	B-86 : B-87
10356	E-12
1035HT	A-50
10391N	E-32
103CG	E-54
104-(PFA)	B-102 : B-103
105-(H.P. PFA)	B-104 : B-105
10456	E-12
10556	E-12
105CG	E-54
10654	E-8
10656	E-13
10691N	E-32
10691NRD	E-33
10693N	E-41
10694	E-44
10695	E-44
106CG	E-55
106CY	E-60
106SF	E-64
10756	E-13
10791N	E-33
107CG	E-55
10856	E-14
10891N	E-33
108MS	E-62
10C56	E-20
110-(PVDF)	B-106 : B-107
111-(PVDF)	B-106 : B-107
11192	E-40
111CG	E-55
1120	D-4
11356	E-14
113CY	E-60
11C56	E-20
12891N	E-33
12892	E-40
13491N	E-34
134MS	E-62
13754	E-8
13756	E-15
13791N	E-34
13793N	E-42
137CG	E-56
13954	E-8
13956	E-15
13991N	E-34
13993N	E-42
139CG	E-56
139CY	E-60
13E56	E-14
14156	E-16
14191N	E-35
14956	E-16
14K93N	E-42
16191N	E-35
16791N	E-35
16792	E-40
16991N	E-35
16992	E-40
17791N	E-36
17991N	E-36
19256	E-20
19291N	E-39
1AL56	E-21
1AL91N	E-36
1ALCG	E-56
1B156	E-21
1B256	E-21
1B291N	E-39
1B456	E-21
1C356	E-22
1C456	E-22
1C556	E-22
1C656	E-23
1C956	E-23
1CA56	E-23
1CE56	E-24
1CF56	E-24
1D056	E-25
1D256	E-25
1D956	E-25
1FN91N	E-37
1FUCG	E-57
1GKCY	E-61
1GK91N	E-39
1HUSQ	E-65
1J056	E-17
1J0CG	E-57
1J156	E-17
1J191N	E-37
1J256	E-18
1J556	E-18
1J754	E-7
1J756	E-19
1J791N	E-37
1J793N	E-43
1J7CG	E-57
1J954	E-8
1J956	E-19
1J991N	E-37
1J993N	E-43
1J9CG	E-57
1J9CY	E-61
1JBSF	E-64
1JC54	E-7
1JC56	E-17
1JC91N	E-38
1JC93N	E-43
1JCCG	E-58
1JCCY	E-60
1JS56	E-18
1JSCG	E-58
1JSSF	E-64
1L956	E-16
1L9CG	E-58
1LMCY	E-61
1P691N	E-36
1PDCY	E-61
1Q191N	E-38
1TFMS	E-62
1TU56	E-19
1TU91N	E-38
1TUCG	E-58
1WU54	E-9
1WW54	E-9

For detailed ordering information, please consult price list or contact Parflex Division.

Part Number Index (cont.)

Part Number	Page
1WY54	E-9
20090	E-30
201-(Metric FTFE)	B-58, B61
20151	E-5
20190	E-26
201BU	E-52
203-(Metric FEP)	B-86 : B-87
20351	E-5
204-(Metric PFA)	B-102 : B-103
205-(Metric H.P. PFA)	B-104 : B-105
20651	E-6
20690	E-27
206BU	E-52
20851	E-6
20890	E-27
208MS	E-63
213BU	E-52
22890	E-27
23490	E-28
23790	E-28
23951	E-6
23990	E-28
24398-PFD	F-17
2613	F-20
2625	F-20
26190	E-28
26790	E-29
26990	E-29
2740	F-20
27790	E-29
2799	F-20
27990	E-29
2GK-Nut	E-39, E-61
2TFMS	E-63
332T-115V-PFD	F-17
3PSG	F-19, E-62
510A	A-34
510C	A-35
515H	A-38
518C	A-36
518D	A-37
520N	A-39
526BA	A-40
527BA	A-41
528N	A-39
53DM	A-42
538DM	A-42
540N	A-43
540P	A-44
548N	A-62
55LT	A-45
55AG	F-19
55SG	F-19
55SSG	F-19
5PSG	F-19
56DH	A-46
568DH	A-46
560TJ	A-30
563TJ	A-31
575X	A-47
575XN	A-47
580661-PFD	F-17
580N	A-48
588N	A-48
590TJ	A-32
594TJ	A-33
5CNG	A-52
5CNG/CNGLT	F-18
6-2 CTX-S	F-9
6-6 CTX-S	F-8, F-9
60 HAB	E-30
61 HAB	E-30
68NTA	D-12
685RA	E-9
703	B-100 : B-101
704	B-100 : B-101
705	B-100 : B-101
731512-Blue, Red	D-8
731513-Blue, Red	D-8
731516	D-8
731522	D-8
731611-Blue, Red	D-8
731612-Blue, Red	D-8
741526	D-8
741590-Blue, Red	D-8
751597	D-8
751634	D-10
751641	D-8
751655	D-8
751656-Blk	D-8
751657	D-11
751658-Blue, Red	D-11
751659	D-11
751660-Blue, Red	D-11
771164	D-11
801048	D-9
801595	D-9
801632	D-9
80C-0DR-PFD	F-15
80C-SDR	F-15
811537	D-12
81914/1	B-85 : B-86
81914/3	B-96 : B-97
81C-R01-PFD	F-16
81C-R02-PFD	F-16
822011	F-8, F-9
822012	F-8, F-9
822031	F-8, F-9
82C-061L-PFD	F-10
82C-0AP-PFD	F-13
82C-0EP-PFD	F-14
82C-0HP-PFD	F-14
82C-CHD-PFD	F-10
82C-KKB-PFD	F-10
82C-R01-PFD	F-5, F-8, F-10, F15
82C-R02-PFD	F-10
83C-080-PFD	F-12
83C-081-PFD	F-12
83C-0CB-PFD	F-12
83C-0DR-PFD	F-15
83C-R02-PFD	F-12
83C-R02H-PFD	F-12
83C-S40-PFD	F-12
83C-S20-PFD	F-12
83FR	A-49
85C-00L-PFD	F-10, F-11
85C-061L-PFD	F-11
85C-0HP-PFD	F-14
85C-0EP-PFD	F-14
85C-1PH-PFD	F-10, F-11
85C-CHD-PFD	F-11
85C-KKB-PFD	F-11
85C-R01-PFD	F-11, F-15
85C-R02-PFD	F-11
85C-STD-PFD	F-10, F-11
881540-PFD	F-17
8PC-030-PFD	F-16
8PC-00P-PFD	F-16
8WC-00P-PFD	F-16
919	A-63
919B	A-63
919J	A-64
919U	A-65
929	A-66
929B	A-66
929BJ	A-67
939	A-68
939B	A-68
943B	A-69
944B	A-70
94C-080-PFD	F-5

Part Number Index (cont.)

Part Number	Page
94C-001-PFD	F-5
94C-002-PFD	F-5
94C-MKS	F-7
950B	A-71
955B	A-72
9A	A-83
9H	A-83
9M	A-83
9P	A-83
A0	C-8
AS-Y	F-20
AHUFS	C-17
AUFS	C-14
B9	A-51
CL	E-47
CNG	A-53
CNGG	F-18
CR	B-98 : B-99
CV	B-80 : B-81, B-94 : B-95
CVL	B-82 : B-83
CVH	B-82 : B-83
CY02-652317	E-61
D6R	A-22
D6RX	A-22
E	B-12 : B-15, E-47
EB	B-12 : B-15
EA	B-16 : B-17
F	B-34 : B-35
F64	B-34 : B-35
FBS	E-47
FC	C-11
FIL	E-48
FJX	E-49
FL	C-11
FLR	D-7
FN	C-12
FORFS	E-49
FP	E-48
FR	C-12
FS	C-9, F-20
G	B-32 : B-33
G64	B-32 : B-33
GH9211	D-8 : D-10
GH9212	D-8 : D-10
H580N	A-48
H6	A-25
HBR	F-18
HDPE	B-20 : B-21
HFSR	A-23
HFS2R	A-24
HJK	A-29
HLB	A-54
HS1.25FEP	B-92
HS1.3FEP	B-88 : B-89
HS1.6FEP	B-90 : B-91
HS2TFI	B-72 : B-73
HS2TFL, AWG	B-74, B-77
HS2TFL, Fractional	B-72 : B-73
HS2TFS, AWG	B-74 : B-75
HS2TFS, Fractional	B-72 : B-73
HS2TFT, AWG	B-74, B-76
HS2TFT, Fractional	B-72 : B-73
HS4TFI	B-78 : B-79
HTB	A-27
HTC	F-17
HTFL	D-6
HU	B-44 : B-45
HUFR	B-42 : B-43
HUM	B-46 : B-47
M8	A-28
MBS	E-47
MC	C-10
MCB	C-18
ME	C-10
MIL	E-48
ML	C-11
MLB	C-19
MP	E-49
MSAN	E-51
MSH	A-55
MSXL	A-56
N	B-22 : B-25
NB	B-22 : B-25
NBR	B-28 : B-29
NCB	A-81
NCW	A-81
NN	B-22 : B-25
NNR	B-28 : B-29
NR	B-28 : B-29
NTNA	B-30 : B-31
NA-6520	E-39, E-61
PAT	B-26 : B-27
PC300	E-46
PCB	A-76
PCBV	A-78
PCBV-FS	A-80
PCW	A-76
PCWV	A-78
PCWV-FS	A-80
PEFR	B-18 : B-19
PF ANSI Flange	E-50
PF150	E-50
PF154	E-50
PF156	E-50
PFT	D-4 : D-5
PLCF	E-50
PP	B-36 : B-37
PPB	B-36 : B-37
PSG	F-21
PTC	F-17
PTC-001-RB	F-17
PTH	A-57
PV (guard)	F-18
PV (tubing)	B-48 : B-50
R6	A-26
RC300	E-46
RCTB	A-82
RCTW	A-82
S5N	A-58
S6	A-59
S9	A-60
SAN	E-51
SB	C-20 : C-21
SBF300	E-46
SBFW	A-74
SC300	E-46
SCB	A-75
SCBV	A-77
SCBV-FS	A-79
SCW	A-75
SCWV	A-77
SCWV-FS	A-79
SFR	E-51
SG	C-13
SLH	A-61
SplashShield	F-22
SQ-101-SW	F-13
SQ Mender	F-13
ST300	E-46
STB	A-73
STW	A-73
TFB	B-69
TFH, AWG	B-64 : B-65
TFL, AWG	B-64, B-68
TFL, Fractional	B-62 : B-63
TFS, AWG	B-64, B-66
TFS, Fractional	B-62 : B-63
TFT, AWG	B-64, B-67
TFT, Fractional	B-62 : B-63
TH11-1-PFD	F-17
TH8-1-XXX	F-14
TH9-1-XXX	F-14
TS	C-13
TSSL	B-93
TSSS	B-93
TSWTF	B-70 : B-71
TUBE	E-50
U	B-38 : B-39
UC	C-12
UM	B-40 : B-41
UFS	C-16
VBL	F-14
VBS	F-14

For detailed ordering information, please consult price list or contact Parflex Division.

Key Word Index

Part Number	Page
1.25/1 Heat Shrink	B-92
1.3/1 Heat Shrink	B-88 : B-89
1.67/1 Heat Shrink	B-90 : B-91
2 : 1 Heat Shrink	B-72 : B-77
4 : 1 Heat Shrink	B-78 : B-79
51 Series	E-5 : E-6
54 Series	E-7 : E-9
56 Series	E-10 : E-25
90 Series	E-26 : E-30
91N Series	E-31 : E-39
92 Series	E-40
93N Series	E-41 : E-43
94 Series	E-44
95 Series	E-44
A-Lok Fitting	E-36, E-50, E-56
Abrasion King	A-26
Adapters	E-5
Air Brake Tubing	D-4
Air Hose	C-4 : C-21
Anti-Kink Casing	F-20
Armor Guard	F-19, F-21
AWG Tubing	B-64 : B-68
Beading	B-69
Bend Restrictor	F-18
Brakcoil	D-8
Breathing Air Hose	A-40 : A-41
BU Series	E-52
Bulkhead Nut	E-61
Bundles	D-13
CG Series	E-53 : E-58
Clear Vinyl Hose Guard	F-21, F-23
Clear Vinyl Tubing	B-48 : B-51
Collars	E-46
Conversion Kits	F-16
Convoluted Hose	A-68, A-75 : A-78, A-81
Convoluted Tubing	B-80 : B-85, B-94 : B-97
Corrugated Tubing	B-98 : B-99
Crimp Fitting	E-2
Crimpers	F-5, F-10 : F-12
Cut-off Tools	F-17
CY Series	E-59 : 61
Grease Zerk Fitting	E-61
Diagnostic Hose	A-46
Die Racks	F-15
Dies	F-15
Diesel Fuel Tubing	D-5 : D-7
DollyCoil	D-10
Double Shrink	B-93
Duo-Coil	D-9
Duraflex	A-62
DuraGard	A-49
Duramax	A-42
E-Z Flex	A-28
Elec. Conductive Compressed Nat. Gas Hose	A-52 : A-53
Eliminator	A-27
Fast Response Hose	A-47
Fast-Stor Air Hose	C-8 : C-9
Fast-Stor Fittings	C-10 : C-14, C-18 : C-19
FEP Heat Shrink	B-88 : B-93
FEP Tubing	B-86 : B-99
Field Attachable Fitting	E-2
Fifth Wheel Slider	D-12
Fire-Screen	A-24
Fire Sleeve	F-20
Flange	E-37, E-42, E-48, E-50, E-51
Flange Retainer	E-51
Flare-Seal Hose	A-79 : A-80
Flex Tubing	B-106 : B-107
Fluoropolymer Tubing	B-52 : B-107
Gates Conversion Kit	F-16
General Hydraulic Hose	A-35, A-39, A-43
General Purpose Transfer Hose	A-51
Guards	F-18 : F-22
Harnesses	D-13
Heat Shrink Tubing	B-72 : B-79
Heavy Wall Hose	A-66
High Density Tubing	B-20 : B-21
High Pressure Hose	A-27, A-29, A-48, A-58 : A-62, A-83 : A-85
High Purity Tubing	B-104 : B-105
Highjack	A-29
High Temperature Hose	A-50, A-69 : A-72
High Temperature Power Cleaning Hose	A-50
Hose Cutter	F-17
Hose Guard	F-18 : F-22
Hybrid Hose	A-22, A-23, A-24, A-26 : A-29
Hydraulic Press Kit	F-16
I-Line Fitting	E-48
Insertion Block	F-14
Jackline Hose	A-29
Karrykrimp	F-10
Karrykrimp 2	F-11
Low Temperature Hose	A-45
Lubrication Line Hose	A-54
Marine Hose	A-55 : A-57
Metal Hose	A-83
Microweld Tubing	B-42 : B-43
MiniKrimp	F-5
Mounts	F-6
MS Series	E-62 : E-63
Multitube® Bundles	A-84
NoMar Fast-Stor Assy	C-14 : C-15, C-17
NoMar Fast-Stor Coils	C-16
NoMar Fast-Stor Fittings	C-18 : C-19
Non-Conductive Hose	A-36 : A-37
Nylon Air Brake Tubing	D-4
Nylon Tubing	B-22 : B-31
PAGE Fittings	E-45 : E-51
PAGE-flex™ SBF™	A-74
Parkrimp Dies	F-15
Parkrimp 2	F-12
Parprene Tubing	B-32 : B-35
Partek Sleeve	F-20
PFA Tubing	B-104 : B-105

Key Word Index (cont.)

Part Number	Page
polyflex Hose	A-85
Polyethylene Tubing	B-12 : B-21
Polypropylene Tubing	B-36 : B-37
Polyurethane Tubing	B-38 : B-41, B-44 : B-47
Predator	A-58 : A-60
PTFE Heat Shrink	B-72 : B-79, B-85
PTFE Hose	A-63 : A-78
PTFE Tubing	B-58 : B-85
Pumps (Crimpers)	F-13 : F-14
Pure Air Tubing	B-26 : B-27
PVDF Tubing	B-106 : B-107
Rapid Assy Fitting	E-9
Refrigerant Hose	A-34
Replacement Parts (MiniKrimp)	F-8 : F-9
Retractable Coiled Tubing	B-100 : B-101
Roll Cover	B-92
Rubber Covered Hose	A-82
SCR Hose	D-14 : D-15
Sewer Hose	A-61
SF Series	E-64
Silicone Covered PTFE Hose	A-64, A-67
Sleeve	F-20
SliderCoil	D-11
Spaghetti Tubing	B-64 : B-68
Specialty Water Hose	A-44
Spiral Cut Cable Wrap	B-70 : B-71
SplashShield	F-22
Spring, External & Internal	F-20
Spring Guard	F-19 : F-21
SQ Series	E-65
Super-Flex Tubing	B-106 : B-107
Superbraid	C-20 : C-21
Swager	F-13
Table Mount	F-6
TOUGHJACKET™ Hose	A-30 : A-33

Technical Data

AIR HOSE

Air Hose Size Selection	C-5
Fast-Stor, Measuring Bulk Hose	C-6 : C-7
Fast-Stor, How To Assemble	C-13

FITTINGS

Standard Fitting Configurations by Connection & End Code	E-4
Ferrul-Fix Installation	G-42
Fitting Nomenclature	E-3
Media to Fitting & Seal Compatibility	G-46 : G-47
Metals Corrosion Scale	G-51
Nomar Fast-Stor Assy Instruction	C-19
O-Ring Material Selection Guide	G-50

HOSE

Die Selection /Crimp/Swage	G-43
Hose Assembly & Crimping	G-14 : G-36
Hose Assembly Part Number	14
Hose Construction/Specifications psi	A-9 : A-13
MPa	A-14 : A-17
Hose Diameter Selection	G-5
Hose Fitting Insertion Values	G-44
Hose Fitting Thread Guide	G-45 : G-46
Hose Permeation Data	G-7
Hose Nomenclature	
Thermoplastic Hose	A-18
Parflex PTFE Hose	A-20
Parflex PAGE Hose	A-21
Hose Selection, Inst. & Mtn.	G-11 : G-13
Hose, Volumetric Expansion	G-8 : G- 9
Media to Hose Material Compatibility	G-53 : G-56
Stamped Form	13
Swage Instructions (Sewer Hose)	G-37 : G-39
Twin/Multi-Line Separation	G-40 : G-41
Understanding Parflex Hoses	A-7

OTHER

Government/Agency Specifications	G-61
Materials to Parflex Part Number.	G-52
Metric Conversion Chart	G-60

TOOLING

Swage Specification, (Sewer Hose)	G-43

TUBING

Compatiblity Chart for Fittings.	B-8 : B-9
Fluoropolymer	
Quick Reference.	B-54
Chemical Resistance	B-54
Property Comparison	B-55
Nomenclature	B-56 : B-57
Media to Plastic Tubing Material Guide	G-57 : G-59
Metal Tube & Fitting Material Guide	G-48 : G-49
Pressure Ranges	B-11
Thermoplastic Hose	A-22 : A-62
True-Bore Hose	A-73
Tube Cutter	F-17
Ultra-Lite Superbraid	C-20 : C-21
Ultrapure Tubing	B-26 : B-27
Vise Blocks	F-14
Vise Mount	F-6
Vinyl Tubing	B-48 : B-51
Weatherhead Conversion Kit	F-16

Parker's Motion & Control Technologies

At Parker, we're guided by a relentless drive to help our customers become more productive and achieve higher levels of profitability by engineering the best systems for their requirements. It means looking at customer applications from many angles to find new ways to create value. Whatever the motion and control technology need, Parker has the experience, breadth of product and global reach to consistently deliver. No company knows more about motion and control technology than Parker. For further info call 1 800 C-Parker (1 800 272 7537)



Aerospace

Key Markets

Aftermarket services
Commercial transports
Engines
General & business aviation
Helicopters
Launch vehicles
Military aircraft
Missiles
Power generation
Regional transports
Unmanned aerial vehicles

Key Products

Control systems & actuation products
Engine systems & components
Fluid conveyance systems & components
Fluid metering, delivery & atomization devices
Fuel systems & components
Fuel tank inerting systems
Hydraulic systems & components
Thermal management
Wheels & brakes



Climate Control

Key Markets

Agriculture
Air conditioning
Construction Machinery
Food & beverage
Industrial machinery
Life sciences
Oil & gas
Precision cooling
Process
Refrigeration
Transportation

Key Products

Accumulators
Advanced actuators
CO_2 controls
Electronic controllers
Filter driers
Hand shut-off valves
Heat exchangers
Hose & fittings
Pressure regulating valves
Refrigerant distributors
Safety relief valves
Smart pumps
Thermostatic expansion valves



Electromechanical

Key Markets

Aerospace
Factory automation
Life science & medical
Machine tools
Packaging machinery
Paper machinery
Plastics machinery & converting
Primary metals
Semiconductor & electronics
Textile
Wire & cable

Key Products

AC/DC drives & systems
Electric actuators, gantry robots & slides
Electrohydrostatic actuation systems
Electromechanical actuation systems
Human machine interface
Linear motors
Stepper motors, servo motors, drives & controls
Structural extrusions



Filtration

Key Markets

Aerospace
Food & beverage
Industrial plant & equipment
Life sciences
Marine
Mobile equipment
Oil & gas
Power generation & renewable energy
Process
Transportation
Water Purification

Key Products

Analytical gas generators
Compressed air filters & dryers
Engine air, coolant, fuel & oil filtration systems
Fluid condition monitoring systems
Hydraulic & lubrication filters
Hydrogen, nitrogen & zero air generators
Instrumentation filters
Membrane & fiber filters
Microfiltration
Sterile air filtration
Water desalination & purification filters & systems



Fluid & Gas Handling

Key Markets

Aerial lift
Agriculture
Bulk chemical handling
Construction machinery
Food & beverage
Fuel & gas delivery
Industrial machinery
Life sciences
Marine
Mining
Mobile
Oil & gas
Renewable energy
Solenoid valves
Transportation

Key Products

Check valves
Connectors for low pressure fluid conveyance
Deep sea umbilicals
Diagnostic equipment
Hose couplings
Industrial hose
Mooring systems & power cables
PTFE hose & tubing
Quick couplings
Rubber & thermoplastic hose
Tube fittings & adapters
Tubing & plastic fittings



Hydraulics

Key Markets

Aerial lift
Agriculture
Alternative energy
Construction machinery
Forestry
Industrial machinery
Machine tools
Marine
Material handling
Mining
Oil & gas
Power generation
Refuse vehicles
Renewable energy
Truck hydraulics
Turf equipment

Key Products

Accumulators
Cartridge valves
Electrohydraulic actuators
Human machine interfaces
Hybrid drives
Hydraulic cylinders
Hydraulic motors & pumps
Hydraulic systems
Hydraulic valves & controls
Hydrostatic steering
Integrated hydraulic circuits
Power take-offs
Power units
Rotary actuators
Sensors



Pneumatics

Key Markets

Aerospace
Conveyor & material handling
Factory automation
Life science & medical
Machine tools
Packaging machinery
Transportation & automotive

Key Products

Air preparation
Brass fittings & valves
Manifolds
Pneumatic accessories
Pneumatic actuators & grippers
Pneumatic valves & controls
Quick disconnects
Rotary actuators
Rubber & thermoplastic hose & couplings
Structural extrusions
Thermoplastic tubing & fittings
Vacuum generators, cups & sensors



Process Control

Key Markets

Alternative fuels
Biopharmaceuticals
Chemical & refining
Food & beverage
Marine & shipbuilding
Medical & dental
Microelectronics
Nuclear Power
Offshore oil exploration
Oil & gas
Pharmaceuticals
Power generation
Pulp & paper
Steel
Water/wastewater

Key Products

Analytical Instruments
Analytical sample conditioning products & systems
Chemical injection fittings & valves
Fluoropolymer chemical delivery fittings, valves & pumps
High purity gas delivery fittings, valves, regulators & digital flow controllers
Industrial mass flow meters/controllers
Permanent no-weld tube fittings
Precision industrial regulators & flow controllers
Process control double block & bleeds
Process control fittings, valves, regulators & manifold valves



Sealing & Shielding

Key Markets

Aerospace
Chemical processing
Consumer
Fluid power
General industrial
Information technology
Life sciences
Microelectronics
Military
Oil & gas
Power generation
Renewable energy
Telecommunications
Transportation

Key Products

Dynamic seals
Elastomeric o-rings
Electro-medical instrument design & assembly
EMI shielding
Extruded & precision-cut, fabricated elastomeric seals
High temperature metal seals
Homogeneous & inserted elastomeric shapes
Medical device fabrication & assembly
Metal & plastic retained composite seals
Shielded optical windows
Silicone tubing & extrusions
Thermal management
Vibration dampening

ENGINEERING YOUR SUCCESS.

Parker Fluid Connectors Group
North American Divisions & Distribution Service Centers

Your complete source for quality tube fittings, hose & hose fittings, brass & composite fittings, quick-disconnect couplings, valves and assembly tools, locally available from a worldwide network of authorized distributors.

Fittings:
Available in inch and metric sizes covering SAE, BSP, DIN, GAZ, JIS and ISO thread configurations, manufactured from steel, stainless steel, brass, aluminum, nylon and thermoplastic.

Hose, Tubing and Bundles:
Available in a wide variety of sizes and materials including rubber, wire-reinforced, thermoplastic, hybrid and custom compounds.

Worldwide Availability:
Parker operates Fluid Connectors manufacturing locations and sales offices throughout North America, South America, Europe and Asia-Pacific.

For information, call toll free...

1-800-C-PARKER
(1-800-272-7537)

North American Divisions

Fluid System Connectors Division
Otsego, MI
phone 269 694 9411
fax 269 694 4614

Hose Products Division
Wickliffe, OH
phone 440 943 5700
fax 440 943 3129

Industrial Hose Division
Wickliffe, OH
phone 440 883 2120
fax 440 833 2230

Parflex Division
Ravenna, OH
phone 330 296 2871
fax 330 296 8433

Quick Coupling Division
Minneapolis, MN
phone 763 544 7781
fax 763 544 3418

Tube Fittings Division
Columbus, OH
phone 614 279 7070
fax 614 279 7685

Distribution Service Centers

Buena Park, CA
phone 714 522 8840
fax 714 994 1183

Conyers, GA
phone 770 929 0330
fax 770 929 0230

Louisville, KY
phone 502 937 1322
fax 502 937 4180

Portland, OR
phone 503 283 1020
fax 503 283 2201

Toledo, OH
phone 419 878 7000
fax 419 878 7001
fax 419 878 7420
(FCG Kit Operations)

Canada
Grimsby, ONT
phone 905 945 2274
fax 905 945 3945
(Contact Grimsby for other Service Center locations.)

Mexico
Toluca, MEX
phone (52) 722 2754 200
fax (52) 722 2722 168

© 2017 Parker Hannifin Corporation - All Rights Reserved

CAT 4660 RP 02/17

Parker Hannifin Corporation
Parflex Division
1300 North Freedom Street
Ravenna, Ohio 44266
Phone 330.296.2871
Fax 330.296.8433
www.parker.com/pfd